
N69-17026 NASA CR-54557



## SINGLE STAGE EXPERIMENTAL EVALUATION OF VARIABLE GEOMETRY GUIDE VANES AND STATOR BLADING

PART IV - DATA AND PERFORMANCE FOR VARIABLE CAMBER GUIDE VANE AND STATOR B

BY

B.A. JONES AND R.P. OSCARSON

Prepared For National Aeronautics And Space Administration

Contract NAS3-7604

Pratt & Whitney Aircraft DIVISION OF UNITED AIRCRAFT CORPORATION FLORIDA RESEARCH AND DEVELOPMENT CENTER

BOX 2691, WEST PALM BEACH, FLORIDA 33402

### **NOTICE**

This report was prepared as an account of Government sponsored work. Neither the United States, nor the National Aeronautics and Space Administration (NASA), nor any person acting on behalf of NASA:

- A.) Makes any warranty or representation, expressed or implied, with respect to the accuracy, completeness, or usefulness of the information contained in this report, or that the use of any information, apparatus, method, or process disclosed in this report may not infringe privately owned rights; or
- B.) Assumes any liabilities with respect to the use of, or for damages resulting from the use of any information, apparatus, method or process disclosed in this report.

As used above, "person acting on behalf of NASA" includes any employee or contractor of NASA, or employee of such contractor, to the extent that such employee or contractor of NASA, or employee of such contractor prepares, disseminates, or provides access to, any information pursuant to his employment or contract with NASA, or his employment with such contractor.

Requests for copies of this report should be referred to National Aeronautics and Space Administration Scientific and Technical Information Facility P.O. Box 33 College Park, Md. 20740

# SINGLE STAGE EXPERIMENTAL EVALUATION OF VARIABLE GEOMETRY GUIDE VANES AND STATOR BLADING

PART IV - DATA AND PERFORMANCE FOR VARIABLE CAMBER GUIDE VANE AND STATOR B BY B.A. JONES AND R.P. OSCARSON

Prepared For National Aeronautics And Space Administration **31 DECEMBER 1968** Contract NAS3-7604

> **Technical Management** NASA Lewis Research Center Cleveland, Ohio

NASA Program Manager: | James J. Watt

Air Breathing Engines Division

NASA Research Advisor: L. Joseph Herrig

Fluid Systems Components Division



BOX 2691, WEST PALM BEACH, FLORIDA 33402

### ABSTRACT

A single-stage experimental investigation was conducted to determine the extent that a variable camber inlet guide vane and a two-part stator having adjustable leading and trailing edge metal angles can increase the stable operating range of a compressor front stage. The stage was designed with zero rotor prewhirl at design equivalent rotor speed (SLTO conditions) and 35-degree hub - 20-degree tip prewhirl at 70% of design rotor speed (high Mach number cruise conditions). The cruise configuration permitted stable operation at a lower flow for a given speed than those attainable with the SLTO configuration. At cruise rotor speed and flow conditions, the adiabatic efficiency of the cruise configuration was approximately 7% higher than that of the SLTO configuration.

# SINGLE STAGE EXPERIMENTAL EVALUATION OF VARIABLE GEOMETRY GUIDE VANES AND STATOR BLADING

PART IV - DATA AND PERFORMANCE FOR VARIABLE CAMBER GUIDE VANE AND STATOR B

B. A. JONES AND R. P. OSCARSON

PRATT & WHITNEY AIRCRAFT
FLORIDA RESEARCH AND DEVELOPMENT CENTER

### SUMMARY

An experimental investigation was conducted with a 0.5 hub/tip ratio single-stage compressor to determine the extent that a variable camber guide vane and a twopart stator having adjustable leading and trailing edge metal angles can extend the range of stable compressor operation. The stage, which resembled the front stage of a typical high cruise flight Mach number compressor, was designed with zero rotor prewhirl at design equivalent rotor speed (sea level takeoff, SLTO conditions), and 35degree hub - 20-degree tip prewhirl at 70% of design rotor speed (high Mach number cruise conditions). The design rotor tip relative Mach number for the SLTO configuration was 1.15, and the design stage pressure ratio and efficiency were respectively 1.32 and 85.1%. The SLTO configuration was tested over a range of speeds from 50 to 110% of design equivalent rotor speed. The cruise configuration and an intermediate configuration (approximately halfway between the SLTO and cruise IGV and stator settings) were tested from 50 to 100% of design equivalent rotor speed. performance goals were met with the SLTO and cruise configurations. The cruise configuration permitted stable operation at a lower flow for a given speed than that attainable with the SLTO configuration. At cruise rotor speed and flow conditions, adiabatic efficiency was approximately 7% higher for the cruise configuration. Moreover, the cruise configuration exhibited a substantial improvement in stall margin over that obtained with the SLTO configuration in the range of rotor speeds between 50 and 80% of design equivalent rotor speed. intermediate setting of the guide vanes and stator (halfway between the SLTO and cruise configurations) resulted in flow reductions at SLTO and cruise design pressure ratio equal to approximately 40% of the reduction in flow between the SLTO and cruise configuration. The stall limit flow for the intermediate configuration at cruise rotor speed

was approximately 2% less than that for the SLTO configuration and 10% greater than that for the cruise configuration.

### INTRODUCTION

The supersonic cruise operating point of fixed-geometry front stages of turbojet engine compressors tends to approach the stall line as cruise Mach number increases. This results from the flow limitation in the compressor rear stages at cruise rotor speed and pressure ratio conditions. This imposes a reduction in compressor inlet flow and axial velocity below that for which the front stages are designed to operate efficiently. When the reduction in front-stage axial velocity becomes proportionally greater than the reduction in blade tip velocity, rotor incidence angle increases above the sea level takeoff design value. If the increase in incidence angle is sufficiently large, the front stage(s) may be subject to stall, which can lead to reduced compressor performance and possibly to compressor surge. One approach in overcoming this problem is to provide mechanical adjustment of the guide vane and stator leading and/or trailing edge metal angles to permit selection of the proper stage velocity triangles over the required operating range.

A single-stage compressor experimental investigation was conducted to evaluate the extent to which variable geometry concepts can be applied to increase the stable operating range of a compressor front stage. A variable camber inlet guide vane, rotor, and two variable geometry stator configurations were designed, fabricated, and tested over a range of equivalent rotor speeds from 50 to 110% of the design rotor speed. The stage was designed with zero rotor prewhirl at design equivalent rotor speed and 35-degree hub - 20-degree tip prewhirl at cruise conditions. Design point (sea level takeoff, SLTO) equivalent rotor speed and flow were respectively 6050 rpm and 265 lb/sec; off-design (simulated high Mach number cruise) equivalent rotor speed and flow were respectively 4235 rpm and 143 lb/sec.

The variable-camber guide vanes comprised modified 63-series airfoil sections and were configured with a fixed leading-edge segment and two articulated flap segments. The rotor, designed with circular arc airfoils, had a tip inlet relative Mach number of 1.15. The stator configurations, comprised of 65-series airfoil sections, were designed to turn the flow back to the near axial direction at the SLTO operating point and to provide a (hypothetical) 2nd-stage rotor prewhirl distribution of

approximately 30-degree hub - 25-degree tip at the cruise operating point. One stator design had a fixed-geometry leading edge and an adjustable trailing edge (Stator A), and the other stator design had adjustable leading and trailing edge geometry (Stator B).

Details of the experimental stage aerodynamic and mechanical design are presented in Reference 1. The results of an annular cascade test program for the preliminary evaluation of candidate variable geometry concepts are presented in Reference 2. The data and performance obtained with the variable camber guide vane, rotor, and Stator A are presented in Reference 3. This report presents the data and performance obtained with the variable camber guide vane, rotor, and Stator B design that had variable leading and trailing edge geometry. The variable-geometry stage was tested with the guide vanes and stator in their SLTO position, cruise position, and an intermediate position halfway between the SLTO and cruise positions.

### TEST EQUIPMENT

### Facility

The compressor test facility is shown in figure 1. The compressor rotor is driven by a single-stage free turbine that is powered by exhaust gases from a J75 slave engine. Drive turbine speed is controlled by means of the engine throttle. Air entered the compressor test section through a 103-ft combined inlet duct, plenum, and bellmouth inlet and exhausted through an exit diffuser to the atmosphere. A 7-degree diffuser at the plenum inlet and 10:1 bellmouth contraction ratio ensured uniform flow conditions at the compressor inlet.

### Compressor Test Rig

The compressor rig, shown in figure 2, comprises bellmouth inlet, test section, and exhaust section. The rotor assembly and shaft are supported on two bearings that transmit loads to the outer case through the stationary leading-edge segments of the variable-geometry inlet guide vanes and the struts in the exhaust case. A set of motor-driven throttle vanes is located in the exhaust case to vary flowrate. A section view of the flowpath is shown in figure 3. The guide vane inlet station is preceded by a flow-straightening section approximately 10-in. long. The inner flowpath wall converges from a diameter of 18.70 in. at the guide vane inlet to a diameter of 25.60 in. at the stator exit. The outer wall diameter converges slightly from 43.20 to 42.10 in. The hub/tip ratio at

the rotor leading edge is 0.492. In general, the flowpath is designed to resemble the front-stage environment of a state-of-the-art high cruise Mach number compressor. The blade rows were spaced sufficiently apart to permit the installation of instrumentation.

A machined aluminum shroud was used for the rotor to prevent damage to the blade tips in the event a rub occurred during operation near or in stall. The nominal blade tip clearance was 0.050 in.

### Blading Design

### Inlet Guide Vane

The variable camber inlet guide vane was designed to provide axial inlet flow (zero swirl) in the SLTO configuration and 35-degree hub - 20-degree tip swirl distribution in the cruise configuration. Slightly-modified 63-series airfoil sections were used. The basic camber was selected to provide approximately two-thirds of the anticipated air turning requirement at the cruise operating point.

The SLTO and cruise positions were achieved by actuating two articulated flap segments in the appropriate direction to reduce or increase camber angle from the basic design camber angle. A photograph of the guide vane is shown in figure 4. Guide vane geometry details are summarized in table la; symbols are defined in Appendix A. Table la includes the leading and trailing edge metal angles for an intermediate guide vane setting that was tested following the tests with the SLTO and cruise geometries. Additional design information for the inlet guide vane is presented in Reference 1.

### Rotor

The rotor was comprised of 34 blades, designed with circular-arc airfoil sections. The design point inlet relative Mach number at the tip was 1.15 and the design diffusion factor was nominally 0.40. Blade chord length and solidity were representative state-of-the-art values for a high cruise Mach number front stage. A part span shroud was added at 40% span from the tip to reduce blade resonance stress. Rotor geometry details are summarized in table 1b, and additional rotor design information is contained in Reference 1.

Table 1. Design Data

a. Inlet Guide Vane Geometry

		<sup>လ</sup>	Approximately 1.0 Degree Estimated		° <b>~</b>	7.522			
		ь	1.412 1.245 1.080 0.913 0.748		Ь	1.412 1.245 1.080 0.913 0.748			
		υ	######################################		υ	7 1 . 4 7 . 4 7 4 . 4 7 4 7 4 7 4 7 4 7 4 7			
		۰	0.000		۰,	21.1 20.5 19.9 18.2			
		₽	25.6 23.9 22.1 20.5 18.6		0	56.2 54.5 52.7 51.1 49.2			
		X G	3.7 1.9 0.3		<b>x</b> 2	23246 23246 290 290 290		* 2	20.7 19.0 17.2 15.6
63 20 2.642 0.09	c1	x 1	200.2	ion	$\kappa_1$	200.2	Iguration	<b>κ</b> 1	200.2
Airfoil Series: No. of Blades: Aspect Ratio: Thickness Ratio:	SLTO Configuration	Percent Span (from tip)	90 70 30 10	Cruise Configuration	Percent Span (from tip)	90 70 30 10	Intermediate Configu	Percent Span (from tip)	90 70 30 10

Design Data (Continued) Table 1.

Rotor Geometry , Q

Circular Arc 34 Airfoil Series: No. of Blades: Aspect Ratio:

# SLTO Configuration

ìз	0.024	0	0.033	0	0.		ij	0	0	0.030	0	۲.
40	6.1	4.3	ထို	3,3	3.8		40	•		5.9		•
t/c	0.0744	0.0641	0.0542	0.0445	0.0355		t/c	Eigura	figuration	nfiguration	figura	figuration
ь	1.42	1.30	1.20	1.12	1.06		Ь	COI	S	SLTO Con	Coi	Cor
υ	.2	7.	3,63	φ,	0.		υ	as	ສຸ	Same as	ຜ	as
÷t E	1.4	1.4	1.2	<b>†</b> •0	0.0		i. E	-1.7	2.3	4.3	6.1	4.5
7.0	•	•	48.2	•	•		٧°	tion	tion	tion	tion	tion
0	29.8	20.0	14.0	11.0	10.3		0	Configura	Configura	Configuration	Configura	Configuration
<b>K</b>	18.8	32.5	42.1	9.84	52.9		, K	SLTO	SLTO	SLTO	SLTO	SLTO
γ 1	9.84	52.5	9	59.6	63.2	ration	ĸ	Same as	Same as	Same as	Same as	Same as
Percent Span (from tip)	0 ę	70	50	30	10	Cruise Configuration	Percent Span (from tip)	06	70	50	30	10
			6									

Table 1. Design Data (Continued)

# c. Stator B geometry

65

Airfoil Series: No. of Blades:

		ĮЗ		022		- 13		000			
		ô	84.			0		1 <del>-</del> 1 0			
		40	10			°	11	ာထာတ			
		ь	24.	1.07		ø	1.28	100			
		υ	7-00	3.13		U					
		i m	# m r	1 1 1 2 2 2 3 3 3 4 3 5 4 3 5 5 5 5 5 5 5 5 5 5 5 5		÷Ę	1.7				
		۰,	9 7 7	11 H 13 2 2 3 2 2 3 2 2 3 2 2 3 2 2 3 2 2 3 2 2 3 2 2 3 2 3 2 3 2 3 2 3 2 3 2 3 2 3 2 3 2 3 2 3 2 3 2 3 2 3 2 3 2 3 3 2 2 3 2 2 3 2		°¢		1 1 6 1 1 6 1 4 1			
		•	o = 0	007		•		1			
•		* 2	7.8	, a a		<b>K</b>	7.80	18.0	<b>ا</b> ة	K 2	4 N N N 4 W N N O H
2.939	<b>¤</b>	κ	40.9	34.7	ion	ĸ <sub>1</sub>		#3.0 #5.0	Configuration	κ1	45.44 339.2 40.55
Aspect Ratio: Thickness Ratio:	SLTO Configuration	Percent Span (from tip)	90	50 30 10	Cruise Configurat	Percent Span (from tip)	900	.30 .10	Intermediate Conf	Percent Span (from tip)	90 70 50 30 10

### Stator B

A photograph and section view of Stator B are shown in figure 4. The design point geometry was developed from 65-series airfoil sections; the vanes were designed to preserve as much as possible of the basic 65-series airfoil shape. Pursuant to this objective, the two flap segments were selected to have approximately the same chord length and an overlap of 15% of the basic 65-series chord length. The leading edge of the forward flap is identical to the basic 65-series airfoil up to 30% of the forward flap The geometry of the remainder of the forward flap was generated by combining the thickness distribution for a 65-series airfoil (having a chord length equal to the flap chord and thickness at 30% chord as defined by the basic airfoil) with the basic airfoil suction surface contour. For the rear flap, the uncovered section (55 to 100% of the basic airfoil chord) is identical to the basic 65-series airfoil geometry. A NACA-4-digit series airfoil shape was used for the covered leading edge section (40 to 55% basic chord) to permit low-loss operation over a wide range of incidence angles. A small slot was provided between the two segments in this position to reduce recirculation in the pressure surface cavity that is formed by the two segments.

Minimum loss incidence angle, loss, and deviation angle for the SLTO geometry airfoil were predicted from conventional 65-series airfoil cascade data. Midspan values of stator inlet Mach number and diffusion factor were 0.56 and 0.33, respectively. Additional design information is presented in Reference 1.

To obtain the desired incidence and exit angle distributions for operation at the cruise conditions, the forward segment was rotated to increase the leading edge metal angle 9 degrees and the rear segment was rotated to increase the trailing edge metal angle 26 degrees. The net effect was a decrease in camber angle of 17 degrees. For the intermediate geometry setting, the forward segment was rotated 4.5 degrees and the rear segment was rotated 13 degrees. Stator design details are presented in table 1c.

### Instrumentation

Instrumentation was provided to obtain overall and blade element performance data for each blade row. Axial locations of instrumentation stations are indicated in figure 2 and the circumferential locations of instrumentation at each axial station is shown in figures 5 through 7.

Airflow was measured with an ASME standard thin-plate orifice located in the inlet duct, as indicated in figure 1. Inlet total pressure and temperature were measured in the plenum by means of three Kiel-type total pressure probes and six half-shielded total temperature probes. Four equally spaced static pressure taps were located on both the inner and outer wall at Station O. The static pressure measurements at this station were used to check the orifice weight flow.

Air angles were measured by means of 20-degree wedge traverse probes. Behind the inlet guide vane and stator these probes were located circumferentially as required to keep them out of vane wakes. Each 20-degree wedge probe includes a total pressure tube for total pressure measurement as shown in figure 8.

Total pressure measurement behind the guide vane and stator was accomplished by means of two stationary wake probes at each station. One wake probe had sets of 14tube rakes at 10, 50, and 90% span locations; the other wake probe had sets of 14-tube rakes at 30 and 70% span locations. The angle settings of both the rake heads and the probe stem were selected to permit alignment with the airstream within approximately +5 degrees for both SLTO and cruise geometry. The acceptance yaw angle (pressure accuracy within +1% of P - p) of the rake tubes is +10 degrees. The wake probe was translated circumferentially to keep the wake centered on the rakes when the quide vane and stator flaps were in the cruise position. A typical rake head is shown in figure 9. The 20-degree wedge traverse probes used for air angle measurement behind the quide vane and stator also measured total pressure, which provided a check on the midchannel total pressures obtained with wake probes. Total pressures behind the rotor were measured with the two 20-degree wedge traverse probes and two radial rakes with Kiel heads at 10, 30, 50, 70, and 90% span. The traverse probes and radial rakes were spaced so as to approximately average the circumferential total pressure profile generated by the inlet guide vanes. Total temperatures were measured behind the stator using Kieltype probes mounted on four radial rakes. The temperature rakes were spaced as shown in figure 7; they were located with respect to each other at 0, 1/4, 1/2, and 3/4 of a quide vane gap. Total pressure and temperature rakes are shown in figure 10.

Radial distribution of static pressures behind the guide vanes, rotor, and stator were measured by means of 8-degree wedge traverse probes, which are shown in figure 11. Four approximately equally spaced static pressure taps were provided on the inner and outer walls behind

the guide vane and stator. Four taps were located on the inner wall and twelve taps were located on the outer wall behind the rotor. The eight additional outer wall taps behind the rotor were spaced across a guide vane gap to determine the static pressure variation associated with guide vanes wakes and/or stator flow fields.

Three Kistler high response pressure transducers were installed approximately 30 and 60 degrees apart at 10% span behind the rotor to measure the number, size, and rotational speed of rotating stall zones.

Rotor blades and stator vanes were instrumented with strain gages to measure torsional and bending stresses.

Rotor speed was measured with an electromagnetic sensor mounted adjacent to a 60-tooth gear on the rotor shaft. Gear-tooth-passing frequency was displayed as rpm on an Anadex digital counter.

Steady-state pressure measurements were recorded on a scannivalve multichannel pressure transducer system. Traverse probe data (total and static pressures, air angle, and radial position) were recorded on magnetic tape at the rate of 60 samples (2.0 in. probe travel) per minute. Temperatures were indicated on precision potentiometers and manually recorded.

Orifice static pressure, bellmouth static pressure, plenum pressure, and representative stage exit pressure instrumentation were close-coupled to transducers for high response transient recording of flow and pressure ratio during operation into and out of stall. Similar instrumentation was connected to manometers in the control room to permit setting the desired steady-state pressure ratio and flow conditions.

### **PROCEDURES**

### Test Procedure

Overall and blade element performance data were obtained at three settings of the variable camber inlet guide vane and variable geometry Stator B: sea level takeoff, cruise, and an intermediate setting approximately halfway between the SLTO and cruise settings. Data were obtained at 50, 70, 80, 100, and 110 percent of design equivalent rotor speed with the SLTO configuration, and 50, 70, 80, and 100 percent of design rotor speed with the cruise and intermediate configuration. Data points were distributed between maximum flow and near stall flow at each rotor speed.

For the SLTO configuration, points near stall at 100 and 110% of design speed were obtained with a reduced inlet pressure (approximately 11 psia) because of the test stand horsepower limit. For each data point the fixed pressure and temperature instrumentation data were recorded with the traverse probes withdrawn. The traverse probes were subsequently immersed in the airstream and recorded as they were traversed from the inner to the outer wall.

The compressor was operated into and out of stall at each of the test rotor speeds; orifice and bellmouth static pressures, exit total pressure, and rotor speed were recorded on magnetic tape at the rate of 600 samples per minute. Kistler transducer data were also recorded during the excursions into stall to define the rotating stall patterns. Time correlation between the Kistler and stall transient pressure recordings permitted correlation of the Kistler and stall transient data.

### Data Reduction Procedure

Data reduction was accomplished in four steps. Initially, the raw data compiled on magnetic tape and IBM cards were converted to engineering units that were subsequently recompiled on a storage tape and tabulated for preliminary inspection. The second data reduction step accomplished the following:

- 1. Mach number corrections, as required, for traverse probe data
- 2. Correction of pressure and temperature data to NASA Standard Day conditions
- 3. Mass averaging of guide vane and stator wake pressures (these were subsequently performed in a separate computer program)
- 4. Calculation of corrected flow
- 5. Calculation of radial distribution of flow parameter (for radial mass flow averaging of total pressures in subsequent procedure)
- 6. Circumferential arithmetic averaging of fixed and traverse instrumentation data.

The results of this data reduction step were printed to permit a more detailed inspection of the data to eliminate apparent inconsistencies prior to the calculation of performance and vector diagram variables. Pressure ratios were calculated for the rotor, guide vane-rotor, and the entire stage. Stage inlet total pressure was corrected to the NASA Standard Day conditions, 14.69 psia. The guide vane, rotor, and stator exit total pressures were weighed according to local mass flow to obtain the average values. The guide vane and stator wake total pressures at each radial measuring station were mass-averaged using the local total pressures in the wake and the 8-degree wedge probe static pressure to define the local Mach numbers. Mass flux was then obtained from the relationship

$$\overline{m} = \frac{W\sqrt{T}}{PA} = \sqrt{\gamma g/R} \quad M \left[1 + \frac{\gamma - 1}{2} M^2\right]^{1/2} \quad P/P$$

where T is measured total temperature and A is the flow area associated with each total pressube tube. With the radial distribution of total pressure and mass flux thus calculated, the total pressures were mass-averaged in the radial direction. Behind the rotor, the total pressures obtained with the two 20-degree wedge probes were arithmetically averaged, and the resulting radial distribution was mass-flow-averaged using the 8-degree wedge probe static pressure and stator exit radial temperature distribution to define weight flow.

Performance and vector diagram calculations were performed two ways: one method used the measured static pressure distributions to define the velocity distributions at each axial station; the second method, a streamline analysis, calculated a static pressure distribution that satisfied radial equilibrium and continuity. For the streamline analysis calculation, adjustments could be made to an input boundary layer displacement factor to achieve agreement between the calculated and measured static pressure. The primary purpose for using the streamline analysis computer program was to permit translation of the velocity diagram data from instrumentation axial stations to the respective adjacent blade row leading and trailing edge stations for comparison with the design velocity diagram results (Reference 1). The translation was performed with the assumption of isentropic flow and constant angular momentum along design stream annuli whose centers intersected each blade row leading edge at 10, 30, 50, 70, and 90% span positions from the tip. velocity diagram data presented herein were calculated by means of the streamline analysis computer program and correspond to the leading and trailing edges of the rotor and stator blade rows as defined by the dashed lines in figure 3. Loss coefficient calculations for the guide vane and stator were performed in a separate computer program to permit use of the wake freestream total pressure

as the upstream pressure and to permit the elimination of certain rake tube pressures that were apparently faulty and affected the credibility of the calculated loss coefficient. Rotor overall performance and loss coefficients were based on inlet total pressures that resulted from integration of the as-measured quide vane wake pressures. The discrepancies in guide vane wake pressures that influenced guide vane loss coefficients had a negligible effect on the calculated rotor loss. Because of the sensitivity of the calculated rotor blade relative total pressure to static pressure, the rotor loss coefficients were based on the static pressure values measured at the instrumentation stations rather than those calculated for the leading and trailing edge stations. Consequently, the loss coefficient data for the three blade rows correspond to the instrumentation stations upstream and downstream of each blade row (along the aforementioned design streamline) rather than to the blade row leading and trailing edges.

### PRESENTATION OF DATA

### Overall Performance

Overall performance data are presented in terms of pressure ratio and adiabatic efficiency as functions of corrected weight flow,  $W\sqrt{\theta}/\delta$ ; specific weight flow,  $W\sqrt{\theta}/\delta A_A$ ; and equivalent rotor speed,  $N/\sqrt{\theta}$ . Overall performance is also summarized in terms of pressure rise coefficient,  $\Psi$ , as a function of flow coefficient,  $\Phi$ . Definitions of calculated performance variables and symbols are presented in Appendix A.

Pressure ratio and efficiency for the rotor, guide vane-rotor, and guide vane-rotor-stator B are presented respectively in figures 12, 13, and 14 for the SLTO configuration; in figures 15, 16, and 17 for the cruise configuration; and in figures 18, 19, and 20 for the intermediate configuration. The dashed-line portion of the curves in figures 14, 17, and 20 refer to transient data, and the data point on the stall line is the incipient stall point determined from the transient data. The corrected flows and pressure ratios for steady-state data points are tabulated in table B-1. Efficiency contours are presented for the three configurations in figure 21, and the pressure rise coefficient,  $\Psi$ , is presented as a function of the flow coefficient,  $\Phi$ , in figure 22.

Two qualifying statements must be made concerning the efficiency data presented in figures 12, 13, 15, 16, 18, and

19. First, the mass-average temperature used in the efficiency calculations was based on the temperature and flow distributions measured at Station 2A downstream of the stator. Redistribution of the flow through the stator may produce a slight difference between the mass-average temperature behind the rotor and the value based on stator exit conditions. This temperature difference would be reflected in the rotor and guide vane-rotor efficiencies. The second qualification concerns the use of measured guide vane wake total pressure (as discussed under Data Reduction Procedure) in the calculation of rotor pressure ratio and efficiency. Discrepancies in rotor efficiency, resulting from observed discrepancies in the guide vane wake profiles, are within +1.0 percent.

Although the performance levels in figures 12, 13, 15, 16, 18 and 19 are generally correct for the rotor and guide vane-rotor combination, a more valid assessment of stage and blade-row performance is presented in the overall performance data in figures 14, 17, and 20, and the detailed blade element data in the following section.

Figure 14 indicates that the SLTO configuration slightly exceeded its predicted performance. The predicted stage pressure ratio and efficiency were 1.32 and 85.1% compared with measured values of 1.347 and 87.8% at the design flowrate. The higher measured performance is partially attributable to slightly high rotor tip loading due to slightly negative swirl produced by the guide vanes in their SLTO position, as seen in figure 23.

(Note in figures 12 through 14 and in table B-1 that only three data points were processed for the 110% of design rotor speed condition. Discrepancies in the plenum pressure measurement were noted for the other three data points, which resulted in questionable performance values. The source of error was not discovered and the three questionable data points were, therefore, omitted from the data presentation).

Figure 17 shows that the predicted stage pressure ratio of 1.129 and efficiency of 88.3% for the cruise configuration geometry were exceeded with a measured pressure ratio of 1.15 and corresponding efficiency of 90% at the cruise design flow.

The intermediate configuration efficiency for cruise design flow in figure 20 is about halfway between the SLTO and cruise configuration efficiencies for the same flow in figures 14 and 17. The corresponding pressure ratio for the intermediate configuration was close to that obtained with the SLTO geometry. The improvement in

efficiency at cruise design conditions, as the stage geometry was changed from the SLTO configuration to the cruise configuration, is indicated by the efficiency contours in figure 21.

The pressure coefficient-flow coefficient characteristics in figure 22 indicate that the SLTO and cruise configurations are fairly well matched with their respective design conditions.

Blade Element Performance for Sea Level Takeoff Configuration

### Inlet Guide Vane; SLTO

Guide vane exit air angle distributions for the sea level takeoff configuration are presented in figure 23. The design distribution is shown for comparison with the The distribution in figure 23 indicates only a slight variation from the zero swirl design distribution. The swirl distribution corresponding to design flow imposed slightly higher incidence on the rotor tip relative to design incidence conditions. The wide variation of swirl angle with flow in the tip region is attributable to (1) influence of the rotor on the static pressure gradient in the tip region ahead of the rotor and (2) possible influence of the relief cut in the tip of the guide vane flap to permit wall clearance in the cruise configuration. A similar trend of tip region swirl angle variation with flow was noted in the Stator A test program reported in Reference 3.

Guide vane loss coefficient for the hub, mean, and tip sections are presented in figure 24. Because the guide vane loss coefficients were calculated in a separate computer program and involved the detailed inspection of each guide vane wake, only the data for the 70 and 100% design rotor speeds at the hub, mean, and tip sections were processed. These results provide assessment of the guide vane losses with respect to spanwise variation and Mach number. The loss coefficient values obtained with the Stator A SLTO configuration of Reference 3, also presented in figure 24, indicate good agreement with the Stator B SLTO configuration results.

Guide vane velocity diagram data for all five spanwise measuring stations are presented in table B-2.

### Rotor; SLTO

The rotor inlet relative Mach number and air angle distributions achieved with the variable camber guide vane and Stator B in the sea level takeoff position at design equivalent rotor speed are shown in figure 25. The distributions of both Mach number and air angle that correspond to near design flow are in good agreement with the indicated design distribution.

Rotor diffusion factor, deviation angle, and loss coefficient for design equivalent rotor speed are shown in figures 26 through 30. The measured diffusion factors and deviation angles are in generally good agreement with the design values.\* The rotor losses are generally greater than the predicted values. Minimum loss incidence angles for the 10 and 30% span locations (figures 26 and 27) are approximately 4 degrees greater than the predicted incidence angles for minimum loss.

Static pressure measurements obtained behind the rotor at the outer wall locations shown in figure 6 are presented as a function of equivalent guide vane and stator blade gap in figure 31. The pressure distribution indicates two regions of high and low pressure relative to a guide vane gap and one region of high and low pressure relative to a stator gap. The circumferential variation in static pressure is considered to be associated with the stator flow field because (1) the measured guide vane wake at 10% span from the tip was relatively small (figure 32) and (2) the static pressure taps at Station 2 were in close proximity to the stator leading edge (figure 3).

The outer wall value of static pressure obtained from extrapolation of the 8-degree wedge traverse probe static pressure data is shown in figure 31. The extrapolated value is in good agreement with the average of the wall static pressures.

Additional rotor velocity diagram and blade element performance data are presented in table B-2.

<sup>\*</sup> The rotor diffusion factor design points presented in figures 23 through 27 are defined by the corresponding equation in Appendix A. This definition accounts for the effect of the streamline diameter change across the rotor. The effect of this change was significant in the rotor hub region. The predicted rotor diffusion factors presented in Reference 1 do not account for the streamline diameter change and should not be used for comparison with the data in these figures.

### Stator B; SLTO

Stator B inlet conditions for the sea level takeoff configuration are shown in figure 33. The air angle distribution for design flow is in fair agreement with the indicated design distribution. The Mach numbers for design flow are low relative to the design values between hub and midspan.

Stator B diffusion factor, deviation angle, and loss coefficient are presented as functions of incidence angle at the five spanwise measuring stations in figures 34 through 38. In general, the measured diffusion factor, deviation angle, and loss coefficient are in favorable agreement with the respective predicted values with the exception of the hub section loss coefficient, which is substantially greater than the predicted value.

Exit air angle distributions for the Stator B SLTO configuration are compared in figure 39 with the design exit air angle distribution. The measured air angles are slightly less (approximately 2 degrees) than the design values across the span.

Additional Stator B blade element data are presented in table B-2.

Blade Element Performance for Cruise Configuration

### Inlet Guide Vane; Cruise

The swirl distribution achieved with the variable camber inlet quide vane in the cruise configuration at cruise (70% of design equivalent) rotor speed is compared with the design distribution in figure 40. The measured swirl distribution is relatively flat in the hub and tip regions with the exception of the unusually high angle at 10% span for the near stall flow conditions. The swirl distributions in figure 40 are characteristically different from the distributions obtained with the same guide vane configuration in the Stator A tests of Reference 3. Possible reasons for this difference will be discussed in the final report under the contract program. Guide vane loss coefficients for the hub, mean, and tip sections are presented as a function of Mach number in figure 41. Additional quide vane data are contained in table B-3.

### Rotor; Cruise

Rotor inlet relative Mach number and air angle achieved with the cruise guide vane configuration at cruise rotor speed are shown in figure 42. The measured Mach number distribution is close to the design Mach number distribution. The Mach numbers in the hub region are slightly high compared to the design values. The experimental values of inlet relative air angle for design flow agree with the design values between 10 and 50% span and increase to about 4 degrees higher than the design value at 90% span.

As a matter of interest, the relative air angle distribution obtained with the SLTO guide vane configuration at cruise rotor speed and flow conditions is included in figure 42 for comparative purposes. This comparison illustrates the high incidence angles that a fixed sea level takeoff geometry stage would encounter at the specified cruise conditions.

Rotor diffusion factor, deviation angle, and loss coefficient for cruise rotor speed conditions are presented in figures 43 through 47. In general, the experimental values compare well with the predicted values at all span locations. The rotor losses are slightly higher than predicted between the midspan and hub region. The minimum loss incidence angle in the tip region appears to occur at a lower incidence than the predicted minimum loss incidence.

### Stator B; Cruise

Stator B inlet conditions for the cruise configuration at cruise rotor speed are shown in figure 48. The experimental Mach number distribution for design flow is in good agreement with the design values. The experimental air angles for design flow agree with the design values in the hub and tip regions and are slightly higher at midspan.

Stator B diffusion factor, deviation angle, and loss coefficient for cruise configuration at cruise rotor speed are shown in figures 49 through 53. The measured diffusion factors are slightly lower than the values predicted for the design air turning at cruise conditions. Deviation angles are in good agreement with the predicted values. The stator losses are appreciably higher than the losses predicted for a conventional stator designed for the same air turning and operation at minimum loss incidence. The relatively high losses are attributed to the relatively

broad wake generated by the two segments of the Stator B cruise configuration. A midspan wake total pressure profile for near cruise design flow conditions is shown in figure 54.

Exit air angles for the Stator B cruise configuration are compared with the design exit air angles in figure 55. Good agreement is seen between the measured and design air angle values, particularly for the cruise design flow point.

Additional Stator B velocity diagram and performance data for the cruise geometry configuration are presented in table B-3.

Blade Element Performance for Intermediate Configuration

Blade element performance was obtained with the variable guide vanes and Stator B positioned midway between the SLTO and cruise configuration positions. The blade element performance results obtained with this configuration at the 70, 80, and 100% equivalent rotor speed operating conditions are presented in figures 56 through 69. In each figure the predicted design information for the SLTO and cruise operating points are presented for comparison with the data. Inlet guide vane exit air angles and losses are presented only for the 70 and 100% rotor speeds. Additional velocity diagram and blade element performance data for the intermediate configuration are presented in table B-4.

### Inlet Guide Vane; Intermediate

Inlet guide vane swirl distributions for 70 and 100% design equivalent rotor speed conditions are shown in figure 56. The swirl distribution is similar to that obtained with the cruise geometry (figure 40).

Guide vane loss coefficient at the root, midspan, and tip sections for the 70 and 100% rotor speed conditions are presented in figure 57. The loss coefficient levels are similar to those obtained with the SLTO guide vane configuration.

### Rotor; Intermediate

Rotor inlet relative Mach number and air angle distributions for the 70, 80, and 100% rotor speed conditions are shown in figure 58. The maximum and near

stall flow data points are presented to show the overall range at each rotor speed condition.

Rotor diffusion factor, deviation angle, and loss coefficient are presented as functions of incidence angle in figures 59 through 63. The general agreement between experimental results and those predicted for the respective SLTO and cruise configurations indicates that the intermediate guide vane configuration permits the rotor to operate within its low-loss range at both SLTO and cruise rotor speeds. It should be recalled, however, that the intermediate configuration overall pressure ratio and flow did not match either the SLTO or cruise design conditions, and would not be a suitable fixed-geometry stage for the specified operating range.

### Stator B; Intermediate

Stator inlet Mach number and air angle distributions for maximum and near stall flow conditions are compared in figure 64 with the SLTO and cruise design distributions.

Blade element performance for the Stator B intermediate configuration is presented in figures 65 through 69. The values of diffusion factor, deviation angle, and loss coefficient obtained with the intermediate position are consistent with SLTO and cruise configuration values.

### Stall Transient Performance

Stall transient data are presented in figures 70, 71, and 72 in terms of pressure ratio versus corrected weight flow. Each figure includes (1) the steady-state overall performance curve for reference, (2) the transient overall performance curve based on the arithmetic average of stage exit total pressures measured with a single radial rake, and (3) a tabulation of rotating stall pattern results derived from Kistler transducer data. The transient data pressure ratios may be less than or slightly greater than the steady-state (mass flow average) pressure ratios depending upon the radial rake position with respect to stator wakes.

The rotating stall patterns determined from the three Kistler transducers located at 10% span are characterized by a single stall zone that covers approximately one-half of the annulus (circumferentially) and rotates at about one-half of the rotor speed. The stall zone appearance is coincident with the stall point determined from the stall transient data. This point is indicated as point number (1) in the figures. When the throttle vanes are opened and the stage comes out of stall, the size of the

stall zone diminishes, as indicated by the values of percent area tabulated for the last point number in each figure. For the SLTO configuration operating at 70% rotor speed (figure 71) the rotating stall zone disappeared after the stage's initial stall, and operation in stall was fairly steady. The stall zone reappeared as the stage was operated out of stall, and finally diminished in size as indicated in the figure. A similar result was obtained with the Stator A configuration of Reference 3.

A sample of the stall transient data and Kistler transducer traces are presented for the SLTO configuration operating at 100% rotor speed in figure 73. The method used for determining the rotating stall patterns from Kistler transducer data is discussed in Appendix C.

### CONCLUDING DISCUSSION

Tests were conducted with a 0.5 hub/tip ratio compressor stage comprising a variable camber inlet guide vane, rotor, and a variable geometry stator having adjustable leading and trailing edge metal angles. Two design configurations that corresponded to SLTO and supersonic Mach number cruise operating conditions, and a third configuration geometrically midway between the two design configurations, were evaluated. Each of the three configurations were tested over a range of rotor speed and flow that encompassed both the SLTO and cruise design point conditions.

At the SLTO design conditions the SLTO configuration achieved a pressure ratio and adiabatic efficiency of 1.347 and 87.8%, respectively, compared to predicted values of 1.32 and 85.1%. At cruise design conditions the cruise configuration achieved a pressure ratio and efficiency of 1.15 and 90%, compared to predicted values of 1.129 and 88.3%. The efficiency of the SLTO configuration at cruise rotor speed and flow was 83%. In general, the cruise configuration permitted operation at lower flows and with correspondingly higher efficiencies than the SLTO configuration at the cruise rotor speed. Thus, the variable geometry features of the stage permitted efficient, stallfree operation over a wider range of corrected flow than that possible with the SLTO (fixed-geometry) configuration.

The Stator B configuration permitted adjustment of both the leading and trailing edge metal angles for operation at other than SLTO design conditions. This adjustment resulted in the desired match between rotor exit and stator inlet, and stator exit and hypothetical 2nd-stage rotor inlet conditions at the cruise design point. However, for the cruise setting the stator minimum

losses at all span locations were significantly higher than those predicted for a conventional stator designed with the same air turning requirement. The high losses resulted from the generation of a broad wake that was considered to be the product of mixed wakes from the two airfoil segments of Stator B. Although the Stator B rear airfoil segment leading edge was designed to operate with low losses over a wide range of incidence angle (Reference 1), it is apparent that additional design criteria, pertinent to tandem airfoil design, are necessary to define a low-loss Stator B type configuration.

### REFERENCES

- "Single Stage Experimental Evaluation of Variable Geometry Guide Vanes and Stators, Part I - Analysis and Design," NASA CR-54554, PWA FR-2112, August, 1968.
- 2. "Single Stage Experimental Evaluation of Variable Geometry Guide Vanes and Stators, Part II Annular Cascade Investigation of Candidate Variable Geometry Designs," NASA CR-54555, PWA FR-2297, July, 1967.
- 3. "Single Stage Experimental Evaluation of Variable Geometry Guide Vanes and Stators, Part III Data and Performance for Variable Camber Guide Vanes and Stator A," NASA CR-54556, PWA FR-2638, December 1968.





Figure 1. Compressor Research Facility



Compressor Rig Figure 2.




Figure 3. Section View of Flowpath





Figure 4. Variable Geometry Inlet Guide Vane and Stator B






Figure 5. Instrumentation Station 1, FD 25194
View Looking Forward






Figure 6. Instrumentation Station 2, FD 25195
View Looking Forward






- (°) Indicates Wake Rake Location For Cruise Configuration
- Temperature Rake
  (10, 30, 50, 70 and 90% Span) (4)

  P Kiel Total Pressure Probe

(10, 30, 50, 70 and 90% Span) (2)

Figure 7. Instrumentation Station 2A, FD 25196 View Looking Forward



FE 73903

Figure 8. 20-Degree Wedge Probe

FD 25197





Figure 9. Typical Wake Probe Rake FD 25198







Total Temperature and Total Pressure Rakes Figure 10.




Figure 11. 8-Degree Wedge Probe FD 25200




Figure 12. Overall Performance:
Rotor Only, SLTO Configuration




Figure 13. Overall Performance: Guide Vane Rotor, SLTO Configuration




Figure 14. Overall Performance: Guide Vane, Rotor, Stator B, SLTO Configuration

68755

DF




Figure 15. Overall Performance:
Rotor Only, Cruise Configuration




Figure 16. Overall Performance: Guide Vane, Rotor, Cruise Configuration




Figure 17. Overall Performance: Guide Vane, Rotor, Stator B, Cruise Configuration




Figure 18. Overall Performance:
Rotor Only, Intermediate Configuration




Figure 19. Overall Performance: Guide Vane, Rotor, Intermediate Configuration




Figure 20. Overall Performance: Guide Vane, Rotor, Stator B, Intermediate Configuration




Figure 21. Stage Efficiency Contours




Figure 22. Pressure Rise Coefficient vs Flow Coefficient




Figure 23. Guide Vane Exit Air Angle: SLTO Configuration, 100% Equivalent Rotor Speed




Figure 24. Inlet Guide Vane Loss Coefficient vs Inlet Mach Number: SLTO Configuration




Figure 25. Rotor Inlet Air Angle and Mach Number Distribution: SLTO Configuration, 100% Equivalent Rotor Speed




Figure 26. Rotor Blade Element Performance: SLTO Configuration, 100% Equivalent Rotor Speed, 10% Span From Tip




Figure 27. Rotor Blade Element Performance: SLTO Configuration, 100% Equivalent Rotor Speed, 30% Span From Tip




Figure 28. Rotor Blade Element Performance: SLTO Configuration, 100% Equivalent Rotor Speed, 50% Span From Tip




Figure 29. Rotor Blade Element Performance: SLTO Configuration, 100% Equivalent Rotor Speed, 70% Span From Tip




Figure 30. Rotor Blade Element Performance: SLTO Configuration, 100% Equivalent Rotor Speed, 90% Span From Tip




Figure 31. Influence of Guide Vane Wake and Stator on Station 2 Outer Wall Static Pressure




Figure 32. Guide Vane Wake 10% From Tip




Figure 33. Stator Inlet Air Angle and Mach Number Distribution: SLTO Configuration, 100% Equivalent Rotor Speed




Figure 34. Stator Blade Element Performance: SLTO Configuration, 100% Equivalent Rotor Speed, 10% Span From Tip




Figure 35. Stator Blade Element Performance: SLTO Configuration, 100% Rotor Speed, 30% Span From Tip

DF 68775




Figure 36. Stator Blade Element Performance: SLTO Configuration, 100% Equivalent Rotor Speed, 50% Span From Tip




Figure 37. Stator Blade Element Performance: SLTC Configuration, 100% Equivalent Rotor Speed, 70% Span From Tip




Figure 38. Stator Blade Element Performance: SLTO Configuration, 100% Equivalent Rotor Speed, 90% Span From Tip




Figure 39. Stator Exit Air Angle vs Percent Span: SLTO Configuration, 100% Equivalent Rotor Speed




Figure 40. Guide Vane Exit Air Angle: Cruise Configuration, 70% Equivalent Rotor Speed




Figure 41. Inlet Guide Vane Loss Coefficient vs Inlet Mach Number: Cruise Configuration




Figure 42. Rotor Inlet Air Angle and Mach Number Distribution: Cruise Configuration, 70% Equivalent Rotor Speed




Figure 43. Rotor Blade Element Performance: Cruise Configuration, 70% Equivalent Rotor Speed, 10% Span From Tip




Figure 44. Rotor Blade Element Performance: Cruise Configuration, 70% Equivalent Rotor Speed, 30% Span From Tip




Figure 45. Rotor Blade Element Performance: Cruise Configuration, 70% Equivalent Rotor Speed, 50% Span From Tip




Figure 46. Rotor Blade Element Performance: Cruise Configuration, 70% Equivalent Rotor Speed, 70% Span From Tip




Figure 47. Rotor Blade Element Performance: Cruise Configuration, 70% Equivalent Rotor Speed, 90% Span From Tip




Figure 48. Stator Inlet Air Angle and Mach Number Distribution: Cruise Configuration, 70% Equivalent Rotor Speed




Figure 49. Stator Blade Element Performance: Cruise Configuration, 70% Equivalent Rotor Speed, 10% Span From Tip




Figure 50. Stator Blade Element Performance: Cruise Configuration, 70% Equivalent Rotor Speed, 30% Span From Tip




Figure 51. Stator Blade Element Performance: Cruise Configuration, 70% Equivalent Rotor Speed, 50% Span From Tip




Figure 52. Stator Blade Element Performance: Cruise Configuration, 70% Equivalent Rotor Speed, 70% Span From Tip




Figure 53. Stator Blade Element Performance: Cruise Configuration, 70% Equivalent Rotor Speed, 90% Span From Tip




Figure 54. Stator B Cruise Configuration Wake Total Pressure Profile




Figure 55. Stator Exit Air Angle vs Percent Span: Cruise Configuration, 70% Equivalent Rotor Speed




Figure 56. Guide Vane Exit Air Angle: Intermediate Configuration




Figure 57. Inlet Guide Vane Loss Coefficient vs Inlet Mach Number: Intermediate Configuration




Figure 58. Rotor Inlet Relative Air Angle and Mach Number Distribution: Intermediate Configuration




Figure 59. Rotor Blade Element Performance: Intermediate Configuration, 10% Span From Tip




Figure 60. Rotor Blade Element Performance: Intermediate Configuration, 30% Span From Tip




Figure 61. Rotor Blade Element Performance: Intermediate Configuration, 50% Span From Tip




Figure 62. Rotor Blade Element Performance: Intermediate Configuration, 70% Span From Tip




Figure 63. Rotor Blade Element Performance: Intermediate Configuration, 90% Span From Tip




Figure 64. Stator Inlet Air Angle and Mach Number Distribution: Intermediate Configuration

DF 68937




Figure 65. Stator Blade Element Performance: Intermediate Configuration, 10% Span From Tip




Figure 66. Stator Blade Element Performance: Intermediate Configuration, 30% Span From Tip




Figure 67. Stator Blade Element Performance: Intermediate Configuration, 50% Span From Tip




Figure 68. Stator Blade Element Performance: Intermediate Configuration, 70% Span From Tip







Figure 69. Stator Blade Element Performance: Intermediate Configuration, 90% Span From Tip



SLTO Configuration, 100% Design Equivalent Transient Stall Data: Rotor Speed Figure 70.



SLTO Configuration, 70% Design Equivalent Transient Stall Data: Rotor Speed 71. Figure



Cruise Configuration, 70% Design Equivalent Transient Stall Data Rotor Speed 72. Figure




Figure 73. Transient and Rotating Stall FD 25734 (Kistler Trace) Data

# APPENDIX A DEFINITION OF SYMBOLS

	DEFINITION OF SIMBODS
AA	Flowpath annular area, in. 2
a' <sub>0</sub> 1	Inlet relative stagnation velocity of sound, ft/sec
c	Chord length, in.
C <sub>P</sub>	Specific heat of air, 0.24 Btu/lb <sup>O</sup> F
đ	Diameter
D	Diffusion factor
g	Gravitational constant, 32.2 ft/sec <sup>2</sup>
i <sub>m</sub>	Incidence angle, deg (based on equivalent circular arc for stators)
J	Mechanical equivalent of heat, 778 ft-lb/Btu
$\overline{m}$	Mass flow parameter, $\sqrt{\gamma g/R}$ M $\left[1 + \frac{\gamma - 1}{2} M^2\right]$ 1/2 p/P
M	Absolute Mach number
P	Total pressure, psia
p	Static pressure, psia
q	Pressure equivalent of the velocity head, psia
R	Gas constant for air, 53.3 $\frac{\text{ft-lbs}}{\text{lb-oR}}$
S	Blade spacing, in.
s	Blade span, in.
T	Total temperature, OR
$^{\mathrm{T}}\mathbf{s}$	Static temperature, OR
t	Blade maximum thickness, in.
ū	Rotor speed, ft/sec
Δ	Absolute velocity, ft/sec
W	Actual flow rate, lbm/sec
β	Absolute air angle, deg
γ	Ratio of specific heats

γο	Blade-Chord angle, deg
δ	Ratio of total pressure to NASA standard sea level pressure of 2116 psf
δ <sup>O</sup>	Deviation angle, deg
$\eta_{ m ad}$	Adiabatic efficiency
$\eta_{ m p}$	Polytropic Efficiency
θ	Ratio of total temperature to NASA standard sea level temperature of 518.70R
Κ	Blade metal angle, deg (based on equivalent circular arc for stators)
ıρ	Density, $lb_m/ft^3$
. <b>σ</b>	Solidity, c/S
φ	Blade camber angle, deg (based on equivalent circular arc for stator B and on the 0.5% chord and 95% chord for the IGV)
$\psi$	Pressure rise coefficient
$\bar{\omega}$	Total pressure loss coefficient
Subscripts	
0	Compressor inlet instrumentation station
1	Guide vane exit/rotor inlet instrumentation station
2	Rotor exit/stator inlet instrumentation station
<b>2</b> A	Stator exit instrumentation station
fs	Freestream value of guide vane or stator rake total pressure
id	Isentropic condition
le	Leading edge
te	Trailing edge
m	Midspan
s	Static condition
z	Axial component
θ	Tangential component

## Superscripts

Relative rotor blade

- Mass average value (used for overall and blade element performance)

Nomenclature used for blade element data tabulation (tables B-2, B-3, and B-4)

PCT SPAN Percent Span

DIA Diameter, inches

BETA Absolute air angle, degrees

BETA (PR) Relative air angle, degrees

V Absolute velocity, ft/sec

VZ Axial component of velocity, ft/sec

V-THETA Tangential component of absolute velocity, ft/sec

V(PR) Relative velocity, ft/sec

V-THETA PR Tangential component of relative velocity, ft/sec

U Wheel speed, ft/sec

M Absolute Mach number

M(PR) Relative Mach number

TURN Air Turning, degrees

TURN (PR) Relative air turning, degrees

 $\overline{\omega}$  Loss coefficient

DFAC Diffusion factor

EFFP Polytropic efficiency

EFF Adiabatic efficiency

INCIDM Incidence, degrees

DEVM Deviation, degrees

# NOTE

The numbers following the nomenclature in Tables B-2, B-3, and B-4 refer to the leading and trailing edges of the respective blade rows, as indicated below:

3 IGV<sub>le</sub>
4 IGV<sub>te</sub>
6 Rotor<sub>le</sub>
7 Rotor<sub>te</sub>
9 Stator<sub>le</sub>
10 Stator<sub>te</sub>

#### DEFINITION OF CALCULATED PERFORMANCE VARIABLES

Overall Performance Data

Inlet Mach Number:

$$\frac{W\sqrt{\theta}\sqrt{518.7}}{\delta P_{O}^{A}A_{O}} = g\sqrt{\gamma/g} M_{O} \left[1 + \frac{\gamma - 1}{2} M_{O}^{2}\right]^{1/2}$$

Pressure Ratio:

Rotor: 
$$\frac{\overline{P}_2}{\overline{P}_1}$$
 Rotor-Guide Vane:  $\frac{\overline{P}_2}{14.696}$  Stage:  $\frac{\overline{P}_{2A}}{14.696}$ 

Corrected Flow

$$W\sqrt{\theta/\delta}$$

Corrected Specific Flow:

$$\frac{W\sqrt{\theta}}{\delta A_{A}}$$

Corrected Rotor Speed:

$$N/\sqrt{\theta}$$

Adiabatic Efficiency (overall):

$$\eta_{\text{ad}} = \frac{(\overline{P}_2/\overline{P})^{\frac{\gamma-1}{\gamma}} - 1}{\overline{T}_{2A}/\overline{T}_1 - 1}$$
 (e.g., for rotor)

Pressure Rise Coefficient:

$$\psi = \frac{c_{p} JgT_{o} \left[ (\overline{P}_{2A}/P_{o}) \frac{\gamma - 1}{\gamma} - 1 \right]}{U^{2} le_{m} | rotor}$$

Flow Coefficient:

$$\phi = V_{zle_{m}}/U_{le_{m} \text{ rotor}}$$

Incidence Angle:

$$i_m = \beta_{le} - \kappa_{le}$$

Diffusion Factor:

Rotor: D = 1 - 
$$\frac{V_{te}^{\prime}}{V_{le}^{\prime}} + \left(\frac{d_{te}V_{\theta te} - d_{le}V_{\theta le}}{(d_{le} + d_{te})^{\sigma}V_{le}^{\prime}}\right)$$

Stator: D = 1 - 
$$\frac{v_{te}}{v_{le}}$$
 +  $\left(\frac{d_{le}v_{\theta le} - d_{te}v_{\theta te}}{(d_{le} + d_{te}) \sigma v_{le}}\right)$ 

Deviation Angle:

$$\delta^{O} = \beta_{te} - \kappa_{te}$$

Loss Coefficient:

IGV: 
$$\overline{\omega} = \frac{P_{fs} - \overline{P}_{1}}{P_{fs} - P_{O}}$$

(p<sub>o</sub> was found from linear interpolation of inner and outer wall static pressures at Station 0.)

Rotor: 
$$\overline{\omega} = \frac{\overline{P}_{2id} - P'_{2}}{\overline{P}'_{1} - P_{1}}$$

where:

$$P_{2id} = P_{1}^{i} \left\{ 1 + \frac{\gamma - 1}{2} \left( \frac{U_{te}^{2}}{a_{01}^{2}} \right) \left[ 1 - \left( \frac{d_{1e}}{d_{te}} \right)^{2} \right] \right\} \frac{\gamma}{\gamma - 1}$$

P' is found from 
$$p/P' = \left[1 + \frac{\gamma - 1}{2} M'^2\right]^{\frac{\gamma}{\gamma - 1}}$$

and M' is calculated using trigonometric functions and the measurements of U,  $\beta$ , P, and p.

Stator: 
$$\overline{\omega} = \frac{P_{fs} - \overline{P}_{2a}}{P_{fs} - P_{2}}$$

Adiabatic Efficiency:

Rotor: 
$$\frac{\left[ (P_{te}/\overline{P}_{1e})^{\frac{\gamma-1}{\gamma}} - 1 \right]}{T_{te}/T_{0} - 1}$$

Polytropic Efficiency:

IGV: 
$$\eta_{p} = \frac{\ln \left(T_{s_{1e}}/T_{s_{te}}\right)}{\frac{\gamma-1}{\gamma} \ln p_{1e}/p_{te}}$$

Rotor: 
$$\eta_p = \frac{\frac{\gamma-1}{\gamma} \ln (P_{te}/P_{le})}{\ln T_{te}/T_o}$$

Stator: 
$$\eta_p = \frac{\frac{\gamma-1}{\gamma} \ln (P_{te}/P_{le})}{\ln T_{s_{te}}/T_{s_{le}}}$$

#### APPENDIX B

### TABULATED PERFORMANCE

The stage overall performance, rotor performance, and corrected weight flow for each test point are presented in table B-1.

Tables B-2 and B-3, respectively, present SLTO and cruise configuration blade element data for each test point. Table B-4 presents blade element data for the intermediate configuration.\* Definition of the blade element velocity triangle and performance variables as tabulated in the computer printout is given in Appendix A.

<sup>\*</sup>At 110% of design rotor speed for the SLTO configuration, three data points were omitted from the data presentation because of questionable plenum pressure data.

Table B-1. Overall Performance SLTO Configuration

	$\eta_{\rm p}$ %		76.3	'n	. ₽	i	•	<u>.</u>		78.9	81.0	87.4	94.1	93.7	91.9
Stage	$\eta_{ad\%}$		0	3,3	3.9	4.2	Ŋ,	8.7		<b>4.</b> 8	0.5	7.1	93,99	3.5	1.7
	$\overline{P}_{2A}/P_{0}$		0.	.087	060.	.085		090		Ч.	.183	.184	1,1809	.160	.121
Rotor	np.%		9	9	86.7	1	96.3	က်		5	5	0	97.4	ις.	œ
Guide Vane Rotor	Tad%	or Speed	5.9	9.2	6.5	0.9	96.18	3.7	or Speed	5.4	5.2	6.6	97.29	5.3	8.5
Guid	$\overline{\mathbb{P}}_2/\mathbb{P}_0$	Equivalent Rotor	260.	n60°	.093	.087	1.0778	·064	gn Equivalent Rotor	.195	.194	.190	1.1877	.164	.131
	$\eta_{\rm D}\%$	n Equiv	9	9	6.98	١	•	6.46	n Equiv	9	5	0	98.2	9	9
Rotor	nad%	50% Design	6.1	4.6	9.9	6.5	96.45	8 • <del>1</del>	70% Design	5.7	5.4	0.4	98.07	6.6	9.8
	$\overline{P}_2/\overline{P}_1$	Ď	.098	160.	.093	.087	1.0781	.065	7(	.195	.195	.191	1,1893	.165	.132
Corrected	Weight Flow $WV\theta/\delta$ lb/sec		2.5	7.00	6.90	21.2	133,18	49.4		33.8	40.3	51.3	171,33	87.2	07.0
	Point Number		7	148	149	'n	151	146		7	141	7	143	⇉	139

Table B-1. Overall Performance (Continued) SLTO Configuration

	$\eta_{\mathrm{p}\%}$		7	$\infty$	0.06	0	5	$\vdash$		0	0.98	0	3	2	3
Stage	$\eta_{ad\%}$		6.3	7.6	89.63	9.8	5.0	1.3		9.0	85.24	<b>7.</b> 0	2.2	1.6	3.1
ţ	$\overline{P}_{2A}/P_0$		.237	.249	52	.252	.207	-		419	1.4301	. 431	.414	.362	.240
otor	$\eta_{\rm pg}$		2	'n	89.5	9	9	9	ಶ	7	88.2	9	ij	2.	0
Guide Vane Rotor	$\eta_{ad\%}$	r Speed	1.9	2.7	89.05	4.6	6.1	9.3	Rotor Speed	3.1	87.60	0.6	0.8	2.0	9.6
Guide	$\overline{P}_2/P_0$	alent Rotor	.256	.265	1,2507	.251	.209	.174	Design Equivalent Rot	444.	1.4437	423	. 407	.364	.260
	$\eta_{\rm p}$ %	gn Equiva	$\sim$	$\sim$	90.3	0	9	1	gn Equi	3	87.9	9	-	3	•
Rotor	nad%	0% Desig	2.3	2.5	89.95	9.6	6.5	_	00% Desi	2.9	87.23	6,3	1.4	2.9	1.0
	$\overline{P}_2/\overline{P}_1$	98	.258	.264	1.2534	.252	.210	.180	10	.442	1.4416	425	.410	.368	.264
Corrected	Weight Flow W/8/8 lb/sec		57.4	0.49	176,83	98.6	22.8	38.3		97.3	209,34	24.1	42.4	60.5	80.5
, , ,	Number				134	$\sim$	3	132			155	5		IJ	

Table B-1. Overall Performance (Continued) SLTO Configuration

		ηp%		77.4 86.3 82.4
	Stage	nad%		75.88 85.66 81.77
	ŝ	P <sub>2A</sub> /P <sub>0</sub>		1.5237 1.3896 1.2737
	otor	μ <sub>p</sub> %	Ď	79.1 90.2 86.9
	Guide Vane Rotor	nad%	or Spee	77.72 79.1 89.74 90.2 86.43 86.9
orthographic contractions	Guide	P2/P0	110% Design Equivalent Rotor Speed	1.5385 1.4106 1.2907
7	:	ηp%	gn Equi	79.2 90.6 88.1
	Rotor	nad%	10% Desi	77.85 90.11 87.62
		$\overline{\mathbb{P}}_2/\overline{\mathbb{P}}_1$	11	1.5422 1.4131 1.2956
	Corrected	W/0/8 lb/sec		223.62 279.67 290.69
	Point	Number		161 165 160

Table B-1. Overall Performance (Continued) Cruise Configuration

-	7 p%		0	ģ	ထ	88.0	ထ	ιζ.		2	5	7	0	· h • 96	9
Stage	nad%		0.3	5.8	8.7	•	8° 8°	5.3		2.3	5.0	7.1	0.1	96.35	6.5
S	$\overline{\mathbb{P}}_{2\mathrm{A}}/\mathrm{P}_0$		.087	.083	.078		.059			.173	.170	.164	.153	1,1365	.102
otor	7 p.%		က္	0	3	94.2	9	⇒			$\infty$	91.7	7	1	98.6
Guide Vane Rotor	7ad%	or Speed	3.3	0.5	3,5	94,12	9.9	4.0	or Speed	4.7	8.6	1.4	3.0	100.93	8.4
Guid	$\overline{P}_2/P_0$	Equivalent Rotor	060.	.088	.083	1.0754	.063	.057	ralent Rotor	.179	.178	.173	.160	1.1433	.116
	$\eta_{ m p}$ %	n Equiv	4	H	4	95.3	9	9	gn Equivalent	Ľ	9	92.2	$^{\circ}$	1	100.0
Rotor	nad%	0% Design	3,5	1.1	0.4	95.23	5.8	6.1	0% Desig	0	3	9	9	101.47	0
	$\overline{P}_2/\overline{P}_1$	<u>5</u>	.091	.089	.083	1.0763	·064	.058	7(	.180	.179	.174	.160	1,1441	.118
111	Weight Flow W/8/8 lb/sec		5.5	1.0	9.5	106.21	4.7	21.0		18.8	25.5	31.2	40.0	152,68	4.99
	Foint Number		$\infty$	$\infty$	$\infty$		$\infty$	181		9	9	7	-	173	9

Table B-1. Overall Performance (Continued) Cruise Configuration

	7p%		4	5.	7	0	90.3	7.		82.3	و		0	ं	Š
Stage	nad%		ŝ	4.8	7.5	0.1	60.06	7.0		·	5.6	88.32	0.1	9.6	6.4
	$\overline{P}_{2\mathrm{A}}/\mathrm{P}_0$		34	.221	.214	.195	1.1701	.133		.373	.385	1,3758	.343	. 299	,221
otor	7 p.%q		9	8		3	7.46	9	<sup>෦</sup> ෮	5	9	9.68	ش	₹	e m
Guide Vane Rotor	nad%	r Speed	5.8	7.7	7.8	3.1	94.55	6.1	or Speed	4.8	5.7	89.10	2.8	2.5	3.6
Guide	$\overline{\mathbb{P}}_2/\mathbb{P}_0$	Equivalent Rotor	.240	.229	.214	.202	1.1790	.148	Equivalent Rotor	.390	.386	1,3795	,355	.309	.246
	np%		9	8	6	4.	0.96	œ .	gn	ιŲ.	9	90.2	'n	ကိ	9
Rotor	$\eta_{ad\%}$	% Design	6.2	8.2	8.6	4.7	95.82	7.8	100% Desi	5.1	6.2	89.67	3.6	3,3	5.9
	$\overline{P}_2/\overline{P}_1$	808	.242	,231	.217	.205	1,1815	.150	10	.392	.388	1.3822	,358	.312	.252
Corrected	Weight Flow $W\sqrt{\theta}/\delta$ lb/sec		38.1	47.5	57.9	66.1	176.48	89.0		75.8	84.9	193.09	05.9	17.4	32.5
	Point Number		175	177	178	179	180	174		9	9		9	9	189

Table B-1 Overall Performance (Continued) Intermediate Configuration

	1													
		7 p%					94.5			8	86.0	$\infty$	$^{\circ}$	#
	Stage	nad%		<b>4.</b> 0	9.2	0.6	94.45	8.6		7.7	85.65	8.0	3.7	4.2
		$\overline{P}_{2A}/P_0$		087	0.85	079	1.0684	054		.177	1.1764	.157	.138	.109
	Rotor	70 m		9	2	9	98.1	Ť		ς, •	88.0	٠ •	<b>†</b>	9
	Vane	¶ad%	r Speed	5.9	1.6	9.4	97.99	1.5	rSpeed	2.4	87.73	0.6	4.5	6.7
HICETINGALACE COILLY GALACLON	Guide	$\overline{P}_2/P_0$	Equivalent Rotor	.093	.088	080	1.0710	• 056	Equivalent Rotor Speed	.189	1.1809	.150	,139	.112
ונמדמי		$\eta_{\mathrm{p}\%}$		9	2	0	99.5	3	ı Equiv	3	9.88	0	2	7.
דוורטדו	Rotor	nad%	% Design	6.2	1.8	0.3	99.21	2.9	% Design	2.7	88.24	0.1	2.5	7.6
		$\overline{P}_2/\overline{P}_1$	50	1.0937	.088	081	1.0719	.057	70	.189	1,1820	.161	.136	.113
	Corrected	weignt Flow W/#/8 lb/sec		9.7	7.2	13.0	121,61	38.4		29.8	142.02	63.5	80.3	93.5
		Foint Number		<del></del>	-	-	218	$\vdash$		0	210	Н	Н	0

Table B-1. Overall Performance (Continued) Intermediate Configuration

		$\eta_{\rm P}$ %		0		7	89.8	φ.		3	ന്	88.0	0	<u>,</u>
	Stage	Jad%		9.36	98.6	6.65	89.55	8.50		2.75	2.12		9.92	9.52
		$\overline{P}_{2A}/P_0$		.236	.236	.232	1,2085	.141		1.4105	415	1.4085	.356	. 223
	otor	$\eta_{\mathrm{p}\%}$		5	ñ	ω	91.8	5	rd	⇉	⇉	9.98	М	ഗ്ര
	Guide Vane Rotor	$\eta_{ad\%}$	r Speed	4.8	3.0	8.2	91.45	5.0	or Speed	3.8	3.5	85.93	1.0	3.0
	Guide	$\overline{P}_2/P_0$	Equivalent Rotor Speed	.254	,246	:237	1,2132	.152	Equivalent Rotor	416	.423	1,4010	.361	.232
		7 p%		Ŋ	⇉	9	2	<b>97.</b> 4	E.		7	6.98	2	4
) )	Rotor	nad%	% Design	5.2	(C)	0.0	2.4	97.29	0% Desi	္ထ	3.5	9	1.7	74.46
		$\overline{P}_{2}/\overline{P}_{1}$	80	.255	247	239	215	1,1558	10	T † *	42	. 40	36	• ,•
	Corrected	Weight Flow $W/\theta/\delta$ lb/sec		797	50.2	71.3	88.9	217.93		6.06	99.5	16.	38.1	ιν.
		Point Number		203	200	20.5	206	202		0	0	ြော		196

Table B-2. Blade Element Data SLTO Configuration

			CONF	CONFIGURATION	N/Ve	2/0/2	۰,				
90	PERCENT SPEED	PT. 14	7	SL TO	3010.	92.57					
								ROTOR			
		INLET GUIDE VANE	E VANE								
PCT SPAN	Ö	02	C)	ć	<u>.</u>	PCT SPAN	36	۶	50	Ę	ç T
DIA 3	21,150	26.050	30.950	35,850	40.750	DIA 6	23,385	27.755	32,125	36,495	40.865
BETA 3	00000	0.000	0.000	000.0	00u*0	BETA 6	0.240	0.874	-0.462	-1-120	-3.352
3 TA 4	138	484	151 75	155 00	13.459		204.84	54.707	51.618	45.463	44.033
> > 0 4	139.12	154.69	160-03	165.16	163.45	RETAIDR 7	30.876	47.209	54.368	55.273	50.822
VZ 3	138.93	146.32	151.74	155.08	155.84		153.73	161.86	165.85	175.21	172.28
4 Z V	139.11	153.83	160.02	165.12	163.16	<b>~</b> ^	291.19	266.26	260.66	278.50	276.09
V-THETA 3		00.0	00.0	00.0	00.0	9 ZA	153.69	161.67	165.81	175.16	171.98
		2.66	-1.19	-3.39	-9.86	7 ZV	191.80	153.66	161.75	193.56	195.45
	0.1246	0.1315	0.1362	0.1392	0.1399	V-THETA 6	0.64	2.47	-1.34	-3.42	-10.07
*		0.1388	0.1436	0.1483	0.1467		218.10	217.32	204.33	200.21	195.00
TURN	-0.28	-0.98	0.43	1.18	3.46	V(PR) 6	342.9	396.6	454.6	513.5	573.2
13	<u>ਬ</u> )	(REFER TO 70%	& 100% SPEED	DATA)			224.8	226.5	277.8	339.8	388.8
3 2					0	VIHETA PR6	-306-5	-362.1	-423.3	-482.7	-546.R
DIAC	100.0	-0.046	00.000	-0.076	-0.080	HETA	-115.4	-166.2	-225.8	-279.3	-336.1 534 70
<u>.</u>	0002.0	0061-1	65000	CC00•1	0.1933		333.46	20**00	421.92	479.51	521.12
INCIOM	-50.200	-20.200	-50.200	-20.200	-50.200	- x0	0-1383	0-1453	0.1489	0-1573	0.1547
DEVM	5.116	2.716	2,326	1.477	1.859	× ×	0.2596	0.2367	0.2315	0.2471	0.2446
				-			0.3077	0.3560	0.4081	0.4611	r.5147
						M(PR) 7	0.2004	0.2013	0.2467	0.3016	0.3444
		STATOR	æ			TURN( PR)	32.486	18.706	14.234	14.782	12.717
						13	0,1318	0.2543	0.3237	0.2437	0.2687
PCT SPAN	06	20	50	30	10	DFAC	.5765	.6423	.5792	.5150	668η.
DIA 9	26.021	29.683	33,345	37.007	40.669	EFFP	1.0564	0.9054	0.8970	0.9115	0.8529
4	47.597	53,512	50.039	44.301	43.054	EFF	1.0570	0.9043	0.8957	2016-0	0.8508
8ETA 10	0.288	1.200	0.030	1.342	2.281	INCIDM	14.768	13.438	12.507	10.456	9.340
o :	288.30	265.71	262.73	285.37	285.89			;		,	1
_	166.33	184.79	187.35	219.23	249.19	DEVM	12.076	11.709	12.268	6.673	6.922
6 7 1	191.48	156.71	168.04	204.06	208.90						
21.5	70.401	183.02	186.51	2003	00.647						
V-INTER V	28.717	213.62	201.38	144.51	87.48						
	0.04	79.0	0.22	0 2532	9.96						
· =	0.1477	0.1639	0.1550	0.1941	2000						
	47.309	52.312	50-00-	47.958	40.773						
12	0.2531	0.1709	0.1983	0.2049	0.1413						
3 4 6	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	, 00	6								
UTAC	0.7034	0.6280	0.0240	0.5503	0.44439						
INCLOM	2104.0 9.697	0.5218 16.412	15,339	10.301	7.05						
	900		1	i							
UEVM	8.988	8.700	7.530	9.342	11.161						

Blade Element Data SLTO Configuration (Continued) Table B-2.

			CONFIGURATION	RATION	N/V 60	8/8/m					
50 P	PERCENT SPEED	PT. 14	8	SLTO	3000	100.7					
		TNLAM GITTOR	TVANE					ROTOR			
PCT SPAN	06	70	20	30	10	PCT SPAN	96	10	20	30	υl
DIA 3	21.150	26.050	30.950	35.850	40.750	DIA 6	23,385	27.755	32,125	36,495	40.865
BETA 3	0.000	000.0	000.0	0.000	00000	BETA 6	0.276	0.534	-0.887	-1.586	-4.519
ETA	0.326	0.622	-0.862	-1.665	-4.510		48.993	49.520	45.455	41.272	30.167
	150.55	159.36	165,53	169.10	169.78	BETA(PR) 6	61.326	64.022	66.554	68,395	71.227
4 ° 7	153.60	168.11	1 /4. /4	180.01	160.77		147 02	174 45	0/0.25	197.46	104. L4:
VZ 45	153.59	166.96	174.71	179.93	178-13	o ~ > >	293.84	268.22	265.81	280.42	274.41
THETA	00.0	00.00	00.0	00.0	00.0	VZ 6	166.97	176.23	183.61	191.29	186.91
V-THETA 4	0.87	1.82	-2.63	-5.23	-14.05	7 ZV	191.72	173.94	186.35	210.72	212.75
	0.1351	0.1430	0.1486	0.1518	0.1524	V-THETA 6	0.80	1.64	-2.84	-5.30	-14.77
4	0.1378	0.1509	0.1569	0.1617	0.1605	V-THETA 7	221.74	204.02	189.44	184.97	173.31
TURN	-0.33	-0.62	0.86	1.67	4.51	V(PR) 6	348.0	405.4	461.5	516.5	580.6
13		(REFER TO	0 70% & 100%	SPER		V(PR) 7	222.3	2.69.2	303.3	360.9	414.8
3		•			1	VTHETA PR6	-305.3	-361.7	-423.4	-483.0	-546.7
DFAC	-0.017	-0.049	-0.064	-0.080	+60.0-	ETA	-110.6	-178.2	-239.3	-292.9	-356.7
EFFP	0.9649	1.0899	0.9150	1.0369	0.8061	ر ع : ح	306.11	363.31	420.52	477.72	534.92
MaidNI	-20,200	-20,200	-20.200	-20.200	-20.200	۰ <u>۰</u>	332,35	382.23	428.70	477.91	579.35
	T.	900	0	, ,	0	0 f	6647.0	0.1384	0.1000	0.1719	\$ 10 m
DEVM	2.0.4	2.0.0	20/.2	1.965	2.910		0.2620	0.2387	0.2363	0.2491	7.24.44
						0 F C C C C C C C C C C C C C C C C C C	0.5124	0.3014	0414.0	0.400	C12C*
						- X-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-	21 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	17770	1607	0.3200	2000
		CENTE	, p			LANINA	t/ t-10	166.00	00+++	171.41	Co
		OTHIC				13	0,1926	0,2622	0.2575	0.1808	0,1850
PCT SPAN	90	70	20	30	10	DFAC	.5938	.5790	.5182	.4685	.4381
OIA 9	26.021	29.683	33.345	37.007	699.04	EFFP	1.0029	0.9454	0.9404	0.9458	0.89N7
BETA 9	47.965	48.107	43.694	39.883	37.275	FFF	1.0030	0.9447	0.9396	0.9451	7.8887
Z E	1.304	1.902	1.701	5.104	0.743	INCION	12.726	11.522	10.454	8.795	8.020
6 >	289.91	268.67	270.04	286.94	284.13		1	1		1	
_	180,92	200.68	211.36	238.19	264.09	DEVM	11.045	13.163	9.970	2.00.5	0,240
6 74	79.061	17.771	84.461	220.04	226.09						
0	61.671	198.45	210.35	237.83	204.00						
V-THEIR 9	415.32	00.002	180.04	76.00 T	172.08						
	7030	0.00	7 9 9	0.00	3.42						
F 2	0.1505	0.1782	0.2401	0.2330	0.2341						
N	46.661	46.205	41.992	37.778	36.532						
	2305	0.1033	92.00	0.1172	0.0513						
13	0.6533	CC01.0	200	1 11 11 11 11 11 11 11 11 11 11 11 11 1							
DFAC	0.6534	0.5484	0.5109	0.4558	0.3595						
EFFP	0.4330	0.5225	0.3956	0.2535	0.2300						
INCIDM	<b>590.</b> L	11.007	8.994	5.883	1.275						
AVAC	10.00	97.00	0 201	200	6.64.0						
-	***	*	101.	***	1						

Table B-2. Blade Element Data SLTO Configuration (Continued)

Page				CONFIG	CONFIGURATION	N/S	w/@/x					
### 12.150 2.000 3.00 1.00 PRT SPM 9.00 7.7 Sch 3/0  1.3 2.1150 2.000 3.090 3.5850 0.100 PRT SPM 9.00 7.7 Sch 3/0  1.4 0.1000 0.0000 0.	9 09	PERCENT SPEE	PT. 14	6	SL T0	3040.	106.9					
Shift   State   Court   State   Stat									ROTOR			
13.150   2.00   2.00   3.0   10   10   10   10   10   10   10			ತ	VANE								
1.3   2.000   0.000		06	02	50	30	10		06	۲,	ŗ.	36	
1.   1.   1.   1.   1.   1.   1.   1.	DIA 3	21.150	26.050	30.950	35.850	40.750	DIA 6	23,385	27,755	32,125	36.495	40.04
1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1,			00000	00000	0.000	0.000		0.533	0.670	-0.793	-1.521	-4.50
155.40   165.45   175.41   179.45   180.32   180.32   180.47   177.21   187.25   177.21   187.24   175.11   179.45   180.31   175.45   175.45   175.45   180.31   175.45   1		0.615	0.190	-0.845	-1.587	-4.456	<b>.</b>	50.150	47.238	45.449	40.483	27.316
165.66   185.67   185.67   190.94   190.37   190.94   190.97   190.97   1		159.90	169.54	176.11	179.65	180,32	2	60.149	62.805	65.426	07.517	75.47
Hera   155.85   165.31   176.10   170.64   180.31   7 6   170.10   170.64   180.31   7 6   170.10   170.64   180.31   7 6   170.10   170.64   180.31   7 6   170.10   170.64   180.31   7 6   170.10   170.64   180.31   7 7   170.71   180.70   170.71   170	4 >	164.46	178.24	185.27	190.94	190.37	2R.)	27.222	43,731	49.649	53.155	57.00
Heff A   10.445   176.95   185.25   190.87   189.80   V   V   20.41   231.13   231.25   230.99     Heff A   1.75   2.46   -2.73   -5.29   -14.79   V   V   V   V   V   V   V   V   V		159.89	169.31	176.10	179.64	180,31		177.13	188.26	196.16	232.65	00
1.15	*	164.45	176.95	185.25	190.87	189.80	۸ <u>۲</u>	306.91	283.13	281.23	290,99	2 B.6. 7
Color   Colo		0.0	0.00	00.00	00.0	0.00	9 2/	177.07	188,02	196.10	202.58	4
0.1476 0.1601 0.1664 0.1715 0.1719 V.THFIA 0 2.129 2.7.29 4.115 0.1719 0.1714 A 0.1601 0.1664 0.1715 0.1719 V.THFIA 0 2.129 2.7.18 4.115 0.1601 0.1664 0.1715 0.1719 V.THFIA 0 2.129 4.115 0.1601 0.1664 0.1715 0.1719 V.THFIA PR 2.125 2.7.18 4.115 3.7.18 4.115 0.1601 0.1664 0.1715 0.1719 0.1719 0.1719 0.1719 3.5.18 4.115 3.7.18 4.115 0.1019 0.1719 0.1719 0.1719 3.5.18 4.115 0.1719 0.1719 0.1719 3.7.12 4.7.19 3.6.11 0.1719 0.1719 3.7.12 4.7.10 4.7.19 3.7.12 4.7.19 4.7.19 5.7.19 4.7.19 5.7.1		1.76	2.46	-2.73	-5.29	-14.79		195.59	192.02	95.70c	221.28	0.00
Color   Colo		0.1435	0.1522	0.1581	0.1613	0.1619		1.65	2.23	10001	30.00	1 7 7 9
Charles 10   Cha	Ti so	10.6	1001	0.85	0.171	0.11.0		30.00	411.5	471.6	529.7	, C
Charge 10						•	V(PR) 7	221.2	263.0	320.8	369.1	4.7 A
-0.022 -0.044 - 0.060 -0.0768 -0.097 VHETA PR7 -1101.2 -170.5 -274.6 -2705.4 1 1.1669 1.1205 0.9217 1.0265 0.8979 U 6 310.19 36.19 474.1 444.79 1.1205 0.9217 1.0205 0.8979 U 7 336.79 310.19 36.19 474.1 444.79 1.1205 0.9217 1.0205 0.8979 U 7 336.79 310.19 36.19 474.1 444.79 1.1205 0.20.200 -20.200 -20.200 U 7 336.79 310.19 31.95 0.2279 0.175 0.155 0.2279 0.175 0.1	3	ਕ (*					VTHETA PR6	-308.5	-365.9	P.854-	-489.5	-552
1.1669   1.1205   0.9217   1.0265   0.8979   U   C   316.19   376.19   494.29	DFAC	-0.023	-0.044	-0.060	-0.078	-0.097	VTHETA PR7	-101.2	-179.5	-244.6	-205.4	- 282
M -20.200 -20.200 -20.200 -20.200 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	EFFP	1.1669	1.1205	0.9217	1.0265	0.8979	9 0	310.19	368.16	424.12	484.09	E 4.7
Head	W010W1	-20.200	-20.200	-20.200	-20.200	-20,200		336.79	387.32	434.41	484.79	336.
STATOR B  STATOR		785	0.00	ני ני		ì		0.1591	6.1691	0.1753	1331	X \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
STATOR B  STATOR	DEVM	3	076-3	ر.، رن.>	1.00/	2.850	7 (00 J N	0.2736	C-2527	7.022.0	7.4.7363	407. 7 23.7
## 90							M(DR) 7	0.1071	0.2341	0,0853	0.3279	7.200
Name							TURN (PR.)	32.920	19,745	15.732	14,360	17.50
M         90         70         50         30         10         DFAC         .6192         .5578         .4μ916         .4μ67           26.021         29.683         33.345         37.007         40.669         EFFP         0.9201         0.9201         0.9341         3.9084           9         48.970         45.675         40.951         37.127         35.494         EFF         0.9201         0.9202         0.9341         3.9084           10         48.970         45.675         40.951         39.127         35.494         EFF         0.9201         0.9202         0.9341         3.9084           10         48.970         26.27         27.89         295.98         24.097         DEVM         8.422         10.531         7.569         4.555           199.46         21.09         226.40         251.56         276.24         0.2404         0.842         10.531         7.569         4.555           199.46         10         14.54         0.2546         0.2544         0.2404         0.2404         0.2544         0.2544         0.2544         0.2544         0.2544         0.2544         0.2544         0.2544         0.2544         0.2544         0.2544         0.2544<			STATO				13	0,1949	0.2400	0.2251	0.1522	0.155
26.021 29.683 33.345 37.007 40.669 EFF	PCT SPAN	8	02	Ç	0.6	O.	טניע	.6192	.5578	9167	799n	.h275
48.970         45.675         40.951         39.127         35.494         EFF         0.9192         0.9226         0.9072         0.9072         0.9072         0.9072         0.9072         0.9072         0.9072         0.926         0.9072 <td>DIA 9</td> <td>26.021</td> <td>29,683</td> <td>33,345</td> <td>37,007</td> <td>40.669</td> <td>9 4 4</td> <td>0.9201</td> <td>C. 9731</td> <td>10800</td> <td>3,9084</td> <td>.07</td>	DIA 9	26.021	29,683	33,345	37,007	40.669	9 4 4	0.9201	C. 9731	10800	3,9084	.07
10 4.261 1.866 1.186 1.726 1.027 INCIDM 11.5µ9 10.305 9.326 7.917 30.260 284.37 286.24 297.89 295.98 INCIDM 11.5µ9 10.305 9.326 7.917 195.82 196.83 215.45 297.89 295.98 INCIDM 11.5µ9 10.305 9.326 7.917 195.82 196.83 215.45 230.98 240.97 INCIDM 11.5µ9 10.531 7.599 4.555 196.83 215.45 230.98 240.97 INCIDM 11.5µ9 10.531 7.599 4.555 196.83 215.45 230.98 240.97 INCIDM 11.85 INCIDM 11.	BETA 9	48.970	45.675	40.951	39.127	35.494	FF	0.9192	0.9222	F 9 60 9 7	5.9672	0,840
302.60 284.37 286.24 297.89 295.98 195.73 1286.24 297.89 295.98 195.73 214.24 226.40 251.83 276.30 DEVM 8.422 10.531 7.589 4.555 195.73 215.45 230.80 240.97 193.46 211.92 225.50 251.85 276.24 226.24	BETA 10	4.261	1.866	1.186	1.726	1.027	INCIDM	11.549	10.305	9.326	7.917	7.22
195.73	6 ×	302.60	284.37	286.24	297.89	295.98	1			ì	7,00	à
193.46 219.49 251.50  193.46 218.27 203.43 187.60 251.56  ETA 10 14.54 6.97 4.69 7.58  ETA 10 14.54 6.97 4.69 7.58  0.1737 0.1902 0.2546 0.2647  4.4709 43.809 39.765 37.401.  0.6214 0.5301 0.4902 0.4381  0.5576 0.6465 0.5567 0.5599  DN 8.070 8.575 6.251 5.127	0 5	195.73	214.24	226.40	251.83	27.6.30	DEVM	224.8	164.01	۲۰۷۰)	4.555	T
THETA 9 228.27 203.43 187.60 187.98  THETA 10 14.54 6.97 4.69 7.58  0.2697 0.2532 0.2546 0.2647  10 0.1737 0.1902 0.2009 0.2234  RN 44.709 43.809 39.765 37.401.  AC 0.6216 0.5301 0.4902 0.4381  FP 0.5576 0.6465 0.5567 0.5599  CIDM 12.961 9.366 8.686 9.726	77 70	193.46	211.92	225.50	251.56	240.91						
10 14.54 6.97 4.69 7.58 0.2697 0.2532 0.2546 0.2647 0.1737 0.1902 0.2009 0.2234 44.709 43.809 39.765 37.401. 0.6241 0.0769 0.1043 0.0759 0.6216 0.5301 0.4902 0.4381 0.5576 0.6465 0.5567 0.5599 8.070 8.575 6.251 5.127	THETA	228.27	203.43	187.60	187,98	171.85						
0.2697 0.2532 0.2546 0.2647 0.137 0.1902 0.2009 0.2234 44.1709 43.809 39.765 37.401. 0.2241 0.0769 0.1043 0.0759 0.6216 0.5301 0.4902 0.4381 0.5576 0.5557 0.5599 0N 8.070 8.575 6.251 5.127 0.2961 9.366 8.686 9.726		14.54	6.97	4.69	7.58	4.95						
0.1737 0.1902 0.2009 0.2234 44.709 43.809 39.765 37.401. 0.2241 0.0769 0.1043 0.0759 0.6216 0.5301 0.4902 0.4381 0.5576 0.6465 0.5567 0.5599 DN 8.070 8.575 6.251 5.127 12.961 9.366 8.686 9.726		0.2697	0.2532	0.2546	0.2647	0.2627						
44.709 43.809 39.765 37.401. 0.2241 0.0769 0.1043 0.0759 0.6216 0.5301 0.4902 0.4381 0.5576 0.6465 0.5567 0.5599 DM 8.070 8.575 6.251 5.127 12.961 9.366 8.686 9.726	₩ 10	0.1737	0.1902	0.2009	0.2234	0.2450						
0.2241 0.0769 0.1043 0.0759 0.5216 0.5301 0.4902 0.4381 0.5576 0.5567 0.5599 0.590 0.5599 0.5567 0.5599 0.5599 0.556 8.686 9.726	TURN	44.709	43.809	39.765	37.401	34.467						
0.6216 0.5301 0.4902 0.4381 0.5576 0.5576 0.5599 0.5599 0.5770 8.575 6.251 5.127 0.5599 0.5561 0.5599 0.5599 0.5590 0.559	13	0.2241	6920°0	0.1043	0.0759	0.0392						
0.5576 0.6465 0.5567 0.5599 0 0M 8.070 8.575 6.251 5.127 12.961 9.366 8.686 9.726	DFAC	0.6216	0.5301	0.4902	0.4381	0.3410						
12.961 9.366 8.686 9.726	EFFP	8.070	0.6465	0.5567	6.5599	0.8047						
12,961 9,366 8,686 9,726			<u> </u>									
	DEVM	12.961	9.366	8.686	9.726	6.927						

Blade Element Data SLTO Configuration (Continued) Table B-2.

FOT SPAN 9C 01A 3 01A 3 01A 3 01A 3 01BETA 4 00BETA 6 00BETA 7 00BETA 7 00BETA 7 00BETA 7 00BETA 8 00BETA 9 00BETA 10 00BE	ANE  50 30,950 0,000 0,0	TINNNN ICC TOT	121.2 PCT SPAN DIA 6 BFTA 6 BFTA 6 BFTA (PR) 5 BFTA (PR) 7 V 7 V 7 V 7 V 7 V 7 V 7 V 7 V 7 V 7 V	96 73.385 39.448 39.448 56.462 32.448 20.3.24 20.3.24 187.53 187.54 271.3 271.3 271.3	BOTOR 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	3.5 50 - 0.0 3.4 3.6 5.0 3.4 3.6 5.0 3.4 3.8 5.0 5.0 5.0 5.0 5.0 5.0 5.0 5.0 5.0 5.0	2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	4
FILET GUIDE V  10.150	50 950 942 942 942 943 1.84 1.84 1861 1905 1906 1906 1906 1906 1906 1906 1906 1906		PCT SPAN  D1A 6  BFTA 6  BFTA 7  RFTA 7  RFTA 7  RFTA 7  RFTA 7  V 7  V 7  V 7  V 7  V 7  V 7  V 7	90 73.385 7.454 39.448 56.462 32.824 273.824 273.824 273.824 274.18 274.97 187.59 187.59 187.59 187.59 187.59	ROTOR 7.7.755 7.4.467 34.467 54.867 54.816 216.91 216.91 216.91 220.67 157.01 455.01 455.01 323.5 355.6 365.73		24. 44. 45. 46. 46. 46. 46. 46. 46. 46. 46. 46. 46	7 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 -
21.150 26.750 0.000 0.200 0.537 0.200 0.537 0.203.54 181.78 192.95 181.77 192.69 181.77 192.69 181.77 192.69 181.77 192.69 181.77 192.69 181.77 192.69 0.000 0.446 0.1633 0.1734 0.1633 0.1734 0.0000 0.0000 0.0000 0.0000 0.0000 0.0000 0.0000 0.0000 0.0000 0.0000 0.0000 0.0000 0.0000 0.0000	a		PCT SPAN DIA 6 BFTA 6 BFTA 7 RFTA[DR] 5 RFTA[DR] 7 V 7 V 7 V 7 V 7 V 7 V 7 V 7 V	23.385 23.485 39.466 36.462 20.812 20.812 20.812 20.92 1.62 1.62 1.87 1.62 1.63 1.63 1.63 1.64 1.6	27 - 75 - 75 - 75 - 75 - 75 - 75 - 75 -	32 - 125 - 0.934 - 0.934 - 0.934 - 0.93 - 83 - 0.93 - 0.93	34 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	7 - 4 - 4 - 4 - 4 - 4 - 4 - 4 - 4 - 4 -
21.150 26.050 0.000 0.000 187.93 203.54 187.93 203.54 187.92 203.54 187.92 203.54 187.92 203.69 0.1639 0.1734 0.1639 0.1734 0.1639 0.1734 0.1639 0.1734 0.1639 0.1734 0.1734 0.1734 0.1639 0.1734 0.1734 0.1734 0.1734 0.1734 0.1734 0.1734 0.2020 -20.200 1.003 1.003 26.021 29.683 3.571 32.848 3.574 32.84	a a		014 6 8FTA 6 8FTA 7 8FTA 7 8FTA(PR) 5 8FTA(PR) 5 V 7 V 6 V 7 V 7 V 7 V 7 V 7 V 1 V 7 V 1 V 8 V 1 V 1 V 1 V 1 V 1 V 1 V 1 V 1 V 1 V 1	73.385 7.454 39.444 30.446 30.416 20.816 20.97 20.97 187.59 187.59 271.3 -30.65 -147.5	27.755 34.002 34.002 56.346 27.6.61 27.6.61 27.6.61 67	32.125 32.125 32.838 62.838 62.838 50.537 50.537 731.55 140.55 140.55 140.55 785.0 785.0 785.0	14.499 10.489 10.489 10.489 10.489 10.489 10.489 10.489 10.489 10.489 10.489 10.489 10.489 10.489 10.489	7. 20 20 20 20 20 20 20 20 20 20 20 20 20
0.000 0.000	a as		8FTA 6 8FTA 7 8FTA(PR) 5 8FTA(PR) 5 8FTA(PR) 7 V 5 V 7 V 6 V 7 V 7 V 7 V 7 V 1 V 1 V 1 V 1 V 1 V 1 V 1 V 1 V 1 V 1	7.454 39.448 56.462 32.812 273.23 273.23 273.23 273.23 1187.53 1187.54 271.3 271.3 -376.5 -1476.5	24.477 54.4477 54.4467 64.814 64.814 67.617	10.934 622.838 622.833.838 50.533.93 223.835 233.835 14.3.55 482.1 365.0 1242.0	1.480 54.487 54.487 52.00 52.00 52.00 52.00 52.00 53.00 53.00 53.00 53.00 53.00 53.00 53.00 53.00 53.00 53.00 53.00 50 50 50 50 50 50 50 50 50 50 50 50 5	7.558 7.558 7.558 7.758
0.537	α <u>α</u>		RFTA 7 RFTA(PR) 5 BFTA(PR) 7 V 7 V 7 V 7 V 7 V 7 V 7 V 1 HETA 7 V 1 PR 9 V	39.449 35.462 32.826 295.23 295.24 295.24 1.62.90 1.87.59 1.87.59 1.87.59 1.87.59 1.87.59 1.87.59 1.87.59	34.407 44.407 44.407 216.914 217.86 227.61 0.10 157.01 475.01 373.2 -365.6 -265.6 -365.6	32.838 50.333 50.333 50.333 50.333 50.335 60	50.467 54 467 56 482 581 - 58 581 - 58 587 - 67 142 - 77 142 - 77 4 - 146 - 4 4 - 67 4 - 67 6	26.574 57.04
181.78 192.95 187.93 263.54 187.92 263.54 187.92 762.14 3 0.00 4 1.76 0.1734 0.1633 0.1734 0.1848 F.1439 -0.079 -0.054 0.7981 0.9866 -20.200 -20.20 4.863 3.571  STATOR E 3.564 1.19 256.15 28.683 3.574 251.40 228.99 235.16 228.99 235.16 228.99 235.16 228.99 235.16 228.99 235.16 228.99 235.16	α <u>α</u>		8FTA(PR) 5 8FTA(PR) 7 V 6 V 7 VZ 7 VZ 7 V 1 HFTA 7 V 1 PR 9 R 5 V 1 HFTA PR 5 V 1 HFTA	36.462 37.812 273.24 295.25 206.97 187.59 187.59 271.3 -306.5 -147.5	59.340 216.414 216.67 217.86 229.01 0.10 157.01	62.333 62.333 223.592 223.85 231.59 482.1 462.1 267.0 -267.0	64.742 529.46 529.46 529.57 529.57 142.77 538.1 416.4 -416.8	7.27.65 22.7.7.7.2.2.2.2.2.2.2.2.2.2.2.2.2.2.2.
187.93 263.54 181.77 192.69 181.77 192.69 181.77 192.69 187.92 272.14 0.1633 0.1734 0.1638 0.1734 0.1638 0.1734 0.1638 0.1734 0.1638 0.1734 0.1848 0.1734 0.7981 0.9866 -20.200 -20.200 1.085 3.571 3.571 3.572 3.574 3.51.40 2.28.99 2.25.14	α <b>α</b>		8FTA(DP) 7 V 5 V 7 V 2 7 V 2 7 V 2 7 V 2 7 V 1 PETA 7 V 1 DE 9 V 1 PETA PRS V 1 PET	32.812 295.23 203.24 205.23 205.91 1.65 1.65 187.59 271.3 -30.65 -147.5	44.814 2715.01 2715.01 220.01 70.10 157.01 425.1 323.2 -365.6 -267.8 385.6	50.592 223.91 2233.91 2223.878 231.59 23.55 1482.1 482.1 467.0 2252.1	54.346 281.58 281.58 229.27 247.67 142.77 538.1 416.4 -486.8	2004.09 2004.09 2004.09 2004.09 2004.09 2004.09 2004.00 2004.00 2004.00 2004.00 2004.00 2004.00
181.77 192.69  187.92 2.72.14  0.00 0.00  1.76 0.1734  0.1688 0.1734  0.1688 0.1734  0.1689 0.1734  0.1689 0.1734  0.178 0.1829  -0.029 -0.054  0.7981 0.9866  -20.200 -20.200  1.063 3.571  STATOR B  3.574 32.848  3.574 1.119  295.15 29.683  3.574 1.119  295.15 29.683  3.574 25.140  228.99 2.35.16  228.99 2.35.16  228.99 2.35.16  228.99 2.35.16  228.99 2.35.16	ପ୍ର		V 6 V 7 V 2 6 V 2 7 V 2 7 V 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	273.24 295.23 204.18 226.97 1.65 187.59 367.8 277.8 -306.5 -147.6	216.91 277.86 216.67 229.61 157.61 157.61 425.1 365.6 -265.6 -365.6 365.73	223.91 223.85 223.85 231.59 -3.55 140.55 482.1 365.0 -262.0	229.36 2291.58 229.627 249.627 142.77 538.1 416.4 -486.8 -378.3	224.99 2287.83 2287.83 17.87 1
3 0.00 0.00 4 0.1633 0.174 6.1633 0.1734 6.1634 0.1829 -0.54 0.1829 -0.079 0.0866 -20.200 -20.200 4.863 3.571  STATOR E 3.564 1.119 295.15 29.683 3.574 251.40 228.99 235.16 228.99 235.16 228.99 235.16 228.99 235.16 228.99 235.16 228.99 235.16 228.99 235.16 228.99 235.16	ය යු		V 7 VZ 6 VZ 7 VZ THETA 6 V 1 PR 1 6 V 1 PR 1 7 V 1 PR 1 A PR 5 V 1 HETA PR 5 V 1 HETA PR 7 V 1 6 V 6	295.23 226.97 1.62.97 1.87.59 187.59 277.93 -306.5 -147.7 3.44.57	277.86 226.67 229.67 7.10 157.01 425.1 323.2 -355.6 -277.8 365.73	275.78 231.59 231.59 140.55 1482.1 365.0 -262.0	281.58 242.27 242.67 142.77 538.1 416.4 1286.8	287.83 224.27 224.27 274.81 178.77 591.9 591.9 555.4 601.9 638.80 632.80
3 0.00 0.00 4 1.76 0.46 0.1688 0.1734 0.1688 0.1839 -0.554 -0.13 (REFER TO 708 & -0.054 0.7981 0.9806 -20.200 -20.200 4.863 3.571 STATOR E 3.574 3.848 3.564 1.19 25.021 29.683 3.574 25.16 25.921 29.683 3.574 25.848 3.574 25.848 3.574 25.848 3.574 1.19 25.921 29.683 3.574 1.19 26.021 29.683 3.574 25.848 3.574 1.19 25.931 77 251.40 258.99 235.16 258.99 235.16 258.99 235.16 258.99 235.16 258.99 235.16 258.99 235.16	a g		VZ 6 VZ T T A 6 V-THETA 6 V(PR) 6 V(PR) 7 VTHETA PR5 VTHETA PR5 U 6 U 7	200-10 200-90 187-59 187-59 271-3 -306-5 -147-5 2147-5	229.01 229.01 0.10 157.01 425.01 323.2 -355.6 -257.8 366.73	223.85 231.59 -3.65 149.55 482.1 365.0 -427.0	229.27 242.47 142.77 142.77 538.1 416.4 -426.8 -338.3	224.27 257.41 -17.87 128.77 500.8 479.1 -556.4 -6.4.1 538.40 0.2024
4 1.76 0.46 0.1633 0.1734 0.1638 0.1734 0.1638 0.1734 0.1848 10.708 & 0.1854 0.7981 0.9866 -20.200 -20.200 1.0863 3.571 STATOR E  3.574  3.574  3.574  3.574  3.574  3.574  3.574  3.574  3.574  3.574  3.574  3.574  3.574  3.574  3.588  3.888  3.888  3.888  3.888  3.888  3.888  3.888  3.888  3.888  3.888  3.8888  3.8888  3.8888  3.8888  3.8888  3.8888  3.8888  3.8888  3.88888  3.88888  3.88888  3.88888  3.88888  3.88888  3.888	A.		VZ 7 V-THETA 6 V-THETA 7 V(DR) 6 V(DR) 7 V(HETA PRS VTHETA PRS VTHETA PR7 U 6	726.90 187.59 187.59 367.8 271.3 -306.5 -147.0	229-01 0-10 157-01 425-1 323-2 -365-6 -227-8 365-73	231.59 -3.55 149.55 482.1 365.0 -427.0	247.67 14.5.02 14.2.77 5.02 14.2.77 41.6.4 14.2.8.3 42.3.4 42.3.9	757.41 17.87 17.87 17.87 1.67.6 1.67.6 1.67.6 1.67.6 1.67.6 1.67.6 1.67.6 1.67.6 1.67.6 1.67.6 1.67.6 1.67.6 1.67.6 1.67.6 1.67.6
0.1648	A		V-THETA 6 V-THFTA 7 V(PR) 6 V(PR) 7 V(HFTA PR5 VTHFTA PR7 U 6 U 7	1.62 1.87.59 3.67.8 2.71.3 -1.47.6 3.7.6 3.7.6 3.7.6 3.7.6 3.7.6 3.7.6	0.10 157.01 425.1 323.2 -365.6 -257.8 365.73	149.55 149.55 482.1 365.0 -427.0 -282.7	142.77 142.77 538.1 416.4 1486.8 1328.3	17.87+ 17.87+ 17.87+ 17.87-
0.1688	Gi .		V-THFTA 7 V(PR) 6 V(PR) 7 VTHFTA PR5 VTHFTA PR7 U 6 U 7	187.59 267.9 271.9 1976.5 187.4 78.15	157.01 425.1 323.2 -365.6 -227.8 365.73	149.55 482.1 365.0 -427.0 -262.1	142.77 538.1 416.4 1486.8 -338.3	108.77 108.74
-0.54 -0.13  (REFER TO 70% & -0.029  -0.029 -0.054  0.7981 0.9866  -20.200 -20.200  4.863 3.571  STATOR E  3.577 29.683  3.574 29.848  3.574 1.119  25.77 251.40  258.99 235.16  228.99 235.16  228.99 235.16  228.99 235.16  228.99 235.16  228.99 235.16  228.99 235.16  228.99 235.16  228.99 235.16  228.99 235.16	A .		V(PR) 6 V(PR) 7 VTHETA PR5 VTHETA PR7 U 6 U 7	367.8 271.3 -306.5 -147. 378.15	425.1 323.2 -365.6 -227.8 365.73	482.1 365.0 -427.0 -282.1	538.1 416.4 486.8 -378.3 48.3	44041 -556.4 -676.4 -404.1 -404.1 -404.1 -407.4 -407.4
(REFER TO 70% & -0.029 -0.054 0.9866 -20.200 -20.200 4.863 3.571 STATOR E STATOR E 3.57.78 32.848 3.57.78 32.848 3.57.79 55.15 258.99 235.16 228.99 235.16 228.99 235.16 228.99 235.16 153.14 153.14 153.14	A	•	V(PR) 7 VIHETA PR5 VIHETA PR7 U 6 U 7	2710-3 -3066-5 -1470-6 324-15	323.2 -365.6 -227.8 365.73	365.0 -427.0 -262.0 423.32	416.4 -486.8 -328.3 48.90	470.1 -556.4 -404.1 528.40 632.80
(REFER TO 70% & -0.029 -0.054	A	•	VTHETA PRS VTHETA PR7 U 6 U 7	-306.5 -147.° -348.15 -34.57	-365.6 -227.8 365.73 384.78	-427.0 -282.7 473.32	4446.8 -446.3 486.90	-556.4 -404.1 538.40 532.80 0.2024
-0.029 -0.054 0.7981 0.9866 -20.200 -20.200 4.863 3.571 STATOR E STATOR E 3.574 3.588 3.574 1.119 295.15 29.683 3.574 1.119 295.15 29.883 3.574 25.848 3.574 25.848 3.574 25.848 3.574 25.848 3.574 25.848 3.574 25.848 3.574 25.848 3.574 25.849			VTHETA PR7 U 6 U 7 W 6	-147°C 308°15 334°57	-227.8 365.73 384.78	-282.7	44 90	-404.1 538.40 532.80 0.2024
0.7981 0.9866 -20.200 -20.200 4.863 3.571 STATOR E 26.021 29.683 3.574 32.848 3.574 1.119 295.15 29.683 3.574 1.119 295.17 251.40 251.77 251.40 228.99 235.16 228.99 235.16 228.99 235.16 228.99 235.16 228.99 235.16 15.39 4.91		•	C D D Z ;	408.15 424.57	365.73	473. 12	ψ6 * 28.42	538.47 537.80 0.2024
20.200 -20.200 4.863 3.571  STATOR E  26.021 29.683 37.778 32.848 3.564 1119 295.15 29.34 251.77 251.40 228.99 235.16 228.99 235.16 228.99 235.16 228.99 235.16 15.39 4.91		,	F 4 1	334.57	384.78			532.80 0.2024
4.863 3.571  4.863 3.571  STATOR E  57.778 32.848 37.778 32.848 37.778 32.848 37.778 32.848 37.778 32.848 37.778 32.848 37.778 32.848 37.778 32.848 37.878 32.848 37.878 32.848 37.878 32.848 37.878 32.848 37.878 32.848 37.878 32.848 37.878 32.848 37.878 32.848 37.878 32.848 37.878 32.848 37.878 32.848 37.878 32.848 37.878 32.848 37.878 32.848 37.878 32.848	ř ·	002.02-	√ (1 3: 3:	1000		431.55	491.10	5057 U
90 70 70 70 70 70 70 70 70 70 70 70 70 70		070	.:	1281.	0.1950	0.2014	6476.0	
STATOR 5  90 70 26.021 29.683 37.778 32.848 3.564 1.19 295.15 251.77 258.99 258.99 258.99 249.03 9 180.81 153.94		8.8	>	C. 2637	0.2481	1.2459	0.2510	r.2563
90 70 70 70 70 70 70 70 70 70 70 70 70 70			M(PR) 6	6.3365	0.3823	0.4336	0.4941	7.495
90 70 26.021 29.683 37.778 32.848 3.504 119 295.15 292.34 251.77 251.40 228.99 235.16 249.49 249.03 9 180.81 153.14			M(PR) 7	r . 2423	0.2885	0.3255	0.3711	C-4267
90 70 26.021 29.683 37.778 32.848 3.564 1.119 295.15 787.34 251.77 251.40 228.99 235.16 249.49 249.03 9 180.81 153.14			( dg )Nafil	23.643	14.508	11.738	1.435	10.541
90 70 26.021 29.683 37.778 32.848 3.564 1.119 295.15 28.34 251.77 251.40 228.99 235.16 249.49 249.03 9 180.81 153.14			ū	0.1127	0.1260	0.1112	0.0083	0.1124
26.021 29.683 37.778 32.848 3.564 1.119 295.15 787.34 251.77 251.40 228.99 235.16 249.49 249.03 9 180.81 153.14	0.00	5	DE A C	27,11,75	3853	3766	. 34.93	.3158
37.778 32.848 3.564 1.119 295.15 28.34 251.77 251.40 228.99 235.16 249.49 249.03 9 180.81 153.14		74	0.1.1.1	1.1251	1-1687	1.1052	1.0882	1.0721
3.504 [1.119 295.15 282.34 251.77 251.40 228.99 235.16 249.03 9 180.81 153.14	442 29 254		LL LL	1.1264	1.1705	1,1065	1.0803	1.173
295.15 787.34 251.77 251.40 228.99 235.16 249.49 249.03 9 180.81 153.14 10 15.39 4.91		0.882	NOLUNI	7.862	6.819	6.233	5.182	1.845
251.77 251.40 228.99 235.16 249.69 249.03 9 180.81 153.14 10 15.39 4.91	12.54 290.42				:			
228.99 235.16 249.49 249.03 9 180.81 153.14 10 15.39 4.91			DEVM	14.012	12.314	8.492	5.746	109°17
249,49 249,03 9 180,81 153,14 10 15,39 4,91								
9 180.81 153.14 In 15.39 4.91	59.85 276.92							
in 15.39 4.91								
6.2521								
0.2245 0.2242								
31.728		•						
0.1240 0.0281	0.0494 0.0019							
#								
0.3597 6.3251								
10.4457 C.44137 C.44137 C.4137	-3.238 -1.716	10.21.8						
1/1:41								
DEVM 12.204 8.619 8	8.087 7.938	9.782						

Blade Element Data SLTO Configuration (Continued) Table B-2.

### STATES OF THE COLOR OF THE	PERCENT SPEED PT. 151  INIET GUIDE VANE  21.150	133.1					
### STATUS VANE  ### STATUS CULLUD VANE  ### STATUS CULLUD VANE  ### STATUS CULLUD VANE  ### STATUS CULLUD VANE  ### STATUS COLURN COLU	1 NIET GUIDE VANE  21.150 26.05 30.950 35.850 0.000 0.000 0.000 0.000 0.000 0.000 0.000 0.000 2.765 0.230 -0.989 1.571 209.04 225.49 233.35 227.85 209.02 224.18 233.30 237.65 0.00 0.00 0.00 0.00 2.79 0.1923 0.1991 0.2722 0.1879 0.202 0.009 0.2138 -0.76 0.203 0.209 0.2138 -0.76 0.002 2.008 1.571 20.200 -20.200 -20.200 -20.200 1.57 20.00						
0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0	21.150 26.050 35.850 35.850 0.000 0.			ROTO	~		
21.156   26.775   30.950   35.850   0.01.50   0.14 6   0.175   37.145   3	21.150		06	70	S.	ć,	13
0.700 0.000 0.000 0.000 0.000 BFTA 6 0.666 0.124 -0.893 -1.554 0.000 0.	0.000 0.000	01A 6	23,385	27.755	32,125	36.495	40.865
0.176 0.230 0.099 1.571 3.603 BFTA 7 36.76 32.184 28.752 26.461 9.1571 30.004 2.254.4 233.35 224.40 8FTAPP 1 57.799 66.181 95.575 46.1879 20.004 2.255.44 223.35 224.48 224.18 27.545 224.18 22	0.765 0.230 -0.989 -1.571 201.41 213.86 221.41 224.85 209.04 225.49 233.35 237.63 201.79 213.59 221.39 224.84 209.02 224.18 233.30 237.54 0.00 0.00 0.00 0.00 2.79 0.00 -4.03 233.37 0.1814 0.1923 0.293 0.2138 -0.76 -0.23 0.99 1.57 0.9843 1.7426 0.9280 1.0717 0.9543 1.7426 0.9280 1.0717 0.9543 1.7426 0.9280 1.0717 20.200 -20.200 -20.200 -20.200 0.0503 3.470 2.689 1.671 24.635 3.470 2.689 1.671 25.020 -20.200 -20.200 20.200 20.203 33.345 37.007 24.33 37.667 27.558 25.609 2.086 0.2987 0.169 29.51 188.31 161.69 145.87 138.36 0.2987 0.2883 0.2817 0.2858 0.0501 0.0259 0.0405 0.0257 0.2861 0.2886 0.2865 0.2875 0.5561 -6.500 -7.142 -8.391		0.666	0.124	-0.893	-1.540	-3.781
201.79 213.46 221.41 224.45 224.40 V 6 187.409 65.350 56.661 59.057 62.876 20.277 62.27.40 223.40 223.42 224.42 224.79 V 6 18.70 221.49 224.42 224.79 V 7 6 221.70 221.49 224.79 V 7 6 221.70 221.40 224.79 V 7 6 221.70 221.40 224.79 V 7 6 221.70 224.70 22	209.04 225.49 233.35 237.63 209.04 225.49 233.35 237.63 209.04 225.49 233.35 237.63 209.02 224.18 233.35 237.63 237.64 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0	BFTA 7	36.206	32.184	28.739	26.752	23.041
201.79 213.59 2213.45 224.76 224.77 V 5 27.67 40.132 46.819 51.194 20.00 2 224.18 231.35 224.84 224.79 V 7 370.09 221.39	209.04 225.49 233.35 237.63 201.79 213.59 221.39 224.84 209.02 224.84 233.30 2.79 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0		53,505	56.663	59.957	62.836	66.581
209,02 24,18 231,39 237,39 237,48 4 354,99 V 6 376,09 247,18 246,18 246,18 246,18 246,18 24,18 2	2C1.79 213.59 221.39 224.84 209.02 224.18 233.30 237.54 0.00 0.0 0.0 0.0 0.00 2.79 0.2023 0.099 0.2138 -0.1814 0.2028 0.299 0.2138 -0.1879 0.2028 0.299 0.2138 -0.02 -0.052 0.09280 1.671 2.020 -20.200 -20.200 -20.200 4.635 3.440 2.683 33.345 37.007 2.086 0.412 0.159 2.609 2.087 0.412 0.159 3.007 2.08 0.412 0.159 3.007 2.08 0.412 0.159 0.267 2.08 0.412 0.159 0.267 2.08 0.299 0.2817 0.285 0.2987 0.289 0.2817 0.2859 0.2987 0.2889 0.2817 0.2859 0.2987 0.2889 0.2817 0.2859 0.2050 0.0259 0.0405 0.0427 0.2861 0.2886 0.2817 0.3865 -6.501 0.0259 0.0405 0.03865 -6.501 0.0259 0.0405 0.3865		27.929	40.132	46.819	51.194	55.051
209,02 224,18 233,30 233,40 V7 5315,50 0.00 0.00 0.00 0.00 0.00 0.00 0.00	209.02	\$ ( > :	227.60	242.06	248.77	242.32	247.23
0.000 0.000	0.00 0.00 0.00 0.00 0.00 0.1814 0.273 0.1923 0.1941 0.2032 0.1879 0.2022 0.1879 0.2028 0.2028 0.2039 0.2138 0.99543 1.022 0.0029 0.2020	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	330.69	310.82	306.97	45.016	40.416
0.1814 C.1923 0.709 0.7009 0.7	2.77 0.1814	9 7 7 7	221.33	241.83	748.07	17.767	200
0.1814 (1.1923 0.1991 0.1272 0.1712 0.14Ft A 7 195.36 147.60 0.1814 (1.1923 0.1991 0.1272 0.1712 0.1814 0.1914 0.1922 0.1914 0.1	90		202.642	262-80	20.692	71.077	700.00
0.1879	0.1879		2.64	26.0	90.00	8) • 9-	-13.00
-0.76 -0.23 0.99 1.57 3.60 VPR) 6 387.6 440.2 496.8 511.9 46.02 40.02 1.57 3.60 VPR) 6 387.6 440.2 440.2 496.8 511.9 40.02 40.02 40.02 40.02 40.03 FPEED MAIN) VTHETA RR6 -30.7 6 -430.6 -430.6 6.03 6.0 1.07 6.1 0.01 7.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1.0 1	-0.76		195.33	165.56	147.60	69.661	172.91
(REFER TO 70% & 100% SPEED DATA)  (VIRT)  (C.229 -0.052 -0.063 -0.071 -0.084 VIRETA PR -141.5 -367.6 -490.0 -490.2 -0.052 -0.052 -0.071 -0.084 VIRETA PR -141.5 -367.6 -490.0 -280.200 -20.200	90		387.6	440.2	496.8	551.9	608°1
-0.029 -0.052 -0.052 -0.064 VIHETA PRS 141.5 -221.8 -245.8 -344.6 C.9543 1.0426 0.9280 1.0217 0.8914 U 6 710.1	-0.029 -0.052 -0.053 -0.071  0.9543 1.0426 0.200 -20.200  1.0426 0.2020 -20.200  2.049 1.0717  2.049 1.0717  2.049 1.0717  2.049 33.345 37.007  33.93 33.93 30.467 27.558 25.609  2.097 2.058 33.345 37.007  33.93 31.64 35.345 37.007  2.09 2.056 20.150 20.051  11.13 2.09 29.51  188.31 161.69 145.37 288.66  30.2987 0.2817 0.2858  0.0501 0.0259 0.0405 0.0237  0.2861 0.2886 0.2718  0.2881 0.2886 0.2818  0.0501 0.0259 0.0405 0.0237  0.560 0.2881 0.2888  0.0501 0.2886 0.2888  -6.561 -6.500 -7.142 -8.391	٠.	302.0	344.1	393.3	442.2	
-0.029	-0.029 -0.052 -0.063 -0.017 -0.020 -20.200 -20.200 -20.200  1.635 3.470 2.889 1.871  26.021 29.683 33.345 37.007  26.021 29.683 33.345 37.007  2.086 0.412 0.169 25.609  2.086 0.412 0.169 25.609  2.087 0.412 0.169 25.609  333.83 337.83 37.607  2.08 0.412 0.169 25.609  2.08 0.412 0.169 25.609  2.08 0.412 0.169 25.609  333.83 37.812 20.207  0.2987 0.2839 0.2817 0.2858  0.2987 0.2839 0.2817 0.2858  0.2531 0.2639 0.2618 0.2858  0.0501 0.0259 0.00405 0.0237  0.2861 0.2888 0.2718  0.2861 0.2888 0.2718  0.2861 -6.500 -7.142 -8.391	x 6	-30.7°	-367.6	0.084-	4.00	
(**554) 1.1426 U.92881 1.0217 U.53914 U.6 316.79 386.79 20.010 U.52540 1.0217 U.53914 U.6 316.79 386.79 386.79 20.0200 -20.200 -20.200 U.6500 -20.200 U.6500 -20.200 U.6500 -20.200 U.6500 U.6500 -20.200 U.6500 U.6	90	ž	-141.5	2221.8	-286.8	0 0 0 0 0	1413.3
-20.200 -20.200 -20.200 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	-20.200 -20.200 -20.200 -20.200  \$\frac{1}{4.635}\$ 3.470 2.889 1.871  \text{STATOR} B  \text{STATOR} B  \text{2.02} 2.683 33.345 37.007  26.021 20.683 33.345 37.007  26.021 20.683 33.345 25.609  2.08 0.401 27.558 25.609  305.68 291.50 27.558 25.609  2.08 291.50 27.558 25.609  2.09 271.50 294.44 290.54  2.09 7 294.54 290.54  2.09 7 294.54 290.54  2.09 7 294.54 290.54  2.09 7 294.54 290.54  2.09 7 294.54 290.54  2.09 7 294.54 290.54  2.09 7 294.54 290.54  2.09 7 294.54 290.54  2.09 7 294.54 290.54  2.09 7 294.54 290.54  2.09 7 294.54 290.54  2.09 7 294.54 290.54  2.09 7 294.54 290.54  2.09 7 294.54 290.54  2.09 7 294.54 290.54  2.09 7 294.54  2.		510	363.10	71.024	424.00	242.03
## 1	90 70 30 3.470 2.889 1.871 STATOR B  26.021 20.683 33.345 37.007 34.339 30.4670 27.558 25.609 2.087 33.83 317.64 315.37 320.11 305.68 291.50 294.44 290.54 270.97 271.50 294.44 290.54 2		336.19	587.52	1424.41	0.00.0	7.5.47
# PARTOR B TRATOR B T	STATOR B  26.021		2000	0.2777	0.2742	0.2770	0.2801
### STATOR B  #### PRINT C.2701 0.3075 7.3513 0.3447  ##### PRINT C.2701 0.3077 7.3513 0.3447  ##################################	STATOR B  26.021 29.683 33.345 37.007 34.339 3.660 27.558 25.609 27.868 291.50 294.44 299.54 270.97 271.50 294.44 299.54 270.97 271.50 294.44 299.54 270.97 293.40 299.51 188.31 161.60 145.87 138.36 11.13 2.09 0.2817 0.2858 0.0501 0.0259 0.0405 0.0237 0.5861 0.5878 0.0405 0.0237 0.6506 0.5071 0.4567 0.3865 -6.561 -6.500 -7.142 -8.391	M(PR) 6	0.3441	0.3961	0.4472	0.4969	0.5473
TURN (PP) 25.64 16.5 6 13.133 11.610  TURN (PP) 25.667 16.5 6 13.133 11.610  Z6.021 29.683 33.45 37.007 40.669 EFFP 1.0134 1.0138 1.0243 0.0774  Z6.021 29.683 23.45 25.609 22.189 FFF 1.0147 1.0138 1.0243 0.922  Z6.021 29.683 23.45 27.007 40.669 EFFP 1.0143 1.01243 0.922  Z6.02 20.5 6.4 290.5 6 22.189 FFF 1.0140 1.0243 0.922  Z6.02 20.5 6.4 290.5 6 20.2 6 0.0 25  Z6.02 20.5 6 20.2 6 20.2 6 0.0 25  Z6.02 20.5 6 20.5 6 20.5 6 20.5 6 20.5 6  Z6.02 20.5 6 20.5 6 20.5 6 20.5 6  Z6.02 20.5 6 20.5 6 20.5 6 20.5 6  Z6.02 20.5 6  Z6.02 20.5 6 20.5 6  Z	26.021 29.683 33.345 37.007 34.33.843 36.660 27.558 25.609 27.684 313.83 317.647 0.169 -0.676 313.843 317.64 315.30 320.11 305.68 291.50 294.44 299.54 290.51 181.3 2.09 0.2817 0.2858 0.0501 0.2659 0.2817 0.2858 0.0501 0.0259 0.0405 0.0237 0.2886 0.2888 0.0259 0.0405 0.0237 0.2886 0.2888 0.0259 0.0405 0.0237 0.2886 0.2888 0.0259 0.0405 0.0237 0.2886 0.2888 0.0259 0.0405 0.0237 0.2886 0.2888 0.0259 0.0405 0.0237 0.2886 0.2888 0.0405 0.0237 0.0259 0.0405 0.0237 0.0259 0.0405 0.0237 0.2886 0.2888 0.0405 0.0237 0.2888 0.2888 0.0405 0.0237 0.0237 0.0405 0.0237 0.0237 0.0405 0.0237 0.0405 0.0237 0.0237 0.0237 0.0259 0.0405 0.0237 0	M(PR) 7	0.2701	0.3075	7,3513	0.3947	0.4500
90 0.0978 0.0978 0.0977 0.0825 0.0774 26.021 29.683 33.345 37.007 40.669 EFF 1.0147 1.0138 1.0241 0.9922 34.339 33.345 37.007 40.669 EFF 1.0147 1.0138 1.0243 0.9921 24.339 31.764 315.37 20.676 1.157 INCIDM 4.905 4.161 3.857 3.206 333.83 317.64 315.37 320.11 318.71 INCIDM 4.905 4.161 3.857 3.206 333.83 317.64 315.37 20.518 20.025 0.0258 0.0258 0.0237 0.0233 0.0237 0.0233 0.0237 0.0233 0.0237 0.0233 0.0237 0.0233 0.0237 0.0233 0.0237 0.0233 0.0256 0.0406 0.0233 0.0406 0.0406 0.0233 0.0406 0.0233 0.0406 0.0233 0.0406 0.0233 0.0406 0.0233 0.0406 0.0233 0.0406 0.0233 0.0406 0.0233 0.0406 0.0233 0.0406 0.0233 0.0406 0.0233 0.0406 0.0233 0.0406 0.0233 0.0406 0.0232 0.0406 0.0233 0.0406 0.0233 0.0406 0.0233 0.0406 0.0406 0.0233 0.0406 0.0233 0.0406	26.021 29.683 33.345 37.007 34.33.345 36.021 29.683 33.345 37.007 27.558 25.609 25.684 333.83 317.647 294.44 290.548 270.97 271.56 294.44 290.54 290.51 181.3 2.69 20.0097 0.2817 0.2858 0.0501 0.0259 0.2817 0.2858 0.0501 0.0259 0.0405 0.0237 0.2886 25.0095 0.0405 0.0237 0.2886 25.009 2.0097 0.0237 0.2886 25.0097 0.0237 0.0258 0.0258 0.0237 0.2886 25.0097 0.0237 0.0258 0.0237 0.0258 0.0237 0.0258 0.0237 0.0258 0.0237 0.0258 0.0237 0.0258 0.0237 0.0259 0.0237 0.0259 0.0237 0.0259 0.0237 0.0258 0.0237 0.0258 0.0237 0.0259 0.0237 0.0258 0.0237 0.0259 0.0237 0.0258 0.0237 0.0259 0.0237 0.0237 0.0258 0.0237 0.0258 0.0237 0.0258 0.0237 0.0258 0.0237 0.0258 0.0237 0.0237 0.0258 0.0237 0.0258 0.0237 0.0258 0.0237 0.0	TURN(PP)	25.569	16.506	13,133	11.610	11.530
90         70         50         30         10         0FAC         -3958         -3566         -3362         -3314           26.021         29.683         33.345         37.007         40.669         EFFP         1.0141         1.01241         0.4922           34.339         30.607         27.558         25.609         22.189         EFF         1.0143         1.0140         1.0243         0.9921           2.086         0.417         27.558         25.609         22.189         EFF         1.0143         1.0140         1.0243         0.9921           33.383         31.547         31.57         1.157         1.NC10M         4.161         3.857         3.206           33.483         31.544         299.54         30.264         295.02         0.004         9.129         7.632         4.719         2.594           270.97         271.56         294.44         299.51         30.52         1.719         2.594           270.97         271.56         294.44         299.51         30.959         7.632         4.719         2.594           270.97         271.56         294.44         299.51         30.278         1.20.37         1.20.37         1.20.37 <t< td=""><td>26.021 29.683 33.345 37.007 39.34.39.339 36.600 27.558 25.609 26.615 27.558 25.609 25.68 31.83.84 291.50 27.558 25.609 27.69 291.50 294.44 299.54 291.50 270.97 271.50 293.97 299.51 188.31 16.69 20.87 2.89 26.285 0.0501 0.0259 0.2617 0.2859 0.0273 0.2873 0.0259 0.0405 0.0237 0.2886 26.288 0.0259 0.0405 0.0237 0.2886 26.288 0.0259 0.0405 0.0237 0.2886 26.288 0.0259 0.0405 0.0237 0.2886 26.288 0.0259 0.0405 0.0237 0.2886 26.2895 0.0405 0.0237 0.2886 26.2895 0.0405 0.0237 0.2886 26.2895</td><td>ß</td><td>0.0978</td><td>0.0677</td><td>0.0825</td><td>0.0774</td><td>0.1028</td></t<>	26.021 29.683 33.345 37.007 39.34.39.339 36.600 27.558 25.609 26.615 27.558 25.609 25.68 31.83.84 291.50 27.558 25.609 27.69 291.50 294.44 299.54 291.50 270.97 271.50 293.97 299.51 188.31 16.69 20.87 2.89 26.285 0.0501 0.0259 0.2617 0.2859 0.0273 0.2873 0.0259 0.0405 0.0237 0.2886 26.288 0.0259 0.0405 0.0237 0.2886 26.288 0.0259 0.0405 0.0237 0.2886 26.288 0.0259 0.0405 0.0237 0.2886 26.288 0.0259 0.0405 0.0237 0.2886 26.2895 0.0405 0.0237 0.2886 26.2895 0.0405 0.0237 0.2886 26.2895	ß	0.0978	0.0677	0.0825	0.0774	0.1028
26.021 29.683 33.345 37.007 40.669 EFF 1.0141 1.0138 1.0243 0.9922 34.339 30.600 27.558 25.609 22.189 EFF 1.0143 1.0140 1.0243 0.9921 2.088 20.412 0.169 27.676 1.157 1NCIDM 4.905 4.161 3.857 3.206 333.83 317.64 315.37 320.11 1.017 1NCIDM 4.905 4.161 3.857 3.206 333.83 317.64 315.37 320.11 1.017 1NCIDM 4.905 4.161 3.857 3.206 333.83 317.64 315.37 320.11 1.017 1.0190 7.632 4.719 2.594 290.54 300.26 0EVM 9.129 7.632 4.719 2.594 2.70.97 271.67 279.03 2.88.66 295.02 10.00.97 1.013 2.09.51 300.09 1.0284 0.287 0.2878 0.2878 0.2878 0.2878 0.2878 0.2878 0.2878 0.0227 0.0223 0.0005 0.0023 0.0023 0.0023 0.0023 0.0023 0.0023 0.0025 0.28888 0.28888 0.2888 0.2888 0.2888 0.28888 0.28888 0.2888 0.2888	26.021 29.683 33.345 37.007 34.339 30.600 27.558 25.609 33.83 317.64 315.3 320.11 305.68 291.50 294.44 299.54 270.97 271.50 294.44 299.54 188.31 16.75 279.03 288.66 30.2987 0.283 0.2817 0.2859 0.2987 0.2839 0.2817 0.2859 0.2731 0.2639 0.2817 0.2859 0.2731 0.2639 0.2817 0.2859 0.0501 0.0259 0.0405 0.0237 0.5861 0.2886 0.2888 0.0337 0.5861 0.2888 0.0387 0.0387	DEAC	.3958	3556	.3362	.317h	.2773
34.339 30.600 27.558 25.609 22.189 FFF 1.0143 1.0140 1.0243 0.9921 23.88	34.339 30.600 27.558 25.609 2.086 0.412 0.169 -0.576 335.68 291.56 294.44 299.54 270.97 271.56 294.44 299.54 188.36 291.56 294.92 299.51 188.31 161.60 165.67 0.2987 0.287 -3.53 0.2987 0.287 -3.53 0.2731 0.2839 0.2817 0.2859 0.0501 0.0259 0.0495 0.0237 0.5861 0.2886 0.2878 -6.561 -6.500 -7.142 -8.391	EFFP	1,0141		1.0241	0.9922	1.9801
2.086 0.412 0.169 -0.676 1.157 INCIDM 4.905 4.161 3.857 3.206 333.83 317.64 315.37 320.11 318.71 10.100 4.905 4.161 3.857 3.206 333.83 317.64 315.37 320.11 318.71 10.100 4.905 4.161 3.857 3.206 270.57 271.67 279.03 288.66 295.02 0.207 271.67 279.03 288.66 295.02 0.207 271.67 279.03 288.66 295.02 0.207 11.13 2.09 0.2087 0.2	2.086 0.412 0.169 -0.676 333.83 311.64 315.37 320.11 305.68 291.56 294.44 299.54 270.97 271.60 279.03 288.66 303.61 289.40 293.92 299.51 118.31 161.69 145.87 138.36 0.2731 0.283 0.2628 0.2658 0.2731 0.0259 0.0405 0.0287 0.2861 0.2886 0.2885 0.037 0.6506 0.5971 0.4567 0.3865 -6.561 -6.500 -7.142 -8.391	444	1.0143	1.0140	1.0243	0.9921	6646
333.83 317.64 315.37 320.11 318.71 305.68 291.56 317.64 315.37 320.11 318.71 305.68 291.50 294.44 299.54 309.26 DEVM 9.129 7.632 4.719 2.594 2 2 270.97 279.03 288.66 295.02 303.61 289.40 293.92 299.51 309.09 188.31 161.69 145.87 138.36 120.37 11.13 2.09 0.287 138.36 120.37 11.13 2.09 0.287 138.36 0.2844 0.2844 0.2839 0.2817 0.2888 0.2628 0.2628 0.2628 0.2628 0.2628 0.2628 0.2628 0.2628 0.2628 0.2628 0.2628 0.2628 0.2628 0.2628 0.2628 0.2628 0.2628 0.2629 0.2623 0.2629 0.2620 0.262	333.83 317.64 315.37 320.11 305.68 291.50 294.44 299.54 20.097 271.50 293.92 299.51 188.31 289.40 293.92 299.51 11.13 2.09 145.87 138.36 0.2731 0.2839 0.26.87 -3.53 0.0501 0.0259 0.0405 0.0237 0.2861 0.2886 0.2688 0.2718 0.6506 0.5071 0.4567 0.3865 -6.561 -6.500 -7.142 -8.391	INCIDM	7.905	191.7	3.857	3.206	3.381
305.68 291.56 294.44 299.54 369.26 DEVM 9.129 7.632 4.719 2.594 2 270.97 271.56 279.03 288.66 295.02 303.61 289.46 279.03 288.66 295.02 303.61 289.46 279.87 138.36 120.37 11.13 2.09 0.287 138.36 120.37 11.13 2.09 0.287 138.36 120.37 0.2987 0.2889 0.2888 0.2889 0.2888 0.2884 0.2593 36.288 0.2888 0.2889 26.385 0.0501 0.0259 0.0405 0.0237 0.0233 0.0501 0.0259 0.0445 0.3864 0.3844 -6.50 -7.142 -8.391 -13.811	305.68 294.56 294.44 299.54 270.97 271.56 293.92 299.51 188.31 161.69 145.87 138.36 11.13 2.09 0.287 0.283 0.2987 0.283 0.2817 0.2858 0.2731 0.263 0.2817 0.2858 0.0501 0.0259 0.0405 0.0237 0.2861 0.2886 0.2878 0.0501 0.2886 0.2885 0.0501 0.2886 0.2885 0.0501 0.2886 0.2885 0.0501 0.2886 0.2885 0.0501 0.2886 0.2885			:	,	i	i
270.97 271.50 279.03 288.66 363.61 2899.40 299.51 388.31 161.60 145.87 138.36 0.2987 0.2839 0.2817 0.2858 0.2731 0.2672 0.2628 0.2872 0.253 30.188 27.389 26.285 0.0501 0.0259 0.0405 0.0237 0.2861 0.2886 0.2685 0.2713 0.6501 0.4567 0.3865 -6.561 -6.500 -7.142 -8.391	270.97 271.50 279.03 288.66 363.61 2899.40 299.51 388.31 161.60 145.87 138.36 0.2987 0.2839 0.2817 0.2858 0.2731 0.2672 0.2628 0.2872 0.253 30.188 27.389 26.285 0.0501 0.0259 0.0405 0.0237 0.2861 0.2886 0.2685 0.2713 0.6501 0.4567 0.3865 -6.561 -6.500 -7.142 -8.391	DEVM	9.129	7.632	4.719	2.594	2.151
0.293.97 293.97 293.97 138.36 161.69 293.97 299.51 188.36 11.13 2.09 0.2817 0.2859 0.2917 0.2859 0.2731 0.2672 0.2628 0.2678 0.2859 0.0501 0.0559 0.00405 0.00237 0.2881 0.2886 0.2888 0.00405 0.00237 0.2881 0.2886 0.2888 0.2718 0.4567 0.3866 -6.501 0.4567 0.3866	0.293.97 293.97 293.97 138.36 161.69 293.97 299.51 188.36 11.13 2.09 0.2817 0.2859 0.2917 0.2859 0.2731 0.2672 0.2628 0.2678 0.2859 0.0501 0.0559 0.00405 0.00237 0.2881 0.2886 0.2888 0.00405 0.00237 0.2881 0.2886 0.2888 0.2718 0.4567 0.3866 -6.501 0.4567 0.3866						
188.31 161.69 145.87 138.36 11.13 2.09 0.87 -3.53 0.2987 0.2688 0.2678 32.253 30.188 27.389 26.285 0.0501 0.0259 0.0405 0.0237 0.2861 0.2886 0.2885 0.218 0.6506 0.5971 0.4567 0.3866 -6.501 -6.500 -7.142 -8.391	188.31 161.69 145.87 138.36 11.13 2.09 0.87 -3.53 0.2987 0.2688 0.2678 32.253 30.188 27.389 26.285 0.0501 0.0259 0.0405 0.0237 0.2861 0.2886 0.2885 0.218 0.6506 0.5971 0.4567 0.3866 -6.501 -6.500 -7.142 -8.391						
0.2847 0.2849 0.2847 0.2858 0.2731 0.2863 0.2668 0.2858 32.253 3C.188 27.389 26.285 0.0501 0.0259 0.0405 0.0237 0.42861 0.2886 0.2685 0.2718 0.6506 0.5071 0.4567 0.3866 -6.561 -6.500 -7.142 -8.391	0.2847 0.2849 0.2847 0.2858 0.2731 0.2863 0.2668 0.2858 32.253 3C.188 27.389 26.285 0.0501 0.0259 0.0405 0.0237 0.42861 0.2886 0.2685 0.2718 0.6506 0.5071 0.4567 0.3866 -6.561 -6.500 -7.142 -8.391						
0.2839 0.2817 0.2859 0.2672 0.2678 0.2672 3C.188 27.389 26.285 0.0259 0.0405 0.0237 0.2886 0.2685 0.2718 0.5071 0.4567 0.3865 -6.500 -7.142 -8.391	0.2839 0.2817 0.2859 0.2672 0.2678 0.2672 3C.188 27.389 26.285 0.0259 0.0405 0.0237 0.2886 0.2685 0.2718 0.5071 0.4567 0.3865 -6.500 -7.142 -8.391						
0.2678 0.2678 0.2672 3(0.188 27.389 26.285 0.0259 0.0405 0.0237 0.2886 0.2685 0.2718 0.5071 0.4567 0.3865 -6.500 -7.142 -8.391	0.2678 0.2678 0.2672 3(0.188 27.389 26.285 0.0259 0.0405 0.0237 0.2886 0.2685 0.2718 0.5071 0.4567 0.3865 -6.500 -7.142 -8.391						
6.500 -7.142 -6.500 -7.112	6.500 -7.142 -6.500 -7.112						
0.0259 0.0405 0.0237 0.2886 0.2685 0.2719 0.5071 0.4567 0.3865 -6.500 -7.142 -8.391	0.0259 0.0405 0.0237 0.2886 0.2685 0.2719 0.5071 0.4567 0.3865 -6.500 -7.142 -8.391						
0.2886 0.2685 0.2718 0.5071 0.4567 0.3865 -6.500 -7.142 -8.391	0.2886 0.2685 0.2718 0.5071 0.4567 0.3865 -6.500 -7.142 -8.391						
6.5071 0.4567 0.3866 -6.500 -7.142 -8.391	6.5071 0.4567 0.3866 -6.500 -7.142 -8.391						
-6.500 -7.142 -8.391	-6.500 -7.142 -8.391						
	****						

Blade Element Data SLTO Configuration (Continued) Table B-2.

			CONFIC	CONFIGURATION	N/V	مره ی					
9.05	50 PERCENT SPEED	ED PT. 14	9	SLTO	3040.	149.4					
		INIET GUI	GUIDE VANE					ROTOR			
PCT SPAN	06	70	50	30	10	PCT SPAN	06	0,2	, O	30	10
DIA 3	21.150	26.050	30,950	35.850	40.750	DIA 6	23.385	27.755	32,125	36.495	40.865
BETA 3	0.000	000.0	000 %	000.0	000.0	8ET A 6	0.766	0.187	-0.842	-1.116	-3.870
ETA	0.860	C.320	-0.864	-1.107	-3.890		30.180	26,316	23.190	20.672	17.097
ო >	227.95	241.46	249.67	253.41	253.36	BETA(PR) 6	49.819	53.086	56.860	59.912	64.249
*	236.38	255. 73	263.69	269.01	264.48		26,199	37,425	44. 726	50.253	54.903
5 7 7	221.92	25. 27	243.65	25.59	253.33	o r > >	273.00	00.575	222 00	23.7 66	206.90
THETA	00.00	0.00	40.50 Z	00.0	00.0	9 //	259.03	275.89	280.90	283.68	270.28
V-THFIA 4	9 (g)	1. 24.43	3,98	-5.20	-17.94	7 7 7	312,35	307.15	306.02	306.50	309.96
	0.2050	0.2173	0.2248	0.2282	0.2281		3.47	06.0	-4.13	-5.53	-18.28
	0.2127	0.2303	0.2375	0.2424	0.2382	V-THETA 7	182.43	152.05	131.16	115.66	95.34
TURN	-0.88	-0.32	0.86	1.11	3.89	V(PR) 6	401.5	459.5	513,9	565.9	522.1
1	daase)	200	ו מששמט איייר	( **		V(PR) 7	349.6	387.1	430.9	4.624	539.1
3	् <sup>१</sup>	20 40 0 Tag	usas som	UATA)	9	VTHETA PR6	-306-7	-367.3	- 430,3	-489.6	-560-3
DFAC	-0.029	-0.056	-0.064	-0.072	520.0-	HETA	-154.4	-235.3	-303.2	-,368.6	1.144
7	0.8320	1.0064	0.8527	1.0275	0.7459	o r	310-19	368.16	426.12	484.09	542.05
INCIDM	-20.200	-50.200	-20.200	-20.200	-20 200		0.2334	0.2488	0.2533	0.2558	0.2661
DEVM	4.520	3,380	2.764	1.407	2.290	) <b> -</b>	0.3254	0.3073	0.2982	0.2932	0.2901
i. L.	,		-	•		(PR)	0.3616	0.4141	0.4632	0.5102	0.5605
		SUMMO	ρ			M(PR) 7	0.3135	0.3468	0.3858	0.4291	0.4822
		OINIO				TURN(PR)	23,613	15.639	12.129	9.658	9,345
						13	0,1106	0,0840	0.0752	0.0713	1,60.0
PCT SPAN	06	70	200	30	10	DFAC	.2926	.2875	.2726	.2486	.2188
DIA 9	26.021	25.683	33,345	37.007	40.669	EFFP	0.9984	0.9826	0.9791	0.9651	0.9606
⋖.	28.330	24.832	22.059	19.654	17.069	T.	0.9984	0.9825	0.9790	0.9647	0.9602
BETA 10	1.614	0.717	0.147	-0.655	1.044	INCLOM	1.219	0.586	0.760	0.312	1.049
o	34.0	555.28	341.80	337.11	320.57	***************************************	7,300	1,025	2.636	1.653	20.
0 7 7	320.57	318.63	316.31	317.46	312.12	5		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \			
VZ 10	365.17	346.90	340.09	336.18	337.83						
THETA	175.64	148.36	128.37	113,38	98.56						
V-THETA 10	10.34	4.37	0.87	-3.84	91.9						
<b>○</b>	0.3320	0.3167	0.3062	0.3019	0.2922						
010	0.3295	0.3129	0.3050	0.3011	0.3026						
	77.00	1000 0	11600	0000	75.10.0						
13	0.0465	TOCO*0	0.0245	0.0204							
DFAC	0.1773	0.1791	0.1677	0.1654	0.0988						
INCIDM	-12.570	-12.268	-12.641	-14.346	-18.931						
DEVM	10.31	8.217	7.647	7.345	9.944						

Blade Element Data SLTO Configuration (Continued) Table B-2.

;				CONFI UTRATION	N/N	8/6/3					
4 02	70 PERCENT SPEED	PT. 14	0	SL 10	4255.	133.8					
		INLET GUID	E VANE					ROTOR			
	06	70	50	30	10	PCT SPAN	06	7.0	50	30	12
~	21.150	26.050	30.950	35.850	40.750	IA 6	23,385	27,755	32,125	36.495	40.865
BETA 3	0000	0.000	0.000	00000	0.000	BETA 6	0.965	0.571	-0.480	-0.878	13,052
	205.49	216.49	222.70	225.74	225.24	-	41.14	64.923	67.707	44.07	72.246
	202.69	224.35	234.07	241.83	239.48	BETA(PR) 7	33.673	46.543	54.452	55.874	58.853
VZ 3	205.49	216.09	222.69	225.73	225.23	9 A	225.46	240.25	245.48	257.11	247.49
4	202.61	223.41	233.97	241.77	239.18	۲ ۸	396.71	375.37	365,32	387.20	396.76
V-IHEIA 3	00.00	00.00	0.00	00.00	0.00	9 7 6	225 - 34	240.01	245.37	257.05	747.14
	0.1847	0.1947	0.2003	0.2030	0.2026		3.80	20.042	10.04	40.5.2	13.18
	0.1822	0.2018	0.2106	0.2176	0.2155	V-THFTA 7	293.76	287.80	280,52	273.67	270.44
TURN	-1.11	-0-77	0.42	0.84	2.87		485.8	566.4	646.9	728.4	810.5
()	נטפטיט		0 084		0.150	~	320.4	350.4	402.5	488.2	561.3
3	1010	:	7		0.0540	VTHETA PR6	-430.4	-512.9	-598.5	-681.5	-771.9
DFAC	0.023	-0.029	-0.055	-0.079	060-0-	HETA	-177.6	-254.3	-327.5	-404-2	4.00
EFFP	0.8871	1.0923	0.8383	1.1130	0.8089	9 1	434.16	515,30	596.43	677.56	758.70
INCIDM	-20.200	-20.200	-20.200	-20,200	-20.200		4/1.34	51.246	008.00	96.60	18.05
NA C	h-287	9.00 C	105.0	130	020 1		0.2028	0.2162	0.2210	0.2315	0.2228
E A E		24.50	h3C+3	10137	017	- COO 1 M	0.5320	0.5510	5.3619	0.540	7004
							2700	F005 0	0.000.0	400%	
		STATOR	Ø			TURN(PR)	28.680	18.360	13.247	13.458	13.393
						17	אוצריט	0.2803	0.3620	0.2696	0.3202
PCT SPAN	ç	40	Ç,	ç	Ş	3 }	00,1	130J.	2,173	EOO3	1,719
0 410	24.021	20 683	24.5	700.75	40 440	מינים מ	7500	0070	1010	100.0	0 0536
	46.618	48.963	48.717	43.577	42.177	- 44 - 44 - 44 - 44	1.0959	0.9785	0.9100	0.9173	
BETA 10	2.473	1.747	-0.207	1.092	4.663	INCIDM	13.764	12,423	11.607	9.735	9.046
	394.58	376.19	369.48	394.81	401.99				4		. 3
	238.07	264.76	260.57	300,34	346.98	DEVM	14.873	50°17	12,352	7.274	5.953
6 2	267,33	245.69	243.35	286.00	297.82						
VZ 10	235.12	263.02	260.06	300.25	345.74						
V-THETA 10	10.27	8.07	40.01	57.5	28.21						
	0.3502	0-3325	0.3255	0.3475	0.3525						
, <b>1</b>	0.2097	0.2329	0.2285	0.2631	0.3035						
TURN	44.146	47.216	48.924	45.484	37.515						
13	0.2298	0.1710	0.1975	0.2128	0.1285						
34.	6633	0.5070	0.6266	0.4552	0.4207						
FFP	0.4058	0.4741	0.3223	0.2466	0.2754						
INCIOM	5.718	11.863	14.017	9.577	6.177						
MAN	11.133	6,10, 0	7 203	000	13,563						
Č,	11.1()	7.64	1.677	7.07	127.07						

Blade Element Data SLTO Configuration (Continued) Table B-2.

	40.865 40.865 40.865 71.377 71.377 57.541 50.50 261.88 311.88 311.88 311.88 1.777.1 777.1 777.1 777.1 13.836 0.2722 0.5102 13.836 0.2722 0.8789 0.177	
	36 -16.495 -16.495 -16.413 -16.413 -16.637 -17.024 -17.024 -17.024 -17.024 -17.05 -17.05 -17.05 -19.00 -19.	
	50 -0.632 -0.632 66.658 52.832 52.832 52.832 -2.85	
ROTOR	70 64.031 64.031 65.260 64.031 45.283 250.50 382.63 250.24 1.14 244.05 1.14 244.05 1.14 947.3	
	90 23,385 47,945 61,270 30,794 235,90 412,39 235,90 490,66 3,51 490,66 470,84 0,2123 0,3662 0,2467 0,2153 30,467 0,1270 1,0590 11,0512	
سرق/ج 140•	POT SPAN  DIA 6  BETA 7  BETA 7  BETA 7  V 5  V 7  V 7  V 7  V 7  V 7  V 7  V	
₩/√ø 4250.	10 -0.750 -0.000 -0.000 -0.100 -18.73 -0.2137 -0.2137 -0.2137 -0.2137 -0.2137 -0.2137 -0.2137 -0.2137 -0.2137 -0.2137 -0.425 -0.0200 -0.425 -0.0200 -0.103	7.3964 0.4370 3.022 12.536
CONFIGURATION SL TO	30 35.850 -1.35.850 -0.000 -5.86 0.2136 0.2236	0.5204 0.3406 8.010 9.707
CONFIC 11 DE VANE	50 30.950 0.000 -0.053 233.44 245.85 0.2100 0.2213 0.052 0.0195 -0.059 0.0195 -0.059 0.0195 1.247 33.345 46.631 1.247 31.345 2.523 8 0.0196 0.01	0.5743 0.4359 11.931 8.747
PT. 14	26.050 0.000 0.000 0.000 225.425 236.12 234.94 0.00 1.75 0.2125 -0.203 0.2125 -0.43 1.0569 -20.200 3.275 3.275 70 27.49 27.49 27.49 27.40	C.5805 0.5643 11.940 9.740
70 PERCENT SPEED	90 0.000 0.000 0.000 214.12 213.93 214.12 213.93 0.000 0.1924 0.1925 0.1925 0.009 0.000 0.000 0.000 0.000 0.000 0.000 0.	0.6652 0.4405 6.100 14.019
7 07	PCT SPAN DIA 3 BETA 4 V 2 V 4 V 2 V 4 V 2 V 4 V 2 V 4 V 4 V 4 V 4 V 4 V 1 V 1 V 10 V 10 V 2 V 10 V 10 V 2 V 10	DFAC EFFP INCIDM DEVM

Blade Element Data SLTO Configuration (Continued) Table B-2.

			CONFIGURATION	RATION	N/V@	8/6/2					
70	PERCENT SPEED	) PT. 142	•	St. TO	4250.	151.3					
		INLET GUIDE	. VANE					ROTOR			
PCT SPAN	Ç	0,	r. C	O.F	<u>c</u>	PCT SPAN	06	0,	90	30	10
DIA 3	21,150	26.050	30,950	35,850	40.750	DIA 6	23,385	27.755	32,125	36,495	40.865
۱ _	0000	00000	0.000	00000	0.000	BETA 6	0.804	0.302	-0.882	-1.757	-5.270
BETA 4	0.918	0.395	-0.913	-1.865	-5.195	BETA 7	47.872	46.606	42.636	38.590	34.378
3	230.32	243,85	252.68	257.26	257.17	BETA(PR) 6	59.425	62.107	64.801	66.776	70.246
	233.53	256.47	266.80	274.31	272.78	BETA(PR) 7	59.69	44.326	51.576	53,313	56.821
VZ 3	230.31	243.48	252.67	257.25	257.16	9 ^	254.20	271.97	282.48	294.43	282.65
V2 4	233.49	254,93	266.74	274.15	271.66	۲ >	418.80	387.42	378.46	404.72	410.49
V-THETA 3	00.0	00.0	00.00	00.0	00.0	9 7/	254.10	271.68	282.37	294.27	281.46
	3.74	1.77	-4.25	-8.93	-24.70		279.27	265.85	278.25	316.28	348.79
Æ.	0.2072	0.2195	0.2275	0.2317	0.2316	V-THETA 6	3.57	1.43	-4.35	-6°03	-25.96
4	0.2101	0.2310	0.2404	0.2472	0.2458		310.60	281.52	256.34	252.44	231.79
TURN	-0.92	-0.40	0.91	1.87	5.20	V(PR) 6	9.664	580.9	663.2	746.3	832.8
1:	0,0196		0.0197		0.0280		323.4	372.1	448.0	529.5	1.619
3						VIHETA PR6	-430.1	-513.5	1-000-	1043	2.02.1
DFAC	900.0-	-0.048	-0.064	-0.084	601.0		-160.2	0.002-	-351.0	0.424.	1-210-1
4	0.5825	1.0600	0.882/	1220-1	0.1747		433.03	714.03	0900	0.00	100.101
INCIDM	-20.200	-20.200	-20,200	-20.200	-20,200	~ v	1,000	0.2451	0.2547	0.2656	0.2548
2000	1.1.85	305	2.813	2,165	3,505		0175.0	0.3429	0.3344	0.3571	0.3615
EAU	701:1	2	610.3	604.3		( PR)	0.4498	0.5234	0.5979	0.6732	0.7508
		ECHARO.	a			M(PR) 7	0.2872	0.3293	0.3959	0.4672	0.5451
		SIATOR	a			RNEP	29.718	17.756	13.219	13,461	13.426
						13	0.1141	0,2111	0.2370	0.1804	0.1974
PCT SPAN	C	70	ď	0	-	) F	5785	57.88	.1893	. hh6h	4023
DIA 9	26.021	29.683	33,345	37,007	40.669	EFF P	1.0208	0.9655	0.9613	0.9617	0.9326
		45.171	41.013	36.963	34.260	EFF	1.0212	0.9647	0.9604	2.9607	0.9307
BETA 10		1.885	1.235	1.602	3.648	INCIDM	10.825	6.607	8.701	7.176	7.0u6
6 >		389,12	385.79	417.88	418.40		9			4	
01 >		298.77	308.29	343.75	379-03	DEVM	10.899	11,826	9.476	4.713	3.921
0		272.06	290.26	333.84	345.70						
	259.39	295.87	307.25	343.93	3/8.16						
VITERIA 9	00.00	0.82	11.662	19.0	24.12						
	C	3445	0145	0.3480	3484						
. E	0.2822	0.2632	0.2714	0.3023	0.3332						
TURN	40.235	43.286	39.777	35.361	30.612						
13	0.2354	0.1041	0.1143	0.1083	0.0611						
3 5	0117	0000	000		2,03						
FFFD	0.4202	0.5934	0.5266	0.4318	0.7182						
INCIDM	5.846	8.071	6.313	2.963	-1.740						
3700	רנס אר	385	200	604.0	a i						
OEV.	779.67	7.505	0.133	×00° K	12.540						

Blade Element Data SLTO Configuration (Continued) Table B-2.

O DEDCENT SPEED	t + 0	,	O F	N/V	w/0/s	. <b>'</b>				
3		<b>5</b>	<b>3F 1</b> 0	4255	171.3					
N	INLET GUIDE	E VANE					ROTOR			
	92	οř	Q.	9	PCT SPAN	G	10	Ċ	Cr	
	26.050	30,950	35.850	40.750	DIA 6	23,385	27.755	32,125	36,495	40,865
	0.000	000.0	000.0	000.0	BETA 6	0.870	0.352	-0.386	-1.450	-4.753
	0.444	-0.424	-1.494	-4-780		44.845	39,393	36.554	34.272	30.345
	276.65	287.95	294.28	295.33	BETA(PR) 6	55.980	58.742	61.580	63.946	67.596
	293, 28	304.54	314.98	309.70	BETA(PR) 7	29.177	43.025	48.668	52,731	56.905
	201 01	20% 53	274.20	26.662	o r > :	2.06.2	311.99	324.00	335.54	325.00
	00.0	00.0	10.410	00000	7 42	200 10	299.02	302.90	411.03	410.43
	2.27	-2.25	18.2	-25.81	· · ·	302.03	308.68	323,53	33.00	256.00
	0.2493	0.2557	0.2654	0.2664		4.41	1.91	-2.18	64.8-	-26.93
	0.2645	0.2748	0.2844	0.2796	V-THETA 7	301.90	253.74	239.99	231.46	207.35
	-0.44	0.42	1.49	4.78	V(PR) 6	518.5	4009	680.7	7.63.7	8.648
		0.0216		0.032	V(PR) 7	347.7	422.7	490.1	560.9	648.7
	430	0.043	700	600	VIMEIA PRO	8.624-	2000	3.88.6	1.989-	-785.6
	0.9698	0.8290	1.0426	0.7068	-	434,16	515.30	596.43	44004	758.70
	300		000	2000		471.39	542.13	608.03	677.84	750.81
	-20.500	-202.00	-20.200	-50.500		0.2617	0.2817	0.2927	0.3033	0.2936
	3.256	2.324	1.794	3.180	~	0.3807	0.3550	0.3572	0.3637	0.3624
					M(PR) 5	0.4677	0.5424	0.6149	0.6903	7677
	STATOR	щ			N. C.	26.796	15.688	12.908	11.213	10.690
					13	0.0988	0.1239	0,1091	0.0987	0,1148
	7.0	0.5	30	2	DFAC.	7396	1,61	1,123	1,069	3465
	29.683	33,345	37.007	40.669	EFFP	1.0110	1.0564	1.520	1.0159	0.9922
	37.720	35.157	32.729	29.005	EFF	1.0113	1.0576	1.0532	1.0163	•
	1.087	0.871	-0.258	1.669	INCIOM	7.380	6.242	5.480	4.346	4.3%
	363.27	350 27	16.624	423.43	3	10,377	10,525	4 EK8	133	2
	316.86	335.84	356.42	370.76	1			3	161.4	4.00
	339.55	357.83	384.63	413.43						
	247.51	237.39	229.19	205.57						
	6,51	5.46	-1.73	12.05						
	0.3593	0.3656	0.3753	0.3746						
	0.3038	0.3176	0.3400	0.3652						
	30.033	34.285	32.986	21.336						
	0.0189	0.0567	0.0303	0.0253						
	•	0.3760	0.3471	0.2466						
	0.5314	0.3883	0.2866	0.0131 -6.995						
		}								
	8.587	8.371	7.742	10.569						

	Table	В-2.	Blade www.ret	ade Element ©NFIGURATION	Data N√€	SLTO Confi	Configuration ~√√6/8		(Continued		
70 P	PERCENT SPEED	PT. 144		SLTO	4255.	187.2					
		INLET GUID	IDE VANE					ROTOR			
PCT SPAN	06	07	20		10	PCT SPAN	06	ů2	50	30	c.
	21,150	26.050	30.950	20	40.750	DIA 6	23,385	27.755	32,125	36.495	40.865
BETA 3		0.000	00000		000.0	BETA 6	0.783	0.186	-0.786	-1.669	-4.373
ETA,	<b></b> .	0.275	-0.828	-1.693 -	4.454	BETA /	38.029	33.782	30.616	28.315	24.638
n (	300.27	305.89	336.21		323.91	BETAIPR 7	27.627	60.04	59.183	51.470	55.126
6 74		305.52	317.48	323.41 3	323.89	, , , , , , , , , , , , , , , , , , ,	325.97	348.49	358, 79	366.58	352,28
4 7 A	300.23	322.75	336.23		338.65	٧ ٦	458.41	431.88	424.65	427.54	436.23
V-THETA 3		00.00	00.00		00.00	9 ZA	325.87	348.18	358.70	366.41	351.26
-THETA		1.56	-4.86		-26.38	7.2.7	359.44	358.63	365.28	376.33	396.51
	0.2598	0.2761	0.2867	0.2922 0	2926	V-THETA 6	4.46	1.13	-4.92	-10.67	-26.85
4		0.2935	0.3040		3071	V-THELD 7	282.40	240.14	216.26	202.79	181.85
2		-0.24	68.0		4.40	V (PK ) 0	254.5	1.120	2.007		C.008
13	0.0213		0.0191		0.027	VIHETA PR6	401.0	-514.2	555. A	688.2	-785-6
DFAC	-0.034	090.0-	-0.067		-0.089	VTHETA PR7	-189.0	-302.0	-391.8	-475.0	-569.
EFFP		0.9939	0.8608	1.0135 0	0.7361	9 0	434-16	515.30	596, 43	677.56	758.70
•	-20.200	-20.200	-20.200		20.200	7 0	471.39	542.13	608.03	677.84	750.81
× 200			901		720	<b>9</b>	0.2945	0.3152	0.3248	0.3320	n.3187
DEVM	4.509	3.425	5.7.50	1.993	TC0.7	× 4	0.4091	0.3847	0.3777	0.3798	0.3869
			1			M PK 1	0.2627	0.5619	0 5755	102.00	0.7785
		STATOR	ma			TURN(PR)	25.192	15.799	12.190	10.359	10.782
						13	0.0862	0.0772	0.0823	0.0912	0.1120
PCT SPAN	Ö	0,2	C tr	0.5	5	DEAC	5000	3905	3478	כאיוצ	3078
DIA 9	21	29.683	33,345		699.0	EFF FFF	1.0078	1.0195	1.0188	0.9928	0.9941
6		32,121	29.374		24.385	EFF	1.0079	1.0199	1.0192	0.9926	0.9943
BETA 10	2.280	0.458	0.549	-0.576	1.032	LNCIDM	4.225	3,395	3.085	2.370	2.708
» <del>-</del>		208.10	4204.40		36.08	MV4C	8.827	7.573	1, 801	3.010	2.226
		370.09	378.90		03.43		-	\ \ \ -			
VZ 10		394.79	403.40		135.93						
V-THETA 9		234.24	213.81		182.90						
V-THETA 10		3.18	3.88		7.85						
o :	0.4110	0.3927	0.3880		).3931 3868						
		31.663	28.825	27.623 2	23,353						
T:	4151.0	5040.0	0.0455	0.205	0.0201						
0FAC	0.3194	0.3115	0.2840		2080						
EFFP	0.6005	0.4975	0.4429	0.2585 -0	-0.3022 -11 616						
	-4.022	616.4-	75.750		(10011						
DEVM	10.980	7.958	8.049	7-424	9.932						

Blade Element Data SLTO Configuration (Continued) Table B-2.

			CONFIG	CONFIGURATION	N/N	5/0/2					
4 04	70 PERCENT SPEED	10 PT-139		SLTU	4260.	207.					
		INLET GUID	E VANE					ROTOR			
PCT SPAN	96	02	90	30	10	PCT SPAN	06	70	20	30	0.7
DIA 3	21.150	26.050	30.950	35.850	40.750	DIA 6	23,385	27.755	32,125	36.495	40.865
BETA 3	0000	0.000	0.00	0.000	00000	BETA 6	0.832	0.204	-0.845	-1-774	-3.971
-	202.80	262.06	254.75	260.035	15.970 250 84		065.67	710.67	870 -77	19.018	10.128
	336.82	363.85	376.09	384.09	379.10	RETA(PR) 7	27.520	38.413	45.491	51.072	54.942
KZ 3	323.76	342.64	354.71	360.01	359.81	9 >	370.29	395.30	403.51	407.54	388.06
	336.76	361.93	376.02	383.88	378.19	~ >	498.40	473.07	459.88	451.67	456.46
V-THETA 3	0	00.0	0.00	00.0	0.00	9 2/	370.16	395.01	403.38	407.32	387.13
	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	2.19	00.00	-12.32	-26.25		743164	426.17	424.26	425.23	438.49
n •	0.3045	0-3294	0.3408	0.3482	0.3436	V-THETA 7	246.15	14.1	176.94	152.09	126.80
3	-0.96	-0.34	0.87	1.84	3.97		566.9	648.8	725.6	802.1	876.5
17	0.00		23.88		0000		488.7	544.4	605.5	676.9	763.4
3	0.0219		0.0100		0,020	•	-429.3	-514.5	-603.1	-691.0	-786.5
DFAC	-0-031	- 0.057	-0.068	-0.084	060-0-	I HET A	-225.8	-338.3	-431.8	-526.5	6.429-
EFFP	0.7928	0.9298	0.8270	0.9917	0.7970		434.67	515.90	597.13	678.36	759.59
C C C C C C C C C C C C C C C C C C C	-20.200	-20.200	-20.200	-20.200	-20.200	~ ·	471.94	542.76	608.75	678.64	751.69
DEVN.	Orbital	3,356	2.766	2.130	2.370		0.5534	0.3386	0.3663	0.3700	0.3519
		2000	3	}	2		0.5135	0.5886	0.6586	0. 7283	0.7969
		į					0.4387	0.4878	0.5419	0.6053	0.6825
		STATOR	eq.			•	21.704	14.051	10.727	8.408	8.849
						13	0.0589	0.0530	0.0726	0.0876	0.1113
PCT SPAN	06	70	20	30	01	DFAC	.2939	.2842	.2719	.2476	41115
	26.021	29.683	33,345	37.007	40.669	EFFP	1.0542	1.0482	1.0329	1.0023	1.0068
- -	27-739	24.050	21.461	18.634	15.594	EFF	1,0552	1.0491	1.0335	1.0023	1.0070
	15000	4 80 1 8	217.0	-0.325	1.833	INCIDM	.631	016	.123	-118	-592
. 2	509.30	486.00	474.36	468.22	469.56	DEVM	8.720	5.913	3.391	2.472	2.042
6 ZA	443.27	443.96	440.03	443.25	444.92						
10	506.28	482.93	473.72	468.21	469.15						
V-THETA 9	236.94	199.35	173.23	149.47	124.21						
	0.4574	0.4389	0-4242	0.4188	0.4132						
01	0.4576	0.4359	0.4250	0.4193	0.4202						
$\mathbf{z}$	26.142	23.494	21.248	18.960	13.761						
13	0.0418	0.0279	0.0213	0.0178	0.0315						
DFAC	0.1659		0.1575	0.1513	0.0989						
EFFP		<b>-6.0340</b> -13.050	24.2595 -13.239	<b>36.6491</b> -15.366	2.6005 -20.406						
DEVM	10.297	8.056	7.712	7.675	10.733						

	Tabl	e B-2.	Blade	ade Element	nt Data	SLTO Conf	Configuration		(Continued)	<u> </u>	
80	PERCENT SPEED	ED PT. 137		SL TO	4815.	157.3					
		INLET GUIDE	VANE					ROTOR	~		
PCT SPAN	06		50	30	10	PCT SPAN	ეგ	70	50	30	_
DIA 3	21.150		30.950	35.850	40.750	DIA 6	23,385	27.755	32.125	36.495	4. 845
¥	0.000		00000	0.000	0.000	BETA 6	2.104	1.549	0.424	0.440	-1.467
H	2.414		0.611	-0.446	-1.657	BETA 7	£02°04	51.105	50.062	46.436	43.310
× >	243.97		764.24	267.32	266.65	BETA(PR) 6	956-09	63.663	66.453	68.431	71.282
4	241.01		277.42	286.32	285.70	_	28.727	45.596	51.196	54.187	57.176
VZ 3	243.96		264.23	267,31	266.64	9 >	267.67	285.22	293.32	304.15	294.30
7 7 7	240.74	263.94	277.25	286.23	285.57	٧ ٦	478.35	452.55	439.64	456.66	449.16
	00.0		00.00	0.00	00.0	9 2/	267.37	284.84	293.18	304.09	204.15
V-THETA 4	10.15		2.96	-2.23	-8.26	7 Z V	410.47	283.71	281.98	314.61	341.32
w.	0.2196	4	0.2380	0.2408	0.2402	V-THETA 6	9.82	7.71	2.17	-2.49	9.50
	0.2169		0.2500	0.2582	0.2576		362.12	352.21	337.09	330.90	321.87
TURN	-2.41		-0.61	0.45	1.66	V(PR) 6	550 B	642.2	733.9	927.2	916.6
1		Š	900	( aman came			356.4	386.0	420.4	537.8	628.5
3		(מפונים זון (משישה)	8 T S	(WIW) Des		VTHETA PR6	-481.5	-575.4	-672.8	-769.2	-868.1
DFAC	0.033	-0.015	-0.044	-0.075	-0.087	č	-171.3	-261.3	-351.0	-436.5	-527.7
EFFP	-3.5686	0.8482	0.7890	0.9801	0.8348	99 j	491.30	583,12	674.93	766.74	858.55
	20.200	-20.200	-20,200	-20,200	-20.200	<b>.</b> .	533.43	613.47	688.06	767.05	849.62
INCIDM	07.07	2071	201			<b>.</b> 0	0.2412	0.2572	0.2646	0.2745	0.2655
DEVM	2,986	1.900	1.289	·746	.057	7	0.4237	0.3985	0.3856	0. 1995	0.4091
						M(PR) 6	2965	0.5790	0.6620	0.7465	0.8268
		STATOR	В			M(PR) 7	0.3157	0.3399	0.3951	0.4705	C 54.90
						CXY FX	*12.26	21.042	12.240	042.41	
						13	0.1258	0.2678	0.3319	0.2699	0.2557
PCT SPAN	06	20	50	30	10	DFAC	5880	1019	.5780	5299	.4837
OIA 9	26.021	29.683	33,345	37,007	40.569	EFFP	1.0354	0.9370	0.8850	0.8720	
	48.166	49.802	48.840	45.068	42.220	EFF	1.0365	0.9350	0.8813	0.8675	0.8403
SETA 10	2.534	2.107	0.543	1.529	4.834	INCIDM	12.356	11,163	10,353	8.831	8.082
6 >	474.23	454.64	443.18	465.52	477.51		:	•	,	1	you.
01 ^	266.33	312,99	304.14	344.36	402.59	DEVM	9.927	10.096	9.0%	704.4	4.500
6 2/	311.86	291.97	291.30	328.78	353.50						
	262.98	310.96	303.65	344.22	401.02						
V-THETA 9	353.34	347.26	333.66	379.56	320°88						
V-THETA 10	11.77	11.51	2.88	61.6	33.93						
o ;	0.4199	0.4004	0.3887	0.4073	0.4165						
10	0,2331	0.2736	0.2648	0.2993	0.3496						
TURN	45.633	47.695	48.298	43.538	37.386						
13	0.2278	0.1577	0.1733	0.0967	0.1049						
DFAC	0.7125	0.6147	0.6421	0.5824	0.4496						
EFFP	0.4476	0.5617	0.4357	0.3897	0.4939						
INCIDM	7.266	12,702	077.77	11.068	6.220						
DEVM	11.234	209*6	8.043	9.529	13.734						

Blade Element Data SLTO Configuration (Continued) Table B-2.

		10		39.847	70.094	58.269	315.30	451.83	315.11	346.89	-10.78	10.607	6.626	029.0	-561-0	859.64	850.50	0.2847	0.3951	0.8357	0.5768	11.825	0,1668	.4393	0.9557	0.9540	769.9	240	600.0										
		30	0.05	44,554	67.586	56.329	316.46	433.51	316.44	308-86	0.31	+1.00	6 6 2 9	767.0	7.10-	767.53	767,85	0.2858	0.3800	0.7495	0.4884	11.256	0.2138	4924	0.9594	0.9579	7.986	7.00	1.167										
		50	627.0	47,906	65,630	54,169	305.10	412.33	305.02	47.917	17.7	4 0 C C	(39.3	-673.6	-382.8	675.63	688,77	0.2754	0.3623	0.6672	0.4148	11.456	0.2976	.5338	0.9644	0.9633	9.530	0,000	15.007										
	ROTOR	70	1.927	49,353	62.964	45.433	293.33	432.45	292.85	281.36	9.80	71.076	*****	1572 0	-286.0	583.72	614.11	0.2646	0.3813	0.5813	0.3539	17.506	0.2292	5717	1.0242	1.0249	10.404	600 01	16.733										
		90	200	49*64	60.078	33,106	277.52	451.08	277.26	291.38	20.01	20.24	2000	7 187-	-191-2	491.81	533.98	0.2501	0.3994	0.5010	0.3099	26.964	0.1563	•5900	1.0734	1.0756	0) 11-11	700	000										
مر <i>اق</i> ر کی 164.0		PCT SPAN	′ •	BETA 7		BETA(PR) 7	9 >	~ ` ^ `	9 7.7		V-IMEIA O		0 (00) 1	` ~	VI HET A PR7		<b>~</b> 0	9 1	<b>E</b>		M(PR) 7	TURN(PR)	13	DFAC	EFFP	FF	INCIOM	M VIII	E .										
N/V®		10	000	-2.023	282.01	297.07	282.00	296.88	00.00	64.01	0.6242	2002	70.7		-0.072	0.9722	30.30	203.50	.423					10	699.04	37.905	0.467	4 /0.68	371-38	424.75	289.16	3.46	0.4121	0.3708	37,438	0.0729	0.3930	0.1149	9.367
CONFICURATION SL TO		30	0.00	0.093	280.43	298.62	280.42	298.62	00.0	* c	0.2528	1602.0	0	SPEED DATA)	-0.064	1.1254	5	-40.400	.207					30	37.007	45.869	2,155	444.00	325.49	353.62	302.40	13.32	0.3897	0.3090	40.715	0.1473	0.5075	0.2303	10.155
•	OE VANE	50 05 050		0,531	274.71	291.84	274.70	291.81	00.0	7.7	0.2470	0.000	•	70% & 100% SF	-0.057	1,1912	000	-40.400	1.369		ф	l		20	33,345	46.492	1,012	415.91	285.25	322.95	301.65	5, 73	0.3654	0.2836	45.481	00.11,00	0.5331	11,792	8.512
ED PT. 13	INLET GUII	70	000	2.140	265.14	276.29	264.74	274.45	00.0	10.31	0.2588	0.2430	+1.7	(REFER TO 7	-0.022	1.3886	000	-20.200	1.560		STATOR			25	29.683	41.954	2.670	433.82	288.16	304.16	322.16	14.32	0.3825	0.2693	45.284	0.1264	0.5824	10.85	10.170
80 PERCENT SPEED		90	000	2.355	250.80	254.41	250,79	254.18	00.0	10.45 0.05 0.05 0.05 0.05 0.05 0.05 0.05	0.2238	16220	66.7-		6.007	-2.2464		-20.200	3.045					06	26.021	48 - 584	3.984	444.50	268.86	257.82	333,35	18.15	0.3933	0.2289	44.610	0.2099	0.6819	0.4053	12,684
9 0 8		POT SPAN	BET A 2			4	VZ 3		V-THETA 3		7) ×		, I	13	DFAC	EFFP		NGIDW	DEVM					PCT SPAN	OIA 9	9	щ	<b>&gt;</b> >		01 7A	-THETA	1	o <b>z</b>	N 10	TCRN	El	DFAC	EFFP	DEVM

Blade Element Data SLTO Configuration (Continued) Table B-2.

	Table	e B-Z.	Blade	Blade Element		SLTO Confi	Configuration		(Continued)	_	
<b>d</b> 08	80 PERCENT SPEED	PT - 13	CONFT.	CONFICURATION SLTO	4845°	176.8					
			!					ROTOR			
		INTEL GOIDE	VANE								
PCT SPAN	.6	02	20		10	PCT SPAN	06	70	20	30	<u>د</u> د
DIA 3	21.150	26.050	30,950	20	40.750	DIA 6	23.385	27.755	32.125	36.495	40.85F
BETA 3	00000	000.0	000.0		00000	BETA 6	1.915	1.577	0.357	-0.282	-1.584
TA	2.186	1.777	0.469		-1.428		46.950	46.156	43.625	38.371	36,149
e >	273.06	288.54	298.24		303.12	BETA(PR) 6	58.180	60.950	63.811	65.702	68.957
	274.15	301.47	315.62	323,95	325.26		27.711	43.004	52.123	32.526	54° 450
5 7 A	273 02	200.78	215.53		325.15	0 1-	442.74	451.48	427.22	468.59	( V C T T
THETA	00.00	0.00	00.0		0.00	٧2 6	300.52	320,99	333.00	349.10	325.94
V-THETA 4	10.46	9.35	2.58		-8.11	V Z 7	334.22	312.30	309.02	367.27	100.4B
	0.2461	0.2602	0.2691		0.2735	V-THETA 6	10.05	8.85	2.07	-1.72	06.6-
*	0.2471	0.2720	0.2850		0.2939	V-THETA 7	360.07	325.62	294.75	290.87	285.27
TURN	-2.19	-1.78	-0.47		1.43	V(PR) 6	570.0	661.2	754.6	4.848	935.6
13	(AEF	(REFER TO 70% & 1	100% SPEED D	DATA)		V(PR) 7	379.9	427.6	503.7	505.2	FOO. 5
3 2	410 0		750 0-	040	480	VIHETA PRO	-176.7	-201.7	1-116-	1481	7.045
UTAC FEFD	0.1121	0.7070	0-7142	0.8453	0.7804		494.37	586.75	679.13	771.52	867.97
;	000					· ^	536.75	617.30	692,34	771.83	R54.91
INCI D/M	-40.400	-20.200	-40.400	-20.200	-20.200	s≎ ≅	0.2714	0.2903	0.3011	0.3159	AFUE.0
DEVM	3.214	1.923	1.431	.581	172	~	0.4369	0.3986	0.3761	0.4122	r.4242
						M(PR) 5	0.5144	0.5973	0.6820	0.7675	0 R457
		STATOR	žά			TURN(PR)	30.459	17.922	11.679	13.073	- C - C - C - C - C - C - C - C - C - C
						4,	0.1203	1000	2000	7631 0	386
N POO						3	0	1 0 1	((1)	OLCT-O	2007
rol oran	06	70	50	30	10	DFAC FEE	.5596	5418	1951	60111	16041
•	170.97	29.083	000000	36.501	40.009		1.051	0.901	0.440	0.900	0205
BETA 10	7.367	1.955	0.797		2.613	INCIDM	9.580	8-1150	7.711	6-102	5.757
	487.45	453.81	436.14		492.37					,	
_	296.96	340.43	347.23	393,55	439.24	DEVM	116.8	10.504	10.023	7.056	5.009
6 7.4	333.93	319.87	324.15		399.08						
	291.27	337.46	340.00		455.03						
V-THETA 10	18.00 80.86	11.62	4.83	60.062	20.02						
	0-4320	0.4007	0.3841		0.4320						
01	0.2602	0.2986	0.3042	0.3445	0.3842						
TURN	38.496	42.814	41.034		33.205						
13	0.2182	0.0190	0960°0		0.050t						
DFAC	0.6332	0.5284	0.4924		0.3731						
	0.4286	0.6723	1797.0	0.6728	1.2023						
INCLUM	4.90	600°)	10.		704.						
DEVM	16.067	9-455	8.297	694-6	11.513						

Element Data SLTO Configuration (Continued)

	Table	B-2.	Blade E	ade Element	Data SI	SLTO Config	Configuration	(Continued)	nued)		
80	PERCENT SPEED	ED PT. 13	5	SL TO	4850.	198.6					
								a Car			
		INLET GUIDE	E VANE					NOTON TOTON			
PCT SPAN	06	70	20	30	10	PCT SPAN	06	7.0	20	30	01
DIA 3	21.150	26.050	30.950	35.850	40.750	DIA 6	23,385	27.755	32,125	36.495	40.865
BETA 3	0000	000.0	o. 000	000 0	0.000	BETA 6	2.002	1.610	0.250	-0.292	-2.459
ETA	2.248	1,755	0.320	-0.320	-2.432		47.510	42.020	38.799	35.864	32.460
~ >:	306.61	325, 57	338.66	345.53	346.11	BETA(PR) 6	54.913	57.859	60.494	62.888	66.537
* * *	315-11	35% (5	33.9.17	368.26	368.55	SEI AL PK )	23,339	39.144	46.182	49,508	53,202
7 7.8	314.92	337.26	359,14	368.23	368.22	· >	522,25	485.01	481.70	503.34	514.00
THETA	0.00	00.00	00.00	00.0	00.00	9 7/	339,30	367.62	383.78	396.65	382.52
V-THETA 4	12.36	10.40	2.01	-2.06	-15.64	7 27	350.84	359.85	375.15	407.81	433.76
N 3	0.2767	0.2941	0.3062	0.3125	0.3130		11.87	10.21	1.67	-2.02	-16.50
<b>₹</b>	0.2846	0.3072	0.3251	0.3335	0.3338	V-THETA 7	385.10	324.66	301.83	294.88	275.92
TURN	-2.25	-1.75	-0.32	0.32	2.43	V(PR) 6	590.3	681.8	779.3	869.9	7.096
	(RE)	(REFER TO 70% &	100% SPEED	TA TA )		V(PR) 7	384.2	464.6	542.2	628.2	724.2
3			10 don-	o iii		VI HET A PRO	-483.0	-577.1	-678.2	-774.3	-881.3
DFAC	10000	- G. 02 7	-0.058	-0.069	-0.087	•	-152.2	-293.3	-391.2	-477.7	-579.9
	1170.0	0.1333	0. 1.10	710101	0.44.0	0 =	527 21	417 03	403.04	773 43	
INCIDM	-50.500	-20:500	-20.200	-50.200	-20.200	- · ·	1202.0	0.3288	0.3480	0 3597	000000
DEVM	3.152	אוס ר	1.580	020	.832	o <b>~</b>	0.4633	0.4263	0.5253	0.4436	0.5471
	367.6	(4/11	200	}		M(PR) 6	0.5338	0.6173	0.7064	7893	0.8709
		a City to	ρ			M(PR) 7	0.3408	0.4113	0.4788	0.5537	6367
		TOTAL CONTRACT				TURN( PR)	31.566	18.686	14.305	13.378	13,335
						13	0,1069	0,1096	0,1159	0.0883	9801.0
PCT SPAN	Ç	02	, C	Ç	-	24.7	2	8002	1.550	1.303	2880
0 410	160.46	20 4 92	32 345	27.007	07 07	2000		2000	0030	0.450	6360
	46.161	40.347	37,202	34,312	31.783		0.9312	0.9778	0.9577	0.0564	0. 9339
	4.224	0.960	0.344	-0.561	2.341	INCIDM		•	4.394	3.288	3.337
	516.03	450.39	493.67	521.66	524.74		}			,	٠
	358.69	3 88.17	409.09	438.84	475.53	DEVM	4.539	149°9	7,082	908	•305
6 7 1	350.44	370.31	3 55 02	430.80	445.95						
10	354.53	384.32	407.79	438.70	475.02						
	372.21	317.49	2 58. 49	2 94 • 06	276.39						
•	26.42	6,50	2.45	-4.30	19,43						
5 ·	0.4575	0.4343	1964-0	0.4603	0.4615						
O Z	41.937	35.387	36.858	34.873	29.442						
13	0.1863	0.01.82	0.0623	0-0262	0.0162						
	2010										
DFAC	0.5595	0.4688	0.4352	0.4265	0.3323						
INCIUM	5.261	3.247	2.502	.312	-4.217						
DEVM	12.924	8-460	7.844	7-439	11.241						

	1	í	£	1 3 0 2 0 1		CT TO CORES	Configuration		(Continued)		
	Тарте	B-7.	CONFIG	CONFIGURATION	N/Ve		or a crof		(n)		
80	PERCENT SPEED	ED PT. 13	6 SITO		4850.	222.8					
		Canal Management						ROTOR			
		INTEL COIDE	E VANE								
PCT SPAN	G	6	, c	90	10	PCT SPAN	96	70	O's	30	r I
014 3	21,150	26.050	30,950	35.850	40.750	DIA 6	23,385	27,755	32,125	36.495	40.86F
BETA 3	00000	00000	000.0	00000	0.000	BETA 6	2.053	1.536	0.159	-0.928	-2.467
_	2.328	1.764	0.159	-0.896	-2.296	BETA 7	36.342	32.595	29.468	26.700	23.619
K 3	350.21	371.52	385.15	391.72	392.04	BETA(PR) 6	50.338	53.554	57.097	60.269	64.175
•	365.36	393,91	409.02	416.36	414.65	_	26.105	38,145	45.226	50,354	53.816
VZ 3	350.17	371.07	385.12	391.70	392.02	90 I N	398.80	425.82	439.14	445.26	427.84
4 ZA	365.05	391.35	409.01	416.30	414.32	>	244.22	514.79	206.08	505.83	40.7Ir
V-THETA 3	00.0	0000	00.00	00.0	0.00	9 7/	398.45	425.33	439.06	445.18	457.44
V-THETA 4	14.84	12.12	1,13	-6.51	-16.61	Z 2A	436.33	433,29	440.39	451.82	474.27
T	0.3168	0.3365	0.3492	0.3553	0.3556	V-THETA 6	14.29	11.41	1.22	-7.21	-18.42
J Z	0.3308	0.3573	0.3714	0.3783	0.3767		322.50	277.32	248.96	227.28	207.30
TURN	-2,33	-1.76	-0.16	0.00	2,30	V(PR) 6	624.3	716.2	808.3	897.7	981.2
ł	1)	ARRED TO 204	C TOOK SPEED	DATA)		V(PR) 7	488.2	551.5	625.6	708.2	A03.4
3		e or maran	8	4		8	-480.6	-575.9	-678.6	-119.5	-883.2
DF AC	-0.022	-0.044	-0.061	-0.071	-0.079	VTHETA PR7	-214.8	-340.6	-444.	-545.3	4.04.
EFFP	0.9986	1.0361	0.9500	0.9910	0.8835	9 0	494.88	587.35	679.83	772.31	964.70
60.01014	-20.200	-20.200	-20.200	-20.200	-20,200	<b>~</b> .	537,31	617.93	693.06	772,63	855.87
2002	,		. 1		,	9 i	0.3619	1/86-0	0.5996	0.4053	2000
DEVM	3.072	1.936	1.741	1.1%	96 96		4004.0	0.4389	2064-0	0.4443	7666
						M( PR) 6	0.5665	0149.0	0. (35)	2/19.0	1768
		STATOR	m			T X X X	0.4503	0.4910	11 867	410 0	121101
						1 X L L L L L L L L L L L L L L L L L L	077.47	0000	10011	1100	
						13	0.0936	0.0630	0.0700	0.0727	0.0950
PCT SPAN	06	0,2	50	30	10	DF AC	3996	.3764	.3549	.3276	.2890
OIA 9	26.021	29.683	33,345	37.007	40.669	EFFP	1.0089	1.0101	1.0109	•	
-	34.480	30.892	28.176	25.242	22,770	EFF	1.0001	1.0196	1.0112	0.9972	0.9892
BETA 10	1.858	0.270	0.438	-0.310	1.663	INCIDM	1.738	1.054	.997	.669	16.</th
ტ-: >	549.06	527.32	520.48	525.21	528.43		ì	1	,00	ì	750
	497.62	479.30	484.54	489.06	510.80	DEVM	(OC.)	7.047	2.120	T. (74	ork.
6 7	444.62	449.13	457.86	475.02	487.13						
V 10	27. C.C.	410.01	403.33	403.01	20.6						
		20.00	27.00	17.65	14.02						
•		07.7	2000	60.2-	14.02						
- : E :	6064	0.4700	0.4000	10000	1604.0						
	32.622	30.622	27.738	25.552	21.107						
1		1 00 0		0.00	0200						
3	0.0563	0.0402	0.0440	0.0210	0.20.0						
DFAC	0.2978	0.3001	0.2737	0.2708	0.2082						
EFFP	0.6333	0.5468	0.5486	4074	0.9698						
INCIDM	-6-420	-6.20g	-6.52h	-0.()	-13.63n						
DEVM	10.558	7.770	7.938	7.690	10.563						

	Table	e B-2.	Blade worre	Blade Element confiduration	t Data	SLTO Confi ~√€/s	Configuration ~√€/s		(Continued)		
80	PERCENT SPEE	960 PT. 13	2	SLT?	4850.	239.3					
		INLET GUIL	JE VANE					ROTOR			
PCT SPAN	Ç	ç	л (	'n	ç	PCT SPAN	c o	76	ير	٦	<u>£</u>
	21.150	24.050	050	25.850	46.750	214	77.185	27.755	32,125	36.495	40.865
AFTA 3	0000	( ) • ( ) • ( )		(30.0		RFTA 4	2.045	1,235	0.158	-0.717	-1.579
4	2,339	1,421	101	-6.543	-1.673	ALTA 7	36.33	26.460	23.032	701.197	18. 768
, m	379.32	402.20	416.35	423.05	452.91	PFTA(PR) 4	47.735	51.022	54.855	58.CR1	67.389
	395.48	478.63	443.77	455.45	446.84	SETA(PR) 7	26.235	37.342	44.853	50.528	53.776
VZ 3	379.26	4/1.70	416.31	423.01	422.88	× ×	436°C)	467.55	477.76	484.02	450.11
7 7 7	395.14	476.22	443.19	455.41	446.65	۸ ۲	577.49	547.53	530.46	526.33	537.73
V-THFTA 3	00.0	ري <b>.</b> څ	<u>ပ်</u> ပွဲ ပ	ر. د	60°¢	٧٧ ٨	435.61	467.11	477.66	484.86	458.04
	16.14	10.63	7.82	-4.29	-13.04	7 7	496.21	480.48	488.12	488.25	5. 5°
× ×	0.3438	r.3650	2878.0	r. 3845	0.3944	V-THETA 6	15.56	10.08	1.32	-f J	-12.65
4	0.3588	3897	3.4034	64140	7.4°68		201.67	243.04	207.2A	170.65	145.07
	-2.34	-1.42	-0.11	£5.54	1.67	9 (80)/	447.a	742.8	829.B	1.716	000
1	au,					V(00) 7	5.55.	616.5	6.88.8	748.2	656.2
3	편)	(REFER TO 70% &	_	DATA)		VTHFTA DP4	£ 024-	-577.3	-478.5	-778.4	-877.4
DFAC	-0.021	-r.n52	-8.764	-r.782	-0.77	VTHFTA DR7	-245.4	-374.0	-485.8	-503°C	7.000
EFFP	C.6021	7.8046	C.7327	0.9542	0.6935	ηγ	404.84	587.35	679.83	772.11	864.70
1	000	000	20 200	200	-20,200	11 7	537.31	617.93	90*869	772.63	ກາທຸກ
INCIDM	-40.400	-20*20	203.03-	003.03-	201	× Z	7.3944	r.4764	0.4360	n.4428	0.4184
DEVM	3.061	2.279	1.793	910	•073	. ≥	0.5101	0.4909	D. 4750	r.4655	0.476
						y ( ac ) w	r. 5893	r.6773	. 7573	0.8374	0.0024
		STATOR	m,			w(pa) 7	7.400g	0.5528	0.6168	0.6872	7. 7657
						tag Neit	21.403	13.660	166*6	7.552	4.613
						13	0,0680	0.0654	0.0814	0.0957	0.0874
PCT SPAN	٥	70	r u	3.0	-	DEAC	2989	2962	.2744	,252h	.2192
0 110	26.021	79.683	33,345	77.367	699.35	FFED	1.0662	7.0605	1.0645	1.0186	1.7571
BETA 9	28.411	74.960	21.986	18.746	17,734	4.5	1.6709	1.0620	1.0660	1.0100	1.0514
BETA 10	1.567	<b>^.456</b>	1:3:3-	-r . 924	1.432	₩C1UN1	865	-1.478	-1.245	-1.519	811
oʻ >	590°50	566.69	546.94	540.01	546.43				3		
ု ၁	565-15	564.57	547. A]	542.74	543.33	OFV.	7-435	719.17	2.753	1.928	•876
6 2/	510,59	51c. 84	576.74	511.35	514.62						
	588.67	0.00 C 3.00	547.02	542.45	544,79						
V-THETA 9	240.PZ	24R.32	2C 4. H4	173.54	164.52						
V-THFTA 1:	16.19	67.7	9	-R - 7 7	13.72						
<b>2</b> €	C. 5312	, 57.9°	7,4075	.4438	0.4836 0.4836						
OI F	26.844	24.414	71.802	10,672	16.303						
5 1		•									
3	9.0476	11110°0	0.0364	0.0262	0.0286						
DFAC	0.1672	C.1731	0.1625	.1537	6.1195						
EFFP TNC TOX	14.2247	-11.7738 -12.231	32.33€ -12.81h	10,2793 -15,25h	3. 0490 -18.266						
i de la	(Ott. 17)										
DEVM	10.267	7.956	7.493	7.074	10.332						

Blade Element Data SLTO Configuration (Continued) Table B-2.

	Table	B-2.	ытаае	rrement	-1	SETU CONE	Configuration		(continued)		
001	100 PERCENT SPEED	ED PT. 15	4	CONFIGURATION SL TO	6070°	6/6/0	<b>'</b>				
		INTEL GOLI	DE VANE					ROTOR			
PCT SPAN	S	7.	r.	<u>c</u>	2	PCT SPAN	G G	5	20	E	10
	21.150	26.050	30,950	35,850	40.750	DIA 6	23,385	27.755	32,125	36.495	40.865
۱ ـ	0000	0.00	0.000	000.0	00000	BETA 6	1.139	0.919	-0.173	0.778	3.629
BETA 4	1.299	1.056	-0.173	0.831	4.149			55,500	55.039	41.857	49.803
	303.52	320.83	334.49	343,55	346.36	RETA(PR) 6		64.514	66.442	67.791	69,381
	307.81	333.39	357.90	360.06	375.85		34.155	49.149	57.092	56.627	58.913
٤ ٢٨	303.51	320.28	334.48	343.54	340.33	4 O > >		340.73 F33 GE	571.53	537.01	595.00
\$ 10 10 10 10 10 10 10 10 10 10 10 10 10 1	306-71	551.05	00.00	10.000		Y 4 N		347.74	371.47	392,46	397.73
V-THETA 4	00.4	6.14	1 20	5.22	27.19	7 7		295.73	291.30	400.43	376.84
	0.2739	0.2898	0.3023	0.3107	0.3133			5.58	-1.12	5.33	25.22
4	0.2778	0.3013	0.3239	0.3259	0.3406	V-THETA 7		430.90	416.93	358.87	446.01
	-1.30	-1.06	0.17	-0.83	-4.15	V(PR) 6		808.4	929.5	1038.3	1129.5
15	0.0170		0,0212		0.0230	V(PR) 7		452.8	536.6	728.2	729.9
3 2	000	0	0.43	0,0	• 1 7 0	VIHELA PKS		1262 5	1450.5	1408	-1021-
UTAC FEED	-0.002	0.5512	1.0339	0.8045	1.4089		619.36	735.10	850.84	966.58	1082.32
	C11+0	37660	50000	000 00	600 00	) <b>~</b>		773.37	867.40	966.98	1071.07
INCIDM	-20.200	-20.200	-20.200	-20.200	-20:200	÷c ž		0.3150	0.3366	0.3560	0.3616
DEVM	4.101	2.cdu	2.073	531	-5.749	¥ 4		0.4547	0.4397	0.4671	0.5011
						M(PR) 6		0.7312	0.8420	0.9418	1.0248
						M(PR) 7		0.3937	0.4637	0.6324	0.0203
		STATOR	T.			C X A ) N X O :		12.231	7.343	79111	10.40
						13	0.1133	0.2525	0.3817	0.2334	0.1919
PCT SPAN	06	70	20	30	10	DFAC	.6337	.6472	.6121	.4510	.5287
	26.021	29.683	33,345	37,007	40.669	EFFD	1.0471	0.9430	0.8794	1.0484	0.8776
BETA 9	50.754	54.324	53.414	40.242	47.824	EFF	1.0493	0.9403	0.8735	1.0511	0.8702
⋖	129.4-	769.7	1. (80	204.0	0.07 502 55	INCIDA	14.023	170.71	10.342	0.191	101.0
· -	303.15	363.66	344.13	410.32	516.47	MVHC	15,355	16.049	14.992	0.027	6.013
•	341.07	300.45	301.84	425.51	405.22			•	•	•	
VZ 10	298.78	339.09	341.84	409.16	513.92						
	4.25.05	423.14	409.08	360.49	447.29						
•	-24.45	15.90	-10.69	3.31	51.07						
. Σ Σ ₹	0.2619	0.2957	0.2943	0.3532	0.4409						
٠٤	55,381	51.672	55.194	39.780	42.149						
13	0.2021	0.1963	0.2074	0.2154	0.1396						
26.0	7606	0.6611	0.4872	5443	0.4643						
TERP TERP	0.5266	0.5650	0.3480	0.1494	0-1538						
INCIDM	9.854	17.224	16.71	0.242	11.824						
DEVM	Jr. 073	10.152	6.720	6-1162	1,575						
	7	1/1.71	>17	101:00	?						

Te B-2.  IPEED PT. 155  INLET GUIDE  TO 0.000  C. 790  C. 790  C. 790  343.43  354.44  343.43  355.44  0.000  C. 320  C. 310  C. 310
Table B-2. B1  Table B-2. B1  OD PERCENT SPEED PT. 155  21.150 26.050 30.  1.102 0.000 0.000 0.  1.102 0.000 0.000 0.  325.10 343.43 357.34 327.65 352.14 382 325.10 343.43 357.65 325.10 0.000 0.200 0.0197 0.3106 0.3207 0.0197 0.3106 0.3207 0.0197 0.200 0.200 0.0197 0.200 0.200 0.4678 0.5287 1.0 26.021 29.683 33. 4.298 2.910 2 2.507 0.31462 48. 2.512 25.57 0.3146 2.577 0.3146 0.389 0.1871 0.1782 0.3 0.1871 0.1782 0.6 0.47663 0.65239 0.3 0.3985 0.65239 0.3 0.3985 0.65239 0.3
Table B-  1
00 64 00 00 00 00 00 00 00 00 00 00 00 00 00
SPAN SPAN SPAN SPAN SPAN SPAN SPAN SPAN

			10	40.865	-0.357	39.532	66.633	56.006	403.08	34.80	458.74	-2.89	378.59	1168.8	820.5	-1072.9	-680.3	1050.02	0.4226	0.5145	1.0655	0.7097	10.626	0.1428	1154.	0.9487	0.9456	00400	3.106											
			30	36.495	0.272	42.022	64.483	53.987	455.10	565.19	477-11	2.16	378.35	1056.5	714.1	-953.4	-577.6	955.60	0.4147	0.4908	0.9625	0.6202	10.494	0.0758	•4829	0.9722	0.9707	4.000	5.387											
(Continued)			20	32,125	-0.575	44.975	62.782	53.036	435.03	520.73	454.04	-4-37	368,05	950.9	612.6	-845.5	-489.5	841.17	0.3957	0.4535	0.8650	0.5335	9.739	0,2190	.5207	0.9561	0.9541	200.0	10.936											
		ROTOR	5	27.755	0.426	49.584	60.915	45.891	404.19	534.61	404.24	3.01	407.03	829.2	498.0	-723.7	-357.5	726.75	0.3675	0.4669	0.7528	0.4349	14.892	0.1900	.6340	0.9643	0.9627	615.0	13.371											
Configuration √6/8			06	23,385	0.919	48.175	57.544	32,331	385.66	569.55	362.50	φ	424.43	718.4	449.5	-606.1	-240.4	612.32	0.3497	0.5013	0.6513	0.3956	25.205	0.1137	.5877	1.0366	1.0383	177.0	13.531											
SLTO Config ~\overline{\sigma}/s/s	224.1		PCT SPAN	DIA 6		BETA 7	BETA(PR) 6	ETA(PR)	9 1	~ <u>`</u>	9 7 7	_	V-THETA 7		~	VTHETA PR6	THETA		- v		M(PR) 6	M(PR) 7	TURN( PR.)	, 3	DFAC	EFFP	FF	inc. Da	DEVM											
t Data N∕√ø	6001.		Ç	40,750	00000	-0.213	399.53	432.23	399.51	432.23	00.00	1001	0.3931	0.21		0,0000	-0.084	1.0581	-20.200	-1.387					10	40.669	37.192	623.02	585.24	496.30	584.17	376.61	0.00	0.5058	33.724	0.0328	0.3274	0.7716	767.7	12.368
ade Element configuration	SLTO		30	35,850	0000	0.294	395.81	422.15	395.80	422.14	0000	1032 0	0.3837	-0.29			-0.064	0.7875	-20.200	ýœ					30	37,007	40.152	500-1	479.37	446.91	478.56	377.49	000	0.4136	39.100	0.1317	0.4760	0.4177	0.156	9.052
Blade configu	.0	E VANE	, c	30,950	00000	-0.605	385.92	413.08	385.91	413.05	00.0	00%	0.3752	0.61	0,100	0,0240	-0.076	0.8869	-20.200	202	2	1	<b>d</b>		20	33,345	43,316	526.85	404.83	381.26	402.36	361.43	00.01	0.3498	43.365	0.1519	0.5338	0.4809	0,000	7.451
B-2.	:0 PT. 156	INLET GUIDE	70	26.050	0000	0.501	369.96	385.29	369,36	382,35	0.00	0.00	0.3693	-0.50			-0.037	0.5426	-20.200	3.300	1/4.0	1	STATOR		70	29.683	48.245	447.7	384.76	351.74	379.51	398.54	00*61	0.3327	46.001	0.1472	0.5744	0.5543	11.11	<b>भग</b> ट-6
Table	100 PERCENT SPEED		G	21.150	0000	1.048	349.14	356.48	349.13	356.40	0.00	20.00	0.3226	-1.05	5010	0.010	-0.011	0.4718	-20.200	1, 353	1				06	26.021	47.736	4.343 887.18	317.14	367.23	312.53	412.32	67.47	0.2745	43.343	0.1878	0.6955	0.4282	0.030	13.093
	100 Pt		PCT SPAN	0.54.2	۱ ــ	BETA 4	<u>ب</u>	-	£ .ZA		V-THETA 3		n. 4	_	ı	3	DFAC	EFFP	NO 1941	NAVE OF					PCT SPAN	-	BETA 9	DI 4 5		7	2	V-THETA 9	∢	, C	_	13	DFAC	EFFP	ואכוסו	DEVM

Blade Element Data SLTO Configuration (Continued) Table B-2.

			ç	40,865	-0.622	36.422	65,181	70.00	597.78	501.73	481.00		1105.3	860.4	-1084.9	-713.3	0.79.47	1.68.25	0.5186	1.0931	n.7464	9.174	0.1435	.4217	n. 9487	0.945R	1.981	3,107	N N N										
			30	36.495	-0.835	36.772	62.768	23.399	575.03	499.89	460.49	67.72	1092.4	772.5				0.4571	0.5014	0.9988	0.6736	9.357	0,0878	<b>.</b> 4365	1.0063	1.0067	3.168	1.799											
			ŗ.	32,125	-0.562	39,346	60.420	484.51	543.70	484.38	420.19		0.186	0.099	-853.3	-520.4	848.00	0.4424	0.4756	0.8960	0.5852	9.351	0.1061	.4681	1.0041	1.0043	4.326	8.964											
		ROTOR	2.2	10	0.408	42.865	58.203	21.04	548.64	452.54	401.65	22.0	859.1	565.9	-729.9	-398.1	733.15	0-4127	0.4815	0.7826	0.4966	13.460	0,1150	•5109	1.0298	1.0312	5.703	12.212											
			Ğ	23,385	1.049	47.943	55.136	425.12	591,80	454.94	394.06	0 7 0 7 7	743.4	459.0	6.609-	-231.3	616.13	0.3864	0.5210	0.6758	0.4041	24.868	0.0867	.5958	0.9814	0.9806	6.536	11,461											
W/ 6/8	• 74.7		PCT SPAN	DIA 6	BETA 5		BETA(PR) 6	-	· >	9 2 0		V-THILD O	V(PR) 6	V(PR) 7	VTHETA PR6	HETA	o r	~ v0 Σ:	~	M(PR) 6	M(PR) 7		13	DFAC	FFFP	EFF TAIC TON	INCIUM	DEVM											
N/Ve	•		10	40.750	0.000	-0.488	436.66	436.74	471.03	0.00	-4.01	10670	0.49	0,000	0.0210	-0.083	0.4101	-20.200	-1.112					10	40.669	34.506	621.44	588.25	512.10	587.67	352.04	0.5400	0.5099	31,983	0.0216	0.3090	1.1017	1.494	11.423
RATION	2		30	35.850	0.000	-0.921	435.41	433,39	461.30	00.0	-7.41	0.4205	0.92			-0.073	****	-20.200	1.221					30	37.007	35-140	597.16	520.64	487.93	520.07	343.11	0.5213	0.4519	35.973	0.0384	0.4035	0.6313	1.140	7.167
CONFIGURATION		IDE VANE	50	30,950	0.000	609.0-	423.21	423.19	453,30	0.00	-4.82	0.504	0.61	0,000	30.0	-0.077	00000	-20.200	2.509		ď	<b>n</b>		20	33.345	37.667	556-10	464.51	438.16	462.11	559.82	0.4867	0.4038	38.322	0.0825	0.4378	0.0400	2.967	6.845
, C	•	INLET GUI	02	26.050	0.000	0.490	405.62	405.05	421.86	0.00	3.64	0.3866	64.0-			-0.044	0.0203	-20.200	3.210		000			20	29.683	41.316	551.74	428.86	409.73	423.45	304.20	0.4843	0.3730	40.441	0.0657	0.4889	0.5545	4.216	8.375
O DEOCENT COCED			ê	21.150	0.000	1.188	381.69	381.67	396.27	0.00	8.21	0.3460	-1.19	0.0102	- (-)	-0.027	6760	-20.200	4.212					90	26.021	47.087	579.62	374.96	386.14	369.65	34.54	0.5097	0.3249	41.816	0.2160	0.6086	0.4506	6.187	13.970
			PCT SPAN	IA 3	BETA 3	ETA	n ∢ >≥	× × ×	4 ZA	V-THETA 3	-THETA	o.√	. 272	1.	3	DFAC	ברוד	INCIDM	DEVM					מ	~~	BETA 9		V 10	٥		V-IHELA 9		01 H	TURN	13	DFAC	EFFP	INCIDM	DEVM

Blade Element Data SLTO Configuration (Continued) Table B-2.

		0.00	20 7 72		31,352	60,819	52.751	537.75 544.32 535.76	282.51	10.007	-12.59	304.63	1116.1	826.1	855.3 -974.4 -1085.3		962.20	9664.0	0.5136			2,000	0.0905	.3067	<b>.</b>	8100	<b>)</b>	5.998 4.151 2.938										
	ROTOR	ç	27 76K	0.351	37.274	55,319	42.337	504.50	504.33	459.70	3.09	350.25	886.0	622.6	4.821	731.47	769.55	0.4614	0.5102	0.8104	12,956	1 000	CT00*0	4516	1.0262	1.0273 0.870	\	9.837										
~\ <u>@</u> /6 260.5		SPAN	22	, sc		[PR] 6	7	473.35			9	7	V(PR) 6 770.	į	A PR6	ž L				7025 61 7	- & d						į	116.01										
N/V@		PCT	410 014					473.51 V 6		2 ZA 0010			0.70 V(P	0,000	THE CALL		· >		F M 506-	( C C C C C C C C C C C C C C C C C C C	E 31	1.				30.403 EFF	•	604.83 DEVM	404.50	311,24	14.25	0.5372	0.5280	29.053	0.0143	0.2517	3.5717	1,557
configuration slto		Ċ	9.0					4 471.35		12,58					100			3	1.733						5 37,007			555.16					0 0.4856		5 0.0088		•	0/0.7
CONI PT. 158	inlet guide vane	C P	,		1			442.52 461.84	•	3.68		ċ		1,120.0	,	0.6677 0.9482		•	3.250 2,874		STATOR B					16480 31.331		507.26 529.51					0.4449 0.4640		0.03µµ 0.04µ5	0.3757 0.3463		γμς.ε- υ×ο-1-
100 PERCENT SPEED	NI II	Š						416-77 44			0.3787 0.			0.0181		0.7110		Í	4.177							40°133									0.844L			6.6
100 P		POT SPAN		ີ	BETA 4		•	£ 7A		V-TRETA A	t .	+	TURN	ij	3 2	FFF		NG 10	DEVM						<b>(20)</b>	BETA 9	5	01 °	6 74	_	*		O.	N O	AŞ	DFAC	EFFP	THE THE

Blade Element Data SLTO Configuration (Continued) Table B-2.

			CONFIGURATION	RATION	N/N	3/0)0					
100 p	PERCENT SPEED	EED PT.153		SL TO	6020•	280.5					
		INLET GUIDE	JIDE VANE					ROTOR			
PCT SPAN	Ç	02	ř.	Űŧ.	0	PCT SPAN	C	5	50	30	0
DIA 3	21,150	26,050	30,950	35,850	40.750	DIA 6	23,385	27.755	32,125	36,495	40.865
	000.0	0000	0.000	0.000	0.000	BETA 6	1,382	0.717	-0.240	-1.658	-3.297
w	1.606	106.0	-0.383	-1.653	-3.249	-	31.426	26.761	24.522	22.199	19.349
	463.70	491.39	507.59	514.29	514.09	BETA(PR) 6	48.081	51.129	54.996	59.867	63.078
	483.04	523.00	544.97	557.14	545.55	<del>~</del>	27.224	38,376	45.873	53.654	56.251
8 7 A	463.62	520.80	507.54	514.25	514.05	o ^	540-09	582-15	635.81	584.02	604.200
HETA	00.00	00.0	00.00	00.0	00.0	6 7 7	539.81	581.78	592.69	589.34	561.52
V-THETA 4	13.54	8.28	-3.64	-16.07	-30.92	7 7	589.99	591.17	578.17	542.62	574.86
w.	0.4227	0.4489	0.4644	0.4708	0.4706	V-THETA 6	13.03	7.29	-2.49	-17.06	-32,35
<b>₹</b>	0.4410	0.4791	0.5002	0.5120	0.5008		362.07	298.40	263.88	221.46	201.86
TURN	-1.61	-0.91	0.38	1.65	3.25	V(PR) 6	808.1	927.2	1033.3	1139.9	1240.2
13	0.0281		0.0216		0.0220		666.4	721.8	830.8	715.7	1034.8
DFAC	-0.027	-0.056	-0-077	-0.099	160-0-	VIHETA PR7	-304.8	-468.6	-596.4	-737.6	-860.4
EFFP	0.8119	0.9487	0.9143	1.0087	0.7728		614.26	729.05	843.83	958.62	1073.41
47.4	30.200	-20.200	-20.200	20.200	-20.200	7 0	26.999	767.00	860.25	959.02	1062.25
INCIDA	200500	7	003.03	200.00	003.03	•0 f ΣΕ:	0.4955	0.5362	0.5466	0.5435	0.5171
DEVM	3.794	2.793	1.517	1.953	1.649	/ K	0.6234	0.5934	0.5672	0.5203	0.5402
		STATOR	<b>_</b> 11			C (20) N	0.5982	0.6759	0.7411	0.8129	0.9174
			ı			TURN(PR)	20.851	12.738	9.118	5.211	6.826
						13	0.0423	0.0550	0,1296	0.1682	0.2093
PCT SPAN	0.6	7.0	20	30	10	DFAC	.3341	3096	.30µ	.2901	.2543
	26.021	29.683	33,345	37.007	40.669	EFFP	1.0467	1.0583	0.9908	0.8358	0.8728
BETA 9	29.165	24.917	23.710	20.645	18,538	11 THE TOTAL OF TH	1.0485	1.0604	0,9905	0.8309	0.8685 122
4	715.34	652,76	648,96	614,17	616.27		(*/*	1	10111	3	4
V 10	725.69	650.43	654.82	614.44	652.85	DEVM	8.424	5.876	3.773	5.054	3,351
6 7/	614.96	624.98	593.57	574.71	584.18						
VZ 10	348.60	291.86	24.12	214.25	195.03						
	23.34	7.13	2.21	-15.00	7.43						
	0.6437	0.6223	0.5796	0.5466	0.5465						
N 10	0.6538	C.6201	0.5852	0.5468	0.5813 17.885						
1	0.1347	0-1339	0.1386	0.1160	3000.0						
3	100		3	00110	Coco						
DFAC	0.1583	0.1721	0.1664	0.1760	0.0896						
INC I DM	-11.735	-12.183	-10,990	-13.355	-17.462						
DEVM	10.543	8.092	7.693	6.602	9.552						

Blade Element Data SLTO Configuration (Continued) Table B-2.

	110 PERCI	110 PERCENT SPEED Pt.	Pt. 161	Ö	CONFIGURATION	N/V6	29.853 58.83				
							1				
		INLET GUID	UIDE VANE					ROTOR			
PCT SPAN	ç	20	C tr	Ċ	ē	PCT SPAN	UB	0,4	C Ir	Ċ	-
DIA 3	21.150	26.050	36,950	35,850	40,750	DIA 6	23,385	27,755	32, 125	36.495	47. R55
	0.000	00000	0000	00000	00000	BETA 6	4.220	4.946	4.899	7,218	6.65
	4.859	5,395	5.124	7.590	7.757	BETA 7	50,533	52,310	54.280	51.122	53.819
ო >	356.13	375,33	386.90	392.72	393.36	BETA(PR) 6	58.983	61.672	64.144	65,874	64,397
•	352,51	388,39	416.07	426.56	459.34	A(PR)	50.404	44.611	52.656	53.765	57.965
	356.13	374.61	386.89	3 92 • 71	393,35	9 >	392.17	416.96	435, 75	454.13	451.73
4 7/	351.16	3 84. 99	414.26	422.77	425,41	~ >	652.23	96.109	602.93	648.34	670.58
	00.00	00.00	00.00	0.00	0.00	9 2/	390.88	415.02	433.98	450.47	448.39
V-THETA 4	29.86	36.52	37.16	56.34	57.95	Z 2A	411,50	371.12	351.73	406.83	395.91
m X	0.3223	0.3401	0.3508	C.3552	0.3568		28.86	35.95	37.21	57.06	54.49
4	0.3190	0.3522	0.3780	C-3878	0.3904	V-THETA 7	503,52	481.1C	489,51	504.72	541.35
TURN	-4.86	-5.39	-5,12	-7.59	-7.76	V(PR) 6	758.6	874.8	995.2	1 06601	1217.5
Į,	/ BE	PREFER TO TOK A	TOOK SPERM	CARA V		_	475.9	522.1	580.3	688.4	745.4
3	!	_		(wrw)		VTHETA PR6	-650.1	-160.9	-895.5	-1002.5	-1132.7
DFAC	0.053	0.015	-0.027	-0.014	-0.018	HETA	-233.6	-366.7	-461.3	-555.3	-532.R
EFFP	-0.8387	0.6735	0.9356	0.8945	0.8692	9	678.95	805.83	932.70	1059.58	1185.45
e color	20 200	20,000	-20.200	20.200	-20.200	~	737.16	847.78	950.85	10,0901	1174.12
<u>ا</u>	201	201	707-07-	000	200	9	0.3556	0.3788	r.3964	0.4137	3.6.1
DEVM	0.541	-1.695	-3.224	-7.290	-9.35(	<b>-</b>	0.5721	0.5287	r.5198	0.5573	0.5702
						M(PR) 6	C. 6881	0.7948	n. 9053	1.0012	1.1089
		STATOR	æ			M(PR) 7	0.4174	0.4540	C. 5003	0.5918	7.5345
						TURN(PR)	29.569	17.039	11.479	12,036	17.425
						1	.0688	.2295	.3851	1804	.2947
Warre more						3		,	:i		
PCI SPAN	06	2	20	30	2	DFAC	.6032	· 60µ2	1809	Š	.5744
DIA 9	26.021	29,683	33,345	37.007	40.569	EFFP	1.0152	0.9529	C. 8733	0.9436	7.8258
	46.936	51,295	53.127	49.652	51,367	FF	1.0161	0.9503	n. 8661	0.8973	9.8145
BETA 10	-7.170	3,191	-1.317	1.257	4.493	INCIDM	10.383	9.172	8.0 1	ਜੈਨ • •	5.130
ه د ح	641.29	607.34	606.90	665.42	691.10	: :	10 40		777	276.2	7
2 °	54.0	380,10	3 4 4 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	404.30	26.470	UEV M	10000	177.77	D. 220	2.107	3
6 7 4	212.50	37.376	287.30	430.00	431.40						
V-THETA 9	490,80	473,96	485.50	507,13	539.86						
	-39.88	21,16	-8.93	9.97	45.04						
	0.5618	0.5280	0,5231	0.5725	0.5880						
01 W	0.2736	0.3256	0,3303	0.3849	0.4848						
	57.106	46.105	54.444	48.395	45.874						
13	.0927	1771.	9,181.	.1980	.1217						
0.00	2010	000	5016	0777							
JA 70	*****	00000	5817.0	00000	0.5167						
INCION	9.036	14.195	18-427	15.652	15.367						
DEVM	1.530	10.691	6.183	9.257	13.393						

10 40.865 30.980 64.498 64.498 64.498 58.418 576.37 577.95 -21.36 -2 50 32.125 -1.979 -1.979 58.131 49.689 6521.78 6521.86 5311.86 -27.54 323.30 1121.6 -973.0 -973.0 -677.3 11.0341 -1.034 Blade Element Data SLTO Configuration (Continued) 27.755 -2.043 55.682 55.682 564.47 5610.45 563.682 -20.12 -338.25 -10.4 -10.4 -10.4 -10.4 -10.6 -10. 90 23.336 38.536 53.081 33.458 33.658 554.01 554.01 675.90 472.90 605.91 60 W/0/8 DIA 6 BETA 6 BETA 7 BETA(PR) 6 BETA(PR) 7 6652.0 N/V -0.106 0.9548 -20.200 0.600 10 40 - 75 0 20 - 60 0 10 - 60 0 11 10 40.600 31.500 31.500 31.700 516.52 516.52 316.21 316.37 0.5430 CONFIGURATION -0.094 0.8812 -20.200 30 37.007 29.052 29.052 29.052 584.52 584.52 584.52 311.58 0.13 0.55(3 0 0.55(3 50 256,056 36,955 (42 -2.257 -2.164 93 512.44 541.58 89 486,40 535.19 b6 511.99 541.15 CC 0.30 -2.0.64 R1 -2C.30 -2.0.64 R2 C.4448 C.497C 24 2.26 C.477C -0.053 30.90 30.90 20.90 20.90 20.90 36.90 50.000 50.000 50.000 50.000 50.000 50.000 60.000 60.0000 60.0000 60.000 60.000 60.000 60.000 60.000 60.000 60.000 60.0000 60. -20.200 1.08u 2. 2. 2. 3. 3. 4. 935 INLET GUIDE VANE 110 PERCENT SPEED Pt. 165 -0.079 5.957 70 29.083 31.059 11.059 620.44 520.02 520.01 500.65 300.65 10.05 0.5521 C.45541 0.3077 0.2039 -5.241 Table B-2. 90 21.150 2.0000 2.0000 2.0000 4.58.942 4.58.93 4.58.89 4.71.86 4.71.86 0.600 0.618.71 0.600 0.4385 -6.063 0.8291 90 36.812 36.812 36.812 37.56 542.74 5642.74 5642.85 367.6 -20.200 7.642 INC.DM DEVM

Blade Element Data SLTO Configuration (Continued) Table B-2.

	T CENT	•		CONFIGURATION	6//N		3/0/7	, 		•	
	त्रिश्चस्य ०११	110 PERCENT SPEED Pt.	160	SLTO	668.2		240.69				
		INTEL GUID	GUIDE VANE					ROTOR			
PCT SPAN	S	0,1	ď	S	9	PCT SPAN	G	ç	Ç	Ċ	<u>.</u>
DIA 3	21.150	26.050	36,950	35,850			23.385	27,755	32,125	36.495	40.855
BETA 3	0000	0000	060.	000.0		BETA 6	664.4	4.48E	3.59	2.721	575 · C-
	5.389	5,176	3,996	2.936		BETA 7	31,993	28,758	26,777	26, 797	21.093
m	487.00	515.20	531,18	538.40		_	47,929	51.095	55.488	59.425	53,354
<b>†</b> ^	509.28	550.00	575.38	585.40	571.17	BETA(PR) 7	28.177	38,935	44. 52 A	55.812	56.179
VZ 3	486.53	514.60	531,13	538,37	540.34	•0 ! > °	575.74	616.37	618.69	612,21	600.60
	507.61	545.44	573.93	584.63	571.15	۲ /	752.21	715.79	653. 73	673.15	572.79
V-THETA 3	00.0	00°0	00.0	00.00	00.0	9 7 2	573.75	614.17	617,37	611.49	5.00.5
	68974	0.4716	0.4870	66.67	10.40		032.20	626.91	285.52	248, 37	17.75
1 · 4	0.4660	0.5051	0.5297	0.5394	0.5256	V-THFTA 7	300.53	344.38	294. 52	271.91	242.12
_	-5.39	-5.18	-4.00	-2.94	0.55	•	856.4	97P.1	1089.7	1202.1	1339.5
1	10)	PREFER TO 204 &	5	7.4.7.4.)		-	723.7	806.7	881.3	958.1	1127.8
3				(wrw)		VTHETA PR6	-635.6	-761.0	-897.9	-1 n35.n	-1197.4
DFAC	0.005	-0.019	-C. 045	-0.059	-0.062	_	-341.7	-5n7.n	-666.3	-792.6	-632-9
EFFP	0.9248	0.9473	0.9116	0.9379	0.7668	ر ا ود	681.81	809.22	036.63	1064.04	1191.45
INCIDM	-20,200	-20.200	-20.200	-20,200	-20,200	۰,	740.25	851,35	954.85	1064.48	1179.05
, ALMA	נוס	77.7	700	AcA C.	מט ר	6 F	0.5500	0.0098	0.5720	0.557	0.5543
DEVA	1000	0/11	2000	25.030	-1.022	M ( DO ) A	0.7000	0.00413	1,587.7	1.04	1. 3454
						2 L L L L L L L L L L L L L L L L L L L	10010	2416.0	7056	0070	606291
		STATOR	ma .			TURN(PR)	19.746	12,145	6.955	3.611	7.195
						13	0.0535	0.0625	0.2086	0.1977	0.2423
PCT SPAN	ć	ŀ	C	ć	•		11.00	{			1
OIA O	90	79, 683	50 22 24 F	37,007	10	UFAC	1 0577	1,0545	5168	0.5460	4444.
	29.664	26,707	26,493	24, 771	20.295	. L.	1.0602	1.0568	C. 9400	0. 7565	4008.6
BETA 1C	2.442	1.380	-0.454	-0.289	2.701	INCIDM	-0.671	-1.405	-0.612	-0.175	0.164
	778.60	749.17	646.39	643.21	692.95			,		Š	
2 7	173.27	728.65	656.86	624.58	7.38 . 7.2	DEV M	9.377	0.435	02450	272.	3.6/9
V 10	768.36	724.89	656.02	624.50	707.85						
⋖	385.34	336.70	289.69	269.50	240.35						
V-THETA 10	32.94	17.55	-5.20	-3.15	33.40						
o :	0.7026	0.6741	0.5785	0.5713	0.6152						
01 2	0.6973	0.6540	0.5856	0.5536	0.6305						
- CKS	577.17	176.67	7 96 97	25.060	17.593						
13	0.065lt	0.0571	0.0292	0.0229	0.0259						
DFAC	0.1787	0.2022	0.1884	0.2274	0.1228						
EFFP	-6.5320	-0.9675	3.9187	-2.0430	2.6309 -15.705						
i			i	í	107 11						
DEVM	11.142	8.880	7.046	7.711	100,11						

Table B-3. Blade Element Data Cruise Configuration

		c.	40.865	19.589	72.479	55,114	165.34	155.77	210.94	55.43	240.55	1 0 7 K	1403.4	-305-6	548.83	543.12	78676	0.4545	7.3278	17.363	0.2952	.5710	C756°U	0.0434	7.6(7	2.216											
		30	36.495	22.061	69.283	52.785	173.45	160.73	179.62	65.15	253.77	404.4	-425.0	-236.6	490.14	490.34	0.2766	0.4080	0.2642	16.496	0.1828	.5740	0.9192	0.9181	¥.005	4.185											
		20	32.125	24.619	66.920	49.339	169.24	153.81	158.15	70.50	255.60	342.4	-360.9	-184.2	431.45	439.84	0.1519	0.3523	0.2163	17.574	0.2237	.5672	0.9182	0.9172	10.620	7.239											
	ROTOR	70	27.755	25.845	63.422	40.090	166.90	150.08	164.18	72.76	253.80	333.3	-300.0	-138.4	372.76	392.16	0.2697	0.3012	0.1917	23.314	0.1767	5305		0.9735	10.922	7.590											
		06	23.385	27.835	58.688	23.778	163.56	144.59	166.46	76.37	267.03	7.017	-237.7	-74.0	314.07	341.00	0.1408	0.2498	0.1639	34.902	0,1155	• 11896	0.9570	0.9566	10.088	4.978											
w√ <del>0</del> /6 85.5		PCT SPAN	DIA 6	BETA 6	PR)	BETA(PR) 7	4 O 2 C	9 2/	7 7 7	V-THETA 6	V-THETA 7	V(PK) 0	VTHETA PR6	VTHETA PR7	9	<b>~</b> × ⊃ ‡	0 <b>~</b>	. BB	M(PR) 7	TURN(PR)	13	DFAC	EFFP	EFF	INCION	DEVM											
N/V@ 3078.		10	40.750	00000	142.04	160.03	142.04	00.00	55.84	0.1274	0.1436	74.07-		0.070	0.8521	-20,200	8.579					01	40.669	47.628	25.328	257.81	217.19	232.97	110.29	0.2865	0.2285	22.301	0.2438	0.3900	0.3993	2,628	8.228
CONFIGURATION CRUISE		30	35.850	00000	142.15	165.09	142.14	00.0	65.68	0.1275	0.1482		D DATA)	0.071	1.0498	-20.200	7 1.56	2				30	37.007	53.012	25.801	238.75	189,83	214.90	103.91	0.2807	0.2117	27.212	0.2039.	0.4618	0.5562	10.012	7.801
CONFIG	DE VANE	20	30.950	0.000	140.43	162.70	140.43	00.0	71.39	0.1260	0.1460	-20.03	& 100% SPEED	0.097	0.9458	-20,200	7 1.75	0.40	ſ	n .		50	33,345	56.814	25.991	209.41	165.45	187.79	91.77	0.2696	0.1859	30.823	0.2296	0.5413	0.6494	13.114	164.7
ED PT.182	INLEY GUIF	02	26.050	0.000	137.07	158.86	136.88	00.00	74.10	0.1230	0.1426	-21.80	(REFER TO 70%	0.115	0.9575	-20.200	70.1.7	0.440	1	STATOR		70	29.683	55.735	26.816	204.73	169.21	181.40	92.36	0.2696	0.1820	28.919	0.2149	0.5335	0.6940	9.635	8.316
SOPERCENT SPEED		96	21.150	0.000	130.06	153.75	130.94	00.00	78.78	0.1175	0.1380	-30.82	<b>в</b> )	0.134	0.9635	-20.200	פער	2117				96	26.021	57.942	30.949	126.13	160.15	106.30	200-16	0.2741	0.1119	26.993	0.4963	0.8264	0.4558	8.042	13.649
506		PCT SPAN	~	BETA 3	+ V - V	. 4	6 ZA	THETA	V-THETA 4	e E	<b>7</b>	LEN	13	DFAC	EFFP	WOLDW	OEVH					PCT SPAN	DIA 9	0	BETA 10	01 >	6 7/	2	V-IHEIA 9				13	DFAC	EFFP	INCIDM	DEVM

Blade Element Data Cruise Configuration (Continued) Table B-3.

		1,	40.865	18.562	46.384	70.811	55.645	179.19	140 05	214.70	57°C	225.33	516.A	7.00c	-488.0	114.1	545.09	5.40.47	0.2760	0.4641	0.3385	15.166	0.1890	.5566		1.0110	7.611	2.745												
		30	36.495	22,128	53.850	67.925	52.876	182.96	160.67	181.01	58.92	247.81	450.9	300.0	-417.9	-239.2	486.79	0.1643	0.2732	0.000	0.2670	15.046	0,1191	.5634	0.9431	•	8.325	11,278												
		50	32,125	24.771	57.528	65.257	48.937	179,39	78 671	160-56	75.16	252.44	389.1	244.6	-353.3	-184.4	428.50	430.84	7,2666	0.3494	0.2179	16.314	0.1554	.5561	0.9310	0.9302	9.157	6.837	}											
	ROTOR	5	27.755	25.927	55.046	61.408	39.695	177.51	0000	172.10	77.61	246.49	333,3	223.9	-292.6	-143.0	370.22	384.49	2486	2662 0	0.1999	21.691	0,1160	5053	0.9974	0.9974	8.908	7.192												
		66	23,385	27.538	56.129	57.021	23.084	170.59	31/*10	175.64	78.87	263.34	277.8	105.1	-233.1	-75.3	311.92	338.67	266100	0.2495	0.1717	33.930	0.0739	1,662	0.9778	0.9776	8-421	11.281												
8/@/3		PCT SPAN	DIA 6	BETA 6	BETA 7	BETA(PR) 6		€ F > :	, A.S.	0 7 4 7		V-THETA 7	V(PR) 6	_	VTHETA PR6	THETA	• r ⇒ :	~ ×	C.P-		M(PR) 7	TURNIPRI	13	DEAC	FFF	EFF	INCION	MARC												
N/V6 3057.		10	40.750	0.00	19.766	153.04	169.75	153.04	154.61	57.40	0.1373	0.1524	-19.77		,	0.078	0.8198	-20.200	0.23	1				<u>-</u>	40.669	44.303	25.488	320.18	229.13	241.58	223.63	115.17	0.2850	10 7 0 C	770.07	0.2132	0.3264	0.2465		8.388
configuration cruise		30	35.850	00000	23,344	151.96	175.29	151.95	46.00	9	0.1364	0.1574	-23.34	DATA)	•	0.076	1.0192	-20.200	7.556	3				O.F.	37,007	51.936	26.090	311.94	192.13	223.50	245.60	109.57	0.2777	25.847	10.00	0.1709	0.4042	0.5136 8.936		8.090
CONFIG	DE VANE	20	30.950	0.00	25.934	148.98	174.55	148.97	00.00	76.34	0.1337	0.1567	-25.93	& 100% SPEED	3	0.086	0.9518	-20.200	995.9			д		ç	33,345	56.684	26.771	301.69	165.10	190.53	252.11	96.52	0.2688	29.914	- 1	0.2183	0.5145	0.6442 12.98u	•	8.271
ED PT.183	INLET GUL	70	26.050	0000	27.761	144.39	169.92	144.19	60.0	70.15	0.1296	0.1526	-27.76	(REFER TO 70%	201 07 197	0.101	0.9138	-20.200	6.539	1000		STATOR		2	29.683	53.779	27,115	300.43	176.23	185.07	242.37	95.64	0.2682	26.664		0.1601	0.4992	0 • 7276 7 • 679		8.615
50PERCENT SPEED		06	21.150	00000	30.294	136.98	161.62	136.98	159.00	81.53	0.1229	0.1451	-30.29			0.125	0.8113	-20.200	5.706	3				ç	26,021	55.417	30.112	310.97	173.44	140.32	256.02	82.37	0.2778	25.304	7070	0.3494	0.6789	5.517		12.812
50P		PCT SPAN	DIA 3	BETA 3	ETA		4	£ 7.7	11111	V-THETA 4		4	TURN	ij	3	DFAC	EFFP	NOIDM	DEVM	2				PCT SPAN	DIA 9	BETA 9	BETA 10	6 ÷	6 7 1	01 7			o =	Nation		13	DFAC	INCIOM		DEVM

Blade Element Data Cruise Configuration (Continued) Table B-3.

					ļ	1					
			CONFIG	CONFIGURATION	N/V 69	20 00					
206	50PERCENT SPEED PT.18	ED PT.184		CRUISE	3070°	99.5					
								acutoa			
		INLET GUID!	UIDE VANE					TO TON			
PCT SPAN	90	92	20	30	10	PCT SPAN	06	70	50	30	10
DIA 3	21.150	26.050	30.950	35.850	40.750	DIA 6	23.385	27.755	32.125	36.495	40.85F
BETA 3	0000	000*0	0.000	000 0	0000	BETA 6	28,321	25.924	24.637	21.976	19.119
BETA 4	31.103	27.866	25.986	23.297	20.042		53,397	51.466	24.188	44.450	44.1.17
າ × > >	190.24	75.45	103.51	101 96	185.43	SETA(DR) 7	21.230	37.198	46.248	50.999	55.742
٤, ٧	150.23	158.25	163.50	166.55	167,17		192.63	196.58	197.96	201.02	193.14
4 ZA	156.42	164.96	171.98	176.30	174.20	~ >	328.79	311.65	308.48	312,97	313.02
V-THETA 3	0.00	00.0	00.0	00.00	00.0	9 ZA	169.54	176.65	179.91	186.41	187.49
	94.37	87.73	83.83	75.92	63,55	7	195.02	193.99	180.43	203.44	224.65
m E	0.1348	0.1422	0.1468	0.1495	0.1501	V-THETA 6	91,38	85.94	82.53	75.23	63.26
<b>4</b>	0.1641	0.1686	0.1719	0.1725	0.1666	٠.	263.95	243.79	250.16	18.162	×1.7.
Z Z Z	-31.10	-27.87	-25.99	-23.30	-50.04	V PK 0	2.672	350.1	241.0	4000	t . 10 E
13		(REFER TO 70%	& 100% SPEED DATA)	DATA)			-221.9	-285.9	-347.8	-413.6	-484-
DEAC	0.106	0.096	0.088	0.076	0.081		-76.2	-147.4	-188.5	-251.3	-323.7
EFFP	0.9519	0.9388	0.9562	1.0331	0.8428		313,25	371.79	430.33	488.86	547.4
; ;	000	Ç	000	-20.200	20.200	0.7	340.11	391.15	438.70	489.07	541.71
INCI D/W	-20.200	00.00-	003.03	20367		<b>9</b>	0.1731	0.1766	0.1779	0.1807	0.1735
DEVM	μ-897	<b>ካ</b> ይካ•9	6.514	7.003	8.950		0.2942	0.2785	0.2751	0.2790	0.2789
						M(PR) 6	0.2509	0.3020	0.3519	0.4077	2 . 4 . 4 . 4 . 4 . 4 . 4 . 4 . 4 . 4 .
		STATOR B	<b>m</b>			M(PR) 7	0.1882	0.2178	0.2528	7887.0	16.105
						CKN INSO	006.16	600.17		7	•
						13	0.0361	0.0847	0.1063	0,0780	0.1059
PCT SPAN	90	2	20	30	01	DFAC	.11829	. 11645	.5153	,1/2/11.	.3783
DIA 9	26.021	29,683	33,345	37.007	40.669	EFFP	0.9613	1.0014	0.9163	0.9701	1.0059
BETA 9	52.076	50.185	52.887	47.584	42.618	EFF	0.9610	1.0015	0.9154	0.9697	.900°I
BETA 10	28.701	27.234	26.871	26.096	208.62	EO LONG	010-1	+5. (0)	0.240	1 bi • o	₹ •
0->	223.65	230.12	232,57	265.21	279.23	DEVM	2.130	4.698	h.148	2.399	2.342
6 ZA	195.98	198.59	186.81	214.58	235.56						
	194.57	202.85	206.77	238.02	251,38						
V-INCTA 3	01.007	106.31	106 12	114 44	121 54						
	0.2904	0.2792	0.2770	0.2838	0.2853						
10	0.1992	0.2050	0.2068	0.2359	0.2484						
TURN	23.375	22.951	26.017	21.487	16.815						
13	0.1736	0.1472	0.1810	0,1293	0.1423						
DFAC	0.4788	0.4374	0.4508	0.3398	0.2704						
EFFP	0.7140	0.7266	0.6186	0.5860	0.4492						
DEVM	107.11	8.734	8.371	8.096	8.702						

Blade Element Data Cruise Configuration (Continued) Table B-3.

			T. TITINON	TO THE ACT TO THE PARTY OF	10/2	1/6/1					
		j	CONFIC	JEATLON	D / H	Ø .					
200	SOPERCENT SPEED	D PT.185		CRUISE	3062	100.2					
		INLET GUID	GUIDE VANE					ROTOR			
PCT SPAN	Uo	02	, C	30	10	PCT SPAN	06	22	20	36	01
014.3	21,150	26.050	30,950	35.850	40.750	DIA 6	23,385	27.755	32,125	36.495	40.865
BETA 3	0.000	0000	0.000	000.0	0.000	BETA 6	27.817	25.760	24.332	22.182	18.697
BETA 4	30.713	27.731	25.678	23, 433	19.829		40.454	40.474	50.438	40.034	67.877
m ∢ > >	160.31	202.34	204-18	20.87	107.58	BETA(DR) 7	21.446	35.844	45.294	50.697	55.665
VZ 3	160.30	169.00	174.76	178.05	178.95	<b>6</b> V	206.18	211,76	211.52	213.79	205.9R
	167.48	178.05	184.01	187.81	185.86	۲ ۸	334.13	31.7.30	309.35	311.54	307.80
V-THETA 3	00.0	0.00	0.00	00.0	0.00	9 2/	182.31	95.061	192.71	197.96	195.11
-THETA	99.50	94.15	88.47	81.40	67.02	,	216.17	20.902	196.96	28.612	62.72
m :	0.1439	6161.0	6961.0	0.1599	0.150	VITHEIA O	253 00	261.38	238.40	226.56	207.60
* C -	-30-71	-27.73	-25.68	-23.43	-19.83		282.8	337.8	392.6	452.5	518.1
<b>5</b> }	into /				•		233.4	254.3	280.1	337.6	402.0
3		verent to (Use &	TOO SHEED	LWTA)		VTHETA PR6	-216.2	-278.8	-342.1	-406.9	-48U.
DFAC	0.103	0.086	0.086	0.080	0.083	HETA	-85.3	-148.0	-199.1	-261.2	-332.7
EFFP	0.8489	0.9378	9606*0	0.9789	0.7922		312.44	370.82	429.21	487.50	545.98
20.00	-20,200	-20.200	-20,200	-20,200	-20,200		339.22	390-13	437.56	487.79	5 4 0 4 C
× 20	5	201	000	7 1.27	121 0	o P	0.1853	0.1904	2061-0	2261.0	- C
DEVM	5.287	6,509	0.022	/071	7.11.6	F 10071	6746	0.683.0	0.2703	10770	1.4657
		5	c			M(DR) 4	2000	0.2275	0.2501	0.3013	0,3503
		STATOR	Ä			TURNIPRI	28.411	19.781	15.306	13,357	12,213
						13	0.0143	0.0321	0.0629	0.0462	0.0745
NYOS LOO		į	i	;	:	3.	1	1	ì	9600	3500
TOT OF WE	90	70	50	30 46	10	DFAC	.3915	0.0821	4650	0.987	0.9956
BETA O	47.082	48.135	49.104	45.006	40.523		0.9812	0.9820	0.9327	0.9821	0.9956
8ETA 10	27.511	27.300	27.240	26.255	26.028	INCIDM	1.263	3.147	1.50	4-455	4.677
6 >	332.03	318.88	312.09	317.04	315.61		717 6	2 21.1.	101.5	2,007	2,765
01 %	255.82	75.462	201.94	224.04	230-01		2		***		
V2 10	225.33	224.32	223.28	248.44	263.11						
	246.68	237.40	235.91	224.21	205.07						
	118.17	116.76	115.32	122.62	128.49						
o :	0.2974	0.2852	0.2787	0.2830	0.2815						
200	20.471	20.815	21.864	18.751	14.495						
	E TE O	01110	7271.0	0.1203	0.1068						
13	0.1431	0.1410	111	614.0							
DFAC	0.3699	0.3538	0.3606	0.2748	0.1890						
INCIDA	-1.918	2.015	5.404	5.00¢	127-7-						
	1	ć	i	,	e e						
DEVM	10.211	8.800	8.740	8.255	8.928						

Blade Element Data Cruise Configuration (Continued) Table B-3.

		• •	CONFIGURATION	RATION	₩/V@	8/0/3				•	
50	SOPERCENT SPEED	EED PT.186		CRUISE	3056.	114.7					
		INLET GUIDE	JEDE VANE					ROTOR			
PCT SPAN	Ġ	Ş	ğ	ç	9	PCT SPAN	Ġ	ŕ	Ċ	ć	
	21 150	26.050	050	25.05	10		32 28E	27.755	30 106	36.405	10 40 845
•	000	000		000		٠.	27.653	25.675	24.405	20 428	21 045
	30.554	27.842	26.059	23.698	22,190	BFTA 7	44.651	46.424	43, 792	41.488	43.17
· · · · ·	178.12	187.18	192.02	193.01	185,99		46.790	53.670	58.733	62.361	64.718
. 4	209.38	213.44	213.86	216.12	227.54	RETA(PR) 7	22.668	35.948	44.008	50.165	55.96
	178.11	186.84	192.01	193.00	185.98		221.70	224.48	224.11	226.77	233.11
5 7A	180.28	187.90	191.81	197.40	210.42		338,59	319.71	314,32	311.99	305.50
<b>IHETA</b>	00.00	00.00	00.0	0.00	00.00	VZ 6	196.27	202.11	203.89	209.52	216.22
V-THETA 4	106.44	99.68	93.95	86.86	85.94	7 ZV	239.44	227.93	226.61	233,57	222.81
m Æ	0.1600	0.1681	0.1725	0.1734	0.1671		102.89	97.26	92.60	86.52	R7.12
4	0.1882	0.1919	0.1923	0.1943	0.2047	V-THETA 7	237.96	223.79	217.53	206.68	209.14
TURN	-30.55	-27.84	-26.06	-23.70	-22.19	V(PR) 6	286.7	339.7	392.9	451.7	506.3
13		(REFERENCE 208	ממממט אַייטר אַ			-	261.0	282.0	315.5	364.8	398.3
3		-	TOWN OF THE	₹			-508.9	-272.8	-335.8	-400.1	-457. A
DFAC	0.131	0.130	0.132	0.106	100.0	_	-100.6	-165.6	-219.2	-280.2	-320.1
EFFP	0.9193	0.8754	0.8556	1.0065	0.9144		311.82	370.09	428.36	486.64	544.91
שמיטאיי	-20.200	-20.200	-20.200	-20,200	-20.200		338.56	389.36	436.70	486.84	539.24
	1	1				•0 ! #E :	0.1994	0.2019	0.2016	0.2043	7.2097
DEVM	5-446	6-458	6-441	7.202	6.810		0.3037	0.2864	0.2813	0.2790	0.274
		.!	ı			M(PR) 6	0.2579	0.3055	0.3534	0.4063	7.4555
		STATOR	m			M(PR) /	0.2342	0.2527	0.2823	0.3263	0.355R
						A LANGO	001.47	C 6 4 6 1 7	1 1	601.21	*
						13	0.0398	0.0556	0.0452	0.0322	0.0650
PCT SPAN	06	02	20	30	10	DFAC	.2728	.3217	.3326	.3111	.3256
OIA 9	26.021	29.683	33,345	37.007	40.669	EFFP	1.0160	1.0083	0.9967	1.0137	1.0156
	45.946	45.802	42.312	40.123	41.385	EFF	1.0161	1.0084	0.9967	1.0138	1.015P
	27.160	27.257	27.608	27,113	26.266	INCLOW	-1.810	0.970	2.633	2.761	1.518
φ.	339.21	324.50	320.22	319.43	314.22		3 848	a::-	900	י בלב	2,065
7 70	200 277	23.450	234. 49	276.17	300.00	E AUG	3	7.440	7.700	2	3
01 27	255.05	253.63	260.37	265 03	276 37						
V-THETA O	01.150	220.62	215.56	20.00	207 72						
	131.82	131.55	130.61	135.70	136.59						
	0.3043	0.2908	0.2866	0.2858	0.2808						
	0.2584	0.2569	0.2518	0.2661	0.2757						
TURN	15.786	15.545	14.704	13.009	15.119						
13	0.1832	0.1193	0.1713	0.1020	0.1208						
,	*****	0226	7357	1011	0.70						
17 A	0.4222	0.5146	0.3179	0.2278	-1 3703						
INCION	1756-9-	-3.298	-1.388	-2.877	-3.615						
DEVM	9.860	8.757	9.108	9.112	9.166						

Blade Element Data Cruise Configuration (Continued) Table B-3.

							,	,			
506	SOPERCENT SPEED	ED PT.181	CONFI	CONFIGURATION	N/ï 3080.	121.0					
		INLET GUID	E VANE					ROTOR			
PCT SPAN	06	02	50	30	10	PCT SPAN	06	70	50	36	-
DIA 3	21.150	26.050	30,950	35, 850	40.750	DIA 6	23,385	27.755	32,125	36.495	40.86E
BETA 3	0.00	0.000	0.000	0.00	0.000	BETA 6	27.869	25.392	24.148	22.016	19.075
ETA	30.882	27.581	25.717	23.274	19,867		43.055	41.685	41.208	39.169	36.394
	184.56	194.21	200-22	203.28	203 - 72	BETA(PR) 6	44,310	50.803	56.173	67.4.0	
<b>↑</b>	16.727	250.30	233.27	253.70	275.51		241 42	33.428	243.112	243.875	240.00
	105.04	203-06	210.16	212.68	211.96	c r-	353.23	328-03	319.04	316.25	00,800
THETA	00.0	00.0	0.00	00.0	00.0	VZ 6	713.56	219.25	222.47	226.00	219,13
V-THETA 4	116.67	106.63	101.22	92.34	76.59	7 ZV	256.93	244.79	239,93	745.15	248.14
	0.1658	0.1745	0.1799	0.1827	0.1831	THETA	112.95	104.14	99.75	91.19	75.35
	0.2045	0.2072	0.2099	0.2103	0.2027	V-THETA 7	241.15	218.15	210.18	199.74	182.92
TURN	-30.88	-27.58	-25.72	-23.27	-19.87	V(PR) 6	293.5	347.0	399.6	458.6	522.1
1	מהמשם /		American departed to the control of	(			276.8	300.6	332.4	340.5	437.7
3	, resp.	8 RO OT	TOTAL SCOOL			VTHETA PR6	-201.3	-268.9	-332°n	-399.1	-473. B
DFAC	0.092	0.092	0.089	0.078	0.081	ETA	-100-	-174.3	-229.9	-290.9	-360. A
FFP	0.9056	0.8651	0.8825	0.9607	0.7777	9 D	314.27	373.00	431.73	400.46	640.10
2000	-20,200	-20-200	-20.200	-20.200	-20.200	<b>-</b> 1	341.22	392.42	440.13	490.66	543.47
K C C C			201	003.03		<b>4</b> 0 1	0.2175	0.2186	0.2195	0.2194	2085
DEVM	5.118	6.719	6.783	7.626	9.133		0.3172	0.2942	0.2859	0.2831	0.2757
						A(PR) 5	2992-0	0.3123	0.3597	92158	7.00
		STATOR	g			TION DO	0.2486	15.257	12.307	13,500	0.710
						1	70100	0)100	70,00	71100	0 0433
						3 -	0.100	0.0409	0,500	0.0440	C 200.0
~-	06	2	20	30	10	DEAC	.2282	.2686	.2864	.2758	.2576
•	26.021	29.683	33.345	37,007	40.569	EFFP	1.00.18	1.0347	1.0092	1.0000	0.9650
BETA 9	41.352	40.131	39,949	37,712	35,045	1011	1.00.79	1.0349	1.0093	1.0000	0.9655 1.081
9E1A 10	263 26	71.013	226.07	222 03	401012	INCIUM	-2.690	, KO*T=	0.00	0.00	106.1
	318,75	313.64	303.24	315.74	319.75	DFV₩	2,392	2,928	1.672	1.276	2.562
6 ZA	260.94	253.03	248.00	255.44	256.06			•	•		•
VZ 10	280.19	276.05	267.78	281.30	284.58						
	233.46	214.61	208.09	197.53	179.61						
	148.95	145,40	141.37	143.31	145.68						
o -	0.3173	0.2987	0.2904	0.2892	0.2798						
TURN	13.494	12.514	12,161	10.718	7.940						
1	0.2217	0,1295	0.1729	0.0927	0.0692						
3											
DFAC	0.1812	0.1396	0.1525	0.1005	0.0309						
INCIDM	8.548	696.5-	-3.751	-5.288	-9.955						
DEVM	10.558	9.118	9.288	8.995	10.001						

Blade Element Data Cruise Configuration (Continued) Table B-3.

			10	40.865	51.590	70-114	60.080	269.95	438.45	213.40	164.67	385.63	6.88.8	418.3	-591.4	-362.5	748.16	0.2432	0.3872	0.5666	0.3694	10.033	-0.0184	1987	0116.0	0.9086	6.914	7.180	-											
			30	36.495	55.151	68,591	53,176	246.59	456.69	226.74	96.87	350.55	621.2	405.9	-578.3	-324.9	675.45	0.2220	0.3774	0.5592	0.3590	15.412	0.1658	.5289	0.9423	0.9409	8.991	11.576	1											
			20	32,125	24.810	66.221	49.454	239.76	410.19	217.54	100.60	343.10	539.6	345.8	-493.7	-262.8	605.89	0.2158	0.3637	0.4856	0.3067	16.759	0,2031	.5497	0.9703	9696.0	10.121	7 35	***											
	ROTOR		70	27.755	060-07	63.038	42.261	233.13	405.78	209.30	102.38	342.53	461.4	293.9	-411.1	-197.7	540.21	0.2097	0.3607	0.4151	0.2613	20.741	0.1253	.5720	1.0011	1.00.1	10.518	192 0	101.											
			06	23.385	25.011	58.711	27,473	226.11	419.16	204.83	95.60	349.06	394.4	261.6	-337.0	-120.7	456.03	0.2034	0.3734	0.3548	0.2330	31.229	0.1144	.5794	0.9734	0.9729	10.11	643	6.00											
الم / <u>ھ</u> /ج 118.8		PCT SPAN		DIA 6	BELA O		BETA(PR) 7	٧ ٧	۲ ۸	9 7 6		V-THETA 7	V(PR) 6		VTHETA PR6	HETA		- vc	\ **	M(PR) 6	M(PR) 7	TURN( PR.)	13	DFAC	EFFP	EFF	INCIDM	MAU												
N/V6			10	40.750	0.000	196-41	255.22	196.41	209.53	00.00	0.1765	0.2298	-34.81	0.0420		0.071	166490	-20:200	- 5.815					01	40.669	61.280	23.217	355.45	228,56	326.79	417.38	140.20	0.4214	0.3125	20.00	0.1604	0.5307	0.6810	007*07	6.117
RATION CRUISE			30	35.850	0.000	198.82	235,57	198.81	214.42	0.00	0.1787	0.2120	-24.42			0.061	1000	-20.200	6.483	•				30	37.007	53.905	75.604	431.61	254.27	599,49	348.76	143,79	0.3818	0.2928	106.82	0.2095	0.4501	0.5706	10.305	7.004
CONFIGURATION 8	DE VANE		50	30,950	000.00	197.38	228.94	197.38	205.02	00.00	0.1774	0.2059	-26.35	0.0176	1	0.099	7606.0	-20.200	6.154		æ	1		50	33, 345	55.120	25,119	205 86	236.91	267.26	340.35	125.59	0.3679	0.2610	100.00	0,2426	0.5126	0.6198	11.420	6.619
PT. 16	INLET GUID		7.0	26.050	00000	192,06	222.14	192.69	195,43	00.0	0-1734	0.1998	-27.94			0.122	0649.0	-20,200	6.358	1	STATOR			70	29.683	56.334	26.491	404.65 253.06	223.08	224.73	336.79	112.88	0.3597	0.2234	649.67	0.3502	0.5992	0.4970	10.234	7.991
PERCENT SPEED			06	21.150	0000	184.47	212,14	184.67	187.71	00.0	0.1659	0.1907	-27.75	. O. B.	1	0.125	0.9195	-20.200	8.248					06			37.892		216.29	107.54	340.11	85.50	0.3607	0.1225	19.100	0.5982	0.8908	0.3561	(*T>)	20.592
P 07		WACCO FFOO	LOI SEAN	E A I	BELA 3	<u>.</u> "		~	4	V-THETA 3	+ 4-11-1-A		=	13	3	OF AC	i.	INCIDM	DEVM				;	PCT SPAN	DIA 9	ETA 9	w	o -		VZ 10	_		O	01	2 2 2	13	DFAC	FFFP	E 0.	DEVM

Blade Element Data Cruise Configuration (Continued) Table B-3.

<b>d</b> 0 <b>L</b>	PERCENT SPEED	PT. 16	CONFIG 9	CONFIGURATION CRUISE	N/V@	w√6/8 125.					
		INLET GUI	GUIDE VANE					ROTOR	œ		
PCT SPAN	96	70	50	30	10	PCT SPAN	06	02	20	30	10
~	21.150	26.050	30.950	35,850	40.750		23,385	27.755	32,125	36.495	40.865
BETA 3	28.104	28.214	26.129	24.339	22.887	BETA 7	57.453	52.476	57.514	56.204	51.807
	193.01	202.45	207.55	210.51	211.44	ETA(PR)	56.659	61.041	65.017	67.742	70.630
•	227.28	236.38	243.91	247.75	239.88	BETA(PR) 7	26.653	40.527	49.592	54.049	58.066
٤ ٧٢	193.00	202.20	207.55	210.50	211.43	9   > '	240.94	249.95	251.95	256.71	251.85
4	200.47	207.36	218.95	225.73	221.00	۲ <u>۲</u>	473.54	412.64	412.39	424.18	422.28
V-THETA 3	00.00	00.00	00.00	00.00	00.00	47 6 7 7 7	217.45	224.28	228.44	235.77	253.88
	0-1734	0.1819	0.1866	0.1892	0.1901		103.65	110.00	106-16	101.49	93.43
	0.2044	0.2127	0.2195	0.2230	0.2159	V-THETA 7	357.02	327.26	347.86	352,50	331,88
TURN	-28.10	-28.21	-26.13	-24.34	-22.89	V(PR) 6	395.7	463.3	540.9	622.5	705.2
١;	0.0559		0.0297		07.40.0	_	254.9	330.7	341.7	401.9	493.6
3	Coro.	1	0.00			VTHETA PR6	-330.5	-405.3	-490.3	-576-1	-665.3
DFAC	0.107	0.112	0.085	0.067	0.086	HETA PR	-114.4	-214.9	-260.2	-325.3	-418.9
EFFP	0.8755	0.8710	0.8889	0.9645	0.8260	<b>∵</b> • •	434.16	515.30	596.43	677.56	758, 70
NCION	-20.200	-20.200	-20.200	-20.200	-20.200	~ <b>«</b>	0.2168	0.2250	0.2268	0.2312	0.2268
DEVM	7.896	980.9	6.371	6.561	6,113	) <b>~</b>	0.3773	0.3676	0.3657	0.3752	0.3729
	-		•	•			0.3561	0.4171	0.4870	0.5605	0.6349
		STATOR	æ.			M(PR) 7	0.2271	0.2946	0.3030	0.3554	0.4359
						TURN(PR)	59,999	20.497	15.420	13.691	12.564
						13	0.1112	0.0938	0.1518	0.1260	0,1661
PCT SPAN	06	70	50	30	10	DFAC	5983	98617	.5578	5344	.4581
01A 9	26.021	25.683	33,345	37,007	40.669	EFFP	0.9734	1.1008	59	0.9376	0.9653
	57.432	51.155	56.208	54.559	49.411	EFF	0.9729	1.1029	0.9588	0.9360	0.9644
<b>BETA 10</b>	29.828	25.604	25,779	25.819	23.346	INCION	8.059	8.541	8.917	8.142	7.430
6 : >:	412,33	413.43	415.40	430.00	436.45		i	, to 0	607	7. 0.14	7
0 0	185.29	257 00	292.46	337.50	303.94	DEVM	(<0.)	0.02	1 •476	).m	2.100
01 77	158.02	759.67	262.54	303.56	334.15						
THETA	347.49	322.00	345.22	350.32	331.44						
V-THETA 10	92.16	125,38	127.19	146.99	144.22						
<b>О</b>	0.3671	0.3684	0.3684	0.3804	0.3858						
01	0.1632	0.2575	0.2579	0.2970	0.3203						
TURN	27.604	25.550	30.429	28,739	26.065						
13	0.4871	0.1942	0.2387	0.1844	0.1740						
DFAC	0.7813	0.4907	0.5249	0.4351	0.3712						
EFFP	0.4153	1.0757	0.6335	0.5565	0.4033						
INCIDM	7.532	5.055	12.508	11.559	דניוייין						
DEVM	12.528	7.104	7.279	7.819	6.246						

Blade Element Data Cruise Configuration (Continued) Table B-3.

		•					1	•			
			CONFIGURATION	RATION	N/ 4 0	8/0/0					
70 P	PERCENT SPEED	ED PT. 170		CRUI SE	4260.	131.					
		INLET GUIDE	VANE					acinoa	Ω		
									<b>:</b>		
Not Span		i	1		,	PC# SPAN	į	i		9	:
	90	70	50	30	10		90	70	50	30	010
DIA 3	21.150	26.050	30.950	35.850	0.000	DIA 6	25.385	26.65	32.125	35.495	22.345
	27.905		26.087	24.317	23.385	BETA 7	54.041	53.696	55.887	54.311	926.03
- - - - - -	201.08	211.15	217.20	220.82	222,12	2	54.798	59.745	63, 786	66.709	69.501
· <b>&gt;</b>	239,85		255.14	258.08	252.82	BETALPR) 7	23,765	38.801	48.354	53.268	56.845
	201.07		217.20	220.82	222.11	9 >	254.45	260.72	263.89	268.24	266.15
	211.95		229.13	235.19	232.05	٧ ٢	441.90	423.39	417.36	425.76	429.48
V-THETA 3	00.0		00.00	0.00	00.00	V2 6	230.11	233.53	239.44	246.59	246.16
	112.23		117.19	100.00	100.35		100	23.00	110.00	104047	0.00
	0.2158		0.2297	0.2324	0.2276	V-THETA 7	357.69	341.20	345.54	345.80	328.88
	-27.90	-28.22	-26.09	-24.32	-23.39		399.2	463.6	542.1	623.6	702.9
J	0.0,0		0.0362		0.0460	~	283.5	321.7	352.2	415.3	505.0
3						D.	-326.2	-400-4	-486.3	-572.8	-658.4
DFAC	0.093	0.105	0.085	0.073	0.087	THETA	-114.3	-201.6	-263.2	-332.8	-422.8
H G G	0.9153	0.8863	0.9222	0.9919	0.8922		434.67	515.90	597.13	678.36	759.59
INCIDM	-20.200	-20.200	-20.200	-20.200	-20,200		46.174	542.16	608.73	40.870	731.69
N DECK	8 005	6.077	6.1.13	583	5.015	C ↑	1677*1	0.2348	0.2377	0.271	0.2799
	1000	•		6			0.3595	0.4175	0.4883	0.5619	0.6332
		STATOR B				M(PR) 7	0.2530	0.2865	0.3127	0.3678	0.4467
		;				TURN(PR)	31.027	20.924	15.428	13.440	12.656
						13	0.1034	0,0840	0.1029	0.0856	0.0874
PCT SPAN	06	70	20	30	10	DFAC	.5266	£025	5341	.5060	4,329
DIA 9	26.021		33.345	37.007	40.669	EFFP	0.9702	1.0394	0.9531	0.9429	0.9820
6	53.534		54.579	52.541	47.807		0.9696	1.0402	0.9521	0.9415	0.9815
BETA 10	28.939		26.056	25.879	25.081	INCIDM	6.198	7.245	7.086		105.0
> >	228.78		302.98	349-31	372.04	N N H N	3965	6.301	6.251	4.060	3.945
6 7/	252.22		243.23	262.81	299.32	1	\ \ \ \	•			
	197.78	260.07	271.24	314.01	336.96						
	347.09		46.246	545.25	330.13						
M 9	0.3855		133.08	0.3830	0.3946						
M 10	0.2019		0.2673	0.3079	0.3279						
TURN	24.595		28,523	26.662	22.726						
13	0.3440	0.1928	0.1874	0.1207	0.1575						
DFAC	0.6740	0.5096	0.4974	0.3975							
EFFP	0.5606	0.6823	0.6868	•	0.4987						
I AC LDM	3.634	6.307	10.079	9.541	2.807						
DEVM	11.639	7.490	7.556	7.879	7.981						

Blade Element Data Cruise Configuration (Continued) Table B-3.

70 P	PERCENT SPEED	PT.171	CONFIGURATION CRU	ATION CRUISE	N/VØ 4245.	140.05					
		SO THE BOLING	THE DE TAME								
			VANE					ROTOR			
PCT SPAN	06	70	50	30	10	PCT SPAN	06	70	50	30	10
DIA 3	21.150	26.050	30.950	35.850	40.750	01A 6	23.385	27.755	32.125	36.495	40.865
		0.000	0.000	000.00	0.000	BFTA 6	25.436	26.298	25.162	23.174	23.225
6 t A 4		725.45	232.77	236.88	23.4.32	DB )	52.067	57.383	61.277	64.516	68.146
• >	256.86	265.72	276.96	278.11	270.99	BETA(PR) 7	22.410	37,118	45.866	52.870	55.638
VZ 3		225.20	232.76	236.83	237.31	۰ ۲	272.78	278.96	286.55	291.09	781.83
4		232. 79	24/*66	253.73	247.	, A	456.44	740.80	250.31	2434.61	258 00
V-THETA 4		125.78	123.96	114.97	109.84	7 7	781.44	269.16	251.64	280.49	293.35
	0.1926	0.2028	0.2094	0.2132	0.2135	V-THETA 6	117.16	123.59	121.84	114.55	1111.14
<b>4</b>	0.2313	0.2394	0.2496	D.2507	0.2442	V-THETA 7	353.59	336.97	347.13	331.43	320.00
TURN	-28.17	-28.25	-26.59	-24.42	-53.91	V(PR) 6	400.7	463.7	539.6	65179	695.8
13	0,0460		0.0307		0.0320	, (	306.1	337.9	361.5	444.5	519.7
3 5	i d	ò	0	0	i de	VTHETA PR6	-316.0	-390.5	75.2	-561.4	1645
UTAC GEED	160.0	0.8867	1.0825	1.2081	1.0722	4	7110.7	514.00	595,03	675.97	756.93
	1000.00	1000.00	6 34 00	160.00	77.007		470.28	540,85	606.61	676.25	749.04
INCIDM	-40.400	-20.200	-20.200	-50.500	-20.200		0.2458	0.2515	0.2584	0.2625	0.2541
DEVM	7.834	6.0l48	5.912	6.482	5.068	7 1	C.404A	0.3849	0.3813	0.3857	0.3851
		4	p			4(pg) 6	0.3611	0.4180	0.4866	0.5609	0.6272
		SIATOR	ז			M(PR) 7	0.2736	20.245	0.3215	13.665	12.508
						1	0.0686	0 0503	9020	9190.0	0.027
WACO BOOK						3	0000	2000	5	\	1010 1010
PGF SPAN		70	50	30	c <sub>1</sub>	DFAC	· 1.609	.1,573	5075	.4416	.3932
^		29.683	33,345	37.007	40.669	EFFP	•	1.0084	0.9174	1026.0	0.9936
BETA 9		50.079	52.668	48, 183	46.102	F F F	0.0557	1.0086	0.9158	9696	0.9934
8 ETA 10	27.622	26.812	26. 757	25.674	26.087	FOI DNI	7.40(	4.003	2.11	4.710	1. YEO
		317.13	318.63	364.24	385.04	DEV	3.610	4.618	3.766	2.270	2.738
~		275.80	261.04	294.67	306.73						
01		280.73	283.63	328.24	345.79						
V-THEIA 9		331.88	17.646	329.52	318° (8						
- I		0.3861	0.3838	0.3979	0.3926						
01 1		C.2811	0.2815	0.3221	0.3404						
TURN		23.267	25,911	22.560	20.015						
13	0.1768	0.1283	0.1837	0.1146	0.1065						
DFAC	0.4872	0.4434	0.4633	0.3572	0.2916						
FF	0.7280	C.7807	0.6571	0.6727	0.6165						
LNCIOM	752.0	3.979	8.908	5.183	1.162						
DEVM	10,322	8.312	8.257	7.624	8.987						

Blade Element Data Cruise Configuration (Continued) Table B-3.

			0 30 10	36.495		44.811	500 62.400 66.495	315.26		289.97	306.17	123.69		483.7		-374.4	678.36	75 678.64 751.69	0.2847	0.5652	574 0.4313 0.4951	11.674	336 0.0399 0.01 <b>90</b>	895 .3559	342 1.0632 1.0336	1.0645	~ono•>	.318 2.126 3.127									
	ROTOR		70 50				53,650 58,5		434.74 427.86			136.25 131.						542.76 608.					0.0388 0.0336	. 3575	7		1.150	1.734 3.									
wÿ/s 152.6					25.452		PR) 6 47.482	-		277.46		9.1	_	۰.۲	1 PR6	A PR7	434.67	471.94	97770	6 0.3706		PR1 22.379	0.0620	. 3209	1.0677	1.0688		6.297									
N/√ <del>0</del> 4260.				40.750 DIA 6		BETA	BETA(	¥ 100	271.40 V 7			0.2334 V-THETA		00.1	O.OLLO VIHETA	T.	0.9200 U 6		0.619	•			i3	10 DFAC		41.748 EFF	432.83	412.45 DEVM	322.89	353.44	194.91	0.3852	0.3666 13.547	9990*0	0.1511	0.4681	-3.52
(FIGURATION CRUISE					00000	24.567	258.84	258.83	273.77	00.00	125.15	0.2331	0.2710			3 0.080		20,200	0.333					30	37.007	43.077	439.55	391.36	321.01	300.21	169.23	0.3921	17.457	0.1299			220.0
CON PT.173		INLET GUIDE VANE	70 50						258.98 269.83			0.2227 0.229			0.032	0.092 0.083	0.9142 0.9628	-20.200 -20.200	0.249 6.210			STATOR B		70 50									0.3277 0.3213 17.317 19.532			· m ·	-T-003 2.544
70 PERCENT SPEED			90	170	1	28.256			254.27	00.00	136.65		-28.26		0.0402		0.9746 0	-20.200	7.711					06		43.882 4		370.82		313.03	168.24		0.3308 0.901				010.0
<i>E</i>				~	BETA 3	₹.	n 4 > >	. ^	4 Z 4	V-THETA 3	THETA	m ·	TIPN NOTE	į ,	3	DFAC	EFFP	NOIDWI	DFVM	:				PCT SPAN	DIA 9	BETA 9	<b>→</b>	01 ^	6 7/	V-IHFIA 9			TURN	13	DFAC	EFFP	E01011

Blade Element Data Cruise Configuration (Continued) Table B-3.

	9	A CHARLENII SPEED	PH 16.7		GARWITHON	M/40 4255.	166.					
			IINULETI GAUTUDE: VIANE	WANTE					HOLLON			
	HCC SPAN	08	<u>@</u>	ē	9	91		9	92	8	30	01
	DIA 3	21.150	26.050	30.950	35.850	40.176	DIA 4	23.385	27.755	32,125	36.495	40.865
	BETA 3	0000	0000	0000	0000	000-0		25.44B	26.157	24.974	23.370	23.131
		1994 * 997 1994 * 997	28° 197	26° 450 (1	24 - 400 P	25 B B B B B B B B B B B B B B B B B B B				47.304	40.080	59-852
	A ∮	2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	20 H La 38		200 De 00 Z	40 mm mm				369-64 64-645	40. R61	54.388
		258 38	2711-115	279-46	283.61	284.35		14 B B B	343.27	344.74	344.41	333.15
	* * * * * * * * * * * * * * * * * * *		28% 38	296.12	3000	294°00		490.09	447-17	441-14	436.98	438.37
	DHETA	_	00-00	000	99-9	99.9	WZ 66	307.66	307.95	312.47	316.15	306.37
	W-ENTRY 4		154.29	11466. 72	137.55	130.02	A ZW	368 96	326.37	325.84	331.92	336.63
	<b>E</b> 19		@2445	0.2519	0.2557	0.2564	W-THEFT &	146-62	151.32	145.55	136.62	130.88
	手手		0.2950	0.2987	6.2985	6 Z964		320-62	300 Page	297.26	284.18	280.80
		-28.58	-28-20	-26.36	-24°60	-23.86		4.21.1	4.76.9	548.6	9-929	698.6
	1,	8 CT		0.007b		@ <u></u>	-	400	403.3	450.4	514.9	578.1
1 !	3							-284°5	-364-0	-450.9	-540.9	-627.8
E F	DIFFAC		<b>6.08</b> 3	@	64.0	9999	WINETA PRI		-236°T	-310.8	-393.7	-470-0
ì	EFFE	<b>9280</b>	0.9062	O. 9318		O. 8623	9	434-16	512.30 515.30	596.43	6777-56	758.70
	malienii etta ette	200,2000	30 200	30 300	30 300	20 200	<b>/</b> 9	471.39	542.13	608.03	677.84	750.81
	HANGE HOUSE			1		1	<b>3</b>	3085	6-3104	0.3116	0.3115	0.3011
		6TT-1	6-10H	@ 1113	6 285	S IN	# F	4 4 4 B 4	4 6 4 6 1 4 B	0.3954	0.3911	0.3917
							TAN PRINGS		0-4313	0.4962	0.5667	0.6314
			STATION B	æ				4096	0.3621	0.4036	0.4609	0.5166
								20 - 07 C	12-07	FE-034	7.833	7.000
							13	0090	0.0550	0.0413	0.0216	-0.0228
	HOLL SHAME	9	9/2	6	96	100	IDFAC	2115	287h	3038	283	.272
		26.021	29.683	· · · · · · · · · · · · · · · · · · ·	700 LE	40-669	EFF	60000	1.0385	1.0328	1.040	1.0211
	BETA 9	380° 2003	41.49B	<b>後明1-11</b>	39.063	37.861	EFF	1 0 5 9 8	1660-1	1.0333	11.0411	1.0215
	BETA 10	27.821	28262	27-647	25.978	25.576		14-1515	18. 13m	683	0.097	0.788
	₽ 3	488-68	453.47	44B-87	447-92	450.25			;	1 1		
	<b>61</b>	44	431°14	417.95	432.50	444.04		A-DA	DE M	1-535	1.261	1.00 I
	W A 9	371.73	337.64	337.26	347.12	355°45						
		393°62	347-72	9488 THE	E .	400-48						
				88 ARK	282°Z"	A 110 . 144						
			NET STAN									
	<b>9</b>											
	9			94149								
		11.681	13.231	13.522	13-086	12 - 284						
	13	0.2017	0.1343	0.1995h	0.1216	0 1345						
	DE-AC	# 14 m	0 1 3 0 0		0 - 1 - 40 - 40	0. 1046						
	EFF			Ī	•	3.2708						
		166-001	109-17	2.53	156.6	-11-1399						
	DEVI	100, 421	9.762	10 miles	J. 970	8 Juil 6						
	: ;		:	:								

Blade Element Data Cruise Configuration (Continued) Table B-3.

			۲.	40.865	19.054	40.054	70.007	56.830	280.55	484.05	265.17	312.21	91.49	371.08	810.7	570.6	-766.1	-477.7	857.64	848.74	0.2520	r.4264	n. 7308	0.5017	14.077	0.2420	1,57	0.079B	0.9791	7.707		3.930												
			<u>د</u>	36.495	22.059	55.652	68,036	53,906	286.51	479.05	265.50	270.22	107.40	395.52	400.0	458.8	-658.3	-370.7	765.94	766.26	0.2583	0.4220	0.6401	0.4042	14.128	0.1511	5318	9.9504	n. 9581	8.436	1	2.30												
			50	32.125	24.739	58.925	65.565	50.406	278.99	464.25	253.29	239.43	116.75	397.63	612.4	376.0	-557.5	-289.7	674.23	687.34	0.2515	0.4102	0.5520	0.3322	15.151	0.1687	አያ የ	0.9665	0.9655	9.465		8°306												
	ROTOR		Ç	27.755	25.936	56.627	62.265	41.400	271.45	464.25	243.85	255.02	118.72	387,69	524.1	340.5	-463.8	-225.1	582.51	612.84	0.2446	0.4120	0.4723	0.3021	20.841	0.1035	4464	1.0549	1.0564	9.765		8.90												
			٥6	23,385	27.554	59.644	58,253	26.477	259.nl	478.08	229.54	230.52	119.81	412.54	436.3	269.9	-371.0	-120.3	490.79	532.87	ñ.2333	0.4251	0.3929	0.2400	31.767	0.0103	6353	0.9947	0.9946	9.653	1	7.677												
8/6/8 138.0		N V GS IIJG	NW 10 10 1		RETA 6	BETA 7	RETA(PR) 6		<b>\$</b>	۲ >	9 2 /	7 7	V-THETA 6		V(PR) 6	V(PR) 7	VTHETA PR6	THETA	٠ ۲		.c ≱	~	M(PR) 6	M(DR) 7	TURN(PR)	.1 <u>3</u>	NEAC	FFFP	EFF	INCIDM		DEVM												
N/ö 4810.			0	40.750	000.0	20.275	234.08	266.24	234.07	249.75	00.0	92.26	0.2106	0.2399	-20.28			0.059	0.8707	200		8.725					Ç	40.669	45,454	21,343	500.75	415.24	338.60	383.45	150 03	0.000	0.3506	26,110	0 21,52	1	0.3856	2-150		t.243
CONFIGURATION CRUISE			30	35,850	000 0	23,381	232.97	273.09	232.96	250.65	00.0	108.37	0.2096	0.2461	-23.38		DATA)	0.061	0.9926	006.06-		7.519					Č.	37,007	53.796	25,791	486.77	383.11	287.32	20.446	93.74.6	60.6001	0.3355	28,005	9616.0	0 11 0	0.4291	10.796		7.791
CONFIG	GUIDE VANE		50	30.950	00000	26.088	229.13	269.00	229.12	241.52	C . C	118.29	0.2061	0.2424	-26.09		& 100% SPEED	0.086	0.9345	200	003	6-412		£	1		0.5	33,345	57.408	25.407	467.38	346.45	250.99	311.08	3430.66	10.641	770-0	32.001	0.21.93	7/11-0	0.4874	13,708		6.907
ED PT.175	INLET GUID		02	26.050	000.0	27.880	222.91	258.51	222.54	227.36	0.0	120.88	0.2005	0.2328	-27.88		OL OL HELEN)	0.115	0.8844	20 200	007.07	6.420		G OT A TP.	`		0,2	29,683	55.432	26.327	462.78	275.69	260.78	244.13	100 001	2017	0.2422	29,104	0.1558	27.	0.6315	9.332	-1	7.827
80PERCENT SPEED			06	21.150	0.00	30.178	212.16	245.99	212,15	212.62	00.0	123.66	0.1907	0.2214	-30.18	• •		0.139	9098-0	20.200	201-01-	5.822	ı				6	26,021	60.417	37.741	461.79	143.68	223.88	111.28	401.04	1017	10110	22.676	0.6653	0000	0.9428	10.517		20.141
3 d 0 8		200					<b>6</b> >	4	٧٤ ع	7 7 4	V-THETA 3	V-THETA 4	E E	٠ <b>٠</b> ټه	TURN	1	3	DFAC	EFFP	•	INC:DW	DEVM					PCT SPAN	DIA 9	BETA 9		0		6 7 7	01	VITELY V			_	į.	3	DFAC	INCIDM		DEVM

Blade Element Data Cruise Configuration (Continued) Table B-3.

			CONFIGURATION	RATION	N/VO	8/010					
80	BOPERCENT SPEED	PT.177	CR	CRUISE	4820.	147.5					
		INLET GUIDE VANE	VANE					ROTOR			
PCT SPAN	06	70	20	30	10	PCT SPAN	06	70	50	30	۲.
m	21.150	26.050	30.950	35.850	40.750		23,385	27,755	32.125	36.495	40.865
		00000	0.000	000.0	000.0	8ETA 5	27.653	25.837	24.631	21.802	20° 281
6E1A 4	30.299	260 020	246 96	250.46	267.07		55.401	50.419	026.95	54.967	A 12 5 12 5
> > u 4		276.09	282,36	286.16	297.29	BETA(PR) 7	23.869	39.393	48.040	53.035	56.822
VZ 3		239.59	246.94	250.45	247.06	9 /	280.73	289.90	293,31	300.52	314.88
4	230.48	243.09	253.43	262.91	276.63	<b>~</b> >	495.19	476.08	476.69	484.30	489.15
V-THETA 3	00.0	00.00	00.0	00.0	00.00	9 7.7	248.55	259.85	266.45	278.94	795.34
V-IHEIA 4	0.2052	128.52	0.2223	0.2255	100.04		130.29	125.95	122.24	111.61	109.14
		0.2488	0.2546	0.2580	0.2682	V-THETA 7	413.27	390.66	399.45	394.41	380.64
TURN		-27.74	-26.07	-23.14	-21.43	V(PR) 6	438.8	526.5	614.3	712.8	806.3
١	icacio)						298.3	352.1	389.1	4.67.4	561.4
3	TE ATTLE )	e e	3	LATA)		VTHETA PR6	-361.5	-457.8	-553.4	-6559	-750.3
DFAC	0.132	0.121	0.109	0.083	0.016	HETA	-120.7	-223.5	-289.3	-373.4	-469.9
EFFP	0.9113	0.8911	0.9012	0.9676	0.9257		491.81	583.72	675.63	767.53	859.44
INCIDM	-20.200	-20.200	-20.200	-20.200	-20.200		533.98	614.11	688.77	767.85	250.50
	5,701	6.456	85,4.9	7.763	7.566	C 7	0.6231	00070	0.4217	0.4270	4004
מאש	1011	27.0		-	3		0.3956	0.4748	0.5541	0.6432	7281
		1				M(PR) 7	0.2658	0.3128	0.3442	0.4121	7.4941
		STATOR B				^	31.610	21.001	16.234	13.920	11.691
						,3	6900.0-	0.0694	0.1172	0.1070	0,1606
PCT SPAN	06	02	0.5	30	10	DFAC	.5652	.5336	.5580	.521h	.4631
OIA 9	26.021	29.683	33.345	37.007	40.669	EFFP	0.9859	1.0125	0.9422	0.9394	0.9713
	56.443	53.726	55.523	52.642	49.095	EFF	0.9855	1.0128	9046.0	0.9375	50703 CEC 7
8 10 × 0 × 0	30.201	476 24	480.43	42 176	504.436	INCLUM	160.0	7.919	0.190	705.)	7.51
07	214.20	328.88	339.01	393.41	425.00	DEVM	5.069	6.893	5.940	4.435	3.922
6 24		279.60	271.16	298.36	328.67						
01		293.62	303.51	354.04	386.80						
	401.81	383.96	396.04	390.88	381.51						
V-IHEIA 10	0-4291	142.38	0.4250	0.4337	1,5,61						
, O.		0.2897	0.2975	0.3448	0.3723						
-	26.243	28.072	29.505	26.967	24.658						
13	0.4783	0.1884	0,2250	0.1543	0.1957						
DFAC	0.7828	0.5150	0.5188	0.4080	0.3530						
	0.4739	0.7058	0.6581	0.5952	0.3437						
INCIDM	6.543	7.626	11.823	9.642	4.095						
DEVM	12.901	7.154	7.518	7.275	7.336						

Blade Element Data Cruise Configuration (Continued) Table B-3.

			CONFIG	CONFIGURATION	N/V	2/9/3					
	80PERCENT SPEED	ED PT.178		CRUISE	4804.	157.9					
								ROTOR			
		INLET GUIL	GUIDE VANE								
PCT SPAN	06	70	20	30	10	PCT SPAN	06	20	20	30	10
DIA 3	21.150	26.050	3 C. 950	35,850	40.750	DIA 6	23,385	27.755	32,125	36,495	40.865
BETA 3	000.0	0.00	0.000	0.000	00000	BETA 6	28.114	25.786	24.581	21.892	17.477
	30.887	27.828	26.109	23,333	18.815		54.156	52.080	54.813	50, 932	44.227
n ,	243.30	756.10	203.14	2000	207.407	BELAIPK) 6	51.128	57.518	607.19	64.819	68.373
* ^ >	243.55	255.80	263.74	268.35	260.40		17.022	30.633	210 02	47. 44.	33.307
4	254.51	264, 78	275.85	284.21	288.12	) h-	521.90	493,93	494.13	503.42	508.11
THETA	3 0.00	00.0	00.00	00.0	00.0	9 7 8	276.16	284.87	290.86	302.51	301.92
		140.52	135.21	122.60	98.17	V2 7	303.70	303.23	284.55	317.19	364.08
m I	0.2192	0.2306	0.2376	0.2418	0.2430	V-THETA 6	147,58	137.74	133,09	121.57	95.06
Ŧ	0.2676	0.2716	0.2773	0.2794	0.2747		423.06	389.64	403.84	390,86	354.41
S I	-30.90		-26.11	-23.33	-18.82	V (PR) 6	440.1	527.7	613.7	711.0	819.2
3	EER)	REFER TO 70% &	100% SPEED 1	DATA)		VIPK) /	374.0	5.00.3	401.2	490.8	613.1
DFAC	0.103	0.103	0, 093	970-0	0.053	٠.	-109.2	-222.4	-282.6	4-646-	-693.3
EFFP	0.9134	0.8416	0.8447	0.9286	0.8634	ť	490.18	581.78	673.39	764.99	856.59
6.600	-20.200	-20.200	20.200	20.200	-20.200	7 0	532,21	612.07	686.49	765.30	847.68
(NCIDW)				201	202	<b>.</b> 0	0.2828	0.2859	0.2890	0.2946	0.2858
DEVM	5.103	6-472	6.391	7.567	10.185	Z .	0.4662	0.4400	0.4381	0.4453	0.4486
						A C	0.3974	0.4765	0.5542	0.6424	0.7398
						TIENTOR	21 466	21.063	16.555	15 003	16 806
		STATOR I	Д			1	0,000	60000	20.00	200.00	000
TA ACTO STOCK						3	00000	0.0462	0.0862	7,600.0	0.1274
	06	02	5.0	30	10	DFAC	•5019	•4796	.5336	•4788	•3996
	26.021	29.683	33,345	37.007	699.04	EFFP	0.9496	1.0096	0.9241	0.9497	0.9720
	53,383	56.694	53.417	49.003	41.684	FF	0.9484	1.0099	0.9221	0.9481	0.9710
BEIA IO	511.08	405.12	427.07	140.67	500.15	INCI OM	2.528	11.216	₹00°₹	5.219	5.173
01	294.95	349.24	360,76	409.96	435.48	DEVM	0.855	3.733	2.689	1.124	0.667
	299.11	311.48	256.20	336.65	380.18						
		310.15	322.70	369.77	390.59						
		383.11	400.09	387.42	338.60						
V-IHELA	138.15	155.40	159.41	1 6.6	192.43						
	0.2597	6.3082	0.3171	0.3603	0.3824						
TURN	25.452	24.272	27.193	23.462	15.461						
13	0.2718	0.1197	0,1465	0.1027	0,1292						
O. P. P. C.	0.6310	7007 0	2482.0	2003	3000						
EFFP INCIDM	0.6733	0.8138	0.7808	0.7558	0.7778						
	1	1		) ) )							
DEVM	10,631	7.922	7.724	7.541	9.123						

Blade Element Data Cruise Configuration (Continued) Table B-3.

			CONFIG	CONFIGURATION	N/√0	2/0/2					
80B	BOPERCENT SPEED	O PT.179		CRUISE	4842.	166.1					
		INLET GUIDE VANE	VANE					ROTOR			
PCT SPAN	06	70	20	30	10	PCT SPAN	0	6	Ŏ.	Č	9
·CO	21-150	26.050	36.950	35.850	40.750	DIA 6	23,385	27,755	32,125	36,495	40.865
	000.0	000	0.000	0.000	0.000	BETA 6	27.767	25.601	24.407	22.037	18,435
	30.527	27.592	25.825	23,415	19.640		51.010	49.730	52,719	48.934	42.843
	255.08	269.45	278.54	284.09	285.32	BETA(PR) 6	49.290	55.283	60, 124	63.421	67.401
*	513-50	35.238	26.126	364.45	317.04		21.507	36,358	45,415	50, 728	54.835
47 7A	270-09	283.99	294.81	302.78	298.60	0 F > >	530.69	338.44	339.68	346.09	332.65
THETA	000	00.00	00.00	00.0	00.0	, ZA	292.55	304.96	309.27	320,79	315.58
V-THETA 4	159.27	149.32	142.67	131.12	106.56	VZ 7	327.56	321.61	297.05	325,33	364.05
m **	0.2297	0.2428	0.2511	0.2561	0.2573	I HET A	154.06	146.24	140.36	129.86	105.20
·*	0.2831	0.2912	0.2959	0.2982	0.2863	V-THETA 7	406.69	379.97	390.39	373.43	337.63
TURN	-30.53	-27.59	-25.82	-23.41	-19.64	V(PR) 6	448.6	535.6	650.9	717.0	821.2
13	ETE	(REFER TO 70% & 10	100% SPEED I	DATA)		~	353.9	399.7	453.4	514.0	532.1
3 2		ı		/ Heart		VIHETA PR6	-340.0	-440.1	-538.4	-641.2	-758.2
FFF	160.0	0.084	0.082	0.070	0.075	HETA	-129.7	-236.9	-301.5	-397.9	-516.8
	756000	2000	10000	5505.0	600 1.00	o ~	536.42	616.91	601 02	20.177	865.36
INCIDM	-20.200	-20.200	-20.200	-20.200	-20,200		0.2989	0.3060	0.3071	0.3130	0-3007
DEVM	5.473	6.708	6.675	7.485	9.360	- E	0.4683	0.4444	0.4357	0.4391	0.4395
	1	}				M(PR) 6	0.4054	0.4842	0.5614	0.6485	0.7422
							0.3167	0.3567	0.3760	0.4557	0.5596
		STATOR	В			TURN( PR)	27.777	18.903	14. 705	12.692	12.566
						13	1000°0	0.0119	0.0613	0.0390	0.0780
PCT SPAN	06	20	20	30	10	DFAC	7.276	305	1,803	1,31,8	3625
DIA 9	26.021	29.683	33,345	37.007	40.669	EFFP	0.9878	1.0215	0.9250	0.9690	1.0229
BETA 9	49.553	48.400	51.389	46.976	40.050	EFF	0.9876	1.0220	0.9231	0.9681	1.0237
8ETA 10	27.500	27.129	27.202	25, 853	26.501	INCIOM	0.690	2.783	4.02h	3.821	4.201
01	373.41	382.24	374.88	423,37	453.97	DEVM	2,707	3,858	3,315	801.0	7.035
6 7 1	330,13	329.68	307.56	344.34	387.66		<del>-</del>			) 	
	328.74	337.16	332.26	380.74	406.25						
V-THETA 9	394.35	374.20	386.34	369.16	325.89						
	74.21	1 4.30	1 (1.5)	79.491	202.57						
	0.3307	0.3384	0.3303	0.3734	0.440						
TURN	22.053	21.271	24.187	21.123	13.549						
13	0.1543	0.1209	0,1866	0,1299	0,1163						
DEAC	0.4358	0.3971	0.4310	0.3316	0.2208						
EFFP	0.7342	0.7638	0.6009	0.5815	0.5549						
INCIOM	-0.347	2.300	7.689	3.976	-4.950						
DEVM	10.200	8.629	8.702	7.853	1011.6						

Blade Element Data Cruise Configuration (Continued) Table B-3.

			CONFI	CONFIGURATION	N/N	8/6/0					
808	BOPERCENT SPEED	E0 PT.180		CkULsa	4829.	176.4					
		INLET GULD	GUIDE VANE					ROTOR	œ		
PCT SPAN		;	4	.9		PCT SPAN	;	i	;	;	?
10 TO TO	06	20	20	30	10		06	70	50	30	<u></u>
~	21.150	26.050	30,950	35.850	40.750		23,385	27.755	32,125	36.495	40.85E
	0000	000.0	0.000	000.0	0.000	BETA 6	28.125	25.729	24.765	22.079	16.911
BETA 4	31.087	27.876	26.439	23.559	18.269	BETA 7	47.239	46.407	47.901	44.117	37.744
m >	273.48	288.16	297.40	302.65	303.80	BETA(PR) 6	45.650	52.564	57.677	61.612	66.120
4	338,39	344.86	349.41	349.06	339.23	A (PR)	21,679	35.437	44.154	49.655	53,773
٧2 ع	273.46	287.87	297.39	302.64	303.79	9 >	358.77	363,24	365.15	367.84	341.04
4 ZA	289,79	303.12	312.85	319,96	322,13	۷ ۲	532.81	506.41	495.42	499.10	503.65
V-THETA 3	00.00	00.00	00.00	00.00	00.00	9 ZA	316,34	326.98	331,51	340.84	225.87
	174.72	161,24	155.58	139.52	106.34	V.Z. 7	359.98	348.89	331,97	358.25	400.01
X 33	0.2465	0.2599	0.2683	0.2731	0.2742	V-THETA 6	169.12	157.69	152.96	138.27	102.11
4	0.3059	0.3119	0.3161	0.3158	0.3067		391.18	366.77	367.59	347.44	304.83
TURN	-31.09	-27.88	-26.44	-23.56	-18.27	V(PR) 6	452.6	538.1	620.0	716.9	879°
1	and )	( DEFEND TO 20% 8.	י חששפט שיטר י	7,400			389.3	428.6	462.9	553.5	678.4
3	igu.			(WTW)		VTHETA PR6	-323.6	-427.1	-523.9	-630.7	-758.0
DFAC	0.000	0.087	0.088	0.078	0.058		-143.8	-248.5	-322.5	-421.8	-547.3
EFFP	0.9295	0.8987	0.9070	0.9738	0.8301		492.73	584.81	676.89	768.97	861.05
	-20.200	-20.200	-20.200	-20.200	-20.200		534.98	615.26	90.069	769.28	852.00
WC DW	2021			3			0.3247	0.3289	0.3396	0.3331	0.3174
DEVM	4.913	424·9	9.061	7.341	10.731		0.4785	0.4533	0.4418	0.4445	0.4477
						M(PR) 5	0.4097	0.4872	0.5614	0.6493	0.75.00
		STATOR	æ			M(PR) 7	0.3496	0.3836	0.4129	0.4929	n.6n3n
						TURN(PR)	23,966	17.107	13,518	11.955	12.355
*1%						13	-0.0165	0.0134	0.0307	0.0267	0.0855
PCT SPAN	0	7.0	50	90	2	DEAC	3306	3618	יוטיוי	35.82	J213h
DIA 9	26,021	29.683	33,345	37,007	40.669	FFFP	1.0057	1.0419	0.9748	1.0125	1.0336
~	45.705	44.970	46.361	42.338	34.912	EFF	1.0058	1.0429	0.9742	1.0128	1.1346
BETA 10	27.287	27.968	27.310	26.002	26.490	INCION	-2.950	0.064	1.577	2.012	2.928
<b>6</b>	530.01	510.93	502.48	510.84	504.32						. ·
01 ^	430.50	425.05	420.90	451.19	473.12	DEVM	2.879	2.937	2.054	1.055	0.873
	363,72	358.93	345.96	377.54	413.48						
	380.08	372.46	373.06	402.44	423.35						
	379.35	361.09	363.65	344.05	288.63						
V-IMEIA 10	197.30	199.54	193•11	08.74.0	6117						
. S	2036	0.45	0.4463	0000	4104						
ב ב מאם	18.418	17,002	19,051	16.336	8.421						
	אמשר מ	מאר	8861.0	לאבר ט	82,(1.0						
3	0061.0	0061-0	001.100	#0CT*0	00						
DFAC	0.3113	0.2946	0.3095	0.2500	0.1364						
INCIDM	0.6386 -4.195	-1.130	2.661	0.4180	-10.088						
				(	,						
DEVM	9.987	8911-6	8.810	8.002	9.390						

Blade Element Data Cruise Configuration (Continued) Table B-3.

N/ 6	10 FCT SPAN 90, 70 50 10 10 10 10 10 10 10 10 10 10 10 10 10
configuration gruise	30 35.850 0.000 23.706 325.73 376.99 376.99 376.99 376.99 376.99 376.99 376.99 376.99 376.00 376
CONFIC DE VANE	50 30.950 26.242 320.46 320.46 320.46 320.46 320.46 0.2895 0.2895 0.8631 -20.200 0.8631 -20.200 6.258 50 33.345 42.42 50 331.77 22.501 0.1561 0.1561
PT.174 INLET GUI	70 26.050 27.957 310.957 310.58 310.58 328.41 0.2806 0.3386 -27.20 0.083 0.084
BOPERCENT SPEED	90 21.150 0.000 31.109 295.40 369.11 295.38 10.03 190.71 0.2665 0.3343 -31.11 0.9360 -20.200 4.891 0.9360 -20.200 4.891 12.896 0.4505 12.896 0.2215 0.1704 -0.0368
806	PCT SPAN  DETA 3  BETA 3  V 4  V 4  V 5  V 7  V 7  V 7  V 7  V 7  V 7  V 7

Blade Element Data Cruise Configuration (Continued) Table B-3.

			CONFIGU	CONFIGURATION	N/V	2/0/2					
100 f	100 PERCENT SPEED	ED PT.190		CRUISE	6045.	175.8					
			·					ROTOR	œ		
		INIET GU	GUIDE VANE								
PCT SPAN	0	70	20	30	10	PCT SPAN	06	0,2	20	30	10
DIA 3	21,150	26.050	30,950	35.850	40.750	DIA 6	23,385	27,755	2	36.495	40.865
BETA 3	000.0	000.0	0.000	000.0	0.000	BETA 6	27,708	25.276	24.255	22.746	25.909
	30.744	27.379	25.585	24.033	26.982	BETA 7	57.996	55.998	59.161	55.867	61.340
	283.24	295.68	300.90	300.86	288.29	BETA(PR) 6	57.269	61.892	62.419	67.791	68.937
4	314.38	326.61	338,53	345.82	373.29		26.820	41.480	51.549	53.799	62.303
	283,23	294.90	300.89	300.85	288.28	9 >	334.99	345.76	352,93	364.09	388.77
	270.04	288.81	304.31	314.63	332.08	<b>~</b>	600.11	581.96	574.27	604.00	595.53
V-THETA 3	00.00	00.00	0.00	00.0	00.0	9 ZA	296.34	312,17	321.28	335.53	340.70
-THETA	160.71	150.20	146.20	140.84	169,36		313.81	324.59	293.87	338.64	285.37
m æ	0.2554	0.2667	0.2715	0.2715	0.2600	V-THETA 6	155.76	147.63	144.98	140.11	169.87
<b>⊅</b>	0.2839	0.2951	0.3061	0.3128	0.3382		508.90	482.46	493.07	499.95	522.57
TURN	-30.74	-27.38	-25.59	-24.03	-26.98	V(PR) 6	548.2	662.8	172.6	887.8	973.0
13	9990*0		0.0285		0.0320	V(PR) 7	356.4	434.4	473.4	573.8	614.5
OE AC		163		400	100	VIMETA PR6	1.101-	1,084.4	-702.4	-821.8	0.806-
FEED	1910	0.153	61100	0.080	100.00	¥ .	100.9	732 07	967 36	0403.0	1077 07
4	2.60.0	16+0+0	1116.0	0.36.0	0.4033	o +	10.010	770 19	041.34	902.00	1011-01
NOIDM	-20,200	-20.200	-20.200	-20-200	-20.200	- ·c	0.3028	0.3127	0.3103	0.3297	0.3525
DEVM	5.256	6.921	6.915	6.867	2.018	) /~ : .æ	0.5320	0.5139	0.5035	0.5274	0.517
			•	•			0.4955	0.5995	0669.0	0.8038	0.8823
		STATOR	<u>m</u>			M(PR) 7	0.3160	0.3836	0.4150	0.5010	0.5336
						TURN(PR)	30.429	20.374	13.836	13.977	6.634
						13	-0.0259	0.0731	0,1501	0.1505	0.1610
PCT SPAN	06	7.0	50	30	10	DFAC	5.591.3	51,75	.5783	5343	5377
OIA 9	26.021	29,683	33,345	37.007	40.669	EFFP	1.0195	1.0567	0.9479	0.9556	0.9233
<b>A</b>	58.853	54.755	57,399	54.422	58.728	EFF	1.0203	1.0591	0.9456	0.9534	0.9192
BETA 10	41.794	26.575	25.489	26.099	26.332	INCIDM	8.669	9.392	9.319	8.191	5.737
o :	580.51	582.02	580.99	614.28	612.30		6	0	-	1	
-	178.60	356.26	422.91	468.15	519.26	DEVM	8.020	0.990	V:44.V	7*T	(0#°V
6 7 7	130 00	214-18	20.216	62.100	311.41						
-	496.83	475, 33	489-46	19.054	523,34						
	119,03	159,38	181.99	205.95	230,33						
	0.5137	0.5140	0.5094	0.5365	0.5323						
M 10	0.1545	0.3100	0.3676	0.4047	0.4479						
TURN	17.059	28.180	31,911	28.323	32.396						
13	0.7783	0.4749	0,2650	0.2829	0.2006						
DF AC	0.9353	0.6082	0.5029	0.4603	0.3808						
EFF	0.2389	0.3469	0.0450	0.3931	0.2901						
FNCIDM	6.953	8.655	13.699	11.422	13.728						
DEVM	764-77	8.075	6.989	8.099	9.232						

	Table	B-3.	Blade	Element	Data	Cruise Con	Configuration		(Continued	d)	
1.00 P	100 PERCENT SPEED	iu PT. 19		CONFI CURATION CRUISE	N/V@ 6045.	~√6/8 184.	<b>.</b>				
		INLET GUI	DE VANE					ROTOR			
PCT SPAN	06	70	5.00	30	10	PCT SPAN	06	70	50	30	10
DIA 3 BETA 3	0.000	0.000	000.0	000.00	0.000	UIA 6 BETA 6	23.385	25.407	32.125	36.495 22.010	40.865
	30.930	27.187	25.448	23.385	22.542	BETA 7	56.893	56.618	58.130	54.725	52.648
m 4	289.30	303.27	312.02	317.63	319,20	BETA(PR) 6	54.354	59.592	63.250	65.809	57.401
VZ 3	289.30	302.86	312.01	317.62	319,19		362.80	372.20	381.84	394.77	388.02
	292.62	314.90	333,15	344.34	339.89	٨ ٢	616.84	586.15	586.99	612.46	611.74
V-THETA 3	00.00	00.00	00.0	00.0	00.0	9 7 7	320.39	335.92	348.14	365.97	362.09
V-IMEIA 4	0.2609	162.54	138.30	148.91	141.08	7 2 / V-THFTA 6	170,05	327-15	156.65	147.04	171.14
. E	0.3085	0.3219	0.3342	0.3399	0.3333	V-THETA 7	516.70	489.45	498.50	500.01	486.29
TURN	-30.93	-27.19	-25.45	-23.38	-22.54	V(PR) 6	549.8	663.R	773.5	893.1	1005.8
13	0.0656		0.0320		0.0380	V(PR) 7	370.0	427.6	479.1	582.6	688.9
DFAC	0.131	660-0	0.073	0.054	0.068	VIHETA PR7	-153.0	-280.7	-365.3	0.694-	4580.4
EFFP	0.8891	0.8963	0.9185	4166.0	0.9203		615.81	732.07	847.34	962.60	1077.87
WOLDM	-20.200	-20.200	-20,200	-20.200	-20.200		69.699	770.19	863.92	963.00	1066.66
DEVM	5.070	7.113	7.052	7.515	6.458	0 ~ Ē Æ	0.5483	0.5372	0.5461	0.5351	0.3318
						M(PR) 6	0.4978	0.6013	0.7011	0.8102	0.9121
		STATOR	E C			M(PR) 7	0.3288	18.537	0.4208	0.5096	0.6000
						1.	1910	o.outh	0.1023	0.1193	נוטניט
PCT SPAN	Ö	64	ď	O.E.	-	3 2	5622	8711	0000	7,007	270
9 A10	26.021	29.683	33.345	37.007	699.04	FFF	1.0127	1.0198	0.9551	0.9607	0.9614
	57.769	55.428	26.600	52.129	50.107	FFF	1.0132	1.0206	0.9531	0.9587	0.9593
BETA 10 V 9	35.647	584-12	591.17	25.959	26.802	INCIDM	₹ 2.5	7.092	7.150	6.209	5.700
_	199.64	372.77	437,15	494.10	539.55	DEVM	5.623	8.538	7.590	4.023	4.501
	311.51	329.11	324.31	377.72	403.41						
V2 10	159.12	333,04	391.92	443.75	481.59						
	116.35	160.80	190.08	216.28	243.29						
	0.5275	0.5162	0.5192	0.5464	0.5486						
TURN	0.1729	0.3248	0.3803 30.826	0.4282	0.4670						
13	0.7139	0,3876	0.2351	0,2187	0.1794						
DFAC	9.9074	0.5843	6.4843	0.4175	0,3244						
EFFP INCIOM	0.3097 7.869	0.4708 9.328	0.6690	0.4767 9.729	0.3600 5.107						
DEVA	18.347	7.054	7.273	7.959	9.702						

Blade Element Data Cruise Configuration (Continued) Table B-3.

		10	40.			5 67.870		406.76											1066.66						8 0.0784	5 4536		7 0.9881		0046												
		30	36.49	21.72	53.230	64.67	51.43	412.5	620.5	383.2	371.3	152.7	497.0	896.	595.	-808-	-465.9	962.60	963.00	0.374	0.543	0.813	0.522	13.236	0.081	5065		10707	5.075	. 637	0.1											
	~	50	32,125	24.261	56.706	61.861	47.421	400.60	602.70	365.14	330.65	164.61	503.77	774.3	489.0	-682.7	-360.1	847.34	863.82	0.3636	0.5303	0,7027	0.4302	14.435	0.0619	5577	0.9594	0.9576	5.761	100	7.761											
	ROTOR	7.0	27,755	25.677	55.441	57.885	39.272	391.93	598.27	352.90	339.01	169.82	492.70	664.0	438.4	-562.2	-277.5	732.07	770.19	9,3555	0.5297	0.6022	0.3881	18.589	0,0082	5359	1.0181	1.0109	5.385	C C	0.116											
		06	23,385	27.938	55.556	52.324	22.962	382.57	629.22	337.90	353.03	179.24	518.91	552.9	386.5	-437.6	-150.8	616.81	69.699	0.3468	0.5601	0.5012	0.3441	29.355	-0.0737	5356	1.0049	1.0051	3.724	0).	701.4											
193.0		PCT SPAN	01A 6	BETA 6	BETA 7	9	RETA(PR) 7	9 /	٨ ٢	9 2 /	7 7	V-THETA 6	V.	V(PR) 6	~	VTHETA PR6	HETA	9 (1	<b>~</b> 0:	•0 ≯	<b>~</b>	M(PR) 6	M(PR) 7	TURN( PR )	13	DEAC	EFFD	E F F	INCIDM		E ALC											
6045.		ş	40.750	00000	22,016	335.78	384.40	335.77	356.36	00.0	144.10	0.3035	0.3485	-22.02	0,000	00.00	0.070	0.9197	-20,200	300	₩6.9					0	40.569	47.305	27.306	642.05	548.93	455.57	100/24	251.84	0.5616	0.4762	19,999	0.1547	14/	2608-0	2.305	,000
CRUTSE		Č	35,850	000	23,143	333.52	390.91	333,51	359.44	0.00	153.64	0.3015	0.3545	-23.14			0.059	0.9870	-20.200		7-757					Č	37,007	51.142	26.280	633.43	504.79	397.06	01.204	22.50	0.55.0	0.4381	24.862	0.1756	0.000	0.4012	8.142	000
2	GUIDE VANE	i,	30,950	0.00	25,636	326.99	385.73	326.98	347.73	00.0	166.88	0.2954	0.3497	-25.64	0.0080	0.0209	0.077	0.9113	-20.200	0	₹96¶		α			, c	33,345	55.307	25.876	606.74	435.31	344.05	284.88	180.08	0.5338	0.3785	29.431	0.2295		0.5045	11.607	
PT. 19	INTEL GOLD	Ć,	26.050	000-0	27.432	316.93	374.67	316.54	330.66	00.0	172,61	0.2862	0.3395	-27.43			0.094	0.8967	-20,200	203	6.868		STATION.			202	29.683	54.101	25.716	597.23	413.29	347.38	368.50 30	100.17	0.5287	0.3611	28.385	0.2120		0.5146	8.001	
100 PERCENT SPEED		; 6	21.150	000	30.800	301.61	361.17	301.60	310.22	00.00	184.93	0.2722	0.3270	-30.80	0,000	0.0002	0.117	0.8848	20.200	201	5.200					Ö	26.021	55,995	30.942	60.639	246.37	334.04	50807	126.67	0.5411	0.2138	25.054	0.5785		0.8271	0.4312 6.095	1 2 2 1
100		PCT SPAN	DIA 3	•	BETA 4	· ~		V Z 3	4 Z V	THETA	V-THETA 4		4		1	3	DFAC	EFFP		WCIDW.	DEVM					PCT SPAN	O V O	BETA 9	BETA 10	6 >	01 -	6 7 7	01 70			, <u>c</u>		1	3	DFAC	INCIDM	

Blade Element Data Cruise Configuration (Continued) Table B-3.

							ı				
. Ç31	IC) PERCENT SPEED	ED PT. 193	CONFIG	CONFIGURATION CRUISE	N/VØ 6745.	w√⊕/8					
		INLET GUIDE	VANE					ROTOR			
PCT SPAN	ě	70	ν.	ć.	ć.	PCT SPAN	Û	70	ř.	j.	·
DIA 3	21.150	26.050	30,950	34,850	40.750	014 6	24.385	27.755	32,125	34.405	4. 965
⋖	0.000	600.0	<b>€</b> 00	ر ¢ و و ر	0,000	RETA 6	27.892	25.541	24.392	22.C16	21.167
⋖	369.3€	27.632	25.995	23.571	21.180	AFTA 7	53.064	50.978	53.452	57,319	44.464
٧ ع	323.93	341.57	352.24	367.94	358.90	RETA(PR) 4	48.544	54.474	59.075	62.746	64.500
, <del>†</del>	397.61	41.9.33	418.45	418.38	412,32	_	10.579	15.539	43.970	49.838	63.443
٨2 ع	323.92	341.19	352.23	357.03	458.89	۸ >	420.14	432,17	438.37	442.48	429.77
4 Z V	341.92	360.61	376.09	383,46	384.47	۲ ۷	661.09	627.8R	656.95	430.97	663.43
V-THFTA 3	00.0	() <b>ံ</b>	υ). •	ر ب ن	<b>J</b> (0.0)	9 21	371.31	389.45	399.17	410.37	4.2.49
	202.94	189.84	183,40	167.37	148.97	7 2 7	394.81	394.07	373.16	412.81	449.66
.E.	92020	æ	0.3187	0.3240	6.3249	V-THETA 6	196.47	196.33	181.03	165.05	147.82
4	₽09£•1	C.3717	C.387.2	3.3801	1.3745		528.41	487.80	203.67	495.60	460.23
TURN	-30.69	-27.63	0.3*96-	-23.57	-21.19	V(00) V	560.9	2.019	776.8	1.966	1013.4
1,	0.063		0.0200		0.0390		421.5	495.8	518.7	524.7	755.
3	4000		0.02/		20.0	VT4FT& PRA	-450.3	-545.7	-666.3	-196.7	-03
DFAC	\$0U*U	r.083	44.0	99⊝•∪	0.158	Y >	-141-3	7.242-	-360.2	4.77.4	-475.4
EFFD	2086°0	0.0180	0.9372	0.9356	0.9064	7 +	616.81	732.07	947.34	962.60	16.77.1
20.000	-20,200	-20.200	-20.200	-20.200	-20.200	7 ::	660.69	770.19	853.82	963.00	1066.66
202		001				¥ :	. 3819	1666.0	0.3989	0.41.29	0086
DEVM	5.310	999.9	6.505	7.329	7.820		8065°C	0.5588	0.5541	A 5556	0.5651
						9 (86)	76350	1.019°	1, 1368	91196	\$126°0
		STATOR 1	æ			M(50) 7	30 050	0.4324	3.4585 3.5 ±0.0	1.56.0	1.00.1
						- X	B .		601.	10.00	•
						13	-0.0613	0000-0-	0.0368	0.0523	0.0584
PCT SPAN	٥	ÚŽ	C L	3,	Į. I	NEAC	.4755	.4577	5088	1,621	.3989
	26.021	29.683	33,345	37.007	40.669	CHH)	0.9779	1.0446		0.9796	[d .c.
BETA 9	52.1Rn	40.50C	52.026	48.220	43.884	11.	r.9767	1.0463	9612	0.9787	1.0085
BETA 10	27.948	27.129	27.025	25,991	28.250	INCIDA	-0.050	1.974	2.975	3.146	3,399
o :	648.83	629.42	633.24	645.58	654.99		0000	600	833	Acc r	นี้
01 °	24:000 2000	440.04	47.47.	10.010	101	۶ ۲	2.5	2.039	7.010	7	•
	341.57	303.96	471.91	464.21	480.084						
V-THETA 9	512.53	479.25	400.14	481,41	454.04						
V-THETA 19	183.01	273.42	205.61	226.39	262.94						
	0.5791	0.5603	70550	0.5691	n.575a						
01 ₩	0.3413	0.3016	0.3943	0.4504	r.4938						
TURN	24.232	22.461	24.995	22.23	15.624						
13	0.2915	0.1615	0,2196	0.1214	0.1346						
DFAC	0.5855	0.4674	0.4873	0,3836	6.9923						
EFFP	0.6554	1.7445	0.6566	0.7139	0.6848						
INCIDA	2.280	3.490	8,320	5.220	-1.116						
DEVM	10.648	8.629	8.525	7.991	11.160						

Blade Element Data Cruise Configuration (Continued) Table B-3.

	Table	B-3.	Blade 1	Element		Cruise Con	Configuration		(continued)	(g	
			CONFIGURATION	ATION	N/V 60	2/0/2					
3	IOU PERCENI SPEED			CROISE	• 0 • 0 • 0	•					
		INTER CHITDE	S WANT					ROTOR			
PCT SPAN	Ğ	70	, K	90	2	PCT SPAN	06	70	20	30	10
0.14 3	21,150	26.050	30,950	35,850	40.750	DIA 6	23,385	27.75	32.125	36.495	40.865
BETA 3	00000	000.0	000.0	000.0	000.0	BETA 6	27.941	25.595	24.275	21.672	17.848
	30.906	27.735	25.894	23,330	19.050		48.972	48.463	50.074	45.942	40.401
m >	343.80	362.34	374.14	380.67	381.33	DETAINED 7	420.02	36.655	43.482	6.92.721	53.296
* c > 2	429.29	451.21	374-13	380.65	381.32		455.98	461.85	467.02	471.68	448.14
	368,33	384.79	400044	407.36	409.55	. >	674.19	638.15	657.99	637.42	639.12
V-THETA 3	00.0	00.0	00.0	00.0	00.0	9 2/	402.75	416.24	425.66	438.32	426.57
-THETA	220.50	203.47	194.40	175.69	141.42		440.23	422.82	402.87	44.5. LX	484.08
	0.3109	0.3280	0.3390	0.3450	0.3456	V-THETA 6	508.60	75.64	192.00	458.07	417.29
4 5	0.3904	0.5978	0.4052	0.4038	-19-05	V(PR) 6	569.9	676.1	781.5	902.1	1032.7
¥ .	1.000	+ 7		67.63	0,000	V(PR) 7	471.0	514.4	555.5	671.9	810.0
13	0.0613		0.0294		0560.0	VTHETA PR6	-403.2	-532.5	-655.3	-788.4	-940.5
DFAC	0.080	0.078	0.072	990.0	0.049	œ	-161.1	-292.5	-382.2	-504-9	-649.4
EFFP	0.9511	0.9328	0.9647	0.9919	0.8982	.e.: ⊃:	616.81	732.07	847.34	962.60	1077.87
ريرن ديرن	-20.200	-20.200	-20.200	-20.200	-20.200	<b>~</b> √	696,69	7.03.19	863.82	705.00	1,000
1/0/2	3	1	, ,	i i	0	0 1	40140	0.4210	0.4629	5,450	0.5641
DEVM	5.093	6.565	909-9	7.570	066.6	M (PR) 6	0.5192	0.6162	0.7126	0.8278	0.9403
		CHATC	þ			M(DR) 7	0.4231	0.4596	0.4931	0.5952	0.7149
. 200 8 18/8		NO TWIC	<b>q</b> .			TURNIPRI	25.021	17.315	13.509	12,206	12.307
						13	-0.0689	0.0135	0.0445	0.0567	0.0919
Deft span	. (	ç	C H	· C		2690	377.	1,065	.3970	. 1296	.3422
	90	20 683	33 245	27.007	07	FFFD	0.9844	1.0095	0.9445	0.9973	1.0083
BETA O	170.07	47.098	48,608	44.056	40.523	144	0.9839	1.0098	0.9425	0.9972	1.0087
	28.075	28.125	27-622	26.006	27.323	INCIDM	-3.571	-0.511	0.895	1,328	2.403
6 ^	66.799	642.00	636.57	652.77	647.71		,	,		נפר ט	306
- است	502.34	496.85	501.68	542.07	5/8.4/	OEV#	7.202	2·155	700-1	131.0	2
6 7 7	447.04	434,54	443.37	487.08	513.81						
THETA	493.11	470.28	477.56	453.91	420.85						
V-THETA 10	236.41	234.22	232.59	237.68	265,53						
O I	0.5997	0.5737	0.5654	0.5789	0.5720						
10	0.4441	0.4384	0.4404	0.4760	0.5078						
CKN	19.503	676.81	20.981	060.81	12.500						
13	0.1641	0.1562	0.1783	0.1579	0.1374						
DFAC	0.3874	0.3738	0.3791	0.3237	0.2223						
EFFP	0.7391	0.7066 0.998	0.6203	1.056	0.6573 -4.477						
	\$ (Market )	:		•							
DEVM	10.775	9.625	9.122	900.8	10.223						

Blade Element Data Cruise Configuration (Continued) Table B-3.

	Taple	B-5.	prade 1	ramenr	חמרם	crurse com	COULTYULACTON		י רסוורדוומפת	3	
1000	100PERCENT SPEED	PT.189	CONFIG	CONFIGURATION CRUISE	N/V 60 6055.	232.5					
		INTEL GUID	DE VANE					ROTOR			
PCT SPAN	90	70	20	30	01	PCI SPAN	90	70	20	30	01
DIA 3	21.150	26.050	30.950	35.850	40.750	0[A 6	23,385	27.755	32.125	36.495	40.865
BETA 3	000*0	0000	0.000	000.0	0.000	BETA 6	27.653	25.450	24.218	21.962	18.406
	30.687	27.709	26.007	23.428	19.704	BETA 7	43.384	43.011	43.180	41.269	37.310
e) >	370.78	391,33	404.25	411.12	412.31	BETA(PR) 6	41.504	48.547	54.091	58.647	63.178
•	465.50	476.56	482.51	482.42	473.06	_	21,753	35.331	43.086	48.834	52.986
٧٤ ع	370,75	390.92	404.23	411.10	412.29	9 >	495.16	505.26	508.40	508.52	492.46
	400.31	419.59	433.63	445.63	445,36	~ >	686.68	642.64	633,26	622.28	643.20
V-THETA 3	0.00	0.00	0.00	0.00	00.00	9 7/	438.50	455.91	463.57	471.58	467.27
V-THETA 4	237.57	221.59	211.57	191.81	159.50	7 7	496.59	469.49	461.54	467.63	511.56
	0.3359	0.3549	0.3670	0.3734	0.3745	V-THETA 6	229.81	217.12	208.55	190.18	155.49
4	0.4244	0.4349	0.4405	0.4404	0.4316		471.67	438.37	433.33	410.45	389.86
TURN	-30.69	-27.71	-26.01	-23.43	-19.70	V(PR) 6	585.6	6889	790.5	4.906	1035.6
13	0.0549		0.0230		0.0320	V(PR) 7	537.3	576.0	632.3	725.1	840.8
3				,		VTHETA PR6	-388.0	-516.2	-640.2	-774.0	-924.2
DFAC	0.073	0.069	0.010	0.061	0.046	_	-1661-	-333.1	-431.9	-554.1	-678.6
EFFP	0.9021	0.8948	0.9049	0.9616	0.8298	• • • •	617.83	733.28	848.74	964.19	1079.65
00000000	-20.200	-20.200	-20.200	-20.200	-20.200		670.80	771.46	865.25	964.59	1068.42
200	;						0.4525	0.4621	0.4652	0.4653	0.4500
DEVM	5.313	6.591	6.493	7.472	9.2%	~	0.6212	0.5784	0.5675	0.5557	0.5722
						M(PR) 6	0.5352	0.6301	0.7232	0.8293	0.9462
		STATOR	ф			M(PR) 7	0.4861	0.5184	10 000	0.6476	0.7560
							200	120121	100111	770 *0	741.01
						13	0.0232	0.0838	0.0679	0.0575	0.0578
PCT SPAN	06	70	20	30	10	OFAC	.2453	.2960	.3219	.3085	.2849
OIA 9	26.021	29.683	33,345	37.007	40.669	EFFP	1.0492	1.0578	1.0238	1.0111	0.9643
BETA 9	41.783	41.337	41.751	39.515	31.108	EFF	1.0506	1.0595	1.0246	1.0115	0.9630
ш	28.417	28.667	27.851	25.906	28.591	INCION	-7.096	-3.953	-5.009	-0.953	-0.022
o :	685.92	652.94	645.07	639.83	645.02		,	ě	700	č	700 0
21	86.610	004.97	593. (5	017.97	030.40	DEVE	2.953	7.031	8	T. 2. 1	90.0
6 7/	502.04	480.80	480.25	493.53	22.12						
- i	70.050	87.976	18.626	92.166	208.00						
V-INCIA V	457.03	07.164	427.33	247 80	333.63						
	0.4205	5882	0.5786	5772	2746						
, <u>c</u>	0.5512	0.5424	0.5299	0.5468	0.5659						
TURN	13,366	12.670	13.900	13.609	2.517						
13	0.2422	0,1591	0.1957	0.1351	0,1260						
4 2	200		9								
DFAC EFFP	0.0376	0.0325	-0.1113	-0.4927	-0.8383						
INCLUM	-0.11(	(o) •	-1.343	-3.405	-T3.07£						
DEVM	11.117	10.167	9.351	7.906	11-491						

Table B-4

Table	e B-4.	Blade	Element	t Data	Intermediate		Contiguration		(Continued	d)	
Ö.S.	SU PERCENT SPEED	P1. 21	CONFIG 5 IN P	CONFIGURATION IN FERMEDIA LE	N/V6 3026.	17.68 11.68	م				
		INTER GUIDE	DE VANE					ROTOR			
PCT SPAN	05	70	50	30	01	PCT SPAN	96	7.0	50	30	10
· 10	21.150	26.050	30.950	35.850	43,750	DIA 6	23.385	27.755	32,125	36.495	40.865
BEIA 3	0000	0.000 000 0.000 0.000 0.000 0.000 0.000 0.000 0.000 0.000 0.000 0.000 0.	300°3	0.00 0.00 0.00	530°C	BETA 6	13.502	13,764	13.216	9,699	6.830
1	12.0.01	14-11	10 685	10.2%	7.440		561.55	54.516	754.00	206 • 10	48.634
n .4	140.12	142.54	1.40.00 1.58.1	1635.05	150.34	BETAIDS 7	25. 727	43.810	520.10	55.167	50.44
٧2 ع	135.77	142.53	140.46	149.55	150.33		151.20	161.19	163.81	1 70.97	169-14
V2 4	135.29	146.84	153.85	160.43	158.99	2 /	307.62	280.4R	274.98	286.65	284.35
V-THETA 3	ງດ•ງ	0.00	00.00	0.00	0.0.0	۸۶ ۴	146.97	156.40	159.42	168.51	167.94
-I HETA	96.3G	38,89	38°03	29.13	20.76		184.97	163.39	155.90	178.94	189.31
n ×	0.1218	1871.0	≈ 151.0 €	2+61-0	7.1345	V-THEIA 6	35.50	334 535 334 535	36.45	28.80	20.01
TURN	1 5 6 6	- 14, 77	-13-85	0.1404	24.5	4 (	26.44.2	245.9	610.07	683.5	544.9
1					•	V(PR) 7	206.8	226.7	257.7	313.3	377.4
3	H)	(REFER TO 70% 8	& 100% SPEED	DATA)		VTHETA PR6	-272.8	-327.4	-385.9	-452.1	-518.4
DFAC	0.100	0.070	c. 051	0.008	3,003	HET	8.68-	-157.0	-205.1	-257.2	-320.7
EFFP	0.8572	1.0482	0.8412	0.9062	0.7647	ψ) ))	308.15	365.73	423.32	480.90	538.49
INCIDM	-20.200	-20,200	-20.200	-20.200	-20,200	, ,	334.57	384.78	431,55	481.10	532.89
) EVE	8,61,8	000	7 12 5	л ЖОК	7.85)	<b>∪</b> ► 3	0.1357	0.1447	0.1471	0.1355	0.1519
-	2	773.4	1	2	1	M(PR) 6	0.2781	0.3257	0.3748	0.4337	0.4897
						M(PR) 7	0.1845	0.2020	0.2292	0.2783	0.3304
		STATOR	В			TURNI PR)	35.955	20.633	14,802	14.389	12.602
						13	0,1229	0.2067	0.2780	0.2199	0,2665
PCT SPAN	ୃତ	٦٢.	90	30	91	DFAC	.5839	.5828	•5739	.5312	.4818
UIA 9	26.021	590.57	53.345	37.007	40.569	EFFP	1.0038	0.9792	0.9283	0,9031	0.8774
BETA 9	52. 3cc	53.467	54.159	49.449	45.857	EFF	1.0038	0.9790	0.9274	0.9018	0.8757
BETA IC	21.57	18.535	15.440	14.703	11.737	INCIDA	13.019	11.966	11.422	9.958	8.849
o = > >	0/•K57	275.30	276.74	292.72	293.52	\$ 35 G		016 11	10,663	6 567	6.588
6 7/	160.36	165,51	161.56	189.99	734.47	0 2 4	9.921	11.510	(H)	5	
	139.28	174.63	170.25	227.43	245.3(						
HETA	45.753	224.29	224.34	222.55	210.63						
V-THETA 10	55.85	70.65	4 8 do	59.74	26.05						
ο : Σ	C. 2674	6.2489	0.2462	0.2600	J. 2608						
70 TO	0.154c 30.754	34.877	6.1628 36.710	34-730	5, 2219 34, 120						
13	0.3605	0,1866	0,2603	0,1306	0,1152						
3 2		,	. 6								
FFF FFF FFF FFF FFF FFF FFF FFF FFF FF	0.1754 0.4501 6.966	11.807	0.0104 0.0104 11.959	0.4952 0.6027 10.989	3504°C						
	2	2		(0/10)							
DEVM	17.227	13.023	046.6	9.703	7.637						

Blade Element Data Intermediate Configuration (Continued) Table B-4.

Τa	Table B-4.	ыдаае		Element Data	Interm	Intermediate Co	nrıgure	1011	configuration (continued)	lea)	
50	SOPERCENT SPEED	PT.216	CONFIGU	CONFIGURATION Interm.d fate	N/ <b>V</b> @ 3027.	24.6 27.2	N				
	-	INLET GUIDE	DE VANE					ROTOR	ine:		
						4					
PCT SPAN	06	7.0	50		10	PCT SPAN	υĖ	7.	C L	<b>3</b> ,5	ç
DIA 3		26.050	30.950		40.750	DIA 4	23.385	27.759	22,125	30.495	40.94R
BETA 3		0.000	0.00		0.00.0	BFTA 5	13.976	13.007	12.719	16v*6	4.256
ETA	15,387	14.925	13.648		4.804	BETA 7	51.646	52,785	50.687	47,303	4 E . 7 RO
ح س		154.82	159.53		162.70	BFTA(PR) 6	£7.61	62.615	£11. £78	53.651	יס, חמה
₹.	163.71	164.55	169.83	174.47	173.55	a a	22.507	40.441	47.152	52.412	د١٠٠٧٤
		154.68	159.53		162.69	٠ <b>٢</b>	174.47	173.52	170.44	184.01	100.04
		158.11	165.03		172,33	۲ >	321.60	202,00	207.14	238.42	204.32
V-THETA 3	00.0	00.0	0.00	င <i>်</i> ၁	0 0 0 0 0 0	4 Z V	149.27	140.27	174.	132.43	170.12
		42.38	40.07		20.56		198.43	177.11	191.02	2,02,33	30.400
		0.1390	0.1432		7.146C	V-THFTA 5	42.14	41.60	36.36	7.67	10.01
* P	0.1470	0.1477	0.1525	6.1567	0. 158 0. 158		75.76.	14.66	277.14	219.33	31 ° 1 C
<u></u>				21.6	n		710.7	233 7	2.40	) = 0 0 0 0 0 0 0	
3	(REFER TO 70%	એ	100% SPEED DATA)	(¥.		VINETA DOA	1256 7	-32/-0	- a 1 - x - 1	151.0	
DEAC	0.042	0.076	0.062	0.017	400.0-	VIHETA DR7	1 2 X	152.3	1210 4	4.07.4.	270
F 10	4-3323	9059	0.7536		C-7223	1 9 1	308.86	364.58	424.30	487.17	530,74
			200			, r-	325,35	385.67	432.5	487.22	524.12
NCIDW	-20.200	-20.200	-20.200	-50.200	-20.200	· •	7.1547	ר. וייא	0.1502	0.1660	0191
DEVM	5.313	4.075	3.552	5.838	8.496	2	7973	r.2612	0.2857	1.2553	0.2646
			•				7.2837	0.3296	r. 3705	C.4345	4407.
		STATOR	<b>a</b>			M(pp) 7	1,1931	C. 2023	0.2475	0.462.0	CA140
						TURN(PR)	34.009	21.034	14.502	15.633	13.072
						13	0.1252	0.1652	0.1897	0.1587	0.1919
PCT SPAN	06	20	50	30	10	DEAC	•5634	.5698	.5246	-4942	•4706
DIA 9		29,683	330345	37.007	40.669	de de	4.4.06°U	0.0100	ξαΙυ•c	P. 8834	70E8 C
		51.492	49.155		44.537	i i i	J*90.65	r.2120	72150	C. 8830	C 280 J
	22.584	17.216	15.137	14.820	9.562	LOCION	9.001	10.115	9.576	8.451	7.785
» =		292.93	206 21		504 • 75 266 20	* > 50	1 707	ואר א	2 052	2.813	בננין
6 2/		181.05	189.52		217.20		<u>.</u>	101	-		}
VZ 10	167.11	196.34	198.43		262.57						
V-THETA 9		229.24	219.80		213.74						
V-THETA 10		61.38	53.85		44.24						
Σ.		0.2611	0.2587		0.2705						
0 T		0.1842	0.1830		0.2360						
2 2 2		34.276	34.018		34.976						
13	0.2858	0,1323	0,1976	0.1623	0.0715						
DFAC	0.6229	0.5270	0.5415		0.3976						
EFFP INCIDM		0.7519 9.892	0.6155 9.955	0.6276 7.208	0.7923						
NA CO	18.24.8	11,761	0.637	0 820	2,4,5						
D L V Z	2	4	3	7.010	7.405						

Blade Element Data Intermediate Configuration (Continued) Table B-4.

•.	SOPERCENT SPEED	ED PT.217	CONFIG	CONFLUNRATION INFERMEDIATE	N/VO 3037.	270/8/2/2013.0					
		INLET GUIDE	GUIDE VANE					ROTOR			
PCT SPAN	<b>ગ</b> ુક	<u>5</u>	ů, O	30	10	PCT SPAN	96	7.0	5.0	3.0	10
DIA 3	21.150	26.050	36.950	35.850	43.750	Φ,	23,385	27.755	32.125	36.495	40.865
BETA 3	0.000 0.416	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	C. 000 3 % 6.68	0.000 9.658	2000	BEIA 6	14.333	15.525	12.586	9 0 0 0 c	38.140
	170.63	180.48	186.54	189.77	190.15	V(PR)	54.260	57.605	61.451	64.580	68.189
· >	162.40	156.28	200.96	205.25	201.09	PETA(PR) 7	22.894	38.733	46.615	51.777	56.118
V2 3	170.62	180.25	186.53	189.76	130.12	<b>^</b>	194.46	208.41	211.65	216,39	208.48
		188.84	155.31	2.02 - 3.3	195.61	۲ ،	331.21	304.13	298,11	299.46	299.57
V-THETA 3	20.0	၁၈ ၁၈ ၁၈ ၁၈	0.00	0.00 36 47	0.00 0.40	9 7/	188.36	202.44	206,52	213.70	207.09
	3	0.1621	0.1076	0.1705	0.1708		48.14	42.44	46.12	33.96	26.05
Ŧ	0.1036	0.1764	0.1800	0.1345	0.1807	V-THETA 7	240.12	212.17	203.25	191.72	185.01
TUKN	-15.81	-14.63	-13.61	19.6-	96.9-	V(PR) 6	322.5	378.0	432.1	497.9	557.4
13	(REFER	TO 70% &	100% SPERD DATA	ТА)		V(PR) 7	247.5	275.3	317.5	371.8	422.6
3 ;			##	· · · · · · · · · · · · · · · · · · ·		VIHETA PR6	-261.7	-319.1	-379.6	-449.6	-517.5
DFAC	1808J	0.052	0.62.0	0.010	)*006	VIHELA PK	146.5 2005	267 70	-230.7	1.292.	-350°9
;	1.000	11015	6110.00	625.00	50000	o	336.45	386.94	433.03	483.81	535.89
INCIDA	-20.200	-20.200	-20,200	-20.200	-20-200	3	0.1747	0.1873	0.1903	0.1946	0.1874
DEVM	1,846	1.368	3.592	5.912	8.335	۷ ع	0.2962	0.2717	0.2660	0.2669	0.2566
						M(PK) 6	0.2893	1988.0	0.3885	0.4476	0.5010
		STATOR	щ			M ( PR) 7	0.2214	0.2495	0.2833	0.3314	0.3751
						- X4 - X - X - X - X - X - X - X - X - X	966.16	848-81	14.851	17.801	170.21
						13	0.0714	0.0867	0.0838	0.0999	0.1051
PCT SPAN	<i>ن</i> ې	7.0	50	3.0	10	UFAC	7454.	.4337	1614.	.3947	.3820
DIA	26.021	25.083	30.345	37.007	599.65	EFFP	0.9587	9666	0.9884	0.9492	0.8990
BETA S	45.218	45.88C	41.437	38,393	37,163	ا الله الله الله	0.9582	0.9995	0.9885	0.9487	0.8978
BETA IC	17.642	15.060	14.080	13.932	11.970	I NC I DM	2.000	5.105	5.351	096*17	4.707
ر - × - ×	740.64	200°0000	249. db	270.14	235.72	DEVM	160-17	6.233	, 5, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1,	3.177	3.288
6 ZA	225.51	222.69	420.65	240.34	244.52		t }		7		
	85.522	234.14	241.75	262.06	279.45						
0 4 1 1 1 1 A		200.28	2,00,55	190.44	165.37						
V-1751A 10		65.51	40.40°	05.27	39.26						
. O1 : <b>¥</b>	U. 216c	0.2178	6.2225	0.2404	0.2541						
TURN	27.576	27.820	27.356	24.41.2	25.193						
13	0.1375	0.0844	0,0843	0.2490	-0.0076						
DFAC	95540	C. 3551	0.3781	0.30%	0.2598						
EFFP INCIG	0.7113 -0.182	C.7642 1.280	2.237	6.9252 -0.107	1.2011 -3.337						
DEVM	13.342	9.560	8.580	8,982	7.870						

Blade Element Data

Tab	Table B-4.	Blade	Element	ıt Data	Intermediate		Configuration		(Continued)	ed)	
. <b>.</b> .	oduso Indivación.	7 E 0	CONFI UURATION	VFI CURATION	N/V	2 / 8 / 3					
					•	) • • • •					
		INLET GUIDE VANE	E VANE					ROTOR	~		
PCT SPAN	75	787	50	Ç	0.7	PCT SPAN	, i.e.	7.0	50	3.0	.0
D1A 3	21.156	20.050	36.550	35,850	40.750	DIA 6	23,385	27,755	37-125	36.495	40.865
BETA 3	0000	0.00	000.3	0.000	3,000	BETA 6	14,365	13,479	12.237	8.806	6.129
		14.574	12.51	9.345	5.623	HETA 7	40.011	39,381	37.241	33,882	31.688
د ع		154.31	201.02	204.59	234.55	BETA(PR) 6	50.777	54.528	58.769	62.352	66.357
4		212.30	216.77	220.40	215.55	A(PR)	24.003	38.118	45.656	51,096	55.451
5 27	IE3. EU	194.CE	2c1.01	204.50	274.95	ر ا ب ا	211.52	225.58	228.63	232.22	223.00
	24°041	27.477	21C.98	510°50	21.412	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	333.13	305.35	799.35	298.58	297.97
V-1111 V	00.40	, . ,	0 % 5 3 4	20°0	0.00 0.00 0.00	۲ / ۷	251 74	235 80	228 10	26.4.4	27.1.72
	2101.0	0.1746	0.1807	- 5 × 1 × 3	0.1842		52.48	52.58	48.46	75.55	73.81
. T	0.1775	0.1909	0.1944	0.1902	0.193E	V-THETA 7	215.84	193.73	181.15	166.51	156.52
TUKN	-15.00	-14.57	-13.27	66.6-	-6.6.2	V(PR) 6	324.1	377.R	430.0	494.5	552.9
1	( PERPER	( REPER TO JOH ALL 1		TATA )		V(PK) 7	276.8	3000€	340.9	394.8	447.1
3	Maran )	B		(W		VIHETA PRS	-251.0	-307.6	-368.4	-438.0	-506.5
DFAC	6,00	C 5 C 4 7	ر• 0±۵ ا	0.011	500°C	4	-112.6	-185.2	-243° ×	-307.3	-369.2
EFFP	0.6250	1.0062	0.6423	6.4535	7.6592	9 P	303.46	360.16	416.87	473.58	530.29
ואטוטאו	-20.200	-20.200	-20.200	-20,200	-20.200	- v	74.626	66.60	75.474 70.00	4 (3.17	254.11
DEV.	1, 817	1, 1,26	3,020	800.9	8.677	L P	20010	0.2029	0.02.0	6802.0	9062.00
E AU	1100	02#•#	7.757	203	200	4 10 E	#847*D	75/27	0 2076	0000	0.4034
						0 1 0 0 0 0	6152.0	250000	0.000	7 7 7 7 7 7 7	2764-0
		STATOR	В			TUKNON	26.763	16.386	13.168	11,254	10.905
						1	,	1		0,70	0700
PCT SPAN						3	0.0360	0.0354	0.0346	0.0059	0.0009
		7.	20	30	10	DFAC	.3364	.3556	•3393	.3199	•3038
6 VIO		25.683	33.345	37.007	43.665	4 T. F. P.	1.0.01	1.0650	1.0782	1.0410	0.9938
CHE A V		51.893	55. (7)	32.103	53.46.4	11 T	2,177	1.0656 2.208	0.010.1	1.0414	0.9938
2 2 2	0000	300-32	10.01	306.47	73.20	10101			2003	261.2	167.6
)   		274.09	273.43	284.54	297.13	₽ ^ 3G	5.208	5.618	3,556	2.496	2,551
6 ZA		242.36	246.45	257.79	252.06						:
VZ 10		263.42	254.84	276.50	249.01						
		189.98	178.30	165.55	133.79						
V-TEETA 10	57.21	68.25	65.50	66.93	58.78						
o . •	1657.0	0.2768	0.2727	0.2738	0.2712						
TURN	23.202	23.467	21.901	860.6	17.015						
13	0.0965	0,0850	0,1057	0.0944	0.0722						
DEAT.	£	7776 . 1	7777	3100	0 1603						
7 2 2	7.707.0	0.000	0.2030	0.2213	0.1393						
INCION	-6.217	-3.707	-3.425	-5.797	-10.096						
	Š	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	ć	0	ac						
UEVM	11.001	9.750	175.0	0°00	X • 5 U.D						

Blade Element Data Intermediate Configuration (Continued) Table B-4.

			CONFIGURATION	RATION	6/N	3/6/3	1				
	SOPERCENT SPEED	) PT.214	INTE	Intermediate	3017.	138.4					
		INLET GUIDE VANE	VANE					ROTOR			
POT SPAN	ć	ŕ		ć	9	PCT SPAN	ć	ç	í	ć	Ş
: <b>C VIO</b>	90	26.050	30,950	30 35 850	10	010	73,385	27,755	32,125	36.405	40,046
. ⊴	0.00	000.0	0.00	000.0		BETA 6	13.820	13,150	12.081	98.0	770 u
	15,396	14.370	13,033	9.668	6.238	BETA 7	34.954	33.404	27.142	28.365	24,003
		222.89	229.99	233.65	234.02	~	46.307	50.430	45.144	59.285	43.790
4		242.60	248.05	251.36	246.56	BETA(PR) 7	21.643	34.641	43.297	49.152	52.777
VZ 3		222,63	229.97	233.63	234.01	9 >	245.79	260.04	252.18	263.99	25.575
4	219.68	233,86	242.23	247.78	245.07	۲ ۸	372.15	340.08	354.26	121.97	322.41
⋖		00.00	00.0	00.0	00.0	۷7 ۶	234.13	253.03	254.32	260.66	562,33
-THETA	90.50	60.21	26.07	42.21	27.05	7 7	303.71	284.30	274.43	283.27	204.44
	0.1897	0.2005	0.2069	0.2102	r.21n6	V-THETA A	58.59	59.19	54.87	41.70	25, 93
4 S	0.2050	0.2183	0.2238	0.2263	0.2219	⋖ :	213.21	187.72	177.51	152.97	131.14
- CEN	-15.40	-14.37		19.6-	-6.30	V(PR) 6	344.9	797.	448.45	510.3	U
13	(AEFE	(REFER TO 70% & 1	100% SPEED D	DATA)		V(DR) /	328.2	346.	7.7.6	N. 0000	6.07
DEAC	790.0	0.0	0.042	0.015	400.0	VINETA PRO	-121.0	106.7	, dir.	1450.1	
2 1 1 1	0.8879	0.9432	0.8516	0.0486	0.7475		307.84	365.37	422,00	480.43	10 LC5
•			21000	0.15.4.0	000 00		334.74	384.39	431.17	490.62	42.025
INCIDM	-50.200	-20.200	-20.200	-20.200	-20.200	· vc	7,2208	C-2342	0.2351	0.2378	r. 2203
DEVM	5.304	4.630	4.167	5.932	9,002	7	0.3343	0.3059	5005	).29H3	C. 2897
						M(PR) 6	0.3103	F.357R	0.404	7045.0	0.514"
		COTA TO	م.			M(PR) 7	1.2947	0.3103	01 EE 0	3879	15445
			n			TURN( PR.)	24.657	15.758	11.052	10,132	10.070
						13	0.0326	0.0388	0.0508	0.0611	0.0910
PCT SPAN	06	7.0	50	30	υI	DEAC	.2175	.2592	.2703	.2484	421/h
	26.021	29.683	33,345	37.007	43.569	EFFP	0.9547	0.480°C	10.03.0	0.9415	7.9714
6		31,906	30.921	27.211	23.375	FFF	7.9639	0.9950	78860	3.9413	1170.0
w	15,756	14.730	14.113	13,465	13,356	INCIDA	-2.293	-2.070	-0.956	-0.315	7.580
5 € >>		248.24 223 08	330.41	330.48	321.15	NA GC	2,/81.2	111.0	187	623	0.807
		293.96	283.00	293.98	300.81		C to C	141.2	01.1		
VZ 10		321.03	310.53	312.66	317.71						
	204.30	184.08	169.78	151.12	130.04						
		84.92	78.20	74.87	75.45						
o^ : ₹:		0.3125	0.2961	3,2961	0.2935						
0 7 10	0.3153	0.2994	0.2873	0.2879	10.026						
<u> </u>	920.0	21100	100.01	27700	320.00						
3	0.0050	O.0445	0.0277	0.000/	0.0915						
DFAC EFFP	0.1604	0.1567	0.1506	0.1347	0.0854 -8.9810						
INCIDM	-12.015	169.6-	-8.279	-11.289	-17.125						
DEVM	11.456	9.230	8.613	8.465	9.256						

Blade Element Data Intermediate Configuration (Continued) 129.8 N/V@ 4223. CONFIGURATION IN FERMEDIALE 70PERCENT SPEED PT.209 Table B-4.

ROTOR

INLET GUIDE VANE

PCT SPAN	Ü	20	50	90	0.	PCT SPAN	Co	10	50	30	<u>c</u>
0 IA 3	21.150	26.050	30,950	35,850	40,750	DIA 6	23,385	27,755	32,125	36.495	40. RAE
BETA 3	0000	0.000	00000	0.000	000.0	BETA 6	13,898	13,794	12.978	9.258	5,084
	15.450	14.805	13.770	9.872	6.553	BETA 7	52.725	54.769	54.129	50,530	48.422
٠ >	198.07	208.47	214.94	218.65	219,27		60.428	63.345	66.316	68.571	71.32
	205.42	223,38	232,27	238.25	235.88		25.565	44.342	51,359	54.033	57.730
VZ 3	198.06	208.12	214.94	218.65	219.26	9 >	220.94	235.55	242.07	251.36	247.14
4 ZA	197.97	214.93	225.54	234.70	234,34	٨ ٦	431.01	389.72	391.n2	408.19	414.62
V-THETA 3	00.00	00.00	00.00	00.0	00.00	VŽ 6	214.40	228.52	235.41	248.05	245,70
V-THETA 4	54.72	57.08	55.28	40.84	26.92	7 2 7	259.72	224.51	228.95	259.41	274.07
<b>€</b>	0.1780	0.1874	0.1933	0.1966	0.1972	V-THETA 6	53.07	56,16	54.36	46.44	25.77
	0.1846	0.2009	0.2090	0.2144	0.2122	_	342.97	318.33	316.86	315.11	311.12
TURN	-15.45	-14.80	-13.77	-9.87	-6.55	V(PR) 6	434.5	504.5	587.1	0.670	767.4
ı	0		o too		0000	~	289.4	314.4	3.66.9	441.8	413.3
3	0.0250		0.0240		0.000	VTHETA PR6	-377.8	-455.3	-537.6	-632.0	-727.2
DFAC	0.105	190.0	0.049	0.004	-0.014	4 8	-124.9	-219.7	-286.6	-357.6	-434.
EFFP	0.8255	1.0221	0.9021	0.9789	0.8144	9 0	430.90	511.42	591.95	672.47	752,99
1	-20.200	-20.200	200	000	000 00	1 0	467.84	538.05	603.46	072.74	745.14
NCIDW			000	00101	20.5	.90 Æ	0.1987	0.2119	0.2179	0.2263	r.2225
DEVM	5.250	4.195	3.430	5.728	8.747	<b>≻</b>	0.3834	0.3455	0.3457	0.3599	0.3641
						M(PR) 6	0.3907	0.4584	0.5283	0.6113	.109.
		STATION	æ			M(PR) 7	0.2574	0.2787	0.3244	0.3895	0.4500
		NO.TWITO				TURN (PR)	34.853	18.980	14.949	14.531	12,596
						13	0.0863	0,1686	0.2466	0.2125	0.2588
PCT SPAN	G	0,2	Ċ,	0.4	5	ט מיט ט	ניסו	787	56.30	4200	ሊርኒ
0.410	26 031	20 4 92	245	700 75	079 07	2 0	1204.	6706.0	0.0252	• •	
0 0 4 1 0	120.02	2000	200	410.0%	600.04	ער ה	1,000	0.000	0660	•	
	32.053	070 71	400.76	17.010	10 724	TAT TAT	11 828	10000	• -	6 9063	Ç a
	419.38	388.73	304.27	416.16	427.50		070-11	TO - 042	017.01	0.77	077-0
	211.81	264.72	264.12	310.97	360.01	MV#C	6.765	C.18. LL	0 200	A 1.28	- A30
2 2	251.93	228.65	237.68	272.81	293,71		<u> </u>		(7.)	2	1
	191.18	251.22	254.98	301.57	353,71						
V-THETA 9	332.31	313.22	314.06	314.16	310.62						
V-THETA 10	85.65	76.81	65.59	75.08	66.99						
<b>○</b> I	0.3728	0.3446	0.3486	0.3669	0.3756						
M 10	0.1864	0.2333	0.2321	0.2728	0.3151						
TURN	28.556	36.817	38,425	35.045	35.878						
13	0.3699	0.1575	0.2490	0.2257	0.1483						
DFAC	0,7150	0.5686	0.6075	0.5206	0.4360						
EFFP	0.5027	0.7265	0.5494 13.60h	0.4756	0.4468						
			† :								
DEVM	19.553	11.368	8.878	8.971	6.624						

Blade Element Data Intermediate Configuration (Continued) Table B-4.

		10	40.865	5.898	41.430	55.172	268.09	430.74	266.67	322.95	20.73	776.8	565.5	-729.5	-464.2	757.09	149.22	6147.0	0.6998	0.4988	14.749	0.1918		0.9283	6.721	•	2.272										
		30	36.495	9.306	45.435	52.435	278.40	416.30	274.70	292.06	204 50	688.3	479.2	-631.1	-379.8	676.13	0.2500	0.3680	0.6204	0.4236	14.041	0.1406		0.9386	6.887		3.835										
	æ	20	32.125	12,556	48.843	49.269	269.04	399.91	262.52	263.00	20.105	597.5	403.4	-536.7	-305.7	595.17	0.2424	0.3544	0.5383	0.3575	14.657	0.1645	1964.	0.9747	7.835		7.169										
	ROTOR	70	27.755	13,565	50.049	42,107	261.04	401.63	253.52	257.57	207.10	519.2	347.6	-453.0	-233.1	514.21	0.2351	16620	0.4677	0.3088	18.636	0.1429	5197	1.0022	8.266		6.607										
		06	23,385	14.548	57.508	25.997	244.71	435.99	236.78	279.15	222 27	440.8	312.6	-371.8	-137.0	433.25	4.00.39	0.3884	0.3968	0.2785	31,501	0.0611	.5211	1.0153	8.908	•	7.11.7										
142.0		PCT SPAN	DIA 6	BETA 6		BETA(PR) 7	9 >	~ >	9 2/		V-THEIA O		V(PR) 7	VTHETA PR6		9 :	~ 4		(PR)	_	TURN(PR)	13	DFAC	EFFP	INCION		DEVM										
N/V@		10	40.750	0.000	0.416	259.69	239.42	258.06	00.0	29.02	0.2230	-6.42	0000	0.0220	-0.024	0.8045	-20.200	8.88					10	40.669	13.657	437.75	375.39	325.97	364.65 202	98.64	0.3862	0.3300	28.182	0.1279	•	0.6645	9.557
CONFIGURATION INTERMEDIATE		30	35.850	000-0	9.995	261.25	240.09	257.25	00.0	45.35	0.252	-10.00			0.007	0.9802	-20.200	5.605	<b>)</b>				30	37,007	14,176	426.65	337.59	307.22	321.26	82.68	0.3773	0.2971	29.760	0.1444	0.4419	0.6618 5.436	9.176
CONF	E VANE	50	30.950	000.0	13.501	254.85	236.59	247.74	00.0	59.50	0.2265	-13.50	7000	0.0220	0.050	0.8723	-20.200	3.699	***	ŗ	ц		20	33,345	13.931	406.34	295.75	275.00	280.50	71.20	0.3601	0.2607	33,366	0.1987	0.5184	0.6135 8.097	8.431
ED PT.210	INLET GUIDE VANE	70	26.050	000.0	14.628	246.09	229.06	236.92	00.0	62.15	0.2004	-14.63			0.065	C.5621	-20.200	11.372	) } †	CH ARC	NOTHIC		7.0	25.683	15.806	462.50	295.26	263.41	78.187	80.42	0.3575	C.2608	32,580	0.1211	C.4930	0.7462 7.186	10.306
7CPERCENT SPEED		06	21.150	000.5	16.104	228.53	217.55	219.54	00.0	63.39	0.1936	-16.10		0.0220	660.0	0.8201	-20.200	705-1					06	26.021	21.760	454.54	250.08	272.56	60.622	922.10	0.3783	0.2206	27.544	0.3136	0.6130	0.5449 3.903	17.460
705		PCT SPAN	DIA 3	BETA 3	-	> > J -4	VZ 3	4	V-THETA 3	-THETA	η « Σ. 3		1	3	DFAC	EFFP	INCIDM	N N H C					PCT SPAN		BETA 9			6 7/	V. 100 V	V-THETA 3		₩ 10	TURN	13	DFAC	EFFP	DEVM

Blade Element Data Intermediate Configuration (Continued) Table B-4.

		-	10 A A E	4.447	77.430	44.745	E4.04F	210,40	02.007	30K	741.74	3 P	/ L = L //	9 603	710	-404-7	753.70	785.87	7.00c	かしゅと し	2.306.	7. A.7.4.7	11.02	0.0971	.3778	A\$ 10.0	5 1 10°C	3.565	1.945												
		ć	35.435	4.1 33	39.292	53.031	51.0.15	\$20.74	+23.73	314.68	327.92		ت ا ا ا	0.00	4.654-	1.604-	673,11	673,38	1.28.17	11.37.12	1.6307	1.4627	12.025	0.0694	.3927	3.9612	4.096°	3.431	2,1,05												
		ď	32.135	12,353	47.578	ro. gal	45.004	312.27	416.77	204.07	10.00	76.43	7.44.	7 7 7 7	1 · 11 · 11 · 1	7 206-	507, 51	604.03	ט נפר יע	2734	0. 54 97	, 30ge	13.097	0.0496	.4193	C. GARR	7.080°	3.781	3.891												
	ROTOR	7 6	27.755	13,412	43.407	56.047	37.766	מני שעצ	430.94	294.76	312.67		, to	305	1.177-	-242.5	511.91	530.55	r.2754	r.3841	0.4700	0.3530	14.274	0.0186	.4301	1.0103	1.0105	3.567	5.266												
i		c	73.385	13,794	45.737	52.603	22.631	285.93	464.08	19.11.	322.90	71.80	557.44	351 6	1.545-	-135.3	431.31	468.29	7.2578	7.4154	7.4122	7.3141	50.964	0.0203	of 444.	7.9526	0.9517	4.003	3,831												
153.5		PCT SPAN	DIA A	RETA 4	BFTA 7	3 (50) VETA		۷ ۶	۲ >	۷ <u>۲</u> ۶	7 / 1	V-IHIIA O		V(PS) 2		VTHETA PR7		~	•	۲ ۲	4(PP) 5		TIJRN(PR)	13	DFAC	FFFF	<u>.</u>	FVC1 DW	OEVA												
N/V Ø 4227.		2	40.750	0.000	6.957	283.72	297.89	280.21	595.69	00.0	36.08	7.52.6	14.04	06.001	0.0100	0.001	0.7273		-20.200	8.343					10	40.669	36.004	5.789	441.22	356.92	398.21	259.37	40.37	7 3636	30.215	90500		0.3349	967-1	,	1.269
FIGURATION IN FERAEDIATE		C.F.	35,850	3.000	9.732	279.28	303.33	279.27	298.96	0°0	51.28	0.2517	15/250	61.61		900.0	0.9485		-20.200	5.868					3.0	57.007	37.902	6.108	435.19	343.28	369.48	267.34	39.55	0.3865	31,793	0.0654		0.3898	- 598 - 0-598	.1	1.108
CONFIGURATION INTERAEDIA	IDE VANE	ů.	30,950	0.000	13,354	273.96	295.62	273.95	287.61	00.0	66.28	C - 2409	1 2 25	13,32	0.0247	0.046	0.7805		-20.200	3.846		-			50	33.345	41.112	5.962	426,34	370.36	340.11	280.33	35.62	0.3793	35,150	0.0817		0.4486	1.912	1	204.0
ED PT.211	INLET GUID	70	26.050	0.00	14.516	264.58	286.85	264.23	276.00	00.00	71.90	0.2383	U. 2387	76.41-		0.054	0.8644		-20.200	<b>181-1</b>		STATION	SIRIOR		70	29,683	41.918	6.165	434.67	320.03	331.64	290.38	36.13	0.3876	35,753	2001.0		0.4670	0.318	1	6000
70PERCENT SPEED		Ü	21,150	0.000	15.194	249.65	268.77	244.90	259.37	00.0	70.44	0.2250	0.2422	61.401.	0.0200	690.0	0.7646		-20.200	5.506					06	26.021	44.566	7.544	456.47	319.48	324.83	320.32	43.34	0.4075	37.023	6661.0	1 1 1 1 1 1	0.5058	-0.834		3.244
70		PCT SPAN	DIA 3	BETA 3		e >	<b>4</b>	۸۶ ع				n ,	2 H		13	DFAC	EFFP		Neiby	DEVM					PCT SPAN	DIA 9		BETA 10	o =	2 2	VZ 10			o -		١,	3 ;	DFAC	INCIDM		DEVM

Blade Element Data Intermediate Configuration (Continued) Table B-4.

r.T.	Table B-4.	ыдаае	rement	חב חמר זוו	•	TII CETIII ENTACE CO	COIII TÀ MT M CTOII		יייייייייייייייייייייייייייייייייייייי	(par	
			CONFIGURATION	RATION	N/V@	2/0/2	-				
72	7CPERCENT SPEED	D PT.212	INTER	Intermediate	4230.	180.3					
		INLET GUIDE	VANE					HOLOR			
PCT SPAN	06	70	50	30	10	PCT SPAN	06	02	50	30	91
DIA 3	21,150	26.050	30.950	35.850	40.750	DIA 6	23.385	27,755	32,125	36.495	40.865
7	00000	000.0	0.000	000 • 0	000.0	BETA 6	13.868	13.530	12.092	9.086	5.124
ETA	15.445	14.792	13.199	6.715	5.467		38.397	38.408	36.119	32.973	28.685
m >	279.56	255.34	304.90	309.63	309.72	BETA(PR) 6	48.505	52.332	56.778	119.09	02.190
4	300.10	320.65	327.97	332.32	327.61	ž	22.269	33.884	45. (11	44.440	336.366
5 7 7	20.000	27.07.5	304.88	30%-61	224 12	0,6	40.776	242.50	240.34	441.54	447.88
4 t t	CZ • 60 Z	1000	07.616	#6.12c	21.026	· · · ·	77.4	44.48	340.53	348.02	334.85
VITHER S	79.92	8 . 8	74.89	56.08	31.21	2 2 2	388.03	355.09	357,96	370,35	392,90
	0.2520	0-7664	0.2752	0.2795	0.2796		77.38	80.31	72.97	55.66	30.03
	0.2708	C. 2896	0.2964	0.3003	0.2960	V-THETA 7	308.97	281.80	261.35	240.30	214.98
	-15.45	-14.79	-13.20	-9.71	-5.47	V(PR) 6	473.0	545.9	621.6	709.2	797.9
ť	0		000		0000	V(PR) 7	421.3	438.7	496.0	570.2	6.099
3	0.0180		0.0228		0.0230	VTHETA PR6	-354.2	-432.0	-520.0	-617.9	-724.2
DFAC	0.073	0.055	0.048	C.018	-0.007	PR	-159.6	-257.1	-343.1	-433.6	-531.4
EFFP	1.9216	1.7942	1.4591	1.7423	1.4428	• • ⊃:	431.61	512.27	592.93	673.58	754.24
2010(61	-20.200	-20.200	-20.200	-20.200	-20.200	~ · ⊃ :	468.62	538.94	604.46	673.86	746.39
10000	1	000	100	נסמ		,Ó (	0.2916	0.3104	0.3151	0.3189	0.3039
DEVM	5.255	4.208	100.1	۲ <sub>00</sub> ۰۲	9.833	~ X	0.4466	0.4059	0.3961	0.3938	0.3988
		STATOR	m			A PK 10	0.4273	0.443	0.0023	0.041	0.1213
						TURN(PR)	26.228	16.426	13.001	11,120	11.664
						13	0.0278	0.0187	0.0342	0.0745	0.1075
MAGO WAG						3	2130			•	
rci span	.06	70	50	30	10	DFAC	.2936	.3413		3122	.2803
	26.021	589.57	33.345	37.007	40.00	T 1	0666	0.9840	966.0	6296.0	0.43.0
DE A THE	31.055	12 840	34.030	34.700	12.935	TTT MOTON	0.094	0.168	0.578	1.01	1.086
	15-657	460.99	452.70	455.48	455.47				2		3
-	423.88	404.06	404.84	414.35	427.59	DEVM	3-469	3.384	1.671	0.890	0.622
6.74	387.19	366.59	371.86	387.51	400.66						
	400.47	354.50	393.20	403.45	416.60						
	297.02	276.45	257.30	239,34	216.41						
	111.22	90.85	94.16	94.35	95.71						
o :	0.4424	0.4127	0.4047	0.4065	0.4057						
TURN	21.843	22.978	21,191	18,538	15.433						
١	0880	0.01.1.	ט טקע	7250 0	אין ויס						
3	0000.0	0.0444	0.000	0.00	7						
DFAC	0.2794	C. 27C7	0.2536	0.2387	0.1910						
INCLOM	-8.345	-4.753	195-11-	-6.800	-12,132						
DEVM	10,912	8,369	7.91.5	6,162	8.835						
<u>.</u>		\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	<u>}</u>	101.0	11000						

Configuration		AOTOR		55 37,125 36,405	12.1111 A. 967	71.332 27.303	54.172 54.579	49.64	378.91	4 14 15 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	49,465	79.50 59.44	255,33 234,50 205,73 175,23	634.8 722.5	535.6 615.6		512.1 -41 505. 62 275.03	555.63 676.61	2,2434 C.3456 V	4404	0.5753 0.6549	5.55.5 5.55.5	\$61.5x 582.5.1	0.0439	.2383	0.9879 0.9945	3.033	15.01 -1.70 -1.021 -1.021 -1.044	3.019 1.909 1.243 1.495									
			ć	39,384	13.667	22°62	45.672	23.543	34].94	10.12	440.76	93,12	201.75	4.80.4	472.	C 1.	1 3 3 3 3 3 4 3 3 4 3 3 4 3 4 3 4 3 4 3	470.08	3.33	4654	r.4429	4244	((1.0)	0.0241	.1893	1.0355	1.034. -2.028	03/17	4.743									
Intermediate $\omega \sqrt{\theta}/\epsilon$	123.5		PCT SPAN	914.6	AFTA S	RETA 7	SETA(OR) 5	A ( DB )	ر بر ا	, ,	2 Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z Z	THETA	V-THETA 7	V(PP) 6	V(5P) 7	VIMETA DRA	4	: -	·	. *	M(PR) A	W(PR) 7	(ac.)NaOi	13	NFAC	dring	FFF	E (11 Va. 1	DEVM									
Element Data	4245.		<u>c</u>	45.750	ر بر • د د •	6.105	334.48	352,83	334.46	* * * * * * * * * * * * * * * * * * *	37.52	2008	0,3192	-6.10	0.0230	9 9	0.127		-20,200	9.195					<u>c</u>	40.669	23.170	451,76	458.38	415.25	446.74	177.73	104.43	0.4106	10.013	0.0784	0.0653	
	INTERAEDIATE		, c	35. 257	600	9.566	334.33	361.43	334.31	4.4.6 0.0	10 CX	66.8.0	0.3272	-9.57		i i	7640	1.733	-20.200	6.034					30	37.007	26.229	460.52	451.06	413.07	439.67	203.53	64.00	0.4164	13,344	0.0626	7.1243	
Blade El	INTE	DE VANE	C Ur	36.950	0000	13,252	329.21	357.97	329,19	24.5 20.0 00.0	92.04	0.2975	0.3239	-13,25	0-02g)	1 0 0	2000	666	-20.200	3.948		ſ	n		57	33.345	29.875	460.96	450.83	399.07	437.53	729.61	64.501	0.4130	16.296	0.0290	0.1393	
е В-4.	n PT.268	INLET GUID	, ,	26.050	, 000°	14.590	318,99	349.51	318.62	455.63 0.00	87.78	0.2881	1.3153	-14.50		r i	14147	10 11 01	-20.200	1.050		00			7.0	29.683	31,009	10.044 485.15	467.68	413.02	451.20	250.59	11/0.54	(.4563	17.200	0.0588	0.171.0	
Table	70PFRCENT SPEE		ç	21,150	0000	15.294	3r1.87	325.46	301.83	313.43	00° 50° 50° 50° 50° 50° 50° 50° 50° 50°	0.2724	0.294n	-15.20	0810	00100	2000	00000·1	-20.200	5.406					90	26.021	31.657	13.714 414.98	491.21	431.76	470.49	270.28	26-17-1	0.4041	16.079	0.0729	0.1439	
	Ĵ <b>L</b>		PCT SPAN	014 3	⋖	•	٧ ع	•	6 ZA	4	V-17674 5		· 4		13	3 :	UTAC Gran	T .	INCIDM	DEVM					PCT SPAN	DIA 9	BETA 9	) T & T(.	•	C.		V-THETA 9		. E 3	TURN	13	DEAC	5

Blade Element Data Intermediate Configuration (Continued) Table B-4.

ď	ROPERCENT SPEED	PT.203	CONFIG	CON FIGURATION INTERMEDIA FE	N/V 0 4842.	146.4	<b>(</b>				
		INLET GUIDE	GUIDE VANE					ROTOR			
PCT SPAN	<b>ပ</b> 6	20	κ c	ć.	<u>c</u>	PCT SPAN	Ö	۲,	50	ć	, 
C	20	26.050	36.950	35.850	40.750	DIA 6	23.395	27.755	32,125	34.405	4 . AAR
BETA 3		0.000	000.0	<u>ာ</u> ပ်ပ	000	AFTA 6	14.233	17.020	13.044	674.6	60 00
		14. 750	743 83	740.58	7.5.7.5 2.5.5.5	_		63,927	66.2418	69.352	71.042
. 4		53.11	262.21	271.34	269.66	RFTA(DR) 7	22.230	43.683	51.626	55.212	50,431
٧2 ع		733.54	243.82	749.57	250.55	9.7	246.42	263.96	278.36	23. 78	703, 51
4 2 4		242.56	254.33	266.82	267.30	7 V	50 July 90	456.39	442.80	453.04	455.46
V-THETA 3		<u>ပ</u> ၁	ر د د	ري <b>.</b> د	رن ن ن	V7 6	238.70	255.81	271.12	296.63	701.15
-THFTA		64.47	64.79	49.31	35.55	7 7	248.22	738 <u>.</u> 10	269.57	20.00	799,36
		2104	0.2195	7.52.5	0.2256	V-THFFA 5	40. 40.	0.000 0.000 0.000	28.29	4x.	74 478
T T T	0.7178	-14.76	7957	-10-47	17.58	V 1981 V	404.9	50.00	672.9	777	0.479
			0.44			VIPRI 7	269.0	329.0	434.5	526.0	592.1
13		0.1975	0.2936	0.2517	0,3063	Č	1433.5	-422 B	-615.9	-122.2	-424.5
DFAC		C.057	<b>3.</b> 056	C.012	-0.00p	VTHFTA DR7	-102.1	-227.8	-340.7	U-2×4-	מ נוניו
EFFP	0.8219	C* 0152	0.8703	\$986°	406 <b>€</b>	æ ! = :	404.06	586.39	678.73	77] - (14	863,36
INCIDM	-20.200	-20.200	-20.200	-20.200	-20,200	~ · · · · · ·	7.55.47	0.2378	0.2509	F. 2622	0.04.5% 0.0556
DEVM	5.328	11.244	3.120	5.129	7.724	. ^	7544	0.4026	43934	C. 39A2	1001
					•		. 4455	47650	0.6766	1. 7C . B	7 A A A
		STATOR B	æ			7 (aa)w	P. 2389	0.2010	0.3830	0.4623	62173
						TURN(DR)	38.005	112.00	14.610	13.129	11.611
						3	9080.0	0.1975	0.2936	0.2517	0.3063
PCT SPAN	٥٥	70	5.0	3)	, <u>, , , , , , , , , , , , , , , , , , </u>	PFAC	.7353	46554	.5353	00617.	988 <sup>†</sup>
~		29.683	33,345	37.207	40.669	C III	1.8967	6.9259	1906.	r.9770	4000
		57.187	50.682	47.030	47,114	ا المانية المانية	2 803 a	4626	3,9466	24/50	
META IC		1	445.444 445.444	1.5.1.2.2	11.00 K	F 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	12.50	17.02	10.141	0.(36	2000
, 0 1 2		27.70	296.13	340.44	4:17.44	oFV*	3.438	11.183	9.526	6.612	6.731
6 2 1		242.75	281.15	314.73	321.41		1				
10	195.50	280.01	290.02	331.13	399.57						
V-THETA 9	420.17	381.18	344.93	338.(8	344.99						
V-THETA 1	91.54	97.17	69°02	77.65	81.18						
. E . E		2.2596	C. 2535	1,2973	. 3552						
TURN	35.225	46.122	36.73R	33.945	35.552						
13	0.4073	0.2175	0,3109	0,2671	0,1257						
DEAC		r. 6113	0.62CR	0.5267	1.4067						
EFFD	2.1	.5819	0.3573	6.3117	0.4150						
INCLOW	14.676	15.587	11.482	8.530	419.9						
DEVM	20.551	11.566	8.1415	8.185	7.462						

H	Table B-4.	Blade	Element	ent Data	a Interi	Intermediate Co	Configuration		(Continued)	ned)	
Œ.	SOPERCENT SPEFD	PT.264	INI	INTERMEDIATE	4824.	120.0					
		INLET GUIDE	DE VANE					ROTOR			
PCT SPAN	, c	5	r. C.	.e	Ç	PCT SPAN	c c	70	Ç V	j	<u> </u>
	, r	7.7	36,050	25, 25.	40,750	D.T.A. A.	23,395	27,755	32,175	36.495	4. 94.
Ā			ن درن	C.)Co		BFTA 6	14.044	13,881	12.800	9.648	7.037
ᆸ	۵.		13. 464	10.459	745.8	SETA 7	54.778	56.001	51,643	47.7.1	47,117
× 3	-		251.12	255.24	254.92	RFTA(PP) 5	46.065	62. PF 6	65.439	67.812	21.002
		259.96	249.82	5.J. LL &	276.59	1 (00)	22.478	41.451	40.995	52.424	54.480
7	~.		251.12	255.23	254.91	٠ ٧	256.43	274.12	287.18	207.22	745,74
			251.90	272.42	273.71	۷ ،	5.53	463, 19	451.50	19.994	, to c
V-THETA 3	<u>.</u> د د		00°C	0 0 1 1		4 7 A	747.00	X • C + C + C + C + C + C + C + C + C + C	C 1 4 6 4 5 6 5 6 5 6 5 6 5 6 5 6 5 6 5 6 5	313 03	327.57
	04.40 04.70 0		04.03	12.00 C	33.05		62.07	45.76	63.63	40.4	30.36
∩ √1			0.243	1676	1.2493	V-THETA 7	430 43	384.15	351.09	345.12	25.74
$\Rightarrow$	-15.37	-14.87	-13.86	-10.46	76.8-		406.4	5A2.R	673.5	775.8	pka.1
i	00000/		_	TATA )		•	298.7	346.9	441.6	527.1	50K.5
3	va vav )		AL DESTE N	<b>`</b>		VTHETA DR6	-430.2	-519.4	-612.6	-718.4	B - 105-
DFAC	680°0	C.CAB	ं.55	6.014	-0.034	HET A	د.113-	-230.5	-338.3	4-523-4	140A.
EFFP		0.96r4	0.9182	o, qa2a	1.8327	4 - :	402.22	584.21	676.19	758.17	
INCIOM	-20.200	-20.200	-20.200	-20.200	-20.200	~ v	7.40.4	0.2470	0 2 4 5 4 7 2 5 9 5	10 10 10 10 10 10 10 10 10 10 10 10 10 1	r. 2573
NA C	5,328	4.127	3,336	5.141	7,033	. ^	7.4455	6004.0	K86K*)	0.4163	5,4212
		  -	1				7447	0.5252	7.6074	0. Kaga	r. 7877
						W(DB) 7	r.2642	0.3063	0,3896	0.4625	C. 5210
		STATOR B				TUP N ( DP )	27,670	21.178	15.436	14.375	14.315
						13	0.0730	0.1749	0.2574	0,2097	0.2578
PCT SPAN	96	7.0	ر <del>ب</del> ر	ر بر	J.	DFAC	•6680	.6221	.5247	·4905	.4820
DIA 9			33.345	37.CC7	40.669	D.F.F.D	0715.0	r.0313	0.9776	r.0478	9476
BETA 9			49.473	44.182	46.414	ינוני	2,9125	0.9204	0.9769	7.9460	F. 8772
BETA 10			13,579	13,555	14.212	I NO I OW	11.466	10.356	9.339	8.212	7.802
> <b>&gt;</b>	245.25	305.77	400.70	351.02	47,419	Dr.VM	3.678	9.151	7.895	п.83п	3.788
6 2/			295.16	330.93	337.41			•			
01 ZA			243.22	341.13	397.59						
	407.03		346.04	344.89	354.63						
V-THETA 1)	95.01		71.04	R2.27	67 · UI						
o :			0.4017	4564	0.4784						
TURN	32.827	37.889	35.893	32.627	32.202						
13	0.3910	0,2101	0.2766	0.2437	0.1399						
7640			0.5013	1,5218	0.4153						
EFFP	r.5261		2.4692	0.4971	0.6399						
INCIDM			10.273	7.682	5.914						
DEVM	19.520	11.310	8.079	8.555	10.112						

Blade Element Data Intermediate Configuration (Continued) Table B-4.

80£	BOPERCENT SPEED	ED PT.205	CONFIGURATION INFERMEDIA	figuration intermediate	N/√⊖ 4854.	~ \@\% 171.3					
		INLET GUIDE	GUIDE VANE					ROTOR	œ		
PCT SPAN	06	70	20	30	10	PCT SPAN	O.B.	٧٢	( u	ņ	ţ.
~	21.150	26.050	30.950	35.850	40.750		73.385	27.755	37,125	55.435	; پ • د <del>۲</del> و
BETA 3	٠,	000.0	000.0	000.0	000.0	BETA 5	14.059	12.447	2,010	161.5	
# # # # #	15,331	174.421	15.248	30, 30	5.543		111. 55 000	7 T - 1 A	44. 10. 20.	100 ent	
	281.05	301.07	310,77	319.48	316.97	PETA(PR) 7	20.953	30.05	40.251	15.637	. r o o
VZ 3	261.37	276.83	288.07	294.27	294.82	. 4 >	295.72	316.89	330.44	542.20	171
	271.05	289.40	302.50	314.69	315,03	۲ ۸	522.55	486.35	747.46	+31.7+	, Y 3 1
V-THETA 3	00.00	00.00	00.0	00.00	0.00	9 ZN	286.78	20.702	10.102	337.79	
-IHEIA	74.31	64.48	71.22	55.13	55.02		512.61	10.1 10.0 10.0 10.0	٠	551.33	
n √ E ≱	0.2534	0.2498	0.2378	0.2033	0.2862	V-1HF1 A 7	4. 7.14 4. 7.14	CK . 77 K	304.24	104-00	
	-15.33	-14.42	-13.25	46.6-	16,34		511.4	100 P	400	745 E	ь С С
1		BEFRE TO 70% &	Ę	( *#*		,,-	336.7	6.005	1,474,	540.3	. • 131.
3	_			LMIM)		VTHETA PR6	453.4	-514.	-410.3	-715-3	, , , , , ,
DFAC	0.071	0.051	0.046	0.008	-0.016	HETA	-120.4	-244.1	-356.7	444.8	, 6, 3
EFFP	0.8361	0.9589	0.8601	0.9307	0.7838	9 i	405.28	, a 7 a 4	707	772. 15	3 7 7 5
NO.201	-20.200	-20,200	-20.200	-20.200	-20.200	<b>~</b> 4	537.75	618.44 C 2963	693.63	173.27	1
DEVM	5,369	4.579	3.952	199.5	8,957		0.4643	6.4240	1.17	**************************************	. 6.3.
:					•		0.4614	r.5412	at c x	1.7173	c La
		STATOR	es.			7 (PP) 7	2662°U	ひとかと。シ	C. F. C. D. S. O.	50.05	й 14 г.
						TURN(pp)	34.929	l'év*ve	376 21	13,125	12,67
						13	0.0512	0.0933	0,1092	0,1132	0.1511
PCT SPAN	06	92	20	30	21	DEAC	.5934	.5519	.4712	.4398	9514.
DIA 9	26.021	29.683	33,345	37.007	40.669	EFFP	1468.0	C.0417	C200.4	ct 14.	. 6.3.3
	52.598	49.663	44.198	41.489	40.156	u. L. U.	0.8913	r 0401	1700	27.33	- 2
	19:361	14.230	12.895	13.635	13.201	FOLUNI	7.289	6.586	0.10h	7.5.14	7.CT.
> ~ > >	296.86	344.59	351:94	200.12	444.00	DEVM	5,153	79.1.4	6,15	3.087	2,983
6 7/	301.86	308.02	331.84	370.24	378.01	•	}	3			
01 70	277.52	330.21	341.63	387.66	430.64						
	405.91	366.46	330.75	327.56	318.99						
	98.42	84.70	78.52	94.09	101.02						
> =	0.2500	0.3025	0.3000	0.3502	0.3875						
	33.237	35.433	31.906	27.854	26.955						
13	0.2774	0.1359	0.1576	0.1397	0.0549						
DFAC	0.6396	.523	0.4867	0.4129	0.3211						
EFFP	0.6368 7.198	0.7190 8.063	0.6514 5.598	6.6517 2.989	6.8655 -0.344						
DEVM	15.016	8.730	7.393	8.635	9.101						

Blade Element Data Intermediate Configuration (Continued) Table B-4.

<u>ે</u> થ	3999S INGORBACA	9.2 <b>€*</b> 01.5€		CONFIGURATION Interacidiate	N/VØ	100.000	<b>6</b> 0				
		INLET GUIDI	E VANE					HOTOR	œ		
PCT SPAN	Š	2,2	C G	ć.	<u> </u>	PCT SPAN	Ó	۲	्र क्र	ž	%. <del>≠</del>
DIA 3	21,150	26.050	30,950	35,35	40,750	714 5	73.309	27. 7FF	32,125		4. 0 KE
BETA 3	000.0	်ပ္သာ . သူ .	000 °		30000	00TA 4	14.143	13.254	12.215	7. °C	140.36
851A 4	17.00 001 001	7.0 to 1.0	1 3, 486	77 702	324 70	_	40.4	47° 373	1 - 1 4 4 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	42,235	6.6. 3.6. C
	315.29	77 - 18 E	344.97	15.7.40	347.90	ACTA(PP) 7	21.634	37.721	45.327	47.782	43,490
٧2 ع	291.81	31. 8. 72	327.47	326.44	326.49	. 4 >	325.61	358.40	360.15	114.11	350 35
7 Z A	363.68	275.30	327.46	344.34	345.67	٨ ٢	541. 24	495.01	486.42	497.37	5 2.47
V-THETA 3	00°C	ان • در ان • درا	رن • درن	(	ς · .c •	۶ ۲ ۸	325.24	344.30	360.72	774.	257.6
HETA	84.75	94.07	16.00	59.85	40.40		376.67	446.83	364.42	4.7. CH	40 - 10 C
n ⊲ E 3	25020	7.7.7.7	27.7.5	- 47.7° C	1,2147	V-1HT-0 V-THEYA 7	76. 205	363,00	121.97	201.31	7000
	115.59	14.4		- 16.	54.4		5.54.4	511.8	6.69.7	α . ζ , χ	7 808
1	•					7 (00)	407.3	434.9	518.6	5,812	1.00.7
3		(REFER TO 70%	ઝ	ED DATA)		VTHETA DRA	-411.7	-502.6	-665-	-710.5	7.760-
DFAC	690.0	. 144	5.044	( 35.3	\$0€*J-	VTHETA DR7	C * 12( =	-261.9	-368.4	-47F.	-444.
EFFP	(.8527	1.984	0.8911	10660	°.7192	= ~	76.867	585.42	677.50	760.76	96.1.04
Meibm	-20.200	-20,200	-20.200	-20.200	-50.200	۰ » ت ع	5.35 5.53 5.53 5.53 5.53 5.53	415.90	695.77	47. 47. 47. 47. 47. 47. 47. 47. 47. 47.	70.07
DEVM	y C T	L KOR	1.81	A. 853	8.814	د <i>د</i> د ج	1 . 4 R J II	0.44.0	4322	4664.7	1,4441
	20102	266.4	1			6	474	6.5537	P. 6337	6.77.6	7.8335
		STATOR	221			7 (pg) 7	F & 3.K 3.4	0.3867	G.460B	F 54 93	C-14-7
						THRN(DR)	BU1. JK	18.217	13.632	11.453	12.447
						13	0.0157	0.0235	0.0489	0.0815	0.1128
PCT SPAN	Ğ	7.	ή. Υ.	3.5	-	ت الله الجال	Offi	1991	7907	.3593	.3909
0 A 10	24.723	79.683	33.345	37.7.7	43.669	EFFD	6.9631	C 396° J	1.(349	1.14.6	•
ς.	44.443	64 49	30.443	35.252	366.45	u.	( • 9473	2656	1.6359	1.0018	,0407
BETA 10	0.18°	13.263	17,938	12, 421	12.428	wei Jiù I	3.049	2.773	2.864	2.636	3.38
6 F	520.30	76.807	495.13	5.2.92	511.68 456.05	W. 100	2 83	רצא	3,227	2,182	666*0
۷۲ و	371.83	255.61	202.13	410.45	413.50		100	1			•
	374.67	282.83	389.00	422°C4	444.12						
<	25°12E	346.92	61°516	100000	64.266						
V-THETA 10	166.90	01.17	رة. در م	20.90	98.33						
o :	0.4732	4430	0.4412	C.4466	6.4521						
OT W	7 * 3465	30.586	0.4543 26.864	72,430	72.455						
		,		•	Ι.						
13	0.1581	0.0993	0.1564	0.0803	0.1025						
DFAC	0.4465	6.4139	0.3911	2616.	7.002						
INCIDM,	-0.957	2.140	0.2k3	-3.248	-5.610						
DEVM	11.518	7.863	7.438	7.821	8.325						

Blade Element Data Intermediate Configuration (Continued) Table B-4.

INLET GUIDE VANE  70 50 26.050 30.950 31.95.950 36.951 36.2.78 36.2.78 36.2.78 36.2.78 36.2.78 36.2.78 36.2.78 36.2.78 36.2.36 77 10.0687 70 10.021 70 10.0687 70 10.021 70 10.022 70 10.022 70 10.022 70 10.023 70 10.033 70 10.033 70 10.033 70 10.033 70 10.033 70 10.033 70 10.033 70 10.033 70 10.033 70 10.033 70 10.033 70 10.033 70 10.033 70 10.033 70 10.033 70 10.033 70 10.033 70 10.033 70 10.033 70 10.0												
21.150 26.050 36.950 37.950 40.750 D14 6  21.150 26.050 36.950 36.950 40.750 D14 6  15.600 16.000 16.000 10.000 9.000 9.000 AFTA 7  343.05 36.78 375.11 34.77 407.85 94.74(PR) 7  342.98 36.27 40.977 415.77 407.85 94.74(PR) 7  35.97				E VANE					ROTOR	æ		
21.150 26.050 37.95C 35.950 4C.750 DIA 6 15.650 14.543 13.138 4 9.551 5.000 RETA 6 15.650 14.543 13.138 4 9.551 5.000 RETA 6 373.55 399.92 409.72 415.77 415.77 415.77 373.55 399.92 409.72 415.77 415.77 415.77 39.97 34.14 398.98 381.48 382.19 RETA(RR) 6 4 10.77 10.017 93.13 71.85 41.22 VZ 6 0.3384 0.3384 0.3393 0.3377 0.3773 VHFTA 0R6 0.3384 0.3384 0.3384 0.3956 0.7174 116 -20.200 -20.200 -20.200 -20.200 -20.200 WT 5.050 14.457 1.062 5.649 9.500 WT 5.050 14.457 1.062 5.649 5.649 6.54	SPAN	06	02	<b>5</b>	بر د	ç.	PCT SPAN	ç	7	50	ę.	1
6.000 6.000 6.000 6.000 8FTA 6  343.07 343.53 35.31 34.73 482.10 8FTA 6  343.07 362.74 375.11 34.77 407.85 9FTA(PR) 7  340.07 362.77 386.32 375.11 34.77 407.85 9FTA(PR) 7  4 10.07 10.01 384.14 388.98 409.52 405.76 V 7  6.310 6.00 6.00 6.00 7.380 7.386 7.3864 V 7  6.310 6.320 6.3284 0.3390 6.3300 7.3864 V 7  6.330 6.330 6.3304 7.3369 7.3364 V 7  6.330 6.330 6.3304 7.3369 7.3364 V 7  6.330 6.330 6.3304 7.330 6.00 7.300 7.300 V 7  6.656 6.9318 0.033 6.00 7.300 7.300 V 7  6.656 6.0318 0.033 6.00 7.00 7.00 7.00 0.00 0.00 0.00 0.00		21.150	26.050	30,950	35, 950	46.750	DIA 6	23.385	77.755	32,125	34.495	4. 865
15.650 14.543 13.138 0.551 16.810 RFTAR 7  343.25 362.76 375.11 3A1.77 407.85  343.25 362.76 375.11 3A1.77 407.85  343.25 362.36 409.72 415.77 407.85  4 10.07 36.70 362.76 409.72 415.77 407.85  4 10.07 10.0087 0.390 0.340 0.300 0.00 0.00 0.00 0.00 0.00 0	_	000.0	0.000	20000	C-00-0	0.000	RETA 6	14.716	13.210	11.949	9.319	5,172
347.55 364.72 367.11 371.17 937.17 937.17 937.16 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9		15.650	14.543	13,138	6, 951	5. RJO		35.014	33.789	12.045	79.543	74.540
347.95 362.36 479.07 413.17 431.83 312.83 314.84 342.85 362.36 479.67 479.77 10.17 93.13 71.85 479.7		343.02	362.78	375.11	381.73	482.19		4.0° -0.0	40.00	24.172	747.40	(4x • ) (0
359.77 384.14 398.98 409.72 405.75 V 7  3 0.00 0.00 0.00 0.00 V 7  4 10.01 0.00 0.00 0.00 0.00 0.00 0.00 0.		37.5 00	36.836	404.16	11.614	282 16	X X	60.807	50° 15"	44.199	439.21	424.25
3	0.41	359.70	384.14	308.08	409.57	405-76		501.10	533,79	509.64	5.4.80	404.35
4 100.77 100.17 100.17 43.13 71.85 41.22 VZ 7 10.310 (0.3304 0.3304 0.3304 0.3304 0.3304 0.3304 0.3304 0.3304 0.3304 0.3304 0.3304 0.3305 0.3306 0.3306 0.3306 0.3306 0.3306 0.3306 0.3306 0.3306 0.3306 0.3306 0.3306 0.3306 0.3306 0.3306 0.3306 0.3306 0.3306 0.3306 0.3008 0.00		000	0.0	00.0	60°0	00.0	9 2 /	190.93	417.02	424,17	432.42	472,57
0.31C? (.32R4 0.3399 0.3465) 7.3464 VTHETA 6 0.3384 0.352 0.377 0.377 0.3773 VTHETA 7 -15.65 0.408 1008 SPRED DATA) VTHETA PR7 0.8856 (.9318 9.8483 0.9356 0.7104 116 -20.200 -20.200 -20.200 -20.200 0.708 117 -20.200 -20.200 -20.200 -20.200 0.708 117 -20.200 -20.200 -20.200 -20.200 0.708 117 -20.200 -20.200 -20.200 -20.200 0.708 117 -20.200 -20.200 -20.200 -20.200 0.708 117 -20.200 -20.200 -20.200 -20.200 0.708 117 -20.200 -20.200 -20.200 -20.200 0.708 117 -20.200 -20.200 -20.200 -20.200 0.708 117 -20.200 -20.200 -20.200 -20.200 0.708 117 -20.200 -20.200 -20.200 -20.200 0.708 117 -20.200 -20.200 -20.200 -20.200 0.708 117 -20.200 -20.200 -20.200 -20.200 0.708 117 -20.200 -20.200 -20.200 -20.200 0.708 117 -20.200 -20.200 -20.200 -20.200 0.708 117 -20.200 -20.200 -20.200 -20.200 0.708 117 -20.200 -20.200 -20.200 -20.200 0.708 117 -20.200 -20.200 -20.200 -20.200 0.708 117 -20.200 -20.200 -20.200 -20.200 0.708 117 -20.200 -20.200 -20.200 0.200 0.708 117 -20.200 -20.200 -20.201 0.200 0.708 117 -20.200 -20.200 -20.201 0.200 0.708 117 -20.200 -20.200 -20.201 0.200 0.708 117 -20.200 -20.200 -20.201 0.200 0.708 117 -20.200 -20.200 -20.201 0.200 0.708 117 -20.200 -20.200 -20.201 0.200 0.708 117 -20.200 -20.200 -20.201 0.200 0.708 117 -20.200 -20.200 -20.201 0.200 0.708 117 -20.200 -20.200 -20.201 0.200 0.708 117 -20.200 -20.200 -20.200 -20.201 0.200 0.708 117 -20.200 -20.200 -20.200 -20.200 -20.200 0.708 117 -20.200 -20.200 -20.200 -20.200 -20.200 0.708 117 -20.200 -20.200 -20.200 -20.200 0.200 0.200 0.708 117 -20.200 -20.200 -20.200 -20.200 0.20		100.77	100.17	93,13	71.85	41.22		481.97	442.P1	431,78	439.11	449.2
0.3384		0.3102	( . 3284	0.3399	0.3460	7.3464		97.61	97,95	89.78	76.89	27.75
Color		0.3384	0.3620	0.3720	0.3777	0.3703		330.16	296.58	270.41	248.90	2.6.19
C.CCC	z	-15.65	-14.54	-13.14	-0.95	-5.80		556.1	641.5	724.7	821.6	926,0
C.CCG C.040 0.033 C.055 -0.013 VIHETA DR7 0.8546 C.9318 0.9356 C.7104 U.6			2	\$(O) \$	RED DATE			522.4	546.1	60.2.9	681.3	787.3
C.		e e		<b>2</b>	( yrun ram			-395.4	-487.2	-587.5	1498.6	-873.0
9.504	o i	290.0	0.040	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	\$00.0 0	-0-013	۷ - <u>-</u> - ۱	C*95I-	1 2 1 0 1	-420.	7.076	40.0401
20.200 -20.200 -20.200 -20.200 -20.200 W 7  5.050	<b>a</b> .	0.8546	. 44I8	0.8484	0.4956	<b>†∵T.) *</b> ○	c r	600 600 600 600 600	416 44	16.77	74.074	FOI - 17
\$.050	Mai	-20.200	-20.200	-20.200	-20.200	-20,200		0.000 0.00 0.3655R	0.3897	3444	7804	70.000
#(PR) 6  STATOR B  STATOR B  90  26.021 29.683 33.345 37.07 40.669 EFFP  33.498 32.936 37.495 28.229 27.249 FFF  15.773 13.348 13.781 12.570 12.433 INCIDM  588.01 545.10 520.68 519.75 509.50  587.26 526.71 569.72 570.05 526.18 INCIDM  482.08 520.87 6493.84 497.88 513.77  520.87 520.74 564.23 245.84 192.92  10 145.47 121.59 114.98 116.97 113.28  0.454.6 0.4729 0.4452 0.4555  0.171 0.0687 0.0922 0.1205 0.0761  0.172 0.1671 0.1498 0.1205 0.0761  0.172 0.1671 0.1498 0.1205 0.0761  0.172 0.1498 0.1400 0.0762  11.902 -9.364 -8.705 10.271 -18.251	*	5.050	1,0457	4.062	5.649	9.500		5332	0.4701	0.4568	6.45.15	. 4414
90								F. 5F48	0.5833	0.4592	r.7475	C.8416
90			STATOR	œ			M(DR) 7	C*4112	0.4906	2.5401	£6,39°0	r. 7.3
96 70 50 30 10 0FAC 26.021 29.683 33.345 37.007 40.669 EFFP 1 15.77 15.433 1NCTDW -3. 58.229 72.249 FFF 1 15.77 13.348 13.348 13.348 12.577 12.433 1NCTDW -3. 58.20 72.249 FFF 1 1 2.577 12.433 1NCTDW -3. 58.20 52.80 52.49 FFF 1 1 5.20.80 52.49 FFF 1 1 5.20.80 52.49 FFF 1 1 5.20.80 52.40 FFF 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1				1			THRN( PR)	23.265	13.671	696.6	4.377	7.647
96 70 50 30 10 DEAC 26.021 29.683 33.345 37.007 40.669 EFEP 1 33.498 33.445 37.007 40.669 EFEP 1 1 15.273 13.348 13.349 12.570 12.433 INCTON -3.588.01 546.10 546.10 56.							13	0,0070	0.0265	0.0561	0690	0,1026
26,021 29,683 33,345 37,707 40,669 EFFP 1 33,498 32,236 37,495 28,229 22,249 FFF 1 15,273 13,348 13,381 12,570 12,433 INCIDM -3,588,01 545,19 520,68 519,75 50,57 1 588,01 545,19 520,68 519,75 50,57 1 552,80 560,71 560,22 560,00 526,18 DEVM 3,482,69 468,09 447,74 457,85 471,52 520,77 1 524,52 200,74 264,23 245,84 192,92 1 10 145,47 121,59 16,454 1,456 1,456 1,28 1 18,225 16,883 17,414 15,659 9,815 0,0761 0,171 0,0687 0,0922 0,1205 0,0761 0,044,2 1,140 1,160,27 1,769,2 1,769,2 1,140 1,160,27 1,769,2 1,769,2 1,0073 7,818 7,870 8,333 1,0073 7,818 7,870 8,333	SPAN	<u>0</u> 6	70	50.0	3.5	ر 1	DEAC	.2250	.273h	.2743	.2675	2348
33,498 32,236 37,495 28,229 22,249 FFF 15,773 13,348 13,781 12,577 12,433 INCTDM -3 584,01 582,068 519,75 579,55 10,433 INCTDM -3 582,06 526,18 519,75 579,55 579,55 579,55 579,56 529,82 529,82 579,74 457,85 471,52 529,82 579,74 457,85 471,52 529,82 570,74 457,85 471,52 529,82 570,74 493,84 497,58 513,77 529,82 570,74 52,84 192,92 113,28 145,47 121,592 144,98 113,28 13,28 17,414 15,659 9,815 0,0761 0,0887 0,0922 0,1205 0,0761 0,0761 0,0772 0,1171 0,0687 0,0922 0,1205 0,0761 0,0742 0,1172 0,0341 -0.5561 -1,9369 1,7692 1,769		26.021	29.683	33,345	37.707	40.669	EFFD	1.0151	1.0267	1.1086	r. 96.87	7.9824
15.273 13.348 13.781 12.570 12.433 INCTDW 588.01 545.17 520.68 519.75 509.57 509.57 552.6 552.6 552.6 56 519.75 509.57 509.57 552.6 552.6 56 519.75 509.57 509.57 509.57 509.57 509.57 509.57 509.57 509.57 509.57 509.57 509.57 509.57 509.57 509.57 509.57 520.57 509.57 5		33,498	32.236	30.495	28.229	22.249	FFF	1.0154	1.0267	1.00 AB	∵α9υ°∪	C.9822
588.01 545.10 520.68 519.75 579.55  588.01 545.10 520.68 519.75 579.55  488.69 458.09 447.74 457.85  520.82 578.04 493.84 497.58 513.77  9 324.52 590.74 264.23 245.84 192.92  10 143.47 121.59 114.98 115.97 113.28  0.457.2 144.7 0.447.1 0.445.4 1.455.5  0.1171 0.0687 0.0922 0.1205 0.0761  0.172 0.1671 0.1498 1.140.0 0.044.2  0.173 0.0341 -0.4561 -1.9349 1.7692  -11.902 -9.364 -8.761 1.9349 1.7692		15.273	13,348	13.181	12.570	12.433	NO LON I	-3.272	-3.061	-1.928	-1.358	-0.354
552.26 576.71 559.72 579.40 575.18 DEVM 482.69 576.71 559.77 575.18 DEVM 482.62 576.94 493.84 497.84 497.85 513.77 524.52 290.76 264.23 245.84 192.92 10 145.47 121.59 114.98 110.97 113.28 1.45.47 121.59 114.98 110.97 113.28 1.45.47 121.59 1.46.71 1.46.55 1.45.47 121.59 1.46.71 1.46.55 1.45.47 1.21.59 1.46.71 1.46.71 1.8.225 1.8.889 17.414 15.659 9.915 0.1171 0.0687 0.0922 0.1205 0.0761 0.172 0.1671 -1.9369 1.7692 -11.902 -9.364 -8.705 -10.271 -18.251		584.03	545.10	520.68	519.75	50.9.52		e i	6	ő	170	0
48.25	c ·	552,26	526.71	50.805 10.40	00°616	526.18	•	2.62(	3.250	×60.2	TO2 • T	6.677
9 329,87 7 18,94 493,34 447,38 10 14,52 24,52 249,67 10 14,54 110,47 10,454 10,454 10,454 10,454 10,454 10,454 10,454 10,454 10,454 10,454 10,454 10,454 10,454 10,454 10,454 10,454 10,448 10,44 10,4	6	50° 20° 1	408.04	t - / t t	40.7 cm	20114						
10 145.47 121.50 114.98 115.57 0.5303		79.456	25 000	266 23	74.50	103 03						
0.1171 0.0687 0.0922 0.1205 0.1171 0.0687 0.0922 0.1205 0.1171 0.0687 0.0922 0.1205 0.1713 0.0341 -0.5561 -1.9369 0.073 7.818 7.581		165 67	101.50	114.98	110 07	113 28						
0.1171 0.0687 0.0922 0.1205 0.1171 0.0687 0.0922 0.1205 0.172 0.11671 0.1498 0.1205 0.173 0.0341 0.05561 0.0346 0.173 0.0341 0.05561 0.0346		0.5303	C 49C 2	- 4671	0.4654	11.04.0 0.4555						
18.225 16.883 17.414 15.659 0.1171 0.0687 0.0922 0.1205 0.1722 0.1661 0.1498 0.1400 0.1732 0.0341 0.5561 0.1403 0.1732 0.0341 0.5561 0.271 0.0073 0.08.8 0.087	c	4964	0.4729	4552	0.4562	0124-0						
0.1171 0.0687 0.0922 0.1205 0.1722 0.1661 0.1498 0.14400 0.1713 0.0341 0.5561 0.4369 0.0000 0.1713 0.0341 0.5561 0.271 0.00000000000000000000000000000000000	· Z	18,225	15.883	17.414	15.659	9.815						
0.1722 0.1671 0.1498 0.1470 0.1713 0.0341 -0.4561 -1.9369 04 -11.902 -9.364 -8.705 -10.271		1711	0.0687	0.0922	0.1205	0.0761						
04 - 11,9020,364 -0,561 - 1,9369 04 - 11,9020,364 -8,705 - 10,271 0,818 7,520		1733	1771	00%	V081 C	0.0000						
04 -11,902 -9,364 -8,705 -10,271		0 1713	C. 0.361	- 1440 - 7554	-1 0360	1 7802						
7.81.8 7.581	IDM	-11,902	-9.36h	-8.705	-10.271	-18.251						
10.072 7.EB1 7.EB1				3								
C) C: 1	¥	10.973	7.848	7.581	7.570	8.333						

Blade Element Data Intermediate Configuration (Continued) Table B-4.

100	PERCENT SPEFO	791•197	CONFIGURATION	figuration Intermedia <i>t</i> e	N/V & 6.60.	8 / 6 / 3					
		INLET GUID	GUIDE VANE					ROTOR			
PCT SPAN	i c	7	i.	ć	•	PCT SPAN	Ç	.c	) V	35,	<u>, , , , , , , , , , , , , , , , , , , </u>
	7	010	0.00	לין. כיזס פכ	11 250	4 4 1 0	32 205	37 766	32 125	36. 495	40.045
BFTA 3	0.00.0	000.0	0.00.0	. 64.66 COO.0	000.0	RFTA A	14.490	14.200	12.910	11.574	12,049
Z Z	15.774	15,136	14.048	12,582	13,982	RETA 7	57.662	59,319	52,339	49.109	50,602
	294.38	311,69	324.18	330.67	347.94		59.120	52.204	64.630	66.581	60.489
4	314.69	337. PO	348.04	361.67	367.10	RETAIDR) 7	21.589	45.174	50.713	52.647	57.051
¥.2.3	294.38	311,25	324.17	330.66	26.085	<b>*</b>	330.79	352,33	372.83	301.05	341.00
	302.75	323.61	338.48	352,88	356.23	٧ ٦	635.41	579.61	562.88	538.47	610.63
V-THETA 3	رن° ن	0u•0	c c	© <b>€</b>	<b>€</b> 0.* €	۷7 ۸	320.17	340.99	363.30	393.91	272.12
	R5.52	88.20	84.70	78.17	υ	7 7	337.46	295.40	343.66	300.04	386.91
<u>Σ</u>	0.2455	7.2814	0.000	9.20gg	16660	V-THETA 6	42.17	50°28	93,30	78.63	85.84
4	C.2841	4506.0	C. 3157	0.3274	0.3324		536.86	499.48	445.60	453,04	472.48
TURN	-15.77	-15.14	-14.05	-12.58	-13.98	V(pp) 6	624.7	731.4	848.0	964.9	1.62.
1	0		0960		0.010	V(D0) 7	365.5	402.0	543.1	444.5	7111.2
3	0.010		0.0200		1000	VTHETA DD6	-535.6	-645.9	-766.1	4.986-	-094.7
DFAC	080°0	0.060	0.055	n. 326	0.025		-134.5	-273.6	-450.4	-515-3	-596.B
EFFP	2686°U	0.466*O	C-9178	1.0386	1.3181	۲ =	618.34	733. RG	849.44	96.996	1090.54
tale in Ass	-20-200	-20,200	-20.200	-20.200	-20.200	<b>7</b>	671.34	772.10	865.97	965.39	6 0901
	700	3 961.	מור	9,0	0	u (	6867	X (	0.3377	0.000	> 0 4 6 5 C
DEVM	07K-th-	13.00	-3-122	-3.010	-1.310	- ·	5 5 5 5 5	0.5070	0.4921	0.5210	0.5280
						4(DR) 4	0.5639	0.6618	0.7682	0.8761	0.4676
		STATOR	Ø			MIDK)	7225.0	3574	12 011	1194.0	10 6 20
			•			- X-1	CCC+1.		116.61	266.4	
						13	0.0597	0.1840	0.2781	0.2405	0.2149
PCT SPAN	J6	70	50	35	<u>.</u>	DFAC	64/89	.6728	5401	.5058	5008
OIA 9	26.021	29.683	33.345	37.007	43.669	FFFD	0.9140	0.9000	0.9827	0.0678	0.9156
◂	57,915	58.129	50.346	47.702	49.397	i i	2016.0	0.8956	C.9819	0.96.0	7.9107
BETA 1	21.730	13.812	8.691	16.451	16.202	INCIDA	10.529	702.6	8.530	6.981	6.289
o >	613.52	575.68	567.82	613.A2	613.96	:	0		0	3	נטר י
	245°C0	364.51	357.73	415.08	529.26	₩ A ± C	5.700	10.274	8.013	10.1	161.1
6 77	318.98	300.52	360.94	412.99	399.48						
	224.61	340.43	351.00	5 - 6 - 6	00%						
	27.00	40.00t	77.04	70.404	147.67						
	0.5303	4605.0	0.4966	0.5347	0.5307						
, <u>c</u>	0.2104	0.3141	0.3084	0.3569	C-4548						
TURN	36.186	44.318	41.655	37.051	33,195						
13	0.4518	0.1987	0.3017	0.3220	0.1288						
	6										
DFAC	0.8640	. 6554	40000	0.6103	- 39In						
INCLOW	12.515	16.529	11.146	9.202	8.897						
	ı .										
DEVM	17.430	8.312	3.191	5.651	12,102						

Blade Element Data Intermediate Configuration (Continued) Table B-4.

H	Table B-4	. Blade	Element	ent Data		Intermediate C	Configuration		(courtinea)	nea)	
10	100PERCENT SPEED	ED PT.198	CONFIGURATION INTERMEDIA	figuration intermédiate	N/V 6063.	$\omega \sqrt{\omega}/\delta$					
		INLET GUIDE	DE VANE					ROTOR	Œ		
PCT SPAN	06	02	20	30	10	PCT SPAN	06	C <b>Z</b>	r C	-34,	Ç.
m	21.150	26.050	30.950	35.850	40.750	DIA 6	23,385	27.755	32,125	36.4.35	\$0.0 °
BETA 3	0000	0.00	0.000	000.0	0.000	8ETA 6	14.519	14.126	12.707	10,829	11.72
ETA	15.717	15.057	13.749	11.680	12.674		57.721	56.345	51,339	48.977	661.13
n . > :	308,36	326.80	339.95	341.29	348.49	SETA(PR) 6	57.823	26 % · US	43.434	10° to	
* <sup>*</sup> *	350.50	356.45	30 000	347 27	384.24		27 • (22	41.4(3	200.000	27.37.7	75.01
7 7 X	318.14	338.16	356.97	373,30	374.88	· >	641-24	584.21	560.17	501.05	37.100
THETA	00.00	00.00	00.00	00.0	00.0	4 Z A	334.72	158.44	291.00	+0.2.11	ינו נוט כ
V-THETA 4	89.53	91.68	87.35	77.17	84.30	7 7	340.09	323,38	254.40	394.49	. U . U .
æ	0.2783	0.2953	0.3074	0.3141	0.3152	V-THETA 6	86.65	46.37	44.33	76.93	67.10
Ŧ	0.2987	0.3193	0.3328	0.3455	0.3483	V-THETA 7	542.14	486.29	443.49	453.57	453.74
TURN	-15.72	-15.06	-13.75	-11.68	-12.67	V(PR) 6	628.6	737.2	1.630	975.3	1.74.4
13	02.00		0.0235		0.0190	V(PR) 7	366.1	4.70.1	547.0	246.7	1.704
3 6		ć		;		VIHETA PR6	-532.0	-643.9	763.0	5 × 88 -	000
) A (	770.0	290.0	840.0	410.0	0.018	VIHELA PK	9.621-	1286.7	1.2.2.	-517.3	1.00
-	0.9155	0.9454	0.916	1.0254	1.0019	e r	618.65	1.44.73	1	100.47	31. ° 0. 7. 7. 7. 7. 7. 7. 7. 7. 7. 7. 7. 7. 7.
NOIDW	-20.200	-20.200	-20.200	-20,200	-20.200	~ 4	0/1-09	7 7 5 4 X	707 707 707 707 707	100.87	7667
DEVM	_l983	-3.943	-3.451	-3.920	-2.626	· >	0.5651	0.5122	C 707	48.00	6424
	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \					M(PR) 6	0.5685	0.6577	C - 7742	3.8356	
						M(PR) 7	0.3226	r. 3780	1807	1.5e3J	1007
		STATOR B				TURN(PR)	37.034	19.392	13.605	13.254	12.041
						13	0.0549	0.1405	0.2314	0.1745	0.1462
PCT SPAN	Ö	02	9	50	-	DEAL	0207	7607	ביסבק	5003	SO L
OAIO	26.021	20-683	32 245	700.75	40.64.0	2 11 11	2,000	70.50	0.000	56.5	20.27
BETA 9	57,959	55.049	649.64	47,434	48.794	. u.	46880	0.9273	C. 80.7	1.65	
	23.487	14.414	11.063	12.669	15.159	INCIUM	9.223	8.398	7.393	6.051	5.200
6 >	618.83	581.51	572.26	616.45	641.15					, j	, i
_	261.08	381.82	376.17	435.03	556.32	DF VM	1.922	8.975	7.082	3.795	3-459
6 7/	321.21	329.42	368,96	416.77	422.36						
	236.43	365.04	367.90	424.05	536.95						
		4/6.63	436-11	454.02	482.37						
1		95.04	72.30	95.41	145.47						
o =	0.5441	0.5097	0.5009	0.5369	0.5545						
TURN	34.472	40.635	38.586	34.765	33.635						
13	0.4465	0.1896	0.2814	0,2999	0.1004						
	1				,						
DFAC	0.8335	0.6131	0.6217	0.5655	0.3891						
INCIDM	12.559	13.449	10.449	8.934	8.294						
DEVM	19.87	8.91µ	5.563	4.669	11.059						

E	Table B-4.	Blade		Element Data		Intermediate C	Configuration	ation	(Continued)	ned)	
10	Indreaceut speen	PT.199	CONFIGURATION INTERMEDIAL	nfigurat ion intermedia le	N/√ <b>Ø</b> 6^36.	2/6/5 215.	<b>L</b> n				
		ENLET GUIDE VANE	VANE					ROTOR	<b>સ</b>		
PCT SPAN	Ö	<u> </u>	Ç		2	PCT SPAN	č	7	נ	į.	-
2 4 4			0.50 0.50 0.50	35.853	750	7 4 4	72 205	27 755	20.105	36 405	4. PAE
ETA J	0.000	٠,	600.7		0.00	RFTA 6	14.594	13.774	12,230	17,192	11.030
BETA 4	ıń.		13.420	11.201	11.235	BETA 7	52,114	51.661	47.249	43.773	44.577
.00	44		373.22	778.39	375.55	3ET4(00) 4	54.35	57.465	999.69	43.196	46.834
*	7		473.69	414.61	422.12		20.769	37.640	46.723	40.754	52.589
٧2 ع			373.20	378.35	375.53	٧ 4.	284.74	413.50	433.91	452.36	433.07
	348.36		302.55	4/8.74	413.92	۰ <u>۱</u>	654.22	60.9°03	592.71	622.42	655.43
V-IHI-V			ن د د د د د د	00.00		۲ / ۲ ۲ / ۲	472.77	26.104	423.91	44.	100
	0.3087		73.03 1986.0	7.5.6.2	0 460 A		40.40	98.47	40.504	25 • 54 40 · 08	
			1.3664	2476.7	3835	V-THETA 7	516.33	477.69	76-516	65.054	475.04
⊃		-14.91	-13.42	-11.69	-11.74	×c	638.7	740.3	865.2	307.2	1797.5
1			0.0256		0,0210		429.7	477-1	586.9	9.509	741.6
3 8	0070		, <u>u</u>			VTHETA DRA	0 · KI	7637.5	-754.7	1,331	K * 666-
DFAC	6 K( • )	0.0404	7,000	6010°	40000	Z	415 BO	730 08	844.08	961.17	1076 25
-					100	- 1	668.7	769-04	862.54	951.56	10.88.01
INCION	-20.200	•	-20.200	-20:200	-20,200	· τ.	7.348B	C. 3757	0.3947	0.4120	P.3939
DEVM	-4.675	-4.089	-3.780	-4.519	-4.065	۸ ۲	r.5795	0.5364	6925.0	0.5451	n.5707
						W(DR) A	U.5797	0.6906	0.7870	2668 0	r.9827
		STATOR B				THOM OF	7.3807 3.572	19.041	0.5159	13,440	14.2457
						•	1,100	0 0603	6911.0	0.0822	0.106
DOM GD AN						3	7770°0	56000	7.77	37000	•
10. TO			, 12 C	30	10.74	UFAC Thris	.572h	5649	7887	1,539	0.1810
DIA V	12.00		53.45 F. 840	100000	40°474	1. U	9478	0000	1.0019	7700 C	0440
BETA TO		14.627	12.925	13.330	15,718	MOIONI	5.750	5,105	1.560	3,506	3.63h
6.7			61.16	642.71	669.38						
_			123.90	475.81	560.68	nFVW	1,969	5.140	4.623	1.154	-0.311
6 2/	381.10		20.02	476.11	451.97						
07 7A				46/.46	24.1.42						
	80.76		04.07	109.77	145.20						
	1655.0		0.5287	0.5636	0.5432						
C.I.			7.3577	0.4122	N.4846						
TURN			32.744	28.864	32.472						
13	0,4153	0.1983	0,2207	0.2070	0.0773						
DFAC	0.7434		0.5405	2×64*U	5.4165						
FFF	395	0.6834	0.6144	0.6722	1050.0						
F.C. 1 2 N. 1	901.0	01/0	605.0	5.703	088.0						
DEV	12,182	9.129	7.325	8.339	10.918						

Blade Element Data Intermediate Configuration (Continued) Table B-4.

	: :		CONFIG	CONFIGURATION	N/V	10/3	<b>.</b>				
<b>Y</b>	100PERCENT SPEED	PT.200	TNTER	TN TERMEDTA TE	6047.	238					
	4	INLET GUIDE VANE	VANE					ROTOR			
PCT SPAN	G	0,	Ç	Ç	2.	PCT SPAN	C	7.0	, C	e e	Ę
D.T.A. 2	5	24.050	0.00	2 4 4 4	70.750	2 410	305 50	27 755	30 105	7.7.7.	370 17
	.•	000	000	000	000	٠ ـ	14.540	12.560	12.321	0.25	7 777
		14.647	13.506	1000	7.616	- V- L-	46.041	77. 74.4	40.540	600 a a a	20.
			414 97	474 57	42 O - 25		50.450	5.4	57. B 27	C 8 8	761 77
		_	7.0077	461.06	676.27	RETAIDD 7	22 261	37.660	25. 25.5	0.00	CC
* * * * * * * * * * * * * * * * * * *			17.644	10.101	- 0 · 0 · 0 · 0 · 0 · 0 · 0 · 0 · 0 · 0		0.7 567	140.15	40.00	01.000	10.3
7 7 7	207 20		410.70	424.50	420.63	c .r > >	01.007	401.00	A C R	0.000	10 S S S S S S S S S S S S S S S S S S S
TUETA	•		430.42	***	n 0 0 0 0		77 017	76.077	7.69.70	**************************************	20 20 3
C ATTITUTE OF	•		00.0	00.00	00.0	0 1	0.00	77.044	2 - C	14.1.00	
-IHE IA		110.16	16.401	81.21	63.04		460•19	41.4.45	1	4 (3.115	3 7
		0.3646	0.3788	0.3859	0.3819	V-THFTA 6	06.801	I 08 • 22	2.5.42	30.45 11.	(1)
r g		6965-0	1505.0	0.4202	0.4340		480.41	44.00	4 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6	57.75	
Z 25	- 10.00	-14.65	-13.51	-10.14	-7.62	V(PR) 6	0.400	C		7.0101	
,3	0.0180		0.0253		0.0200	V(PR)	5000	1,524	1 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	625.9	
DEAC		3	0,00		730 0-	VIHELA PKO	-108.1	1920-1	145.	1 3 7 5 1 1 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	, , , , , , , ,
2 4 4 4		0.000	6.000	2000	- F- CO- CO- CO- CO- CO- CO- CO- CO- CO- CO	1 4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	6.601-	1000	· · · · · · · · · · · · · · · · · · ·	0.000 E	
1111		0016.0	7906.0	7786	1+69-0	0 1	10.077	74.044	74.	76.504	
INCIPM	-20.200	-20.200	-20.200	-20.200	-20.200	- 4	2000	4004	624.0	45.4	1577
DEVM	707-7	-4.353	-3.69h	-5.455	-7.68h	o <b>~</b>	3.5948	0.5420	7.5274	5337	7.8347
						-	7.5004	3006	7.6.00	26.00	4000
						M( DQ ) 7	0.444	7.444	0.5628	7. 7. 7. 7. 7. 7. 7. 7. 7. 7. 7. 7. 7. 7	7213
		STATOR B				۰.	28.191	16.646	11.444	9.822	, L . 9
						17	0.000	0.0278	0.0362	0.078	7721.0
PCT SPAN			(	i	•	3	77.0	2		1000	1,101
		70	50	30	10	DFAC	.11525	9767	1,218	. 3363	44011.
A 410		29.62	35.543	200.16	400.04	1. L	184.0	* C		r.	1 - X - X - X
	101101	13.401	12 470	12 601	11 625	NO LONG	0,060	•	727	1 282	080
2			608.01	625.79	616.42		3	270.4	1		
			482,39	520.23	582.80	∩F V.M	3,161	5.110	4.256	2.458	2.091
6 ZA			460.92	499.47	443.76					:	
VZ 10		_	468.57	507.93	570.68						
	463.36		394.86	376.98	426.67						
V-THETA 10	116.00		105.87	111.72	117.44						
o =		0.5438	0.5381	0.5522	0.5379						
01 E	0.3829 0	0.4108	0.4224	0.4551	0.5075						
Z X Z		32.185	27.820	24.642	32.177						
13	0.2330	0,0980	0.1309	0.1328	0.0535						
DFAC	0.5267 0	0.4557	0.4156	0,3663	0.2996						
EFFP INCIDM			0.6758 1.298	0.6011 -1.457	7.9317 3.303						
	्। 1 1 1		.0	1	1						
DEVM	11.057	8.101	7.178	7-401	7.525						

Blade Element Data Intermediate Configuration (Continued) Table B-4.

æ		1 may may 1	2727 .2196 .2288 0.9883 0.9572 0.9559 0.9880 0.9560 0.9544 -2.368 -1.563 -0.333 2.823 2.947 1.276
RCTOR	77. 75. 13.200 33.808 49.151 36.304 542.07	527.43 549.16 123.79 368.11 806.6 682.1 -610.0 -403.9 733.77 711.97 0.4974 0.5953 0.7402 0.6138	3.80t
	90 23,385 13,043 33,105 45,175 74,277 708,90	603.79 604.93 122.62 397.21 699.7 669.7 618.74 618.74 618.74 618.74 65985 66646 66646 6000	.1961 1.0805 1.0832 -3.494 5.470
26. 26.	PCT SPAN D1A 5 BFTA 5 BFTA 7 BFTA(PR) 5 BFTA(PR) 7 V 6 V 7	V2 6 V2 7 V-THETA 6 V(PR) 6 V(PR) 7 V(PR) 7 V(PR) 7 V(PR) 7 V(PR) 6 U 7 U 7 M(PR) 7 V(PR) 7 V(PR) 7 V(PR) 7 V(PR) 7 V(PR) 7 V(PR) 7 V(PR) 7 V(PR) 8 V(PR) 7 V(PR) 8 V(PR) 9 V(PR) 9 V(	DFAC FFFP FFFP INCIDM DEVM
N/V@	10 0.000 0.000 6.933 473.69 510.79 577.05	0.00 61.65 0.4472 0.0190 -0.019 0.8262 -20.200 -8.367	10 40.669 12.443 12.562 651.65 636.16 636.16 636.19 280.49 0.5824 0.5824 0.5824 0.5824 0.5824 0.5719 0.0719
nfi Jration inferædiate	36.850 6.850 10.359 473.76 519.44 473.73	0.00 9.47 9.4757 -10.36 0.9794 -20.200 -5.241	30 37.007 10.727 10.727 634.24 596.71 565.99 286.28 286.28 286.28 286.28 111.07 0.5688 0.5688 0.1300 0.1300
CONFI CURATION S INFERSEDIAT DE VANE	50 30.950 0.000 13.093 466.99 514.37 466.96	0.00 116.57 0.4708 -13.09 0.0231 0.024 0.9435 -20.200 -4.107	50 33.345 37.252 37.252 645.51 612.45 612.45 556.90 556.90 57.48 325.21 131.19 0.5799 0.5799 0.5789 0.0938
PT.196 INLET GUT	70 0.00 14.682 452.65 496.52 452.09	0.00 1.25.85 0.4538 -14.68 0.9238 -20.200 -4.318 STATOR 1	70 29.683 13.226 578.77 642.88 571.22 571.22 622.26 361.86 147.33 0.5174 18.967 0.03258
100PERCENT SPEED	90 0.000 0.000 15.753 428.60 428.55 448.50	0.00 126.52 0.3897 0.4249 -15.75 0.0200 0.9195 -20.200	90 26.021 31.691 14.236 725.70 679.77 608.43 654.96 381.24 167.15 0.6581 0.101 0.101 0.1715
3.0	ونود	V-THETA 3  V-THETA 4  V-THETA 4  TURN  EN 6  EFP  DEVM	PCT SPAN  DIA 9  BETA 9  SETA 10  V 10  VZ 10  VZ 10  VZ 110  VZ 110

#### APPENDIX C

#### Method of Deducing Rotating Stall Characteristics

The number, rotational speed, and size of rotating stall zones were determined from the results obtained with three Kistler high response pressure transducers located at Station 2, 10% of span from the outer wall, and spaced 30 and 60 degrees apart, respectively. A set of representative transducer signal traces is presented in figure C-1 to illustrate the method used. The method is predicated on a maximum number of stall zones equal to twelve, and equal rotational speed for all zones.




Figure C-1. Transducer Signal Diagram FD 25199

In figure C-1:

X = time between any two adjacent stall zones (or the cycle time of a single stall zone)

y = time for one of twelve or less stall zones to move from the 0-degree to the 30-degree probe.

z = time between a simultaneous stall zone intercept
 at the 0-degree probe and a stall zone intercept
 at the 90-degree probe.

w = the circumferential extent of a stall zone

 $R_{+}$  = time for one rotor revolution

t3600 = time equivalent of 360 degrees on the transducer signal trace

The minimum angular spacing of stall zones is obtained from

 $\frac{30}{y/x}$ 

Thus, if y = x, the minimum angular spacing would be 30 degrees. With the angular spacing known for any two adjacent zones, it is possible to identify the time-equivalent of 360 degrees on the transducer signal trace. The number of stall zones within this time period is the number of stall zones present. The rotational speed of the stall zone in terms of rotor speed is obtained from the ratio

Rt t360°

The extent of the stall zone is

±360°

The third probe can be used for a check on the number of stall zones when the minimum spacing is equal to or greater than 60 or 90 degrees. The third probe also defines the direction of rotation of the stall zones, although this direction is usually that of the rotor.

## NAS3-7604 REPORTS DISTRIBUTION LIST

1.	NASA-Lewis Research Center		
	21000 Brookpark Road		
	Cleveland, Ohio 44135 Attention:		
		1/0 F F	4
	Report Control Office	MS 5-5	1
	Technical Utilization Office	MS 3-19	1
	Library	MS 60-3	2
	Fluid Systems Component	34G 5 0	
	Division	MS 5-3	1
	Pump & Compressor Branch	MS 5-9	6
	A. Ginsburg	MS 5-3	1
	M. J. Hartmann	MS 5-9	1
	W. A. Benser	MS 5-9	1
	D. M. Sandercock	MS 5-9	1
	L. J. Herrig	MS 5-9	1
	T. F. Gelder	MS  5-9	1
	C. L. Ball	MS $5 - 9$	1
	L. Reid	MS 5-9	1
	J. H. De Ford	MS 77-3	2
	S. Lieblein	MS 54-6	1
	C. L. Meyer	MS 60-4	1
	J. H. Povolny	MS 60-4	1
	A. W. Goldstein	MS 7-1	1
	J. J. Kramer	MS 7-1	1
	W. L. Beede	MS 5-3	6
	C. H. Voit	MS 5-3	1
	J. H. Childs	MS 60-4	1
2.	NASA Scientific and Technical I P. O. Box 33 College Park, Maryland 20740	nformation Facility	
	Attention:		
	NASA Representative		6
3.	FAA Headquarters 800 Independence Ave., S. W. Washington, D. C. 20553 Attention:		
	Brig. General J. C. Maxwell F. B. Howard		1 1
4.	NASA Headquarters Washington, D. C. 20546 Attention:		
	N. F. Rekos (RAP)		1

5.	U. S. Army Aviation Material Laborato Fort Eustis, Virginia Attention: John White	ory	1
6.	Headquarters Wright Patterson AFB, Ohio 45433 Attention: J. L. Wilkins, SESOS S. Kobelak, APTP R. P. Carmichael, SESSP		1 1 1
7.	Department of Navy Bureau of Weapons Washington, D. C. 20525 Attention: Robert Brown, RAPP14		1
8.	Department of Navy Bureau of Ships Washington, D. C. 20360 Attention: G. L. Graves		1
9.	NASA-Langley Research Center Technical Library Hampton, Virginia 23365 Attention: Mark R. Nichols John V. Becker		1
10.	The Boeing Company Commercial Airplane Division P. O. Box 3991 Seattle, Washington 98124 Attention: G. J. Schott	MS 80-66	1
1,1,.	Douglas Aircraft Company 3855 Lakewood Boulevard Long Beach, California 90801 Attention:		
	J. E. Merriman  Tachnical Information Center C1-250	1	1

12.	Pratt & Whitney Aircraft Florida Research and Development Center P. O. Box 2691 West Palm Beach, Florida 33402	
	Attention:	1
	R. A. Schmidtke	1 1
	H. D. Stetson	1
	J. M. Silk	1
	W. R. Alley	1
	R. W. Rockenbach	1
	B. A. Jones	1
	B. S. Savin	ı
13.	Pratt & Whitney Aircraft	
	400 Main Street	
	East Hartford, Connecticut	
	Attention:	
	J. A. Fligg	1
	A. W. Stubner	1
	W. D. Harshbarger	1
	P. Tramm	1
	M. J. Keenan	1
	B. B. Smyth	1
14.	Allison Division, GMC	
	Department 8894, Plant 8	
	P. O. Box 894	
	Indianapolis, Indiana 46206	
	Attention:	
	J. N. Barney	1
	R. H. Carmody	1
	G. E. Holbrook	1
	B. A. Hopkins	1
	Library	1
15.	Northern Research and Engineering	
	219 Vassar Street	
	Cambridge 39, Massachusetts	
	Attention:	
	R. A. Novak	1
	K. Ginwala	1

	,	
16.	General Electric Company Flight Propulsion Division Cincinnati 15, Ohio Attention: J. W. Blanton J-19	1
	W. G. Cornell K-49 J. R. Erwin J-162 E. E. Hood/J. C. Pirtle J-165 J. F. Klapproth H-42 J. W. McBride H-44 L. H. Smith H-50 S. N. Suciu H-32	1 1 1 1 1 1
	J. B. Taylor J-168 Technical Information Center N-32	1 1
17.	General Electric Company 1000 Western Avenue West Lynn, Massachusetts Attention:	
	D. P. Edkins - Bldg. 2-40 F. F. Ehrich - Bldg. 2-40 L. H. King - Bldg. 2-40 R. E. Neitzel - Bldg. 2-40 Dr. C. W. Smith Library - Bldg. 2-40M	1 1 1 1
18.	Curtiss-Wright Corporation Wright Aeronautical Woodridge, New Jersey Attention:	
	S. Lombardo G. Provenzale J. Wiggins	1 1 1
19.	Air Research Manufacturing Company 402 South 36th Street Phoenix, Arizona 85034 Attention:	
	Robert O. Bullock John H. Daman	1 1
20.	AiResearch Manufacturing Company 8951 Sepulveda Boulevard Los Angeles, California 90009	
	Attention: Linwood C. Wright	1

21.	Union Carbide Corporation Nuclear Division Oak Ridge Gaseous Diffusion Plan P. O. Box "P" Oak Ridge, Tennessee 37830	
	Attention: R. G. Jordan	1
22.	Avco Corporation Lycoming Division 550 South Main Street Stratford, Connecticut Attention: Clause W. Bolton	1
23.	Continental Aviation & Engineering Corp. 12700 Kercheval Detroit, Michigan 48215 Attention: Eli H. Benstein Howard C. Walch	1 1
24.	Solar San Diego, California 92112 Attention: P. A. Pitt Mrs. L. Walper	1
25.	Goodyear Atomic Corporation Box 628 Piketon, Ohio Attention: C. O. Langebrake	2
26.	Iowa State University of Science and Technology Ames, Iowa 50010 Attention: Professor George K. Serovy Dept. of Mechanical Engineering	1
27.	Hamilton Standard Division of United Aircraft Corporation Windsor Locks, Connecticut Attention: Mr. Carl Rohrback Head of Aerodynamics and Hydrodynamics	1

28.	Westinghouse Electric Corporation Small Steam and Gas Turbine Engineering B-4 Lester Branch P. O. Box 9175 Philadelphia, Pennsylvania 19113 Attention: Mr. S. M. DeCorso	1
29.	J. Richard Joy Supervisor, Analytical Section Williams Research Corporation P. O. Box 95 Walled Lake, Michigan	1
30.	Raymond S. Poppe Building 541, Dept. 80-91 Lockheed Missile and Space Company P. O. Box 879 Mountain View, California 94040	1
31.	James D. Raisbeck The Boeing Company 224 N. Wilkinson Dayton, Ohio 45402	1
32.	James Furlong Chrysler Corporation Research Office Dept. 9000 P. O. Box 1118 Detroit, Michigan 48231	1
33.	Elliott Company Jeannette, Pennsylvania 15644 Attention: J. Rodger Schields Director - Engineering	1